

The `eventB` package*

Thai Son Hoang
ETH-Zurich
<htson at inf dot ethz dot ch>

February 26, 2013

Abstract

This class provides a template for typesetting Event-B models. It was developed at the Swiss Federal Institute of Technology Zurich (ETH-Zurich).

Contents

1	Introduction	1
2	Usage	1
2.1	Package Options	1
3	Implementation	2
3.1	Package Loading	2
3.2	Declaration of Options for the Package	2
3.3	Commands for Pretty-Print Event-B Models	4

1 Introduction

This package was developed in order to ease the typesetting of Event-B models in \LaTeX .

2 Usage

See `sample-eventB.tex` for an example of how to use the package.

2.1 Package Options

The package offers the following options:

- `nobox`: to disable to bounding boxes for the Event-B modelling elements,
- `small`, `compact`, `tiny`: options for font size,
- `colour` (or `color`): to colour several modelling elements.

*This document corresponds to `eventB` v1.1.1, dated 2012/02/21.

3 Implementation

3.1 Package Loading

We begin by loading the required package `xspace` and `xcolor`.

```
1 \RequirePackage{xspace}
2 \RequirePackage{xcolor}
3 \RequirePackage{ifthen}
4 \RequirePackage{etoolbox}
```

3.2 Declaration of Options for the Package

In this part various options for the package are defined.

Option for rounding boxes By default, Event-B modelling elements, e.g., invariants, events, etc., are displayed in a rounding box. This option enables them to be displayed without the rounding box.

```
5 \newlength{\B@oldfboxsep}
6 \newcommand{\event}[7][]{
7   \setlength{\B@oldfboxsep}{\fboxsep}
8   \setlength{\fboxsep}{2ex}
9   \fbox{
10     \ensuremath{
11       \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
12     }
13   }
14   \setlength{\fboxsep}{\B@oldfboxsep}
15 }
16
17 \newcommand{\B@declaration}[2]{
18   \setlength{\B@oldfboxsep}{\fboxsep}
19   \setlength{\fboxsep}{2ex}
20   \fbox{
21     \ensuremath{
22       \B@declarationbase[#1]{#2}
23     }
24   }
25   \setlength{\fboxsep}{\B@oldfboxsep}
26 }
27
28 \newcommand{\B@section}[3][]{
29   \setlength{\B@oldfboxsep}{\fboxsep}
30   \setlength{\fboxsep}{2ex}
31   \fbox{
32     \ensuremath{
33       \B@sectionbase[#1]{#2}{#3}
34     }
35   }
36   \setlength{\fboxsep}{\B@oldfboxsep}
37 }
38
39 \DeclareOption{nobox}{
40   \renewcommand{\event}[7][]{
```

```

41 \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
42 }
43
44 \renewcommand{\B@declaration}[2]{
45 \B@declarationbase{#1}{#2}
46 }
47
48 \renewcommand{\B@section}[3][]{
49 \B@sectionbase{#1}{#2}{#3}
50 }
51 }
52

```

Options for font size and spacing We define the default values for font size and some spacing commands, and how they are redefined according to options `small`, `compact`, and `tiny`. In particular, option `compact` and `tiny` implies option `nobox`.

```

53 \newcommand{\B@fontsize}{\normalsize} % The font size used in Bcode environment
54 \newcommand{\Bvspace}[1][2ex]{\[\[#1]} % Vertical space
55 \newcommand{\Bhspace}[1][2em]{\hspace{#1}} % Horizontal space
56 \newcommand{\B@tab}{\quad} % A small separation space
57
58 \DeclareOption{small}{
59 \renewcommand{\B@fontsize}{\small}
60 \renewcommand{\Bvspace}[1][1ex]{\[\[#1]}
61 \renewcommand{\Bhspace}[1][1em]{\hspace{#1}}
62 \renewcommand{\B@tab}{\ }
63 }
64 \DeclareOption{compact}{
65 \renewcommand{\B@fontsize}{\footnotesize}
66 \renewcommand{\Bvspace}[1][0ex]{\[\[#1]}
67 \renewcommand{\Bhspace}[1][0.5em]{\hspace{#1}}
68 \renewcommand{\B@tab}{\ }
69 \ExecuteOptions{nobox}
70 }
71 \DeclareOption{tiny}{
72 \renewcommand{\B@fontsize}{\scriptsize}
73 \renewcommand{\Bvspace}[1][-0.5ex]{\[\[#1]}
74 \renewcommand{\Bhspace}[1][0.5em]{\hspace{#1}}
75 \renewcommand{\B@tab}{\ }
76 \ExecuteOptions{nobox}
77 }
78

```

Options for colouring Keywords, labels and identifiers in Event-B can be coloured. We define several commands and redefine them accordingly for colouring. When `colour` (or `color`) option is enabled, one can customise the colours for Event-B keywords, labels or identifier or proof obligation labels.

```

79 \newcommand{\B@keyword}[1]{\ensuremath{\B@keywordbase{#1}}\xspace}
80 \newcommand{\B@identifier}[1]{\ensuremath{\B@identifier{#1}}\xspace}
81 \newcommand{\B@label}[2][]{\ensuremath{\B@label{#1}{#2}}\xspace}
82 \newcommand{\B@po}[1]{\ensuremath{\B@po{#1}}\xspace}

```

```

83 \DeclareOption{colour}{
84   \newcommand{\setBKeywordColour}[1]{\colorlet{B@keywordcolor}{#1}}
85   \setBKeywordColour{blue}
86   \newcommand{\setBIdentifierColour}[1]{\colorlet{B@identifiercolor}{#1}}
87   \setBIdentifierColour{blue!50!red}
88   \newcommand{\setBLabelColour}[1]{\colorlet{B@labelcolor}{#1}}
89   \setBLabelColour{green!50!black}
90   \newcommand{\setBP0Colour}[1]{\colorlet{B@pocolor}{#1}}
91   \setBP0Colour{red}
92   \renewcommand{\B@keyword}[1]{
93     \ensuremath{\textcolor{B@keywordcolor}{\B@keywordbase{#1}}}\xspace
94   }
95   \renewcommand{\B@identifier}[1]{
96     \ensuremath{\textcolor{B@identifiercolor}{\B@identifier{#1}}}\xspace
97   }
98   \renewcommand{\B@label}[2][]{
99     \ensuremath{\textcolor{B@labelcolor}{\B@label{#1}{#2}}}\xspace
100   }
101   \renewcommand{\B@po}[1]{
102     \ensuremath{\textcolor{B@pocolor}{\B@po{#1}}}\xspace
103   }
104 }
105 \DeclareOption{color}{
106   \ExecuteOptions{colour}
107 }
108

```

After declaration of options, we execute them accordingly.

```

109 \ProcessOptions

```

3.3 Commands for Pretty-Print Event-B Models

We start with the definition of the `\eventB` macro.

```

110 \newcommand{\eventB}{Event-B\xspace}

```

The `Bcode` environment for displaying Event-B models. The environment has an optional argument for specifying the font size. By default, it is the same as the `\B@fontsize` controlled by the package option.

```

111 \newenvironment{Bcode}[1][\B@fontsize]{\begin{center}#1{\end{center}}

```

Declarations and Collections Event-B modelling elements are organised into declarations (e.g., variables, constants, etc.) or collections (e.g., invariants, axioms). For each declaration, the input is a comma-separated list of elements. For each collection, the input is a newly(`\`)-separated list of elements.

```

112 \newcommand{\carriersets}[1]{
113   \B@declaration{sets}{#1}
114 }
115 \newcommand{\constants}[1]{
116   \B@declaration{constants}{#1}
117 }
118 \newcommand{\axioms}[2][]{
119   \B@section{#1}{axioms}{#2}
120 }

```

```

121 \newcommand{\variables}[1]{
122   \B@declaration{variables}{#1}
123 }

124 \newcommand{\invariants}[2][ ]{
125   \B@section[#1]{invariants}{#2}
126 }

127 \newcommand{\variant}[1]{
128   \B@declaration{variant}{#1}
129 }

```

Event-B keywords We define the keywords for pretty-print Event-B models.

```

130 \newcommand{\Bany}{\B@keyword{any}}
131 \newcommand{\Bbegin}{\B@keyword{begin}}
132 \newcommand{\Bend}{\B@keyword{end}}
133 \newcommand{\Brefines}{\B@keyword{refines}}
134 \newcommand{\Bstatus}{\B@keyword{status}}
135 \newcommand{\Bthen}{\B@keyword{then}}
136 \newcommand{\Bwhen}{\B@keyword{when}}
137 \newcommand{\Bwhere}{\B@keyword{where}}
138 \newcommand{\Bwith}{\B@keyword{with}}

```

Event-B modelling elements We define several macros for pretty-print Event-B modelling elements.

```

139 \newcommand{\Bctx}[1]{\ensuremath{\mathbf{#1}}\xspace}
140 \newcommand{\Bset}[1]{\Bidentifier{#1}}
141 \newcommand{\Bcst}[1]{\Bidentifier{#1}}
142 \newcommand{\Baxm}[1]{\Blabel{#1}}
143 \newcommand{\Bthm}[1]{\Blabel{thm}{#1}}
144
145 \newcommand{\Bmch}[1]{\ensuremath{\mathbf{#1}}\xspace}
146 \newcommand{\Bvrb}[1]{\Bidentifier{#1}}
147 \newcommand{\Binv}[1]{\Blabel{#1}}
148 \newcommand{\Bevt}[1]{\Blabel{#1}}
149 \newcommand{\Bpar}[1]{\Bidentifier{#1}}
150 \newcommand{\Bact}[1]{\Blabel{#1}}
151 \newcommand{\Bgrd}[1]{\Blabel{#1}}
152 \newcommand{\Bbap}[1]{\hbox{\sl\bfseries #1}}

```

Meta-macros for creating macros for modelling elements We define meta-macros to create macros for different modelling elements.

```

153 \newcommand{\B@newmacro}[3][ ]{
154   \ifstrequal{#1}{\B@newmacro}{#2}{\B@newmacro}{#3}{#2}}
155   \expandafter\def\csname #2\endcsname{#3{#2}}
156 }{
157   \expandafter\def\csname #1\endcsname{#3{#2}}
158 }
159 }

160 \newcommand{\newBctx}[2][ ]{\B@newmacro{#1}{#2}{\Bctx}}
161 \newcommand{\newBset}[2][ ]{\B@newmacro{#1}{#2}{\Bset}}
162 \newcommand{\newBcst}[2][ ]{\B@newmacro{#1}{#2}{\Bcst}}

```

```

163 \newcommand{\newBaxm}[2] [] {\B@newmacro[#1]{#2}{\Baxm}}
164 \newcommand{\newBthm}[2] [] {\B@newmacro[#1]{#2}{\Bthm}}
165 \newcommand{\newBmch}[2] [] {\B@newmacro[#1]{#2}{\Bmch}}
166 \newcommand{\newBvrb}[2] [] {\B@newmacro[#1]{#2}{\Bvrb}}
167 \newcommand{\newBinvt}[2] [] {\B@newmacro[#1]{#2}{\Binvt}}
168 \newcommand{\newBevt}[2] [] {\B@newmacro[#1]{#2}{\Bevt}}
169 \newcommand{\newBpar}[2] [] {\B@newmacro[#1]{#2}{\Bpar}}
170 \newcommand{\newBgrd}[2] [] {\B@newmacro[#1]{#2}{\Bgrd}}
171 \newcommand{\newBact}[2] [] {\B@newmacro[#1]{#2}{\Bact}}
172
173 %%%% Theorem Proof Obligation
174 %%%% Print the theorem proof obligation, given the theorem label.
175 %%%% Arguments:
176 %%%% 1. Theorem label
177 %%%%
178 %%%% Usage:
179 %%%% - \thmpo{thm} will produce "thm/THM"
180 \newcommand{\thmpo}[1]{\Bthm[#1]/\Bpo{THM}}
181
182 %%%% Axiom Well-definedness Proof Obligation
183 %%%% Print the axiom well-definedness proof obligation, given the
184 %%%% axiom label.
185 %%%% Arguments:
186 %%%% 1. Axiom label
187 %%%%
188 %%%% Usage:
189 %%%% - \axmwdpo{axm} will produce "axm/WD"
190 \newcommand{\axmwdpo}[1]{\Baxm[#1]/\Bpo{WD}}
191
192 %%%% Invariant Proof Obligation
193 %%%% Print the invariant proof obligation, given the event name and
194 %%%% invariant label
195 %%%% Arguments:
196 %%%% 1. Event name
197 %%%% 2. Invariant label
198 %%%%
199 %%%% Usage:
200 %%%% - \invpo{evt}{inv} will produce "evt/inv/INV"
201 \newcommand{\invpo}[2]{\Bevt[#1]/\Binvt[#2]/\Bpo{INV}}
202
203 %%%% Theorem (in guard) Proof Obligation
204 %%%% Print the simulation proof obligation, given the event name and
205 %%%% the theorem (in guard) label.
206 %%%% Arguments:
207 %%%% 1. Event name
208 %%%% 2. Theorem (in guard) label
209 %%%%
210 %%%% Usage:
211 %%%% - \grdthmpo{evt}{thm} will produce "evt/thm/THM"

```

```

212 \newcommand{\grdthmpo}[2]{\Bevt{#1}/\Bthm{#2}/\Bpo{THM}}
213
214 %%%% Feasibility Proof Obligation
215 %%%% Print the feasibility proof obligation, given the event name and
216 %%%% the action label
217 %%%% Arguments:
218 %%%% 1. Event name
219 %%%% 2. Action label
220 %%%%
221 %%%% Usage:
222 %%%% - \fispo{evt}{act} will produce "evt/act/FIS"
223 \newcommand{\fispo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{FIS}}
224
225 %%%% Variant finiteness Proof Obligation
226 %%%% Print the Variant finiteness proof obligation
227 %%%% Arguments: No arguments
228 %%%%
229 %%%% Usage:
230 %%%% - \finpo will produce "FIN"
231 \newcommand{\finpo}{\Bpo{FIN}}
232
233 %%%% Variant Proof Obligation
234 %%%% Print the guard strengthen proof obligation, given the event name
235 %%%% Arguments:
236 %%%% 1. Event name
237 %%%%
238 %%%% Usage:
239 %%%% - \grdpo{evt} will produce "evt/VAR"
240 \newcommand{\varpo}[1]{\Bevt{#1}/\Bpo{VAR}}
241
242 %%%% Simulation Proof Obligation
243 %%%% Print the simulation proof obligation, given the event name and
244 %%%% the action label.
245 %%%% Arguments:
246 %%%% 1. Event name
247 %%%% 2. Action label
248 %%%%
249 %%%% Usage:
250 %%%% - \simpo{evt}{act} will produce "evt/act/SIM"
251 \newcommand{\simpo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{SIM}}
252
253 %%%% Guard Strengthen Proof Obligation
254 %%%% Print the guard strengthen proof obligation, given the event
255 %%%% name and the guard label
256 %%%% Arguments:
257 %%%% 1. (Abstract) Event name
258 %%%% 2. (Abstract) Guard label
259 %%%%
260 %%%% Usage:
261 %%%% - \grdpo{evt}{grd} will produce "evt/grd/GRD"
262 \newcommand{\grdpo}[2]{\Bevt{#1}/\Bgrd{#2}/\Bpo{GRD}}
263

```

```

264 %%%% Variant Natural Number Proof Obligation
265 %%%% Print the Variant Natural Number proof obligation, given the event name
266 %%%% Arguments:
267 %%%% 1. Event name
268 %%%%
269 %%%% Usage:
270 %%%% - \natpo{evt} will produce "evt/NAT"
271 \newcommand{\natpo}[1]{\Bevt{#1}/\Bpo{NAT}}
272
273 \newcommand{\B@keywordbase}[1]{\mathbf{#1}}
274 \newcommand{\B@identifier}[1]{\mathit{#1}}
275 \newcommand{\B@label}[2][]{
276   \ifstrequal{#1}{}{
277     \mathsf{#2}
278   }{
279     \mathit{#2}
280   }
281 }
282
283
284
285 \newcommand{\eventinline}[7][]{
286   \setlength{\B@oldfboxsep}{\fboxsep}
287   \setlength{\fboxsep}{2ex}
288   \fbox{
289     \ensuremath{
290       \B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
291     }
292   }
293   \setlength{\fboxsep}{\B@oldfboxsep}
294 }
295
296
297 \newcommand{\B@declarationbase}[2]{
298   \begin{array}{l@{\B@tab}l}
299     \B@keyword{#1:} & #2
300   \end{array}
301 }
302
303 \newcommand{\B@sectionbase}[3][]{
304   \ifstrequal{#1}{}{
305     \begin{array}{l}
306       \B@keyword{#2:} \\
307       \begin{array}{l@{\B@tab}l}
308         #3
309       \end{array}
310     \end{array}
311   }{
312     \begin{array}{l@{\B@tab}l}
313       #3
314     \end{array}
315   }
316 }
317

```



```

318 \newcommand{\B@po}[1]{\ensuremath{\mathsf{\#1}}\xspace}
319
320 %%%% (BEGIN) Macros for Pretty-Print Event-B Components %%
321 \newcommand{\SKIP}{\textsc{skip}}
322
323
324 %%%% Pretty print an general Event-B event
325 %%%% Arguments:
326 %%%% 1. (Optional) convergence status.
327 %%%% 2. Name of the event.
328 %%%% 3. Name of the abstract event.
329 %%%% 4. (Comma-separated) list of parameters.
330 %%%% 5. (Newline\\)-separated list of guards.
331 %%%% 6. (Newline\\)-separated list of witness predicates.
332 %%%% 7. (Newline\\)-separated list of assignments.
333 %%%%
334 %%%% Usage: \B@event[conv]{conc}{abs}{x,y}{G1(x,y)\G2(x,y)}{W1\\W2}{S1(v,x,y)\S2(w,x,y)}
335 %%%% will produce the following
336 %%%%
337 %%%% conc
338 %%%% refines abs
339 %%%% status conv
340 %%%% any x, y where
341 %%%% G1(x, y)
342 %%%% G2(x, y)
343 %%%% with
344 %%%% W1
345 %%%% W2
346 %%%% then
347 %%%% S1(v, x, y)
348 %%%% S2(w, x, y)
349 %%%% end
350 %%%%
351 %%%% Special case:
352 %%%% - Empty abstract event --> refines clause is omitted.
353 %%%% - Empty convergence status --> status clause is omitted.
354 %%%% - Empty witness --> with clause is omitted.
355 %%%% - Empty parameters, empty guards --> begin ... end
356 %%%% - Empty parameters --> when ... then ... end
357 %%%% - Empty actions --> \SKIP
358 \newcommand{\B@ifstrequal}{\expandafter\ifstrequal\expandafter}
359 \newcommand{\B@event}[7][]{%
360 { % BEGIN group
361 \newcommand\evt@sts{\#1}% Event status
362 \newcommand\evt@label{\#2}% Event label
363 \newcommand\evt@absevt{\#3}% Abstract event
364 \newcommand\evt@pars{\#4}% Event parameters
365 \newcommand\evt@grds{\#5}% Event guards
366 \newcommand\evt@wits{\#6}% Event witnesses
367 \newcommand\evt@acts{\#7}% Event actions
368 %% Pretty-print convergence status
369 \B@ifstrequal{\evt@sts}{%
370 \newcommand\pretty@sts{}

```

```

371   }{
372     \newcommand\pretty@sts{\B@tab\Bstatus \B@tab \evt@sts \\\}
373   }
374   % Pretty-print abstract events
375   \B@ifstrequal{\evt@absevt}{-}{
376     \newcommand\pretty@absevt{
377   }{
378     \newcommand\pretty@absevt{\B@tab\Brefines \B@tab \evt@absevt} \\\}%
379   }
380   % Pretty-print parameters
381   \B@ifstrequal{\evt@pars}{-}{
382     \newcommand\pretty@pars{
383   }{
384     \newcommand\pretty@pars{\B@tab\Bany \B@tab \evt@pars \B@tab \Bwhere \\\}
385   }
386   % Pretty-print guards
387   \B@ifstrequal{\evt@grds}{-}{
388     \newcommand\pretty@grds{
389   }{
390     \newcommand\pretty@grds@tmp{
391       \begin{array}{@{\B@tab\B@tab}l@{\B@tab}l}
392         \evt@grds
393       \end{array}\\
394     }
395     \B@ifstrequal{\evt@pars}{-}{
396       \newcommand\pretty@grds{
397         \B@tab \Bwhen \\\
398         \pretty@grds@tmp
399       }
400     }{
401       \newcommand\pretty@grds{\pretty@grds@tmp}
402     }
403   }
404   % Pretty-print witnesses
405   \B@ifstrequal{\evt@wits}{-}{
406     \newcommand\pretty@wits{
407   }{
408     \newcommand\pretty@wits{
409       \B@tab\Bwith\\
410       \begin{array}{@{\B@tab\B@tab}ll}
411         \evt@wits
412       \end{array}\\
413     }
414   }
415   % Pretty-print actions
416   \B@ifstrequal{\evt@acts}{-}{
417     \renewcommand\evt@acts{\SKIP}
418   }{}
419   \newcommand\pretty@acts@tmp{
420     \begin{array}{@{\B@tab\B@tab}l@{\B@tab}l}
421       \evt@acts
422     \end{array}\\
423   }
424   \newcommand\pretty@acts@keyword{\B@tab\Bthen \\\}

```

```

425 \B@ifstrequal{\evt@pars}{-}{-}{
426 \B@ifstrequal{\evt@grds}{-}{-}{
427 \renewcommand\pretty@acts@keyword{\B@tab\Bbegin \\\}
428 }{-}{
429 }{-}{
430 \newcommand\pretty@acts{
431 \pretty@acts@keyword
432 \pretty@acts@tmp
433 }
434 % Really do it now
435 \begin{array}{l}
436 \Bvt{\evt@label} \\\
437 \pretty@sts
438 \pretty@absevs
439 \pretty@pars
440 \pretty@grds
441 \pretty@wits
442 \pretty@acts
443 \B@tab\Bend
444 \end{array}
445 } % END group
446 }
447
448 %%%% Pretty print an general Event-B event
449 %%%% Arguments:
450 %%%% 1. (Optional) convergence status.
451 %%%% 2. Name of the event.
452 %%%% 3. Name of the abstract event.
453 %%%% 4. (Comma-separated) list of parameters.
454 %%%% 5. (\land-separated) list of guards.
455 %%%% 6. (\land-separated) list of witness predicates.
456 %%%% 7. (||-separated) list of assignments.
457 %%%%
458 %%%% Usage: \B@eventinline[conv]{conc}{abs}{x,y}{G1 \land G2}{W1 \land W2}{S1 || S2}
459 %%%% will produce the following
460 %%%%
461 %%%% conc (conv) refines abs = any x,y where G1 \land G2 with W1 \land W2 then S1 || S2 end
462 %%%%
463 %%%% Special case:
464 %%%% - Empty abstract event --> refines clause is omitted.
465 %%%% - Empty convergence status --> status clause is omitted.
466 %%%% - Empty witness --> with clause is omitted.
467 %%%% - Empty parameters, empty guards --> begin ... end
468 %%%% - Empty parameters --> when ... then ... end
469 %%%% - Empty actions --> \SKIP
470 \newcommand{\B@eventinline}[7][]{
471 { % BEGIN group
472 \newcommand\evt@sts{#1}% Event status
473 \newcommand\evt@label{#2}% Event label
474 \newcommand\evt@absevs{#3}% Abstract event
475 \newcommand\evt@pars{#4}% Event parameters
476 \newcommand\evt@grds{#5}% Event guards
477 \newcommand\evt@wits{#6}% Event witnesses
478 \newcommand\evt@acts{#7}% Event actions

```

```

479 %% Pretty-print convergence status
480 \B@ifstrequal{\evt@sts}{}{
481   \newcommand\pretty@sts{
482 }{
483   \newcommand\pretty@sts{(\evt@sts)}
484 }
485 % Pretty-print abstract events
486 \B@ifstrequal{\evt@absevt}{}{
487   \newcommand\pretty@absevt{
488 }{
489   \newcommand\pretty@absevt{~\Brefines~\evt@absevt}
490 }
491 % Pretty-print parameters
492 \B@ifstrequal{\evt@pars}{}{
493   \newcommand\pretty@pars{
494 }{
495   \newcommand\pretty@pars{\Bany~\evt@pars~\Bwhere~}
496 }
497 % Pretty-print guards
498 \B@ifstrequal{\evt@grds}{}{
499   \newcommand\pretty@grds{
500 }{
501   \newcommand\pretty@grds@tmp{
502     \evt@grds~
503   }
504   \B@ifstrequal{\evt@pars}{}{
505     \Bwhen~\pretty@grds@tmp
506   }{
507     \newcommand\pretty@grds{\pretty@grds@tmp}
508   }
509 }
510 % Pretty-print witnesses
511 \B@ifstrequal{\evt@wits}{}{
512   \newcommand\pretty@wits{
513 }{
514   \newcommand\pretty@wits{
515     \Bwith~
516     \evt@wits~
517   }
518 }
519 % Pretty-print actions
520 \B@ifstrequal{\evt@acts}{}{
521   \renewcommand\evt@acts{\SKIP}
522 }{}
523 \newcommand\pretty@acts@tmp{
524   \evt@acts
525 }
526 \newcommand\pretty@acts@keyword{\Bthen}
527 \B@ifstrequal{\evt@pars}{}{
528   \B@ifstrequal{\evt@grds}{}{
529     \renewcommand\pretty@acts@keyword{\Bbegin}
530   }{}
531 }{}
532 \newcommand\pretty@acts{

```

```

533 \pretty@acts@keyword~
534 \pretty@acts@tmp~
535 }
536 % Really do it now
537 \begin{array}{l}
538 \Bevt{\evt@label}\pretty@sts\pretty@absepts~\widehat{=}\sim
539 \pretty@pars
540 \pretty@grds
541 \pretty@wits
542 \pretty@acts
543 \Bend
544 \end{array}
545 } % END group
546 }

547 %%%% INITIALISATION label
548 \newBevt{init}
549
550 %%%% Pretty print the initialisation: no ‘refines’ clause. no parameters, no
551 %%%% guards
552 %%%% Arguments:
553 %%%% 1. (Newline(\))-separated) list of assignments.
554 %%%%
555 %%%% Usage: \init{S1(v,x,y)\S2(w,x,y)}
556 %%%% will produce the following
557 %%%%
558 %%%% init
559 %%%% begin
560 %%%% S1(v, x, y)
561 %%%% S2(w, x, y)
562 %%%% end
563 %%%%
564 \newcommand{\initialisation}[1]{
565 \event{\init}{-}{-}{-}{-}{#1}
566 }
```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in **roman** refer to the code lines where the entry is used.

Symbols	A	\B@fontsize
\ 54, 60, 66, 73, 306,	\axioms 118	53, 59, 65, 72, 111
330–332, 334,	\axmwdpo 189, 190	\B@identifier 80, 96, 274
372, 378, 384,	B	\B@ifstrequal
393, 397, 409,	\B@declaration 17, 44,	. 358, 369, 375,
412, 422, 424,	113, 116, 122, 128	381, 387, 395,
427, 436, 553, 555	\B@declarationbase .	405, 416, 425,
 22, 45, 297	426, 480, 486,
	\B@event 11, 41, 334, 359	492, 498, 504,
	\B@eventinline	511, 520, 527, 528
_ 62, 68, 75 290, 458, 470	\B@keyword . . 79, 92,

130–138, 299, 306	\Bvrb 146, 166	\fboxsep . . . 7, 8, 14,
\B@keywordbase	\Bvspace . . 54, 60, 66, 73	18, 19, 25, 29,
. 79, 93, 273	\Bwhen 136, 397, 505	30, 36, 286, 287, 293
\B@label 81, 99, 275	\Bwhere 137, 384, 495	\finpo 230, 231
\B@newmacro 153, 160–171	\Bwith 138, 409, 515	\fispo 222, 223
\B@oldfboxsep		\footnotesize 65
. 5, 7, 14, 18,	C	
25, 29, 36, 286, 293	\carriersets 112	G
\B@po 82, 102, 318	\colorlet . . . 84, 86, 88, 90	\grdpo 239, 261, 262
\B@section	\constants 115	\grdthmpo 211, 212
. 28, 48, 119, 125	\csname 155, 157	
\B@sectionbase		H
. 33, 49, 303	D	\hbox 152
\B@tab 56,	\DeclareOption . . 39,	\hspace 55, 61, 67, 74
62, 68, 75, 298,	58, 64, 71, 83, 105	
307, 312, 372,	\def 155, 157	I
378, 384, 391,		\ifstrequal
397, 409, 410,	E 154, 276, 304, 358
420, 424, 427, 443	\end 111, 300, 309,	\init 555, 565
\Bact 150, 171, 223, 251	310, 314, 393,	\initialisation . . . 564
\Bany 130, 384, 495	412, 422, 444, 544	\invariants 124
\Baxm 142, 163, 190	\endcsname 155, 157	\invpo 200, 201
\Bbap 152	\ensuremath 10,	
\Bbegin 131, 427, 529	21, 32, 79–82,	L
\Bcst 141, 162	93, 96, 99, 102,	\land 454, 455, 458, 461
\Bctx 139, 160	139, 145, 289, 318	
\begin 111, 298, 305,	\event 6, 40, 565	M
307, 312, 391,	\eventB 110	\mathbf 139, 145, 273
410, 420, 435, 537	\eventinline 285	\mathit 274, 279
\Bend 132, 443, 543	\evt@absevt 363, 375,	\mathsf 277, 318
\Bevt 148,	378, 474, 486, 489	
168, 201, 212,	\evt@acts 367,	N
223, 240, 251,	416, 417, 421,	\natpo 270, 271
262, 271, 436, 538	478, 520, 521, 524	\newBact 171
\bfseries 152	\evt@grds 365,	\newBaxm 163
\Bgrd 151, 170, 262	387, 392, 426,	\newBcst 162
\Bhspace 55, 61, 67, 74	476, 498, 502, 528	\newBctx 160
\Bidentifier . . 80, 95,	\evt@label	\newBevt 168, 548
140, 141, 146, 149 362, 436, 473, 538	\newBgrd 170
\Bin 147, 167, 201	\evt@pars	\newBin 167
\Blabel 364, 381, 384,	\newBmch 165
81, 98, 142, 143,	395, 425, 475,	\newBpar 169
147, 148, 150, 151	492, 495, 504, 527	\newBset 161
\Bmch 145, 165	\evt@sts 361, 369,	\newBthm 164
\Bpar 149, 169	372, 472, 480, 483	\newBvrb 166
\Bpo 82, 101,	\evt@wits 366, 405,	\newcommand 6, 17, 28,
180, 190, 201,	411, 477, 511, 516	53–56, 79–82,
212, 223, 231,	\ExecuteOptions . . .	84, 86, 88, 90,
240, 251, 262, 271 69, 76, 106	110, 112, 115,
\Brefines 133, 378, 489	\expandafter	118, 121, 124,
\Bset 140, 161 155, 157, 358	127, 130–143,
\Bstatus 134, 372		145–153, 160–
\Bthen 135, 424, 526	F	171, 180, 190,
\Bthm 143, 164, 180, 212	\fbox 9, 20, 31, 288	201, 212, 223,
		231, 240, 251,

262, 271, 273–	\pretty@grds	\setBKeywordColour .
275, 285, 297,	. 388, 396, 401, 84, 85
303, 318, 321,	440, 499, 507, 540	\setBLabelColour 88, 89
358, 359, 361–	\pretty@grds@tmp . .	\setBPOColour . . . 90, 91
367, 370, 372, 390, 398,	\setlength . 7, 8, 14,
376, 378, 382,	401, 501, 505, 507	18, 19, 25, 29,
384, 388, 390,	\pretty@pars 382, 384,	30, 36, 286, 287, 293
396, 401, 406,	439, 493, 495, 539	\simpo 250, 251
408, 419, 424,	\pretty@sts 370, 372,	\SKIP 321,
430, 470, 472–	437, 481, 483, 538	357, 417, 469, 521
478, 481, 483,	\pretty@wits 406, 408,	\sl 152
487, 489, 493,	441, 512, 514, 541	\small 59
495, 499, 501,	\ProcessOptions . . . 109	
507, 512, 514,		T
523, 526, 532, 564	Q	\textcolor 93, 96, 99, 102
\newenvironment . . . 111	\quad 56	\textsc 321
\newlength 5		\thmpo 179, 180
\normalsize 53	R	V
P	\renewcommand . . 40,	\variables 121
\pretty@absepts . . .	44, 48, 59–62,	\variant 127
. . . . 376, 378,	65–68, 72–75,	\varpo 240
438, 487, 489, 538	92, 95, 98, 101,	
\pretty@acts	417, 427, 521, 529	W
. 430, 442, 532, 542	\RequirePackage . . . 1–4	\widehat 538
\pretty@acts@keyword		X
. . . . 424, 427,	S	\xspace 79–82,
431, 526, 529, 533	\scriptsize 72	93, 96, 99, 102,
\pretty@acts@tmp . .	\setBIdentifierColour	110, 139, 145, 318
. 419, 432, 523, 534 86, 87	

Change History

v1.0	v1.1
General: Initial version 1	General: Re-implement how options are defined, added options 'box' 1
v1.0.1	v1.1.1
General: Ensure that the keywords, labels are in math-mode 1	General: Updated documentation . 1