

# The `eventB` package\*

Thai Son Hoang  
ETH-Zurich  
<htson at inf dot ethz dot ch>

July 3, 2012

## Abstract

This class provides a template for typesetting Event-B models. It was developed at the Swiss Federal Institute of Technology Zurich (ETH-Zurich).

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Usage</b>	<b>1</b>
<b>3</b>	<b>Implementation</b>	<b>1</b>

## 1 Introduction

This package was developed in order to ease the typesetting of Event-B models in L<sup>A</sup>T<sub>E</sub>X.

## 2 Usage

## 3 Implementation

We load the standard `article` class and pass option 10pt to it.

```
%%%% BEGIN Package loading %%%%\n\\RequirePackage{xspace}\n\\RequirePackage{xcolor}\n%%%% END Package loading %%%%\n\n%%%% Keywords can be coloured by package option "color"\n\\newcommand{\\Bkeyword}[1]{\\B@keyword{#1}}\n\\newcommand{\\Bidentifier}[1]{\\B@identifier{#1}}\n\\newcommand{\\Blabel}[2][ ]{\\B@label{#1}{#2}}\n\\newcommand{\\Bpo}[1]{\\B@po{#1}}\n\\newcommand{\\Bvspace}[1][2ex]{\\[\\[#1]}
```

---

\*This document corresponds to `eventB` ?, dated ?.

```

\newcommand{\Bhspace}[1][2em]{\hspace{#1}}
\newcommand{\Bsep}{\quad}
\DeclareOption{color}{
  \colorlet{Bkeywordcolor}{blue}
  \colorlet{Blabelcolor}{green!50!black}
  \colorlet{Bpocolor}{red}
  %%%% Keywords are coloured.
  \renewcommand{\Bkeyword}[1]{\textcolor{Bkeywordcolor}{\B@keyword{#1}}}
  \renewcommand{\Blabel}[2][]{\textcolor{Blabelcolor}{\B@label[1]{#2}}}
  \renewcommand{\Bpo}[1]{\textcolor{Bpocolor}{\B@po{#1}}}
}
\DeclareOption{colour}{
  \colorlet{Bkeywordcolor}{blue}
  \colorlet{Blabelcolor}{green!50!black}
  \colorlet{Bpocolor}{red}
  %%%% Keywords are coloured.
  \renewcommand{\Bkeyword}[1]{\textcolor{Bkeywordcolor}{\B@keyword{#1}}}
  \renewcommand{\Blabel}[2][]{\textcolor{Blabelcolor}{\B@label[1]{#2}}}
  \renewcommand{\Bpo}[1]{\textcolor{Bpocolor}{\B@po{#1}}}
}

\newcommand{\B@keyword}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\B@identifier}[1]{\ensuremath{\mathit{#1}}\xspace}
\newcommand{\B@label}[2][]{
  \def\is@thm{#1}
  \ifx\is@thm\@empty
    \ensuremath{\mathsf{#2}}\xspace
  \else
    \ensuremath{\mathit{#2}}\xspace
  \fi
}

%%%% Bcode environment %%%%
%%%% the same as ‘center’ %%%%
\newenvironment{Bcode}[1][\normalsize]{\begin{center}#1{\end{center}}}
\newcommand{\Bdeclaration}[2]{
  \fbox{
    \ensuremath{
      \B@declaration{#1}{#2}
    }
  }
}

\newcommand{\Bsection}[3][]{
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@section[1]{#2}{#3}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

```

```

\newcommand{\event}[7] [] {
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

\newcommand{\eventinline}[7] [] {
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

\DeclareOption{compact}{
  \renewenvironment{Bcode}[1] [\footnotesize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3] [] {
    \B@section[#1]{#2}{#3}
  }

  \renewcommand{\event}[7] [] {
    \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
  }

  \renewcommand{\eventinline}[7] [] {
    \B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
  }

  \renewcommand{\Bvspace}[1] [0ex]{\\[#1]}
  \renewcommand{\Bhspace}[1] [0.5em]{\hspace{#1}}
  \renewcommand{\Bsep}{\ }
}

\DeclareOption{small}{
  \renewenvironment{Bcode}[1] [\footnotesize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bvspace}[1] [1ex]{\\[#1]}
  \renewcommand{\Bhspace}[1] [1em]{\hspace{#1}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3] [] {
    \B@section[#1]{#2}{#3}
  }
}

```

```

}

\renewcommand{\event}[7][]{
  \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}
\renewcommand{\eventinline}[7][]{
  \B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}

\renewcommand{\Bsep}{\ }

}

\DeclareOption{tiny}{
  \renewenvironment{Bcode}[1][\scriptsize]{\begin{center}#1{\end{center}}}
  \renewcommand{\Bvspace}[1][-0.5ex]{\\[#1]}
  \renewcommand{\Bhspace}[1][0.5em]{\hspace{#1}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3][]{
    \B@section[#1]{#2}{#3}
  }

  \renewcommand{\event}[7][]{
    \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
  }
  \renewcommand{\eventinline}[7][]{
    \B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
  }

  \renewcommand{\Bsep}{\ }

}

\newcommand{\B@declaration}[2]{
  \begin{array}{l@{\Bsep}l}
    \Bkeyword{#1:} & #2 \\
  \end{array}
}
\newlength{\B@oldfboxsep}
\newcommand{\B@section}[3][]{
  \def\no@title{#1}
  \ifx\no@title\@empty
  \begin{array}{l}
    \Bkeyword{#2:} \\
    \begin{array}{l@{\Bsep}l}
      #3 \\
    \end{array}
  \end{array}
  \else
  \begin{array}{l@{\Bsep}l}
    #3 \\
  \end{array}
  \end{array}

```

```

\fi
}

\newcommand{\B@po}[1]{\ensuremath{\mathsf{#1}}\xspace}

%%%% BEGIN Execution of options %%%
\ProcessOptions
%%%% END Execution of options %%%

%%%% (BEGIN) Macros for Pretty-Print Event-B Components %%
\newcommand{\eventB}{Event-B\xspace}
\newcommand{\SKIP}{\textsc{skip}}

%%%% Event-B Keywords %%%
\newcommand{\Bany}{\Bkeyword{any}}
\newcommand{\Bbegin}{\Bkeyword{begin}}
\newcommand{\Bend}{\Bkeyword{end}}
\newcommand{\Brefines}{\Bkeyword{refines}}
\newcommand{\Bstatus}{\Bkeyword{status}}
\newcommand{\Bthen}{\Bkeyword{then}}
\newcommand{\Bwhen}{\Bkeyword{when}}
\newcommand{\Bwhere}{\Bkeyword{where}}
\newcommand{\Bwith}{\Bkeyword{with}}

%%%% Event-B internal elements %%%
\newcommand{\Bctx}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\Bset}[1]{\Bidentifier{#1}}
\newcommand{\Bcst}[1]{\Bidentifier{#1}}
\newcommand{\Baxm}[1]{\Blabel{#1}}
\newcommand{\Bthm}[1]{\Blabel{thm}{#1}}

\newcommand{\Bmch}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\Bvrb}[1]{\Bidentifier{#1}}
\newcommand{\Binv}[1]{\Blabel{#1}}
\newcommand{\Bevt}[1]{\Blabel{#1}}
\newcommand{\Bpar}[1]{\Bidentifier{#1}}
\newcommand{\Bact}[1]{\Blabel{#1}}
\newcommand{\Bgrd}[1]{\Blabel{#1}}
\newcommand{\Bbap}[1]{\hbox{\sl\bfseries #1}}
%%
%%%% Creating Event-B elements macros %%%

%%%% Create a new B macro
%%%% Arguments:
%%%% 1. The macro string, (OPTIONAL) if empty then the expanded string will be used.
%%%% 2. The expanded string
%%%% 3. The mark-up macros, e.g. \Bvrb
%%%% Usage:
%%%% - \B@newmacro[aaa]{a\_a\_a}{\Bvrb} will create a new macro \aaa
%%%% which will be expanded to be \Bvrb{a\_a\_a}
%%%% - \B@newmacro{aaa}{\Bvrb} will create a new macro \aaa
%%%% which will be expanded to be \Bvrb{aaa}
%%

```

```

\newcommand{\B@newmacro}[3][]{
  \def\input@macro{#1}
  \ifx\input@macro\empty
  \expandafter\def\csname #2\endcsname{#3{#2}}
  \else
  \expandafter\def\csname #1\endcsname{#3{#2}}
  \fi
}

%% Create a new context macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBctx[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bctx{a\_a\_a}.
%% - \newBctx{aaa} will create a new macro \aaa which will be
%% expanded to be \Bctx{aaa}.
%%
\newcommand{\newBctx}[2][]{%
  \B@newmacro[#1]{#2}{\Bctx}
}

%% Create a new carrier set macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBset[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bset{a\_a\_a}.
%% - \newBset{aaa} will create a new macro \aaa which will be
%% expanded to be \Bset{aaa}.
%%
\newcommand{\newBset}[2][]{%
  \B@newmacro[#1]{#2}{\Bset}
}

%% Create a new constant macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBcst[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bcst{a\_a\_a}.
%% - \newBcst{aaa} will create a new macro \aaa which will be
%% expanded to be \Bcst{aaa}.
%%
\newcommand{\newBcst}[2][]{%
  \B@newmacro[#1]{#2}{\Bcst}
}

%% Create a new axiom macro
%% Arguments:

```

```

%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBaxm[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Baxm{a\_a\_a}.
%%%%%%%% - \newBaxm{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Baxm{aaa}.
%%%%%%%%
\newcommand{\newBaxm}[2][]{%
  \B@newmacro[#1]{#2}{\Baxm}
}

%%%%%%%% Create a new theorem macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBthm[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bthm{a\_a\_a}.
%%%%%%%% - \newBthm{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bthm{aaa}.
%%%%%%%%
\newcommand{\newBthm}[2][]{%
  \B@newmacro[#1]{#2}{\Bthm}
}

%%%%%%%% Create a new machine macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBmch[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bmch{a\_a\_a}.
%%%%%%%% - \newBmch{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bmch{aaa}.
%%%%%%%%
\newcommand{\newBmch}[2][]{%
  \B@newmacro[#1]{#2}{\Bmch}
}

%%%%%%%% Create a new variable macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBvrb[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bvrb{a\_a\_a}.
%%%%%%%% - \newBvrb{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bvrb{aaa}.
%%%%%%%%
\newcommand{\newBvrb}[2][]{%
  \B@newmacro[#1]{#2}{\Bvrb}
}

```

```

%%%%%%%% Create a new invariant macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBinv[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Binv{a\_a\_a}.
%%%%%%%% - \newBinv{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Binv{aaa}.
%%%%%%%%
\newcommand{\newBinv}[2][]{%
  \B@newmacro[#1]{#2}{\Binv}
}

```

```

%%%%%%%% Create a new event macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBevt[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bevt{a\_a\_a}.
%%%%%%%% - \newBevt{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bevt{aaa}.
%%%%%%%%
\newcommand{\newBevt}[2][]{%
  \B@newmacro[#1]{#2}{\Bevt}
}

```

```

%%%%%%%% Create a new parameter macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBpar[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bpar{a\_a\_a}.
%%%%%%%% - \newBpar{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bpar{aaa}.
%%%%%%%%
\newcommand{\newBpar}[2][]{%
  \B@newmacro[#1]{#2}{\Bpar}
}

```

```

%%%%%%%% Create a new guard macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBgrd[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bgrd{a\_a\_a}.
%%%%%%%% - \newBgrd{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bgrd{aaa}.
%%%%%%%%

```



```

\newcommand{\newBgrd}[2][]{%
  \B@newmacro[#1]{#2}{\Bgrd}
}

%%%%%%%% Create a new action macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBact[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bact{a\_a\_a}.
%%%%%%%% - \newBact{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bact{aaa}.
%%%%%%%%
\newcommand{\newBact}[2][]{%
  \B@newmacro[#1]{#2}{\Bact}
}

%%%%%%%% Pretty print carrier sets
%%%%%%%% Arguments:
%%%%%%%% 1. (Comma-separated) list of carrier sets.
%%%%%%%%
%%%%%%%% Usage: \carriersets{S, T}
\newcommand{\carriersets}[1]{
  \Bdeclaration{sets}{#1}
}

%%%%%%%% Pretty print constants
%%%%%%%% Arguments:
%%%%%%%% 1. (Comma-separated) list of constants.
%%%%%%%%
%%%%%%%% Usage: \constants{m, n}
\newcommand{\constants}[1]{
  \Bdeclaration{constants}{#1}
}

%%%%%%%% Pretty print axioms
%%%%%%%% Arguments:
%%%%%%%% 1. (Newline(\))-separated list of axioms.
%%%%%%%%
%%%%%%%% Usage: \axioms{\Baxm{axm0\_1}: & x \in \nat \\\
%%%%%%%%           \Baxm{axm0\_2}: & y \in \nat \\[2ex]}
\newcommand{\axioms}[2][]{
  \Bsection[#1]{axioms}{#2}
}

%%%%%%%% Pretty print variables
%%%%%%%% Arguments:
%%%%%%%% 1. (Comma-separated) list of variables.
%%%%%%%%
%%%%%%%% Usage: \variables{x, y}
\newcommand{\variables}[1]{
  \Bdeclaration{variables}{#1}
}

```

```

}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%% Pretty print invariants
%%% Arguments:
%%% 1. (Newline(\\)-separated) list of invariants.
%%%
%%% Usage: \invariants{\Binv{inv0\_1:} & x \in \nat \\
%%%          \Binv{inv0\_2:} & y \in \nat \\[2ex]}
\newcommand{\invariants}[2][]{
  \Bsection[#1]{invariants}{#2}
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%% Pretty print variant
%%% Arguments:
%%% 1. The variant
%%%
%%% Usage: \variant{V}
\newcommand{\variant}[1]{
  \Bdeclaration{variant}{#1}
}

%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%%
%%% Pretty print an general Event-B event
%%% Arguments:
%%% 1. (Optional) convergence status.
%%% 2. Name of the event.
%%% 3. Name of the abstract event.
%%% 4. (Comma-separated) list of parameters.
%%% 5. (Newline(\\)-separated) list of guards.
%%% 6. (Newline(\\)-separated) list of witness predicates.
%%% 7. (Newline(\\)-separated) list of assignments.
%%%
%%% Usage: \B@event[conv]{conc}{abs}{x,y}{G1(x,y)\\G2(x,y)}{W1\\W2}{S1(v,x,y)\\S2(w,x,y)}
%%%          will produce the following
%%%
%%%          conc
%%%          refines abs
%%%          status conv
%%%          any x, y where
%%%             G1(x, y)
%%%             G2(x, y)
%%%          with
%%%             W1
%%%             W2
%%%          then
%%%             S1(v, x, y)
%%%             S2(w, x, y)
%%%          end
%%%
%%% Special case:
%%% - Empty abstract event --> refines clause is omitted.
%%% - Empty convergence status --> status clause is omitted.
%%% - Empty witness --> with clause is omitted.
%%% - Empty parameters, empty guards --> begin ... end

```

```

%% - Empty parameters --> when ... then ... end
%% - Empty actions --> \SKIP
\newcommand{\B@event}[7][]{
  \def\evt@sts{#1}
  \def\evt@name{#2}
  \def\evt@absevs{#3}
  \def\evt@pars{#4}
  \def\evt@grds{#5}
  \def\evt@wits{#6}
  \def\evt@acts{#7}
  %% Pretty-print convergence status
  \ifx\evt@sts\@empty
  \def\pretty@sts{}
  \else
  \def\pretty@sts{\Bsep\Bstatus \Bsep \evt@sts \\\}
  \fi
  % Pretty-print abstract events
  \ifx\evt@absevs\@empty
  \def\pretty@absevs{}
  \else
  \def\pretty@absevs{\Bsep\Brefines \Bsep \evt@absevs \\\}
  \fi
  % Pretty-print parameters
  \ifx\evt@pars\@empty
  \def\pretty@pars{}
  \else
  \def\pretty@pars{\Bsep\Bany \Bsep \evt@pars \Bsep \Bwhere \\\}
  \fi
  % Pretty-print guards
  \ifx\evt@grds\@empty
  \def\pretty@grds{}
  \else
  \def\evt@grds@tmp{
    \begin{array}{@{\Bsep\Bsep}l@{\Bsep}l}
      \evt@grds
    \end{array}
  }
  \ifx\evt@pars\@empty
  \def\pretty@grds{
    \Bsep \Bwhen \\\
    \evt@grds@tmp
  }
  \else
  \def\pretty@grds{\evt@grds@tmp}
  \fi
  \fi
  % Pretty-print witnesses
  \ifx\evt@wits\@empty
  \def\pretty@wits{}
  \else
  \def\pretty@wits{
    \Bsep\Bwith\\\
    \begin{array}{@{\Bsep\Bsep}l}
      \evt@wits

```

```

        \end{array}\\
    }
    \fi
    % Pretty-print actions
    \ifx\evt@acts\@empty
    \def\evt@acts{\SKIP}
    \else
    \fi
    \def\evt@acts@tmp{
        \begin{array}{@{\Bsep\Bsep}l@{\Bsep}l}
        \evt@acts
        \end{array}\\
    }
    \def\evt@acts@keyword{\Bsep\Bthen \\\}
    \ifx\evt@pars\@empty
    \ifx\evt@grds\@empty
    \def\evt@acts@keyword{\Bsep\Bbegin \\\}
    \else
    \fi
    \else
    \fi
    \def\pretty@acts{
        \evt@acts@keyword
        \evt@acts@tmp
    }
    % Really do it now
    \begin{array}{l}
    \Bvt{\evt@name} \\\
    \pretty@sts
    \pretty@absepts
    \pretty@pars
    \pretty@grds
    \pretty@wits
    \pretty@acts
    \Bsep\Bend
    \end{array}
}

```

```

%%%%% Pretty print an general Event-B event
%%%%% Arguments:
%%%%% 1. (Optional) convergence status.
%%%%% 2. Name of the event.
%%%%% 3. Name of the abstract event.
%%%%% 4. (Comma-separated) list of parameters.
%%%%% 5. (Newline(\)-separated) list of guards.
%%%%% 6. (Newline(\)-separated) list of witness predicates.
%%%%% 7. (Newline(\)-separated) list of assignments.
%%%%%
%%%%% Usage: \B@event[conv]{conc}{abs}{x,y}{G1(x,y)\G2(x,y)}{W1\W2}{S1(v,x,y)\S2(w,x,y)}
%%%%%         will produce the following
%%%%%
%%%%%         conc
%%%%%         refines abs
%%%%%         status conv

```

```

%%%%%%%% any x, y where
%%%%%%%% G1(x, y)
%%%%%%%% G2(x, y)
%%%%%%%% with
%%%%%%%% W1
%%%%%%%% W2
%%%%%%%% then
%%%%%%%% S1(v, x, y)
%%%%%%%% S2(w, x, y)
%%%%%%%% end
%%%%%%%%
%%%%%%%% Special case:
%%%%%%%% - Empty abstract event --> refines clause is omitted.
%%%%%%%% - Empty convergence status --> status clause is omitted.
%%%%%%%% - Empty witness --> with clause is omitted.
%%%%%%%% - Empty parameters, empty guards --> begin ... end
%%%%%%%% - Empty parameters --> when ... then ... end
%%%%%%%% - Empty actions --> \SKIP
\newcommand{\B@eventinline}[7][{}]{
  \def\evt@sts{#1}
  \def\evt@name{#2}
  \def\evt@absevt{#3}
  \def\evt@pars{#4}
  \def\evt@grds{#5}
  \def\evt@wits{#6}
  \def\evt@acts{#7}
  %% Ignore convergence status
  \def\pretty@sts{}
  % Pretty-print abstract events
  \ifx\evt@absevt\@empty
  \def\pretty@absevt{}
  \else
  \def\pretty@absevt{\Brefines~\evt@absevt~}
  \fi
  % Pretty-print parameters
  \ifx\evt@pars\@empty
  \def\pretty@pars{}
  \else
  \def\pretty@pars{\Bany~\evt@pars~\Bwhere~}
  \fi
  % Pretty-print guards
  \ifx\evt@grds\@empty
  \def\pretty@grds{}
  \else
  \def\evt@grds@tmp{
    \evt@grds
  }
  \ifx\evt@pars\@empty
  \def\pretty@grds{
    \Bwhen~
    \evt@grds@tmp~
  }
  \else
  \def\pretty@grds{\evt@grds@tmp~}

```

```

\fi
\fi
% Pretty-print witnesses
\ifx\evt@wits\@empty
\def\pretty@wits{}
\else
\def\pretty@wits{
  \Bwith~
  \evt@wits~
}
\fi
% Pretty-print actions
\ifx\evt@acts\@empty
\def\evt@acts{\SKIP}
\else
\fi
\fi
\def\evt@acts@tmp{
  \evt@acts
}
\def\evt@acts@keyword{\Bthen}
\ifx\evt@pars\@empty
\ifx\evt@grds\@empty
\def\evt@acts@keyword{\Bbegin}
\else
\fi
\else
\fi
\fi
\def\pretty@acts{
  \evt@acts@keyword~
  \evt@acts@tmp~
}
% Really do it now
\begin{array}{l}
  \Bevt{\evt@name}~\widehat{=}\sim
  \pretty@sts
  \pretty@absevt
  \pretty@pars
  \pretty@grds
  \pretty@wits
  \pretty@acts
  \Bend
\end{array}
}

%%%%% INITIALISATION label
\newBevt{init}

%%%%% Pretty print the initialisation: no ‘refines’ clause. no parameters, no
%%%%% guards
%%%%% Arguments:
%%%%% 1. (Newline(\\)-separated) list of assignments.
%%%%%
%%%%% Usage: \init{S1(v,x,y)\\S2(w,x,y)}
%%%%% will produce the following

```

```

%%%%%%%%
%%%%%%%% init
%%%%%%%% begin
%%%%%%%% S1(v, x, y)
%%%%%%%% S2(w, x, y)
%%%%%%%% end
%%%%%%%%
\newcommand{\initialisation}[1]{
  \event{\init}{}{}{}{}{#1}
}

%%%%%%%% Theorem Proof Obligation
%%%%%%%% Print the theorem proof obligation, given the theorem label.
%%%%%%%% Arguments:
%%%%%%%% 1. Theorem label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \thmpo{thm} will produce "thm/THM"
\newcommand{\thmpo}[1]{\Bthm{#1}/\Bpo{THM}}

%%%%%%%% Axiom Well-definedness Proof Obligation
%%%%%%%% Print the axiom well-definedness proof obligation, given the
%%%%%%%% axiom label.
%%%%%%%% Arguments:
%%%%%%%% 1. Axiom label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \axmwdpo{axm} will produce "axm/WD"
\newcommand{\axmwdpo}[1]{\Baxm{#1}/\Bpo{WD}}

%%%%%%%% Invariant Proof Obligation
%%%%%%%% Print the invariant proof obligation, given the event name and
%%%%%%%% invariant label
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Invariant label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \invpo{evt}{inv} will produce "evt/inv/INV"
\newcommand{\invpo}[2]{\Bevt{#1}/\Binvt{#2}/\Bpo{INV}}

%%%%%%%% Theorem (in guard) Proof Obligation
%%%%%%%% Print the simulation proof obligation, given the event name and
%%%%%%%% the theorem (in guard) label.
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Theorem (in guard) label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdthmpo{evt}{thm} will produce "evt/thm/THM"
\newcommand{\grdthmpo}[2]{\Bevt{#1}/\Bthm{#2}/\Bpo{THM}}

```

```

%%%%%%%% Feasibility Proof Obligation
%%%%%%%% Print the feasibility proof obligation, given the event name and
%%%%%%%% the action label
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Action label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \fispo{evt}{act} will produce "evt/act/FIS"
\newcommand{\fispo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{FIS}}

%%%%%%%% Variant finiteness Proof Obligation
%%%%%%%% Print the Variant finiteness proof obligation
%%%%%%%% Arguments: No arguments
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \finpo will produce "FIN"
\newcommand{\finpo}{\Bpo{FIN}}

%%%%%%%% Variant Proof Obligation
%%%%%%%% Print the guard strengthen proof obligation, given the event name
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdpo{evt} will produce "evt/VAR"
\newcommand{\varpo}[1]{\Bevt{#1}/\Bpo{VAR}}

%%%%%%%% Simulation Proof Obligation
%%%%%%%% Print the simulation proof obligation, given the event name and
%%%%%%%% the action label.
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Action label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \simpo{evt}{act} will produce "evt/act/SIM"
\newcommand{\simpo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{SIM}}

%%%%%%%% Guard Strengthen Proof Obligation
%%%%%%%% Print the guard strengthen proof obligation, given the event
%%%%%%%% name and the guard label
%%%%%%%% Arguments:
%%%%%%%% 1. (Abstract) Event name
%%%%%%%% 2. (Abstract) Guard label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdpo{evt}{grd} will produce "evt/grd/GRD"
\newcommand{\grdpo}[2]{\Bevt{#1}/\Bgrd{#2}/\Bpo{GRD}}

%%%%%%%% Variant Natural Number Proof Obligation
%%%%%%%% Print the Variant Natural Number proof obligation, given the event name

```



```

%% Argument:
%% 1. Event name
%%
%% Usage:
%% - \natpo{evt} will produce "evt/NAT"
\newcommand{\natpo}[1]{\Bevt{#1}/\Bpo{NAT}}

```

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

<b>Symbols</b>		
\@empty ..	2, 4, 6, 11–14	
\	1, 3, 4, 9–12, 14	
\_ .....	5–10	
\_ .....	3, 4	
<b>A</b>		
\aaa .....	5–9	
\axioms .....	9	
\axmwdpo .....	15	
<b>B</b>		
\B@declaration ....	2–4	
\B@event ...	3, 4, 10–12	
\B@eventinline .	3, 4, 13	
\B@identifier ....	1, 2	
\B@keyword .....	1, 2	
\B@label .....	1, 2	
\B@newmacro .....	5–9	
\B@oldfboxsep .....	2–4	
\B@po .....	1, 2, 5	
\B@section .....	2–4	
\Bact .....	5, 9, 16	
\Bany .....	5, 11, 13	
\Baxm .....	5, 7, 9, 15	
\Bbap .....	5	
\Bbegin .....	5, 12, 14	
\Bcst .....	5, 6	
\Bctx .....	5, 6	
\Bdeclaration 2–4,	9, 10	
\begin ...	2–4, 11, 12, 14	
\Bend .....	5, 12, 14	
\Bevt ....	5, 8, 12, 14–17	
\bfseries .....	5	
\Bgrd .....	5, 8, 9, 16	
\Bhspace .....	2–4	
\Bidentifier .....	1, 5	
\Binv .....	5, 8, 10, 15	
\Bkeyword ....	1, 2, 4, 5	
\Blabel .....	1, 2, 5	
\Bmch .....	5, 7	
\Bpar .....	5, 8	
\Bpo .....	1, 2, 15–17	
\Brefines ....	5, 11, 13	
\Bsection ...	2–4, 9, 10	
\Bsep .....	2–4, 11, 12	
\Bset .....	5, 6	
\Bstatus .....	5, 11	
\Bthen .....	5, 12, 14	
\Bthm .....	5, 7, 15	
\Bvrb .....	5, 7	
\Bvspace .....	1, 3, 4	
\Bwhen .....	5, 11, 13	
\Bwhere .....	5, 11, 13	
\Bwith .....	5, 11, 14	
<b>C</b>		
\carriersets .....	9	
\colorlet .....	2	
\constants .....	9	
\csname .....	6	
<b>D</b>		
\DeclareOption ....	2–4	
\def .....	2, 4, 6, 11–14	
<b>E</b>		
\else ....	2, 4, 6, 11–14	
\end .....	2–4, 11, 12, 14	
\endcsname .....	6	
\ensuremath ....	2, 3, 5	
\event .....	3, 4, 15	
\eventB .....	5	
\eventinline ....	3, 4	
\evt@absevt .....	11, 13	
\evt@acts .....	11–14	
\evt@acts@keyword	12, 14	
\evt@acts@tmp ...	12, 14	
\evt@grds .....	11–14	
\evt@grds@tmp ...	11, 13	
\evt@name .....	11–14	
\evt@pars .....	11–14	
\evt@sts .....	11, 13	
\evt@wits ...	11, 13, 14	
\expandafter .....	6	
<b>F</b>		
\fbox .....	2, 3	
\fboxsep .....	2, 3	
\fi .....	2, 5, 6, 11–14	
\finpo .....	16	
\fispo .....	16	
\footnotesize .....	3	
<b>G</b>		
\grdpo .....	16	
\grdthmpo .....	15	
<b>H</b>		
\hbox .....	5	
\hspace .....	2–4	
<b>I</b>		
\ifx .....	2, 4, 6, 11–14	
\in .....	9, 10	
\init .....	14, 15	
\initialisation ...	15	
\input@macro .....	6	
\invariants .....	10	
\invpo .....	15	
\is@thm .....	2	
<b>M</b>		
\mathbf .....	2, 5	
\mathit .....	2	

<code>\mathsf</code> .....	2, 5	<code>\no@title</code> .....	4	<code>\setlength</code> .....	2, 3
<b>N</b>		<code>\normalsize</code> .....	2	<code>\simpo</code> .....	16
<code>\nat</code> .....	9, 10	<b>P</b>		<code>\SKIP</code> .....	5, 11–14
<code>\natpo</code> .....	17	<code>\pretty@absepts</code> .	11–14	<code>\sl</code> .....	5
<code>\newBact</code> .....	9	<code>\pretty@acts</code> ....	12, 14	<b>T</b>	
<code>\newBaxm</code> .....	7	<code>\pretty@grds</code> ....	11–14	<code>\textcolor</code> .....	2
<code>\newBcst</code> .....	6	<code>\pretty@pars</code> ....	11–14	<code>\textsc</code> .....	5
<code>\newBctx</code> .....	6	<code>\pretty@sts</code> ....	11–14	<code>\thmpo</code> .....	15
<code>\newBevt</code> .....	8, 14	<code>\pretty@wits</code> .	11, 12, 14	<b>V</b>	
<code>\newBgrd</code> .....	8, 9	<code>\ProcessOptions</code> ....	5	<code>\variables</code> .....	9
<code>\newBinu</code> .....	8	<b>Q</b>		<code>\variant</code> .....	10
<code>\newBmch</code> .....	7	<code>\quad</code> .....	2	<code>\varpo</code> .....	16
<code>\newBpar</code> .....	8	<b>R</b>		<b>W</b>	
<code>\newBset</code> .....	6	<code>\renewcommand</code> .....	2–4	<code>\widehat</code> .....	14
<code>\newBthm</code> .....	7	<code>\renewenvironment</code> .....	3, 4	<b>X</b>	
<code>\newBvrb</code> .....	7	<code>\RequirePackage</code> ....	1	<code>\xspace</code> .....	2, 5
<code>\newcommand</code> .....	.. 1–11, 13, 15–17	<b>S</b>			
<code>\newenvironment</code> ....	2	<code>\scriptsize</code> .....	4		
<code>\newlength</code> .....	4	<b>X</b>			

## Change History

v1.0

General: Initial version .....