

# The `eventB` package\*

Thai Son Hoang  
ETH-Zurich  
<htson at inf dot ethz dot ch>

July 3, 2012

## Abstract

This class provides a template for typesetting Event-B models. It was developed at the Swiss Federal Institute of Technology Zurich (ETH-Zurich).

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Usage</b>	<b>1</b>
<b>3</b>	<b>Implementation</b>	<b>1</b>

## 1 Introduction

This package was developed in order to ease the typesetting of Event-B models in L<sup>A</sup>T<sub>E</sub>X.

## 2 Usage

## 3 Implementation

We load the standard `article` class and pass option `10pt` to it.

```
%%%% BEGIN Package loading %%%%
\RequirePackage{xspace}
\RequirePackage{xcolor}
%%%% END Package loading %%%%

%%%% Keywords can be coloured by package option "color"
\newcommand{\Bkeyword}[1]{\B@keyword{#1}}
\newcommand{\Bidentifier}[1]{\B@identifier{#1}}
\newcommand{\Blabel}[2][ ]{\B@label{#1}{#2}}
\newcommand{\Bpo}[1]{\B@po{#1}}
\newcommand{\Bvspace}[1][2ex]{\B@vspace{#1}}
```

---

\*This document corresponds to `eventB` ?, dated ?.

```

\newcommand{\Bhspace}[1][2em]{\hspace{#1}}
\newcommand{\Bsep}{\quad}
\DeclareOption{color}{
  \colorlet{Bkeywordcolor}{blue}
  \colorlet{Blabelcolor}{green!50!black}
  \colorlet{Bpocolor}{red}
  %%%% Keywords are coloured.
  \renewcommand{\Bkeyword}[1]{\textcolor{Bkeywordcolor}{\B@keyword{#1}}}
  \renewcommand{\Blabel}[2][]{\textcolor{Blabelcolor}{\B@label{#1}{#2}}}
  \renewcommand{\Bpo}[1]{\textcolor{Bpocolor}{\B@po{#1}}}
}
\DeclareOption{colour}{
  \colorlet{Bkeywordcolor}{blue}
  \colorlet{Blabelcolor}{green!50!black}
  \colorlet{Bpocolor}{red}
  %%%% Keywords are coloured.
  \renewcommand{\Bkeyword}[1]{\textcolor{Bkeywordcolor}{\B@keyword{#1}}}
  \renewcommand{\Blabel}[2][]{\textcolor{Blabelcolor}{\B@label{#1}{#2}}}
  \renewcommand{\Bpo}[1]{\textcolor{Bpocolor}{\B@po{#1}}}
}

\newcommand{\B@keyword}[1]{\ensuremath{\mathbf{#1}}}
\newcommand{\B@identifier}[1]{\ensuremath{\mathit{#1}}\xspace}
\newcommand{\B@label}[2][]{
  \def\is@thm{#1}
  \ifx\is@thm\@empty
    \ensuremath{\mathsf{#2}}\xspace
  \else
    \ensuremath{\mathit{#2}}\xspace
  \fi
}

%%% Bcode environment %%%%
%%% the same as ‘center’ %%%%
\newenvironment{Bcode}[1][\normalsize]{\begin{center}#1{\end{center}}}
\newcommand{\Bdeclaration}[2]{
  \fbox{
    \ensuremath{
      \B@declaration{#1}{#2}
    }
  }
}

\newcommand{\Bsection}[3][]{
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@section[#1]{#2}{#3}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

```

```

\newcommand{\event}[7][]{
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

\DeclareOption{compact}{
  \renewenvironment{Bcode}[1][\footnotesize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3][]{
    \B@section[#1]{#2}{#3}
  }

  \renewcommand{\event}[7][]{
    \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
  }

  \renewcommand{\Bvspace}[1][0ex]{\\[#1]}
  \renewcommand{\Bhspace}[1][0.5em]{\hspace{#1}}
  \renewcommand{\Bsep}{\ }
}

\DeclareOption{small}{
  \renewenvironment{Bcode}[1][\footnotesize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bvspace}[1][1ex]{\\[#1]}
  \renewcommand{\Bhspace}[1][1em]{\hspace{#1}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3][]{
    \B@section[#1]{#2}{#3}
  }

  \renewcommand{\event}[7][]{
    \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
  }
  \renewcommand{\Bsep}{\ }
}

\DeclareOption{tiny}{
  \renewenvironment{Bcode}[1][\scriptsize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bvspace}[1][-0.5ex]{\\[#1]}
  \renewcommand{\Bhspace}[1][0.5em]{\hspace{#1}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }
}

```

```

\renewcommand{\Bsection}[3][]{
  \B@section[#1]{#2}{#3}
}

\renewcommand{\event}[7][]{
  \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}
\renewcommand{\Bsep}{\ }

}

\newcommand{\B@declaration}[2]{
  \begin{array}{l@{\Bsep}l}
    \Bkeyword{#1:} & #2 \\
  \end{array}
}
\newlength{\B@oldfboxsep}
\newcommand{\B@section}[3][]{
  \def\no@title{#1}
  \ifx\no@title\@empty
    \begin{array}{l}
      \Bkeyword{#2:} \\
      \begin{array}{l@{\Bsep}l}
        #3 \\
      \end{array}
    \end{array}
  \else
    \begin{array}{l@{\Bsep}l}
      #3 \\
    \end{array}
  \fi
}

\newcommand{\B@po}[1]{\ensuremath{\mathsf{#1}}\xspace}

%%%%% BEGIN Execution of options %%%%
\ProcessOptions
%%%%% END Execution of options %%%%

%%%%% (BEGIN) Macros for Pretty-Print Event-B Components %%%
\newcommand{\eventB}{Event-B\xspace}
\newcommand{\SKIP}{\textsc{skip}}

%%%%% Event-B Keywords %%%%
\newcommand{\Bany}{\Bkeyword{any}}
\newcommand{\Bbegin}{\Bkeyword{begin}}
\newcommand{\Bend}{\Bkeyword{end}}
\newcommand{\Brefines}{\Bkeyword{refines}}
\newcommand{\Bstatus}{\Bkeyword{status}}
\newcommand{\Bthen}{\Bkeyword{then}}
\newcommand{\Bwhen}{\Bkeyword{when}}
\newcommand{\Bwhere}{\Bkeyword{where}}

```

```

\newcommand{\Bwith}{\Bkeyword{with}}

%%%% Event-B internal elements %%%%
\newcommand{\Bctx}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\Bset}[1]{\Bidentifier{#1}}
\newcommand{\Bcst}[1]{\Bidentifier{#1}}
\newcommand{\Baxm}[1]{\Blabel{#1}}
\newcommand{\Bthm}[1]{\Blabel{thm}{#1}}

\newcommand{\Bmch}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\Bvrb}[1]{\Bidentifier{#1}}
\newcommand{\Binv}[1]{\Blabel{#1}}
\newcommand{\Bevt}[1]{\Blabel{#1}}
\newcommand{\Bpar}[1]{\Bidentifier{#1}}
\newcommand{\Bact}[1]{\Blabel{#1}}
\newcommand{\Bgrd}[1]{\Blabel{#1}}
\newcommand{\Bbap}[1]{\hbox{\sl\bfseries #1}}
%%%%
%%%% Creating Event-B elements macros %%%%

%%%% Create a new B macro
%%%% Arguments:
%%%% 1. The macro string, (OPTIONAL) if empty then the expanded string will be used.
%%%% 2. The expanded string
%%%% 3. The mark-up macros, e.g. \Bvrb
%%%% Usage:
%%%% - \B@newmacro[aaa]{a\_a\_a}{\Bvrb} will create a new macro \aaa
%%%% which will be expanded to be \Bvrb{a\_a\_a}
%%%% - \B@newmacro[aaa]{\Bvrb} will create a new macro \aaa
%%%% which will be expanded to be \Bvrb{aaa}
%%%%
\newcommand{\B@newmacro}[3][{}{
  \def\input@macro{#1}
  \ifx\input@macro\@empty
    \expandafter\def\csname #2\endcsname{#3{#2}}
  \else
    \expandafter\def\csname #1\endcsname{#3{#2}}
  \fi
}

%%%% Create a new context macro
%%%% Arguments:
%%%% 1. The macro string (OPTIONAL)
%%%% 2. The expanded string
%%%% Usage:
%%%% - \newBctx[aaa]{a\_a\_a} will create a new macro \aaa
%%%% which will be expanded to be \Bctx{a\_a\_a}.
%%%% - \newBctx{aaa} will create a new macro \aaa which will be
%%%% expanded to be \Bctx{aaa}.
%%%%
\newcommand{\newBctx}[2][{}{
  \B@newmacro[#1]{#2}{\Bctx}
}

```

```

%%%%%%%% Create a new carrier set macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBset[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bset{a\_a\_a}.
%%%%%%%% - \newBset{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bset{aaa}.
%%%%%%%%
\newcommand{\newBset}[2][]{%
  \B@newmacro[#1]{#2}{\Bset}
}

```

```

%%%%%%%% Create a new constant macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBcst[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bcst{a\_a\_a}.
%%%%%%%% - \newBcst{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bcst{aaa}.
%%%%%%%%
\newcommand{\newBcst}[2][]{%
  \B@newmacro[#1]{#2}{\Bcst}
}

```

```

%%%%%%%% Create a new axiom macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBaxm[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Baxm{a\_a\_a}.
%%%%%%%% - \newBaxm{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Baxm{aaa}.
%%%%%%%%
\newcommand{\newBaxm}[2][]{%
  \B@newmacro[#1]{#2}{\Baxm}
}

```

```

%%%%%%%% Create a new theorem macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBthm[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bthm{a\_a\_a}.
%%%%%%%% - \newBthm{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bthm{aaa}.
%%%%%%%%

```

```

\newcommand{\newBthm}[2][]{%
  \B@newmacro[#1]{#2}{\Bthm}
}

```

```

%%%%% Create a new machine macro
%%%%% Arguments:
%%%%% 1. The macro string (OPTIONAL)
%%%%% 2. The expanded string
%%%%% Usage:
%%%%% - \newBmch[aaa]{a\_a\_a} will create a new macro \aaa
%%%%% which will be expanded to be \Bmch{a\_a\_a}.
%%%%% - \newBmch{aaa} will create a new macro \aaa which will be
%%%%% expanded to be \Bmch{aaa}.
%%%%%
\newcommand{\newBmch}[2][]{%
  \B@newmacro[#1]{#2}{\Bmch}
}

```

```

%%%%% Create a new variable macro
%%%%% Arguments:
%%%%% 1. The macro string (OPTIONAL)
%%%%% 2. The expanded string
%%%%% Usage:
%%%%% - \newBvrb[aaa]{a\_a\_a} will create a new macro \aaa
%%%%% which will be expanded to be \Bvrb{a\_a\_a}.
%%%%% - \newBvrb{aaa} will create a new macro \aaa which will be
%%%%% expanded to be \Bvrb{aaa}.
%%%%%
\newcommand{\newBvrb}[2][]{%
  \B@newmacro[#1]{#2}{\Bvrb}
}

```

```

%%%%% Create a new invariant macro
%%%%% Arguments:
%%%%% 1. The macro string (OPTIONAL)
%%%%% 2. The expanded string
%%%%% Usage:
%%%%% - \newBinu[aaa]{a\_a\_a} will create a new macro \aaa
%%%%% which will be expanded to be \Binu{a\_a\_a}.
%%%%% - \newBinu{aaa} will create a new macro \aaa which will be
%%%%% expanded to be \Binu{aaa}.
%%%%%
\newcommand{\newBinu}[2][]{%
  \B@newmacro[#1]{#2}{\Binu}
}

```

```

%%%%% Create a new event macro
%%%%% Arguments:
%%%%% 1. The macro string (OPTIONAL)
%%%%% 2. The expanded string
%%%%% Usage:
%%%%% - \newBevt[aaa]{a\_a\_a} will create a new macro \aaa
%%%%% which will be expanded to be \Bevt{a\_a\_a}.

```

```

%% - \newBvt{aaa} will create a new macro \aaa which will be
%% expanded to be \Bvt{aaa}.
%%
\newcommand{\newBvt}[2][]{%
  \B@newmacro[#1]{#2}{\Bvt}
}

%% Create a new parameter macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBpar[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bpar{a\_a\_a}.
%% - \newBpar{aaa} will create a new macro \aaa which will be
%% expanded to be \Bpar{aaa}.
%%
\newcommand{\newBpar}[2][]{%
  \B@newmacro[#1]{#2}{\Bpar}
}

%% Create a new guard macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBgrd[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bgrd{a\_a\_a}.
%% - \newBgrd{aaa} will create a new macro \aaa which will be
%% expanded to be \Bgrd{aaa}.
%%
\newcommand{\newBgrd}[2][]{%
  \B@newmacro[#1]{#2}{\Bgrd}
}

%% Create a new action macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBact[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bact{a\_a\_a}.
%% - \newBact{aaa} will create a new macro \aaa which will be
%% expanded to be \Bact{aaa}.
%%
\newcommand{\newBact}[2][]{%
  \B@newmacro[#1]{#2}{\Bact}
}

%% Pretty print carrier sets
%% Arguments:
%% 1. (Comma-separated) list of carrier sets.
%%

```



```

%% Usage: \carriersets{S, T}
\newcommand{\carriersets}[1]{
  \Bdeclaration{sets}{#1}
}

%% Pretty print constants
%% Arguments:
%% 1. (Comma-separated) list of constants.
%% Usage: \constants{m, n}
\newcommand{\constants}[1]{
  \Bdeclaration{constants}{#1}
}

%% Pretty print axioms
%% Arguments:
%% 1. (Newline(\)-separated) list of axioms.
%% Usage: \axioms{\Baxm{axm0\_1}: & x \in \nat \
                \Baxm{axm0\_2}: & y \in \nat \[2ex]}
\newcommand{\axioms}[2]{}{
  \Bsection[#1]{axioms}{#2}
}

%% Pretty print variables
%% Arguments:
%% 1. (Comma-separated) list of variables.
%% Usage: \variables{x, y}
\newcommand{\variables}[1]{
  \Bdeclaration{variables}{#1}
}

%% Pretty print invariants
%% Arguments:
%% 1. (Newline(\)-separated) list of invariants.
%% Usage: \invariants{\Binv{inv0\_1}: & x \in \nat \
                    \Binv{inv0\_2}: & y \in \nat \[2ex]}
\newcommand{\invariants}[2]{}{
  \Bsection[#1]{invariants}{#2}
}

%% Pretty print variant
%% Arguments:
%% 1. The variant
%% Usage: \variant{V}
\newcommand{\variant}[1]{
  \Bdeclaration{variant}{#1}
}

```

```

%%%%% Pretty print an general Event-B event
%%%%% Arguments:
%%%%% 1. (Optional) convergence status.
%%%%% 2. Name of the event.
%%%%% 3. Name of the abstract event.
%%%%% 4. (Comma-separated) list of parameters.
%%%%% 5. (Newline(\\)-separated) list of guards.
%%%%% 6. (Newline(\\)-separated) list of witness predicates.
%%%%% 7. (Newline(\\)-separated) list of assignments.
%%%%%
%%%%% Usage: \B@event[conv]{conc}{abs}{x,y}{G1(x,y)\\G2(x,y)}{W1\\W2}{S1(v,x,y)\\S2(w,x,y)}
%%%%% will produce the following
%%%%%
%%%%%      conc
%%%%%      refines abs
%%%%%      status conv
%%%%%      any x, y where
%%%%%          G1(x, y)
%%%%%          G2(x, y)
%%%%%      with
%%%%%          W1
%%%%%          W2
%%%%%      then
%%%%%          S1(v, x, y)
%%%%%          S2(w, x, y)
%%%%%      end
%%%%%
%%%%% Special case:
%%%%% - Empty abstract event --> refines clause is omitted.
%%%%% - Empty convergence status --> status clause is omitted.
%%%%% - Empty witness --> with clause is omitted.
%%%%% - Empty parameters, empty guards --> begin ... end
%%%%% - Empty parameters --> when ... then ... end
%%%%% - Empty actions --> \SKIP
\newcommand{\B@event}[7][]{
  \def\evt@sts{#1}
  \def\evt@name{#2}
  \def\evt@absevt{#3}
  \def\evt@pars{#4}
  \def\evt@grds{#5}
  \def\evt@wits{#6}
  \def\evt@acts{#7}
  %% Pretty-print convergence status
  \ifx\evt@sts\@empty
  \def\pretty@sts{}
  \else
  \def\pretty@sts{\Bsep\Bstatus \Bsep \evt@sts \\}
  \fi
  % Pretty-print abstract events
  \ifx\evt@absevt\@empty
  \def\pretty@absevt{}
  \else
  \def\pretty@absevt{\Bsep\Brefines \Bsep \evt@absevt \\}
  \fi

```

```

% Pretty-print parameters
\ifx\evt@pars\@empty
\def\pretty@pars{}
\else
\def\pretty@pars{\Bsep\Bany \Bsep \evt@pars \Bsep \Bwhere \\\}
\fi
% Pretty-print guards
\ifx\evt@grds\@empty
\def\pretty@grds{}
\else
\def\evt@grds@tmp{
  \begin{array}{@{\Bsep\Bsep}l@{\Bsep}l}
    \evt@grds
  \end{array}\\\}
\ifx\evt@pars\@empty
\def\pretty@grds{
  \Bsep \Bwhen \\\}
\def\pretty@grds@tmp{
  \Bsep \Bwhen \\\}
\else
\def\pretty@grds{\evt@grds@tmp}
\fi
\fi
% Pretty-print witnesses
\ifx\evt@wits\@empty
\def\pretty@wits{}
\else
\def\pretty@wits{
  \Bsep\Bwith\\\}
  \begin{array}{@{\Bsep\Bsep}l}
    \evt@wits
  \end{array}\\\}
\fi
% Pretty-print actions
\ifx\evt@acts\@empty
\def\evt@acts{\SKIP}
\else
\fi
\def\evt@acts@tmp{
  \begin{array}{@{\Bsep\Bsep}l@{\Bsep}l}
    \evt@acts
  \end{array}\\\}
\def\evt@acts@keyword{\Bsep\Bthen \\\}
\ifx\evt@pars\@empty
\ifx\evt@grds\@empty
\def\evt@acts@keyword{\Bsep\Bbegin \\\}
\else
\fi
\else
\fi
\def\pretty@acts{

```

```

\evt@acts@keyword
\evt@acts@tmp
}
% Really do it now
\begin{array}{l}
\Bevt{\evt@name} \\
\pretty@sts
\pretty@absevt
\pretty@pars
\pretty@grds
\pretty@wits
\pretty@acts
\Bsep\Bend
\end{array}
}

%%%% INITIALISATION label
\newBevt{init}

%%%% Pretty print the initialisation: no ‘refines’ clause. no parameters, no
%%%% guards
%%%% Arguments:
%%%% 1. (Newline(\\)-separated) list of assignments.
%%%%
%%%% Usage: \init{S1(v,x,y)\\S2(w,x,y)}
%%%% will produce the following
%%%%
%%%% init
%%%% begin
%%%% S1(v, x, y)
%%%% S2(w, x, y)
%%%% end
%%%%
\newcommand{\initialisation}[1]{
\event{\init}{\{}\{\}\{\}\{#1}
}

%%%% Theorem Proof Obligation
%%%% Print the theorem proof obligation, given the theorem label.
%%%% Arguments:
%%%% 1. Theorem label
%%%%
%%%% Usage:
%%%% - \thmpo{thm} will produce "thm/THM"
\newcommand{\thmpo}[1]{\Bthm{#1}/\Bpo{THM}}

%%%% Axiom Well-definedness Proof Obligation
%%%% Print the axiom well-definedness proof obligation, given the
%%%% axiom label.
%%%% Arguments:
%%%% 1. Axiom label
%%%%
%%%% Usage:

```

```

%%%%% - \axmwdpo{axm} will produce "axm/WD"
\newcommand{\axmwdpo}[1]{\Baxm{#1}/\Bpo{WD}}

%%%%% Invariant Proof Obligation
%%%%% Print the invariant proof obligation, given the event name and
%%%%% invariant label
%%%%% Arguments:
%%%%% 1. Event name
%%%%% 2. Invariant label
%%%%%
%%%%% Usage:
%%%%% - \invpo{evt}{inv} will produce "evt/inv/INV"
\newcommand{\invpo}[2]{\Bevt{#1}/\Binv{#2}/\Bpo{INV}}

%%%%% Theorem (in guard) Proof Obligation
%%%%% Print the simulation proof obligation, given the event name and
%%%%% the theorem (in guard) label.
%%%%% Arguments:
%%%%% 1. Event name
%%%%% 2. Theorem (in guard) label
%%%%%
%%%%% Usage:
%%%%% - \grdthmpo{evt}{thm} will produce "evt/thm/THM"
\newcommand{\grdthmpo}[2]{\Bevt{#1}/\Bthm{#2}/\Bpo{THM}}

%%%%% Feasibility Proof Obligation
%%%%% Print the feasibility proof obligation, given the event name and
%%%%% the action label
%%%%% Arguments:
%%%%% 1. Event name
%%%%% 2. Action label
%%%%%
%%%%% Usage:
%%%%% - \fispo{evt}{act} will produce "evt/act/FIS"
\newcommand{\fispo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{FIS}}

%%%%% Variant finiteness Proof Obligation
%%%%% Print the Variant finiteness proof obligation
%%%%% Arguments: No arguments
%%%%%
%%%%% Usage:
%%%%% - \finpo will produce "FIN"
\newcommand{\finpo}{\Bpo{FIN}}

%%%%% Variant Proof Obligation
%%%%% Print the guard strengthen proof obligation, given the event name
%%%%% Arguments:
%%%%% 1. Event name
%%%%%
%%%%% Usage:
%%%%% - \grdp{evt} will produce "evt/VAR"
\newcommand{\varpo}[1]{\Bevt{#1}/\Bpo{VAR}}

```

```

%%%%%%%% Simulation Proof Obligation
%%%%%%%% Print the simulation proof obligation, given the event name and
%%%%%%%% the action label.
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Action label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \simpo{evt}{act} will produce "evt/act/SIM"
\newcommand{\simpo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{SIM}}

%%%%%%%% Guard Strengthen Proof Obligation
%%%%%%%% Print the guard strengthen proof obligation, given the event
%%%%%%%% name and the guard label
%%%%%%%% Arguments:
%%%%%%%% 1. (Abstract) Event name
%%%%%%%% 2. (Abstract) Guard label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdpo{evt}{grd} will produce "evt/grd/GRD"
\newcommand{\grdpo}[2]{\Bevt{#1}/\Bgrd{#2}/\Bpo{GRD}}

%%%%%%%% Variant Natural Number Proof Obligation
%%%%%%%% Print the Variant Natural Number proof obligation, given the event name
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \natpo{evt} will produce "evt/NAT"
\newcommand{\natpo}[1]{\Bevt{#1}/\Bpo{NAT}}

```

## Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

Symbols	B	
\@empty .. 2, 4, 5, 10, 11	\B@declaration .... 2–4	\Baxm ..... 5, 6, 9, 13
\ \ ..... 1, 3, 4, 9–12	\B@event ..... 3, 4, 10	\Bbap ..... 5
\_ ..... 5–9	\B@identifier .... 1, 2	\Bbegin ..... 4, 11
	\B@keyword ..... 1, 2	\Bcst ..... 5, 6
	\B@label ..... 1, 2	\Bctx ..... 5
\_ ..... 3, 4	\B@newmacro ..... 5–8	\Bdeclaration ... 2, 3, 9
	\B@oldfboxsep ..... 2–4	\begin ..... 2–4, 11, 12
	\B@po ..... 1, 2, 4	\Bend ..... 4, 12
<b>A</b>	\B@section ..... 2–4	\Bevt .... 5, 7, 8, 12–14
\aaa ..... 5–8	\Bact ..... 5, 8, 13, 14	\bfseries ..... 5
\axioms ..... 9	\Bany ..... 4, 11	\Bgrd ..... 5, 8, 14
\axmwdpo ..... 13		\Bhspace ..... 2, 3

\Bidentifier . . . . .	1, 5	\evt@sts . . . . .	10	\newBpar . . . . .	8
\Binv . . . . .	5, 7, 9, 13	\evt@wits . . . . .	10, 11	\newBset . . . . .	6
\Bkeyword . . . . .	1, 2, 4, 5	\expandafter . . . . .	5	\newBthm . . . . .	6, 7
\Blabel . . . . .	1, 2, 5			\newBvrb . . . . .	7
\Bmch . . . . .	5, 7	<b>F</b>		\newcommand . . . . .	1–10, 12–14
\Bpar . . . . .	5, 8	\fbox . . . . .	2, 3	\newenvironment . . . . .	2
\Bpo . . . . .	1, 2, 12–14	\fboxsep . . . . .	2, 3	\newlength . . . . .	4
\Brefines . . . . .	4, 10	\fi . . . . .	2, 4, 5, 10, 11	\no@title . . . . .	4
\Bsection . . . . .	2–4, 9	\finpo . . . . .	13	\normalsize . . . . .	2
\Bsep . . . . .	2–4, 10–12	\fispo . . . . .	13		
\Bset . . . . .	5, 6	\footnotesize . . . . .	3	<b>P</b>	
\Bstatus . . . . .	4, 10			\pretty@absepts . . . . .	10, 12
\Bthen . . . . .	4, 11	<b>G</b>		\pretty@acts . . . . .	11, 12
\Bthm . . . . .	5–7, 12, 13	\grdpo . . . . .	13, 14	\pretty@grds . . . . .	11, 12
\Bvrb . . . . .	5, 7	\grdthmpo . . . . .	13	\pretty@pars . . . . .	11, 12
\Bvspace . . . . .	1, 3			\pretty@sts . . . . .	10, 12
\Bwhen . . . . .	4, 11	<b>H</b>		\pretty@wits . . . . .	11, 12
\Bwhere . . . . .	4, 11	\hbox . . . . .	5	\ProcessOptions . . . . .	4
\Bwith . . . . .	5, 11	\hspace . . . . .	2, 3		
				<b>Q</b>	
<b>C</b>		<b>I</b>		\quad . . . . .	2
\carriersets . . . . .	9	\ifx . . . . .	2, 4, 5, 10, 11		
\colorlet . . . . .	2	\in . . . . .	9	<b>R</b>	
\constants . . . . .	9	\init . . . . .	12	\renewcommand . . . . .	2–4
\csname . . . . .	5	\initialisation . . . . .	12	\renewenvironment . . . . .	3
		\input@macro . . . . .	5	\RequirePackage . . . . .	1
<b>D</b>		\invariants . . . . .	9		
\DeclareOption . . . . .	2, 3	\invpo . . . . .	13	<b>S</b>	
\def . . . . .	2, 4, 5, 10, 11	\is@thm . . . . .	2	\scriptsize . . . . .	3
				\setlength . . . . .	2, 3
<b>E</b>		<b>M</b>		\simpo . . . . .	14
\else . . . . .	2, 4, 5, 10, 11	\mathbf . . . . .	2, 5	\SKIP . . . . .	4, 10, 11
\end . . . . .	2–4, 11, 12	\mathit . . . . .	2	\sl . . . . .	5
\endcsname . . . . .	5	\mathsf . . . . .	2, 4		
\ensuremath . . . . .	2–5			<b>T</b>	
\event . . . . .	3, 4, 12	<b>N</b>		\textcolor . . . . .	2
\eventB . . . . .	4	\nat . . . . .	9	\textsc . . . . .	4
\evt@absepts . . . . .	10	\natpo . . . . .	14	\thmpo . . . . .	12
\evt@acts . . . . .	10, 11	\newBact . . . . .	8		
\evt@acts@keyword . . . . .	11, 12	\newBaxm . . . . .	6	<b>V</b>	
\evt@acts@tmp . . . . .	11, 12	\newBcst . . . . .	6	\variables . . . . .	9
\evt@grds . . . . .	10, 11	\newBctx . . . . .	5	\variant . . . . .	9
\evt@grds@tmp . . . . .	11	\newBevt . . . . .	7, 8, 12	\varpo . . . . .	13
\evt@name . . . . .	10, 12	\newBgrd . . . . .	8		
\evt@pars . . . . .	10, 11	\newBinv . . . . .	7	<b>X</b>	
		\newBmch . . . . .	7	\xspace . . . . .	2, 4, 5

## Change History

v1.0

General: Initial version . . . . . 1