

The `eventB` package*

Thai Son Hoang
ETH-Zurich
<htson at inf dot ethz dot ch>

July 3, 2012

Abstract

This class provides a template for typesetting Event-B models. It was developed at the Swiss Federal Institute of Technology Zurich (ETH-Zurich).

Contents

1	Introduction	1
2	Usage	1
3	Implementation	1

1 Introduction

This package was developed in order to ease the typesetting of Event-B models in \LaTeX .

2 Usage

See `sample-eventB.tex` for an example of how to use the package.

3 Implementation

```
%%%% BEGIN Package loading %%%%\n\RequirePackage{xspace}\n\RequirePackage{xcolor}\n%%%% END Package loading %%%%\n\n%%%% Keywords can be coloured by package option "color"\n\newcommand{\Bkeyword}[1]{\ensuremath{\B@keyword{#1}}\xspace}\n\newcommand{\Bidentifier}[1]{\B@identifier{#1}\xspace}\n\newcommand{\Blabel}[2][ ]{\ensuremath{\B@label[#1]{#2}}\xspace}\n\newcommand{\Bpo}[1]{\ensuremath{\B@po{#1}}\xspace}
```

*This document corresponds to `eventB ?`, dated ?.

```

\newcommand{\Bvspace}[1][2ex]{\[\[{\#1}]
\newcommand{\Bhspace}[1][2em]{\hspace{\#1}}
\newcommand{\Bsep}{\quad}
\DeclareOption{color}{
  \colorlet{Bkeywordcolor}{blue}
  \colorlet{Blabelcolor}{green!50!black}
  \colorlet{Bpocolor}{red}
  %%%% Keywords are coloured.
  \renewcommand{\Bkeyword}[1]{\ensuremath{\textcolor{Bkeywordcolor}{\B@keyword{\#1}}}\xspace}
  \renewcommand{\Blabel}[2][\]{\ensuremath{\textcolor{Blabelcolor}{\B@label{\#1}{\#2}}}\xspace}
  \renewcommand{\Bpo}[1]{\ensuremath{\textcolor{Bpocolor}{\B@po{\#1}}}\xspace}
}
\DeclareOption{colour}{
  \colorlet{Bkeywordcolor}{blue}
  \colorlet{Blabelcolor}{green!50!black}
  \colorlet{Bpocolor}{red}
  %%%% Keywords are coloured.
  \renewcommand{\Bkeyword}[1]{\ensuremath{\textcolor{Bkeywordcolor}{\B@keyword{\#1}}}\xspace}
  \renewcommand{\Blabel}[2][\]{\ensuremath{\textcolor{Blabelcolor}{\B@label{\#1}{\#2}}}\xspace}
  \renewcommand{\Bpo}[1]{\ensuremath{\textcolor{Bpocolor}{\B@po{\#1}}}\xspace}
}

\newcommand{\B@keyword}[1]{\ensuremath{\mathbf{\#1}}\xspace}
\newcommand{\B@identifier}[1]{\ensuremath{\mathit{\#1}}\xspace}
\newcommand{\B@label}[2][\]{
  \def\is@thm{\#1}
  \ifx\is@thm\@empty
    \ensuremath{\mathsf{\#2}}\xspace
  \else
    \ensuremath{\mathit{\#2}}\xspace
  \fi
}

%%%% Bcode environment %%%%
%%%% the same as ‘center’ %%%%
\newenvironment{Bcode}[1][\normalsize]{\begin{center}\#1\end{center}}
\newcommand{\Bdeclaration}[2]{
  \fbox{
    \ensuremath{
      \B@declaration{\#1}{\#2}
    }
  }
}

\newcommand{\Bsection}[3][\]{
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@section{\#1}{\#2}{\#3}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

```

```

\newcommand{\event}[7] [] {
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

\newcommand{\eventinline}[7] [] {
  \setlength{\B@oldfboxsep}{\fboxsep}
  \setlength{\fboxsep}{2ex}
  \fbox{
    \ensuremath{
      \B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
    }
  }
  \setlength{\fboxsep}{\B@oldfboxsep}
}

\DeclareOption{compact}{
  \renewenvironment{Bcode}[1] [\footnotesize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3] [] {
    \B@section{#1}{#2}{#3}
  }

  \renewcommand{\event}[7] [] {
    \B@event{#1}{#2}{#3}{#4}{#5}{#6}{#7}
  }

  \renewcommand{\eventinline}[7] [] {
    \B@eventinline{#1}{#2}{#3}{#4}{#5}{#6}{#7}
  }

  \renewcommand{\Bvspace}[1] [0ex]{\[\[ #1]}
  \renewcommand{\Bhspace}[1] [0.5em]{\hspace{#1}}
  \renewcommand{\Bsep}{\ }
}

\DeclareOption{small}{
  \renewenvironment{Bcode}[1] [\footnotesize]{\begin{center}#1{\end{center}}
  \renewcommand{\Bvspace}[1] [1ex]{\[\[ #1]}
  \renewcommand{\Bhspace}[1] [1em]{\hspace{#1}}
  \renewcommand{\Bdeclaration}[2]{
    \B@declaration{#1}{#2}
  }

  \renewcommand{\Bsection}[3] [] {

```

```

\B@section[#1]{#2}{#3}
}

\renewcommand{\event}[7][]{
\B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}
\renewcommand{\eventinline}[7][]{
\B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}

\renewcommand{\Bsep}{\ }

}

\DeclareOption{tiny}{
\renewenvironment{Bcode}[1][\scriptsize]{\begin{center}#1{\end{center}}
\renewcommand{\Bvspace}[1][-0.5ex]{\[\[#1]}
\renewcommand{\Bhspace}[1][0.5em]{\hspace{#1}}
\renewcommand{\Bdeclaration}[2]{
\B@declaration[#1]{#2}
}

\renewcommand{\Bsection}[3][]{
\B@section[#1]{#2}{#3}
}

\renewcommand{\event}[7][]{
\B@event[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}
\renewcommand{\eventinline}[7][]{
\B@eventinline[#1]{#2}{#3}{#4}{#5}{#6}{#7}
}

\renewcommand{\Bsep}{\ }

}

\newcommand{\B@declaration}[2]{
\begin{array}{l@{\Bsep}l}
\Bkeyword{#1:} & #2
\end{array}
}

\newlength{\B@oldfboxsep}
\newcommand{\B@section}[3][]{
\def\no@title{#1}
\ifx\no@title\@empty
\begin{array}{l}
\Bkeyword{#2:} \\\
\begin{array}{l@{\Bsep}l}
#3
\end{array}
\end{array}
\end{array}
\else
\begin{array}{l@{\Bsep}l}
#3

```

```

\end{array}
\fi
}

\newcommand{\B@po}[1]{\ensuremath{\mathsf{#1}}\xspace}

%%%% BEGIN Execution of options %%%
\ProcessOptions
%%% END Execution of options %%%

%%% (BEGIN) Macros for Pretty-Print Event-B Components %%
\newcommand{\eventB}{Event-B\xspace}
\newcommand{\SKIP}{\textsc{skip}}

%%% Event-B Keywords %%%
\newcommand{\Bany}{\Bkeyword{any}}
\newcommand{\Bbegin}{\Bkeyword{begin}}
\newcommand{\Bend}{\Bkeyword{end}}
\newcommand{\Brefines}{\Bkeyword{refines}}
\newcommand{\Bstatus}{\Bkeyword{status}}
\newcommand{\Bthen}{\Bkeyword{then}}
\newcommand{\Bwhen}{\Bkeyword{when}}
\newcommand{\Bwhere}{\Bkeyword{where}}
\newcommand{\Bwith}{\Bkeyword{with}}

%%% Event-B internal elements %%%
\newcommand{\Bctx}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\Bset}[1]{\Bidentifier{#1}}
\newcommand{\Bcst}[1]{\Bidentifier{#1}}
\newcommand{\Baxm}[1]{\Blabel{#1}}
\newcommand{\Bthm}[1]{\Blabel{thm}{#1}}

\newcommand{\Bmch}[1]{\ensuremath{\mathbf{#1}}\xspace}
\newcommand{\Bvrb}[1]{\Bidentifier{#1}}
\newcommand{\Binv}[1]{\Blabel{#1}}
\newcommand{\Bevt}[1]{\Blabel{#1}}
\newcommand{\Bpar}[1]{\Bidentifier{#1}}
\newcommand{\Bact}[1]{\Blabel{#1}}
\newcommand{\Bgrd}[1]{\Blabel{#1}}
\newcommand{\Bbap}[1]{\hbox{\sl\bfseries #1}}
%%%

%%% Creating Event-B elements macros %%%

%%% Create a new B macro
%%% Arguments:
%%% 1. The macro string, (OPTIONAL) if empty then the expanded string will be used.
%%% 2. The expanded string
%%% 3. The mark-up macros, e.g. \Bvrb
%%% Usage:
%%% - \B@newmacro[aaa]{a_a_a}{\Bvrb} will create a new macro \aaa
%%% which will be expanded to be \Bvrb{a_a_a}
%%% - \B@newmacro{aaa}{\Bvrb} will create a new macro \aaa
%%% which will be expanded to be \Bvrb{aaa}

```

```

%%}%
\newcommand{\B@newmacro}[3][{}]{
  \def\input@macro{#1}
  \ifx\input@macro\@empty
  \expandafter\def\csname #2\endcsname{#3{#2}}
  \else
  \expandafter\def\csname #1\endcsname{#3{#2}}
  \fi
}

%%}% Create a new context macro
%%}% Arguments:
%%}% 1. The macro string (OPTIONAL)
%%}% 2. The expanded string
%%}% Usage:
%%}% - \newBctx[aaa]{a\_a\_a} will create a new macro \aaa
%%}% which will be expanded to be \Bctx{a\_a\_a}.
%%}% - \newBctx{aaa} will create a new macro \aaa which will be
%%}% expanded to be \Bctx{aaa}.
%%}%
\newcommand{\newBctx}[2][{}]{%
  \B@newmacro[#1]{#2}{\Bctx}
}

%%}% Create a new carrier set macro
%%}% Arguments:
%%}% 1. The macro string (OPTIONAL)
%%}% 2. The expanded string
%%}% Usage:
%%}% - \newBset[aaa]{a\_a\_a} will create a new macro \aaa
%%}% which will be expanded to be \Bset{a\_a\_a}.
%%}% - \newBset{aaa} will create a new macro \aaa which will be
%%}% expanded to be \Bset{aaa}.
%%}%
\newcommand{\newBset}[2][{}]{%
  \B@newmacro[#1]{#2}{\Bset}
}

%%}% Create a new constant macro
%%}% Arguments:
%%}% 1. The macro string (OPTIONAL)
%%}% 2. The expanded string
%%}% Usage:
%%}% - \newBcst[aaa]{a\_a\_a} will create a new macro \aaa
%%}% which will be expanded to be \Bcst{a\_a\_a}.
%%}% - \newBcst{aaa} will create a new macro \aaa which will be
%%}% expanded to be \Bcst{aaa}.
%%}%
\newcommand{\newBcst}[2][{}]{%
  \B@newmacro[#1]{#2}{\Bcst}
}

%%}% Create a new axiom macro

```

```

%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBaxm[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Baxm{a\_a\_a}.
%%%%%%%% - \newBaxm{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Baxm{aaa}.
%%%%%%%%
\newcommand{\newBaxm}[2][]{%
  \B@newmacro[#1]{#2}{\Baxm}
}

%%%%%%%% Create a new theorem macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBthm[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bthm{a\_a\_a}.
%%%%%%%% - \newBthm{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bthm{aaa}.
%%%%%%%%
\newcommand{\newBthm}[2][]{%
  \B@newmacro[#1]{#2}{\Bthm}
}

%%%%%%%% Create a new machine macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBmch[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bmch{a\_a\_a}.
%%%%%%%% - \newBmch{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bmch{aaa}.
%%%%%%%%
\newcommand{\newBmch}[2][]{%
  \B@newmacro[#1]{#2}{\Bmch}
}

%%%%%%%% Create a new variable macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBvrb[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bvrb{a\_a\_a}.
%%%%%%%% - \newBvrb{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bvrb{aaa}.
%%%%%%%%
\newcommand{\newBvrb}[2][]{%
  \B@newmacro[#1]{#2}{\Bvrb}
}

```

```

}

%%%%%%%% Create a new invariant macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBinv[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Binv{a\_a\_a}.
%%%%%%%% - \newBinv{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Binv{aaa}.
%%%%%%%%
\newcommand{\newBinv}[2][]{%
  \B@newmacro[#1]{#2}{\Binv}
}

%%%%%%%% Create a new event macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBevt[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bevt{a\_a\_a}.
%%%%%%%% - \newBevt{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bevt{aaa}.
%%%%%%%%
\newcommand{\newBevt}[2][]{%
  \B@newmacro[#1]{#2}{\Bevt}
}

%%%%%%%% Create a new parameter macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBpar[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bpar{a\_a\_a}.
%%%%%%%% - \newBpar{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bpar{aaa}.
%%%%%%%%
\newcommand{\newBpar}[2][]{%
  \B@newmacro[#1]{#2}{\Bpar}
}

%%%%%%%% Create a new guard macro
%%%%%%%% Arguments:
%%%%%%%% 1. The macro string (OPTIONAL)
%%%%%%%% 2. The expanded string
%%%%%%%% Usage:
%%%%%%%% - \newBgrd[aaa]{a\_a\_a} will create a new macro \aaa
%%%%%%%% which will be expanded to be \Bgrd{a\_a\_a}.
%%%%%%%% - \newBgrd{aaa} will create a new macro \aaa which will be
%%%%%%%% expanded to be \Bgrd{aaa}.

```



```

%%
\newcommand{\newBgrd}[2][]{%
  \B@newmacro[#1]{#2}{\Bgrd}
}

%%
%% Create a new action macro
%% Arguments:
%% 1. The macro string (OPTIONAL)
%% 2. The expanded string
%% Usage:
%% - \newBact[aaa]{a\_a\_a} will create a new macro \aaa
%% which will be expanded to be \Bact{a\_a\_a}.
%% - \newBact{aaa} will create a new macro \aaa which will be
%% expanded to be \Bact{aaa}.
%%
\newcommand{\newBact}[2][]{%
  \B@newmacro[#1]{#2}{\Bact}
}

%%
%% Pretty print carrier sets
%% Arguments:
%% 1. (Comma-separated) list of carrier sets.
%%
%% Usage: \carriersets{S, T}
\newcommand{\carriersets}[1]{
  \Bdeclaration{sets}{#1}
}

%%
%% Pretty print constants
%% Arguments:
%% 1. (Comma-separated) list of constants.
%%
%% Usage: \constants{m, n}
\newcommand{\constants}[1]{
  \Bdeclaration{constants}{#1}
}

%%
%% Pretty print axioms
%% Arguments:
%% 1. (Newline(\)-separated) list of axioms.
%%
%% Usage: \axioms{\Baxm{axm0\_1}: & x \in \nat \\\
%% \Baxm{axm0\_2}: & y \in \nat \\[2ex]}
\newcommand{\axioms}[2][]{
  \Bsection[#1]{axioms}{#2}
}

%%
%% Pretty print variables
%% Arguments:
%% 1. (Comma-separated) list of variables.
%%
%% Usage: \variables{x, y}
\newcommand{\variables}[1]{

```

```

\Bdeclaration{variables}{#1}
}

%% Pretty print invariants
%% Arguments:
%% 1. (Newline(\))-separated list of invariants.
%% Usage: \invariants{\Binv{inv0\_1:} & x \in \nat \
\Binv{inv0\_2:} & y \in \nat \[2ex]}
\newcommand{\invariants}[2][{}{
\Bsection[#1]{invariants}{#2}
}

%% Pretty print variant
%% Arguments:
%% 1. The variant
%% Usage: \variant{V}
\newcommand{\variant}[1]{
\Bdeclaration{variant}{#1}
}

%% Pretty print an general Event-B event
%% Arguments:
%% 1. (Optional) convergence status.
%% 2. Name of the event.
%% 3. Name of the abstract event.
%% 4. (Comma-separated) list of parameters.
%% 5. (Newline(\))-separated list of guards.
%% 6. (Newline(\))-separated list of witness predicates.
%% 7. (Newline(\))-separated list of assignments.
%% Usage: \B@event[conv]{conc}{abs}{x,y}{G1(x,y)\G2(x,y)}{W1\W2}{S1(v,x,y)\S2(w,x,y)}
%% will produce the following
%%
%% conc
%% refines abs
%% status conv
%% any x, y where
%% G1(x, y)
%% G2(x, y)
%% with
%% W1
%% W2
%% then
%% S1(v, x, y)
%% S2(w, x, y)
%% end
%%
%% Special case:
%% - Empty abstract event --> refines clause is omitted.
%% - Empty convergence status --> status clause is omitted.
%% - Empty witness --> with clause is omitted.

```

```

%% - Empty parameters, empty guards --> begin ... end
%% - Empty parameters --> when ... then ... end
%% - Empty actions --> \SKIP
\newcommand{\B@event}[7][]{
  \def\evt@sts{#1}
  \def\evt@name{#2}
  \def\evt@absepts{#3}
  \def\evt@pars{#4}
  \def\evt@grds{#5}
  \def\evt@wits{#6}
  \def\evt@acts{#7}
  %% Pretty-print convergence status
  \ifx\evt@sts\@empty
  \def\pretty@sts{
  \else
  \def\pretty@sts{\Bsep\Bstatus \Bsep \evt@sts \\\}
  \fi
  % Pretty-print abstract events
  \ifx\evt@absepts\@empty
  \def\pretty@absepts{
  \else
  \def\pretty@absepts{\Bsep\Brefines \Bsep \evt@absepts \\\}
  \fi
  % Pretty-print parameters
  \ifx\evt@pars\@empty
  \def\pretty@pars{
  \else
  \def\pretty@pars{\Bsep\Bany \Bsep \evt@pars \Bsep \Bwhere \\\}
  \fi
  % Pretty-print guards
  \ifx\evt@grds\@empty
  \def\pretty@grds{
  \else
  \def\evt@grds@tmp{
    \begin{array}{@{\Bsep\Bsep}l@{\Bsep}l}
      \evt@grds
    \end{array}
  }
  \ifx\evt@pars\@empty
  \def\pretty@grds{
    \Bsep \Bwhen \\\
    \evt@grds@tmp
  }
  \else
  \def\pretty@grds{\evt@grds@tmp}
  \fi
  \fi
  % Pretty-print witnesses
  \ifx\evt@wits\@empty
  \def\pretty@wits{
  \else
  \def\pretty@wits{
    \Bsep\Bwith\\\
    \begin{array}{@{\Bsep\Bsep}ll}

```

```

        \evt@wits
    \end{array}}\}
}
\fi
% Pretty-print actions
\ifx\evt@acts\@empty
\def\evt@acts{\SKIP}
\else
\fi
\def\evt@acts@tmp{
    \begin{array}{c}\Bsep\Bsep\l@{\Bsep}\l}
    \evt@acts
    \end{array}}\}
}
\def\evt@acts@keyword{\Bsep\Bthen \}
\ifx\evt@pars\@empty
\ifx\evt@grds\@empty
\def\evt@acts@keyword{\Bsep\Bbegin \}
\else
\fi
\else
\fi
\def\pretty@acts{
    \evt@acts@keyword
    \evt@acts@tmp
}
% Really do it now
\begin{array}{l}
    \Bevt{\evt@name} \}
    \pretty@sts
    \pretty@absepts
    \pretty@pars
    \pretty@grds
    \pretty@wits
    \pretty@acts
    \Bsep\Bend
\end{array}
}

```

```

%% Pretty print an general Event-B event
%% Arguments:
%% 1. (Optional) convergence status.
%% 2. Name of the event.
%% 3. Name of the abstract event.
%% 4. (Comma-separated) list of parameters.
%% 5. (Newline(\)-separated) list of guards.
%% 6. (Newline(\)-separated) list of witness predicates.
%% 7. (Newline(\)-separated) list of assignments.
%% Usage: \B@event[conv]{conc}{abs}{x,y}{G1(x,y)\G2(x,y)}{W1\W2}{S1(v,x,y)\S2(w,x,y)}
%% will produce the following
%%
%% conc
%% refines abs

```

```

%%%%%%%% status conv
%%%%%%%% any x, y where
%%%%%%%% G1(x, y)
%%%%%%%% G2(x, y)
%%%%%%%% with
%%%%%%%% W1
%%%%%%%% W2
%%%%%%%% then
%%%%%%%% S1(v, x, y)
%%%%%%%% S2(w, x, y)
%%%%%%%% end
%%%%%%%%
%%%%%%%% Special case:
%%%%%%%% - Empty abstract event --> refines clause is omitted.
%%%%%%%% - Empty convergence status --> status clause is omitted.
%%%%%%%% - Empty witness --> with clause is omitted.
%%%%%%%% - Empty parameters, empty guards --> begin ... end
%%%%%%%% - Empty parameters --> when ... then ... end
%%%%%%%% - Empty actions --> \SKIP
\newcommand{\B@eventinline}[7][{}]{
  \def\evt@sts{#1}
  \def\evt@name{#2}
  \def\evt@absevt{#3}
  \def\evt@pars{#4}
  \def\evt@grds{#5}
  \def\evt@wits{#6}
  \def\evt@acts{#7}
  %% Ignore convergence status
  \def\pretty@sts{}
  % Pretty-print abstract events
  \ifx\evt@absevt\@empty
  \def\pretty@absevt{}
  \else
  \def\pretty@absevt{\Brefines~\evt@absevt~}
  \fi
  % Pretty-print parameters
  \ifx\evt@pars\@empty
  \def\pretty@pars{}
  \else
  \def\pretty@pars{\Bany~\evt@pars~\Bwhere~}
  \fi
  % Pretty-print guards
  \ifx\evt@grds\@empty
  \def\pretty@grds{}
  \else
  \def\evt@grds@tmp{
    \evt@grds
  }
  \ifx\evt@pars\@empty
  \def\pretty@grds{
    \Bwhen~
    \evt@grds@tmp~
  }
  \else

```

```

\def\pretty@grds{\evt@grds@tmp~}
\fi
\fi
% Pretty-print witnesses
\ifx\evt@wits\@empty
\def\pretty@wits{}
\else
\def\pretty@wits{
  \Bwith~
  \evt@wits~
}
\fi
% Pretty-print actions
\ifx\evt@acts\@empty
\def\evt@acts{\SKIP}
\else
\fi
\def\evt@acts@tmp{
  \evt@acts
}
\def\evt@acts@keyword{\Bthen}
\ifx\evt@pars\@empty
\ifx\evt@grds\@empty
\def\evt@acts@keyword{\Bbegin}
\else
\fi
\else
\fi
\def\pretty@acts{
  \evt@acts@keyword~
  \evt@acts@tmp~
}
% Really do it now
\begin{array}{l}
\Bvt{\evt@name}~\widehat{=}~
\pretty@sts
\pretty@absepts
\pretty@pars
\pretty@grds
\pretty@wits
\pretty@acts
\Bend
\end{array}
}

%%%% INITIALISATION label
\newBvt{init}

%%%% Pretty print the initialisation: no ‘‘refines’’ clause. no parameters, no
%%%% guards
%%%% Arguments:
%%%% 1. (Newline(\\)-separated) list of assignments.
%%%%
%%%% Usage: \init{S1(v,x,y)\\S2(w,x,y)}

```

```

%%%%%%%% will produce the following
%%%%%%%%
%%%%%%%% init
%%%%%%%% begin
%%%%%%%%   S1(v, x, y)
%%%%%%%%   S2(w, x, y)
%%%%%%%% end
%%%%%%%%
\newcommand{\initialisation}[1]{
  \event{\init}{#1}
}

%%%%%%%% Theorem Proof Obligation
%%%%%%%% Print the theorem proof obligation, given the theorem label.
%%%%%%%% Arguments:
%%%%%%%% 1. Theorem label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \thmpo{thm} will produce "thm/THM"
\newcommand{\thmpo}[1]{\Bthm{#1}/\Bpo{THM}}

%%%%%%%% Axiom Well-definedness Proof Obligation
%%%%%%%% Print the axiom well-definedness proof obligation, given the
%%%%%%%% axiom label.
%%%%%%%% Arguments:
%%%%%%%% 1. Axiom label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \axmwdpo{axm} will produce "axm/WD"
\newcommand{\axmwdpo}[1]{\Baxm{#1}/\Bpo{WD}}

%%%%%%%% Invariant Proof Obligation
%%%%%%%% Print the invariant proof obligation, given the event name and
%%%%%%%% invariant label
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Invariant label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \invpo{evt}{inv} will produce "evt/inv/INV"
\newcommand{\invpo}[2]{\Bevt{#1}/\Binv{#2}/\Bpo{INV}}

%%%%%%%% Theorem (in guard) Proof Obligation
%%%%%%%% Print the simulation proof obligation, given the event name and
%%%%%%%% the theorem (in guard) label.
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Theorem (in guard) label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdthmpo{evt}{thm} will produce "evt/thm/THM"
\newcommand{\grdthmpo}[2]{\Bevt{#1}/\Bthm{#2}/\Bpo{THM}}

```

```

%%%%%%%% Feasibility Proof Obligation
%%%%%%%% Print the feasibility proof obligation, given the event name and
%%%%%%%% the action label
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Action label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \fispo{evt}{act} will produce "evt/act/FIS"
\newcommand{\fispo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{FIS}}

%%%%%%%% Variant finiteness Proof Obligation
%%%%%%%% Print the Variant finiteness proof obligation
%%%%%%%% Arguments: No arguments
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \finpo will produce "FIN"
\newcommand{\finpo}{\Bpo{FIN}}

%%%%%%%% Variant Proof Obligation
%%%%%%%% Print the guard strengthen proof obligation, given the event name
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdpo{evt} will produce "evt/VAR"
\newcommand{\varpo}[1]{\Bevt{#1}/\Bpo{VAR}}

%%%%%%%% Simulation Proof Obligation
%%%%%%%% Print the simulation proof obligation, given the event name and
%%%%%%%% the action label.
%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%% 2. Action label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \simpo{evt}{act} will produce "evt/act/SIM"
\newcommand{\simpo}[2]{\Bevt{#1}/\Bact{#2}/\Bpo{SIM}}

%%%%%%%% Guard Strengthen Proof Obligation
%%%%%%%% Print the guard strengthen proof obligation, given the event
%%%%%%%% name and the guard label
%%%%%%%% Arguments:
%%%%%%%% 1. (Abstract) Event name
%%%%%%%% 2. (Abstract) Guard label
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \grdpo{evt}{grd} will produce "evt/grd/GRD"
\newcommand{\grdpo}[2]{\Bevt{#1}/\Bgrd{#2}/\Bpo{GRD}}

%%%%%%%% Variant Natural Number Proof Obligation
%%%%%%%% Print the Variant Natural Number proof obligation, given the event name

```



```

%%%%%%%% Arguments:
%%%%%%%% 1. Event name
%%%%%%%%
%%%%%%%% Usage:
%%%%%%%% - \natpo{evt} will produce "evt/NAT"
\newcommand{\natpo}[1]{\Bevt{#1}/\Bpo{NAT}}

```

Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the definition; numbers in *roman* refer to the pages where the entry is used.

Symbols		
<code>\@empty</code> ..	2, 4, 6, 11–14	
<code>\</code>	2–4, 9–12, 14	
<code>_</code>	5–10	
<code>_</code>	3, 4	
A		
<code>\aaa</code>	5–9	
<code>\axioms</code>	9	
<code>\axmwdpo</code>	15	
B		
<code>\B@declaration</code>	2–4	
<code>\B@event</code> ...	3, 4, 10–12	
<code>\B@eventinline</code> .	3, 4, 13	
<code>\B@identifier</code>	1, 2	
<code>\B@keyword</code>	1, 2	
<code>\B@label</code>	1, 2	
<code>\B@newmacro</code>	5–9	
<code>\B@oldfboxsep</code>	2–4	
<code>\B@po</code>	1, 2, 5	
<code>\B@section</code>	2–4	
<code>\Bact</code>	5, 9, 16	
<code>\Bany</code>	5, 11, 13	
<code>\Baxm</code>	5, 7, 9, 15	
<code>\Bbap</code>	5	
<code>\Bbegin</code>	5, 12, 14	
<code>\Bcst</code>	5, 6	
<code>\Bctx</code>	5, 6	
<code>\Bdeclaration</code>	2–4, 9, 10	
<code>\begin</code> ...	2–4, 11, 12, 14	
<code>\Bend</code>	5, 12, 14	
<code>\Bevt</code>	5, 8, 12, 14–17	
<code>\bfseries</code>	5	
<code>\Bgrd</code>	5, 8, 9, 16	
<code>\Bhspace</code>	2–4	
<code>\Bidentifier</code>	1, 5	
<code>\Binv</code>	5, 8, 10, 15	
<code>\Bkeyword</code>	1, 2, 4, 5	
<code>\Blabel</code>	1, 2, 5	
<code>\Bmch</code>	5, 7	
<code>\Bpar</code>	5, 8	
<code>\Bpo</code>	1, 2, 15–17	
<code>\Brefines</code>	5, 11, 13	
<code>\Bsection</code> ...	2–4, 9, 10	
<code>\Bsep</code>	2–4, 11, 12	
<code>\Bset</code>	5, 6	
<code>\Bstatus</code>	5, 11	
<code>\Bthen</code>	5, 12, 14	
<code>\Bthm</code>	5, 7, 15	
<code>\Bvrb</code>	5, 7	
<code>\Bvspace</code>	2–4	
<code>\Bwhen</code>	5, 11, 13	
<code>\Bwhere</code>	5, 11, 13	
<code>\Bwith</code>	5, 11, 14	
C		
<code>\carriersets</code>	9	
<code>\colorlet</code>	2	
<code>\constants</code>	9	
<code>\csname</code>	6	
D		
<code>\DeclareOption</code>	2–4	
<code>\def</code>	2, 4, 6, 11–14	
E		
<code>\else</code>	2, 4, 6, 11–14	
<code>\end</code>	2–5, 11, 12, 14	
<code>\endcsname</code>	6	
<code>\ensuremath</code>	1–3, 5	
<code>\event</code>	3, 4, 15	
<code>\eventB</code>	5	
<code>\eventinline</code>	3, 4	
<code>\evt@absepts</code>	11, 13	
<code>\evt@acts</code>	11–14	
<code>\evt@acts@keyword</code>	12, 14	
<code>\evt@acts@tmp</code> ...	12, 14	
<code>\evt@grds</code>	11–14	
<code>\evt@grds@tmp</code>	11, 13, 14	
<code>\evt@name</code>	11–14	
<code>\evt@pars</code>	11–14	
<code>\evt@sts</code>	11, 13	
<code>\evt@wits</code>	11–14	
<code>\expandafter</code>	6	
F		
<code>\fbox</code>	2, 3	
<code>\fboxsep</code>	2, 3	
<code>\fi</code>	2, 5, 6, 11–14	
<code>\finpo</code>	16	
<code>\fispo</code>	16	
<code>\footnotesize</code>	3	
G		
<code>\grdpo</code>	16	
<code>\grdthmpo</code>	15	
H		
<code>\hbox</code>	5	
<code>\hspace</code>	2–4	
I		
<code>\ifx</code>	2, 4, 6, 11–14	
<code>\in</code>	9, 10	
<code>\init</code>	14, 15	
<code>\initialisation</code> ...	15	
<code>\input@macro</code>	6	
<code>\invariants</code>	10	
<code>\invpo</code>	15	
<code>\is@thm</code>	2	
M		
<code>\mathbf</code>	2, 5	
<code>\mathit</code>	2	

<code>\mathsf</code>	2, 5	<code>\no@title</code>	4	<code>\setlength</code>	2, 3
		<code>\normalsize</code>	2	<code>\simpo</code>	16
N				<code>\SKIP</code>	5, 11–14
<code>\nat</code>	9, 10	P		<code>\sl</code>	5
<code>\natpo</code>	17	<code>\pretty@absepts</code> ..	11–14		
<code>\newBact</code>	9	<code>\pretty@acts</code>	12, 14	T	
<code>\newBaxm</code>	7	<code>\pretty@grds</code>	11–14	<code>\textcolor</code>	2
<code>\newBcst</code>	6	<code>\pretty@pars</code>	11–14	<code>\textsc</code>	5
<code>\newBctx</code>	6	<code>\pretty@sts</code>	11–14	<code>\thmpo</code>	15
<code>\newBevt</code>	8, 14	<code>\pretty@wits</code> ..	11, 12, 14		
<code>\newBgrd</code>	8, 9	<code>\ProcessOptions</code>	5	V	
<code>\newBinv</code>	8	Q		<code>\variables</code>	9
<code>\newBmch</code>	7	<code>\quad</code>	2	<code>\variant</code>	10
<code>\newBpar</code>	8	R		<code>\varpo</code>	16
<code>\newBset</code>	6	<code>\renewcommand</code>	2–4	W	
<code>\newBthm</code>	7	<code>\renewenvironment</code> ..	3, 4	<code>\widehat</code>	14
<code>\newBvrb</code>	7	<code>\RequirePackage</code>	1		
<code>\newcommand</code> 1–11, 13, 15–17	S		X	
<code>\newenvironment</code>	2	<code>\scriptsize</code>	4	<code>\xspace</code>	1, 2, 5
<code>\newlength</code>	4				

Change History

v1.0

General: Initial version

v1.0.1

General: Ensure that the keywords,
labels are in math-mode