

Report of Estimation Practical

Gabriel Gostiaux

2024-10-18

Labwork 2: Parameter Estimation in Signal Processing

Gabriel Gostiaux

Contents

1. Estimation under additive normal noise
2. Exponential case
3. Estimator comparison

We consider the relaxation signal of a physical process:

$$s_{\text{clean}} = s_0 e^{-\alpha_0 i}, \quad i \in [0, N-1]$$

The objective here is to estimate α_0 from a noisy signal. We consider successively two types of noises: normal (Gaussian additive) and exponential (multiplicative) noises.

1. Estimation Under Additive Normal Noise

We first assume that the experiment is perturbed by an additive white normal noise.

- **P1** Give the expression of the log-likelihood function $\ell(\alpha)$, then find the expression of the maximum likelihood estimator of α_0 . Can we give an analytical form?

To compute the log-likelihood, we need to find an expression of the probability law of the noisy signal. Here, in the Gaussian additive noise, the resulting signal is simply a Gaussian signal centered on the true signal and with the variance of the noise.

$$P(x_i) = \frac{1}{\sqrt{2\pi}\sigma} \times \exp\left(-\frac{(s_i - s_0 \times \exp(-\alpha_0 i))^2}{2\sigma^2}\right)$$
$$l_\alpha = -\frac{N}{2} \times \log(2\pi\sigma^2) - \frac{1}{2\sigma^2} \sum_{i=0}^{N-1} [s_i - s_0 \times \exp(-\alpha i)]^2$$

The MLE is then obtained for $\frac{\partial l_\alpha}{\partial \alpha} = 0$ and should attain the Cramer Rao Lower Bound (CRLB) defined by $\frac{\partial^2 l_\alpha}{\partial \alpha^2} = 0$:

$$\frac{\partial l_\alpha}{\partial \alpha} = \frac{s_0}{\sigma^2} \sum_{i=0}^{N-1} [i \times \exp(-\alpha_0 i) \times (s_i - s_0 \times \exp(-\alpha_0 i))] = 0$$

- **P2** Give the expression of the Cramer-Rao Lower Bound (CRLB) for the estimation of α_0 . What does the ratio $\frac{s_0}{\sigma}$ represent physically?

$$\frac{\partial^2 l_\alpha}{\partial^2 \alpha} = -\frac{s_0}{\sigma^2} \sum_{i=0}^{N-1} [i^2 \times \exp(-\alpha_0 i) \times (s_i - 2 \times s_0 \times \exp(-\alpha_0 i))]$$

In some cases (which ones?), the expression of the CRLB can be simplified using:

$$\sum_{n=0}^{+\infty} n^2 q^n = \frac{q(1+q)}{(1-q)^3}, \quad q < 1$$

Assuming the mean of the measured signal is the clean signal, we can use the formula:

$$\frac{\partial^2 l_\alpha}{\partial^2 \alpha} = -\frac{s_0^2}{\sigma^2} \sum_{i=0}^{+\infty} [i^2 \times \exp(-2\alpha_0 i)]$$

The CRLB is then equal to:

$$\text{CRLB} = \mathcal{E} \left(-1 / \frac{\partial^2 l_\alpha}{\partial^2 \alpha} \right) = \frac{\sigma^2}{s_0^2} \times \frac{(1 - e^{-2\alpha_0})^3}{e^{-2\alpha_0}(1 + e^{-2\alpha_0})}$$

↪ Design a MATLAB function which gives a realization (length $N = 100$) of the noisy signal. The arguments will be s_0, α_0 and σ , the standard deviation of noise. You can choose the parameters as $\alpha_0 = 0.1$, $\frac{s_0}{\sigma} = 10$.

↪ Design a function which calculates the log-likelihood function $\ell(\alpha)$ using the previous realization. α should be an input parameter of the function.

↪ Plot $\ell(\alpha)$ for $\alpha \in [0, 1]$.

↪ Plot again this curve using other realizations.

Q1: What are your comments?

One can assume this function of α admits a maximum. On the figure, we can estimate $\alpha_0 = 0.1$.

↪ Design a function which finds the maximum likelihood estimator from a realization. You can use the MATLAB functions `fzero` or `fminsearch`.

Decay estimator that minimizes the function: [0.10242188]

↪ Estimate the statistical mean and variance of the estimator with a Monte Carlo simulation.

Q2: Is the estimator biased? Does it reach the CRLB?

The CRLB for a decay rate equal to 0.1 is $4.000028574288418 \times 10^{-5}$.

Since the variance equals the CRLB, the estimator is efficient, and it is not biased since it does not differ from the exact theoretical value as shown by the Monte Carlo simulation.

2. Exponential Case

We now consider that the signal (2.1) is perturbed by exponential noise. Remember that for such a process (with mean I) the probability density is:

$$P(x) = \frac{1}{I} \exp \left[-\frac{x}{I} \right]$$

- **P3** Express the maximum likelihood estimator of α_0 . Is it the same as the Gaussian case?

The resulting random variable follows an exponential probability law shifted by the deterministic signal:

Noisy and clean signal, for $\alpha = 0.1$




Figure 1:

Log-likelihood for one realization




Figure 2: png

Log-likelihood for different realization




Figure 3: png

Mean and var of MLE obtained by Monte Carlo simlation




Figure 4: png

$$\begin{aligned}
P(s_i | \alpha) &= \frac{1}{s_{\text{clean}}} \exp\left(-\frac{s_i}{s_{\text{clean}}}\right) \\
l_\alpha &= -\sum \ln(s_{\text{clean}}) - \sum \left(\frac{s_i}{s_{\text{clean}}}\right) \\
\frac{\partial l_\alpha}{\partial \alpha} &= \frac{\partial}{\partial \alpha} \left[-\sum \ln(s_0 e^{-\alpha i}) - \sum \frac{s_i}{s_0} e^{\alpha i} \right] \\
\frac{\partial l_\alpha}{\partial \alpha} &= \frac{\partial}{\partial \alpha} \left[-N \ln(s_0) + \alpha \sum i - \sum \frac{s_i}{s_0} e^{\alpha i} \right]
\end{aligned}$$

This results in:

$$\begin{aligned}
\frac{\partial l_\alpha}{\partial \alpha} &= \sum i - \sum \frac{s_i}{s_0} i e^{\alpha i} \\
0 &= \sum i - \sum \frac{s_i}{s_0} i e^{\alpha_0 i} \\
0 &= \sum i \left(1 - \frac{s_i}{s_0} e^{\alpha_0 i} \right)
\end{aligned}$$

- **P4** Express the CRLB for α_0 estimation. In order to obtain an analytical form, we can use the result:

$$\begin{aligned}
\frac{\partial^2 l_\alpha}{\partial^2 \alpha} &= -\frac{1}{s_0} \sum s_i i^2 e^{\alpha i} \\
\left\langle \frac{\partial^2 l_\alpha}{\partial^2 \alpha} \right\rangle &= -\frac{1}{s_0} \sum \langle s_i \rangle i^2 e^{\alpha i} \\
&= -\sum i^2
\end{aligned}$$

$$\sum_{n=0}^N n^2 = \frac{N(N+1)(2N+1)}{6}$$

$$\text{CRLB} = -\frac{1}{\left\langle \frac{\partial^2 L_\alpha}{\partial^2 \alpha} \right\rangle} = \frac{6}{N(N+1)(2N+1)}$$

What are the parameters the CRLB depends on?

↪ Design a MATLAB function which gives a realization of the stochastic process.

Noisy and clean signal (exponential white noise), for $\alpha = 0.1$




Figure 5: png

Log-likelihood for one realization (exponential white noise)





Figure 6: png

Log-likelihood for different realization (exponential white noise)



Q3: On which parameters does it depend?

↪ Design a function which finds the maximum likelihood estimator from an experiment. We can use the MATLAB functions `fzero` or `fminsearch`.

Decay estimator that minimizes the function: [0.08886719]

↪ Estimate the statistical mean and variance of the estimator with a Monte Carlo simulation.

Q4: Is the estimator biased? Does it reach the CRLB?

Since the variance equals the CRLB, the estimator is efficient, and it is not biased since it does not differ from the exact theoretical value as shown by the Monte Carlo simulation.

Useful Commands/Tips:

`R = randexp(1, n, lambda)` returns pseudo-random values drawn from an exponential distribution with means stored in the vector $(1 \times n)$ lambda.

3. Estimator Comparison

↪ Apply the maximum likelihood estimator adapted to the normal noise to the signal perturbed by exponential noise. Plot the estimate for several realizations. Estimate the variance.

Q5: What are your comments?

-> to be continued

Mean and var of MLE obtained by Monte Carlo simlation




Figure 7: png