Finite Elements for Linear and Non Linear Mechanics

Gabriel Jezler

March 3, 2026

Contents

1 Introduction **3**

2 Kinematics and Stresses **4**

2.1 Kinematics 4

2.2 Stresses 5

2.3 Strain Energy Density 5

3 Material Behavior **6**

3.1 Linear Materials 6

3.1.1 Linear Elastic Isotropic 6

3.2 Non Linear Materials 7

3.2.1 Saint Venant-Kirchhoff 7

3.2.2 Compressible Neo-Hookean 7

4 Finite Element Formulation **8**

4.1 Equilibrium Equation 8

4.2 Discretization 9

4.3 Elementary description 10

4.4 Numerical Integration 10

4.5 Assembly 11

5 Linear Solution **12**

6 Non Linear Solution **13**

6.1 Newton-Raphson Method 13

6.2 Application to Finite Elements 14

6.2.1 Internal virtual work 14

6.2.2 External virtual work 15

7 The code **16**

7.1 Geometry 16

7.2 Mesh 16

7.3 Material 16

7.4 Element 16

7.5 Model 16

7.6 Boundary Conditions 16

7.7 Post Processing 16

Chapter 1

Introduction

Chapter 2

Kinematics and Stresses

In this section, the kinematics and the different stress tensors used in this paper are defined. The relation between them is also given. Finally, the definition of the strain energy density is given as well as its relation with the different stress tensors. These definitions are used throughout the paper and are important for the understanding of the following sections.

2.1 Kinematics

The kinematics of a body is defined by the transformation between the initial configuration and the current configuration. This transformation can be defined as stated by Equation 2.1. Thoughout this paper, the initial configuration will be denoted by capital letters while the current configuration will be denoted by lowercase letters.

$$\vec{x} = \vec{\phi}(\vec{X},\, t) \tag{2.1}$$

Based on this transformation, it is possible to define the transformation gradient (Equation 2.2) and the Jacobian of the transformation (Equation 2.3).

$$\bar{\bar{\mathrm{F}}} = \bar{\bar{\nabla}}_0 \vec{x} = \frac{\partial \vec{x}}{\partial \vec{X}} \tag{2.2}$$

$$\mathrm{J} = \det \bar{\bar{\mathrm{F}}} \tag{2.3}$$

Based on the tensor $\bar{\bar{\mathrm{F}}}$, it is possible to define multiple tensors to represent the defromation. In this codes, two of then are used: the right Cauchy-Green deformation tensor $\bar{\bar{\mathrm{C}}}$ and the Green-Lagrange strain tensor $\bar{\bar{\mathrm{E}}}$ as given by Equations 2.4 and 2.5 respectively.

$$\bar{\bar{\mathrm{C}}} = \bar{\bar{\mathrm{F}}}^T \bar{\bar{\mathrm{F}}} \tag{2.4}$$

$$\bar{\bar{\mathrm{E}}} = \frac{1}{2}\left(\bar{\bar{\mathrm{C}}} - \bar{\bar{\mathrm{I}}}\right) = \frac{1}{2}\left(\bar{\bar{\mathrm{F}}}^T \bar{\bar{\mathrm{F}}} - \bar{\bar{\mathrm{I}}}\right) \tag{2.5}$$

2.2 Stresses

Four different stress tensors are used throughout this paper and are listed below:

- $\bar{\bar{\sigma}}$: Cauchy stress tensor
- $\bar{\bar{\mathcal{T}}}$: kirchhoff stress tensor
- $\bar{\bar{\mathrm{P}}}$: First Piola-Kirchhoff stress tensor
- $\bar{\bar{\mathrm{S}}}$: Second Piola-kirchhoff stress tensor

They are all stress' representations but under different configurations. They can all be related under the following equation:

$$\bar{\bar{\sigma}} = \mathrm{J}^{-1} \cdot \bar{\bar{\mathcal{T}}} = \mathrm{J}^{-1} \cdot \bar{\bar{\mathrm{P}}}\bar{\bar{\mathrm{F}}}^T = \mathrm{J}^{-1} \cdot \bar{\bar{\mathrm{F}}}\bar{\bar{\mathrm{S}}}\bar{\bar{\mathrm{F}}}^T \tag{2.6}$$

2.3 Strain Energy Density

The strain energy density is defined as:

$$\Psi(\bar{\bar{\mathrm{F}}}, \vec{X}) = \int \bar{\bar{\mathrm{P}}} : \dot{\bar{\bar{\mathrm{F}}}}\,\mathrm{dt} \tag{2.7}$$

From this definition, a new definition for $\bar{\bar{\mathrm{P}}}$ can be stated:

$$\bar{\bar{\mathrm{P}}} = \frac{\partial \Psi}{\partial \bar{\bar{\mathrm{F}}}} \tag{2.8}$$

This can also be written as a function of the tensor $\bar{\bar{\mathrm{C}}}$ as given below:

$$\Psi(\bar{\bar{\mathrm{F}}}, \vec{X}) = \Psi(\bar{\bar{\mathrm{C}}}, \vec{X}) = \int \frac{1}{2}\bar{\bar{\mathrm{S}}} : \dot{\bar{\bar{\mathrm{C}}}}\,\mathrm{dt} \tag{2.9}$$

This means the $\bar{\bar{\mathrm{S}}}$ can be written as:

$$\bar{\bar{\mathrm{S}}} = 2\frac{\partial \Psi}{\partial \bar{\bar{\mathrm{C}}}} = \frac{\partial \Psi}{\partial \bar{\bar{\mathrm{E}}}} \tag{2.10}$$

Chapter 3

Material Behavior

3.1 Linear Materials

3.1.1 Linear Elastic Isotropic

This model uses the hypothesis of small displacements under a elastic regime. This is mainly done by assuming that:

$$\bar{\bar{\nabla}}\vec{u} \approx \bar{\bar{\nabla}}_0\vec{u} \qquad \text{and} \qquad \|\bar{\bar{\nabla}}\vec{u}\| \approx 0$$

This leads to the following conclusions:

$$\begin{cases} \bar{\bar{\mathrm{F}}} & = \bar{\bar{\mathrm{I}}} + \bar{\bar{\nabla}}_0\vec{u} \approx \bar{\bar{\mathrm{I}}} \\ \mathrm{J} & = \det \bar{\bar{\mathrm{F}}} \approx 1 \end{cases} \qquad \Longrightarrow \qquad \bar{\bar{\sigma}} \approx \bar{\bar{\mathcal{T}}} \approx \bar{\bar{\mathrm{P}}} \approx \bar{\bar{\mathrm{S}}}$$

Under this hypothesis, the strain ($\bar{\bar{\varepsilon}}$) is used to model the material. It is defined as:

$$\bar{\bar{\varepsilon}} = \frac{1}{2}\left(\bar{\bar{\nabla}}\vec{u} + \bar{\bar{\nabla}}\vec{u}^T\right) \tag{3.1}$$

Using this, both the strain energy density and Cauchy stress can be defined as:

$$\Psi = \frac{1}{2}\lambda\ (tr(\bar{\bar{\varepsilon}}))^2 + \mu\,\bar{\bar{\varepsilon}} : \bar{\bar{\varepsilon}} \tag{3.2}$$

$$\bar{\bar{\sigma}} = \lambda\, tr(\bar{\bar{\varepsilon}})\bar{\bar{\mathrm{I}}} + 2\mu\,\bar{\bar{\varepsilon}} \tag{3.3}$$

The Equation 3.3 is also known as the generalized Hooke's law for isotropic materials. This is written as a function of the elaticity tensor, which is given by:

$$\bar{\bar{\sigma}} = \bar{\bar{\bar{\bar{C}}}} : \bar{\bar{\varepsilon}} \qquad \text{with} \qquad C_{ijkl} = \lambda\,\delta_{ij}\delta_{kl} + \mu\,(\delta_{ik}\delta_{jl} + \delta_{il}\delta_{jk}) \tag{3.4}$$

This model is characterized by two parameters (λ and μ) which are called the Lamé coefficients. They can be written as a function of the Young's modulus (E) and Poisson coefficient (ν) as follows:

$$\lambda = \frac{E\nu}{(1+\nu)(1-2\nu)} \tag{3.5}$$

$$\mu = \frac{E}{2(1+\nu)} \tag{3.6}$$

3.2 Non Linear Materials

3.2.1 Saint Venant-Kirchhoff

This model can be is often used for moderate deformations under a elastic regime. Unlike the Linear Elastic Isotropic model, the present framework does not uses the small displacement hypothesis and therefore is no longer a linear model.

Similarly, the model uses the strain energy density to correlate the stress and kinematics of the material. Within this context, the strain energy and the second Piola-Kirchhoff stress tensor are give below:

$$\Psi = \frac{1}{2}\lambda \left(tr(\bar{\bar{\mathrm{E}}})\right)^2 + \mu\, \bar{\bar{\mathrm{E}}} : \bar{\bar{\mathrm{E}}} \tag{3.7}$$

$$\bar{\bar{\mathrm{S}}} = \lambda\, tr(\bar{\bar{\mathrm{E}}})\bar{\bar{\mathrm{I}}} + 2\mu\, \bar{\bar{\mathrm{E}}} \tag{3.8}$$

3.2.2 Compressible Neo-Hookean

Unlike the Saint Venant-Kirchhoff model, this model can be employed for large deformations under a elastic regime. It considers a compressible hyper-elastic material that follows the following equations:

$$\Psi = \frac{1}{2}\mu \left(tr(\bar{\bar{\mathrm{C}}}) - 3\right) + \mu\, \ln \mathrm{J} + \frac{1}{2}\lambda\, (\ln \mathrm{J})^2 \tag{3.9}$$

$$\bar{\bar{\mathrm{S}}} = \mu \left(\bar{\bar{\mathrm{I}}} - \bar{\bar{\mathrm{C}}}^{-1}\right) - \lambda\, \ln \mathrm{J}\, \bar{\bar{\mathrm{C}}}^{-1} \tag{3.10}$$

Chapter 4

Finite Element Formulation

4.1 Equilibrium Equation

The equation to be solved is given below:

$$\vec{\mathrm{div}}\bar{\bar{\sigma}} + \vec{f} = \vec{0} \tag{4.1}$$

However, the equation above is in its strong formulation. For the finite elements methods, it is far more useful to convert it to its weak form. This allows for the application of boundary conditions directly in the equation. It can be done by using the virtual work theorem:

$$\vec{\mathrm{div}}\bar{\bar{\sigma}} + \vec{f} = \vec{0} \qquad \Longrightarrow \qquad \delta\mathcal{W} = \int_v \left(\vec{\mathrm{div}}\bar{\bar{\sigma}} + \vec{f}\right) \cdot \delta\vec{u}\,\mathrm{dv} = 0 \quad \forall\,\delta\vec{u} \Longrightarrow$$

$$\Longrightarrow \qquad \delta\mathcal{W} = \int_v \vec{\mathrm{div}}\bar{\bar{\sigma}} \cdot \delta\vec{u}\,\mathrm{dv} + \int_v \vec{f} \cdot \delta\vec{u}\,\mathrm{dv} = 0 \quad \forall\,\delta\vec{u}$$

This can be further developed by applying the following rule (Equation 4.2) along side with the divergence theorem (Equation 4.3).

$$\vec{\mathrm{div}}\bar{\bar{A}} \cdot \vec{b} = \vec{\mathrm{div}}\left(\bar{\bar{A}} \cdot \vec{b}\right) - \bar{\bar{A}} : \vec{b} \tag{4.2}$$

$$\int_v \mathrm{div}\left(\vec{a}\right)\,\mathrm{dv} = \int_s \vec{a} \cdot \vec{n}\,\mathrm{ds} \tag{4.3}$$

By applying both relation on the left hand term of the equation, it is possible to obtain:

$$\delta\mathcal{W} = \int_v \bar{\bar{\sigma}} : \bar{\bar{\nabla}}\delta\vec{u}\,\mathrm{dv} - \left(\int_v \vec{f} \cdot \delta\vec{u}\,\mathrm{dv} + \int_s \vec{t} \cdot \delta\vec{u}\,\mathrm{ds}\right) = 0 \quad \forall\,\delta\vec{u} \tag{4.4}$$

Where:

$$\vec{t} = \bar{\bar{\sigma}} \cdot \vec{n}$$

The next step is to rewrite Equation 4.4 with respect to the initial configuration. This can be done by using the Jacobian of the transformation defined by Equation 2.3. Using this, it is possible to rewrite Equation 4.4 as follows:

$$\int_V \bar{\bar{\sigma}} : \bar{\bar{\nabla}} \delta\vec{u}\, J \,\mathrm{dV} - \left(\int_V \vec{f} \cdot \delta\vec{u}\, J \,\mathrm{dV} + \int_S \vec{t} \cdot \delta\vec{u} \left(\frac{\partial s}{\partial S} \right) \mathrm{dS} \right) = 0 \quad \forall\, \delta\vec{u} \qquad \Longrightarrow$$

$$\Longrightarrow \qquad \int_V \underbrace{\bar{\bar{\mathcal{T}}}}_{\mathrm{J}\bar{\bar{\sigma}}} : \bar{\bar{\nabla}} \delta\vec{u} \,\mathrm{dV} - \left(\int_V \underbrace{\vec{f_0}}_{J\vec{f}} \cdot \delta\vec{u} \,\mathrm{dV} + \int_S \underbrace{\vec{t_0}}_{\left(\frac{\partial s}{\partial S}\right)\vec{t}} \cdot \delta\vec{u} \,\mathrm{dS} \right) = 0 \quad \forall\, \delta\vec{u}$$

Furthermore, the gradient can be written as:

$$\bar{\bar{\nabla}} \delta\vec{u} = \frac{\partial \delta\vec{u}}{\partial \vec{x}} = \frac{\partial \delta\vec{u}}{\partial \vec{X}} \cdot \frac{\partial \vec{X}}{\partial \vec{x}} = \bar{\bar{\nabla}}_0 \delta\vec{u} \cdot \bar{\bar{\mathrm{F}}}^{-1}$$

Finally, using that:

$$\bar{\bar{A}} : \left(\bar{\bar{B}} \bar{\bar{C}} \right) = \left(\bar{\bar{A}} \bar{\bar{C}}^T \right) : \bar{\bar{B}}$$

It is possible to obtain the final equation:

$$\delta\mathcal{W} = \int_V \underbrace{\bar{\bar{\mathrm{P}}}}_{\bar{\bar{\mathcal{T}}}\bar{\bar{\mathrm{F}}}^{-T}} : \bar{\bar{\nabla}}_0 \delta\vec{u} \,\mathrm{dV} - \left(\int_V \vec{f_0} \cdot \delta\vec{u} \,\mathrm{dV} + \int_S \vec{t_0} \cdot \delta\vec{u} \,\mathrm{dS} \right) = 0 \quad \forall\, \delta\vec{u} \tag{4.5}$$

4.2 Discretization

The discretization is a important step for the finite volume method. In this part, we use interpolation based on nodal values for the value of displacement inside an element. This is done by using shape functions (N) for each element node a (N_a).

$$\vec{u}(\vec{X}) = \sum_{a \in e} N_a \left(\vec{\xi} \right) \cdot \vec{U}_a \tag{4.6}$$

$$\bar{\bar{\nabla}}_0 \vec{u}(\vec{X}) = \sum_{a \in e} \bar{\bar{\nabla}}_0 N_a \left(\vec{\xi} \right) \otimes \vec{U}_a \tag{4.7}$$

In those, the shape function is given as a function of the position vector $\vec{\xi}$. This is due to the fact that these functions are defined for a reference coordinate space. For a line element this would be for $\xi \in [-1, 1]$, for example. It is then possible to use the element's transformation (Equation 4.8) to relate the reference system ($\vec{\xi}$) to the element's global coordinates ($\vec{X}$).

$$\vec{X} = \psi(\vec{\xi}) \qquad \Longrightarrow \qquad \vec{\xi} = \psi^{-1}(\vec{X}) \tag{4.8}$$

In addition, the Galerkin method is used, which means that the virtual field is given by:

$$\delta\vec{u}(\vec{X}) = \sum_{a\,\in\,e} N_a\left(\vec{\xi}\right) \cdot \delta\vec{U}_a \tag{4.9}$$

$$\bar{\bar{\nabla}}_0 \delta\vec{u}(\vec{X}) = \sum_{a\,\in\,e} \bar{\bar{\nabla}}_0 N_a\left(\vec{\xi}\right) \otimes \delta\vec{U}_a \tag{4.10}$$

4.3 Elementary description

The total virtual work of the system can be given as the sum of the virtual work for each element as stated below. This means that the final equation will be the result of the sum of the contribution of each element. For that reason, it is possible to work with the element-wise contribution and then add them up in a process called assembly.

$$\delta\mathcal{W} = \sum_{e} \delta\mathcal{W}^{(e)} = 0 \quad \forall\, \delta\vec{u}^{(e)} \tag{4.11}$$

Therefore, by analyzing the element contribution fro the virtual work, the following relation is obtained

$$\delta\mathcal{W}^{(e)} = \int_{V^{(e)}} \bar{\bar{\mathrm{P}}}^{(e)} : \bar{\bar{\nabla}}_0 \delta\vec{u}^{(e)}\,\mathrm{dV} - \left(\int_{V^{(e)}} \vec{f_0}^{\,(e)} \cdot \delta\vec{u}^{(e)}\,\mathrm{dV} + \int_{S^{(e)}} \vec{t_0}^{\,(e)} \cdot \delta\vec{u}^{(e)}\,\mathrm{dS}\right)$$

By using the discretized functions in the equation above, it then becomes:

$$\delta\mathcal{W}^{(e)} = \sum_{a\,\in\,e} \left[\underbrace{\int_{V^{(e)}} \bar{\bar{\mathrm{P}}}^{(e)} \vec{\nabla}_0 N_a\,\mathrm{dV}}_{\delta\vec{\mathcal{W}}^{(e)}_{int,a}} - \underbrace{\left(\int_{V^{(e)}} \vec{f_0}^{\,(e)} \cdot N_a\,\mathrm{dV} + \int_{S^{(e)}} \vec{t_0}^{\,(e)} \cdot N_a\,\mathrm{dS}\right)}_{\delta\vec{\mathcal{W}}^{(e)}_{ext,a}} \right] \cdot \delta\vec{U}_a \tag{4.12}$$

4.4 Numerical Integration

To solve for the integrals in the equations above, a numerical integration strategy is used. This is done with the Gauss quadrature framework.

Before using this process, one additional development needs to be done to Equation 4.12. As mentioned before, the shape functions are written in the space of the reference element. Therefore, it is useful to also integrate in this coordinate system. To make this change in integration variable, a volume and surface Jacobian for the $V \longrightarrow \hat{V}$ and $S \longrightarrow \hat{S}$ transformations are used and are represented by J_V and J_S, respectively.

$$
\begin{aligned}
\delta\vec{\mathcal{W}}_{int,a}^{(e)} &= \int_{V^{(e)}} \bar{\bar{\mathrm{P}}}^{(e)} \cdot \vec{\nabla}_0 N_a \,\mathrm{dV} = \\
&= \int_{\hat{V}^{(e)}} \bar{\bar{\mathrm{P}}}^{(e)} \left(\psi^{(e)}\left(\vec{\xi}\right)\right) \cdot \vec{\nabla}_0 N_a \left(\vec{\xi}\right) \cdot \mathrm{J}_V^{(e)} \mathrm{d}\hat{\mathrm{V}} \\
\delta\vec{\mathcal{W}}_{ext,a}^{(e)} &= \int_{V^{(e)}} \vec{f_0}^{(e)} \cdot N_a \,\mathrm{dV} + \int_{S^{(e)}} \vec{t_0}^{(e)} \cdot N_a \,\mathrm{dS} = \\
&= \int_{\hat{V}^{(e)}} \vec{f_0}^{(e)} \left(\psi^{(e)}\left(\vec{\xi}\right)\right) \cdot N_a \left(\vec{\xi}\right) \cdot \mathrm{J}_V^{(e)} \mathrm{d}\hat{\mathrm{V}} + \int_{\hat{S}^{(e)}} \vec{t_0}^{(e)} \left(\psi^{(e)}\left(\vec{\xi}\right)\right) \cdot N_a \left(\vec{\xi}\right) \cdot \mathrm{J}_S^{(e)} \mathrm{d}\hat{\mathrm{S}}
\end{aligned}
$$

Now, by using the quadrature's approximation, it is possible to write:

$$
\delta\vec{\mathcal{W}}_{int,a}^{(e)} \approx \sum_g \omega_g \cdot \bar{\bar{\mathrm{P}}}^{(e)} \left(\psi^{(e)}\left(\vec{\xi_g}\right)\right) \cdot \vec{\nabla}_0 N_a \left(\vec{\xi_g}\right) \cdot \mathrm{J}_V^{(e)} \tag{4.13}
$$

$$
\delta\vec{\mathcal{W}}_{ext,a}^{(e)} \approx \sum_g \omega_g \cdot \vec{f_0^{(e)}} \left(\psi^{(e)}\left(\vec{\xi_g}\right)\right) \cdot N_a \left(\vec{\xi_g}\right) \cdot \mathrm{J}_V^{(e)} + \sum_{g_s} \vec{t_0^{(e)}} \left(\psi^{(e)}\left(\vec{\xi_{g_s}}\right)\right) \cdot N_a \left(\vec{\xi_{g_s}}\right) \cdot \mathrm{J}_S^{(e)} \tag{4.14}
$$

4.5 Assembly

The final step is to assemble the contribution of each element to obtain the global system of equations. This is done by summing the contribution of each element connected to node a. This results in a system with n_{nodes} equations with a varying from 1 to n_{nodes}:

$$
\sum_{e \in E_a} \left[\delta\vec{\mathcal{W}}_{int,a}^{(e)} - \delta\vec{\mathcal{W}}_{ext,a}^{(e)}\right] = \vec{0} \quad \forall\, a \in \{1, 2, ..., n_{nodes}\} \tag{4.15}
$$

Where E_a is the set of element that are connected to node a. This results in a system of equations that can be solved for the unknowns $\vec{U}_a$.

Chapter 5

Linear Solution

Chapter 6

Non Linear Solution

6.1 Newton-Raphson Method

The Newton-Raphson method is an iterative method used to solve non linear equations. For the case of a 1D equation, the formulation is given by:

$$f(x) = 0$$

The ideia is to start with an initial guess for the solution and then iteratively improve it until convergence is achieved. The method is based on the Taylor series expansion of the function around the current guess. The next guess is then given by:

$$x^{k+1} = x^k + \Delta x^k \qquad \text{where} \qquad \Delta x^k = -\frac{f(x^k)}{f'(x^k)} \tag{6.1}$$

As we expand this formulation, it is possible to solve for a system of equations - where f is now a vector - with n unknowns:

$$\vec{f}(\vec{x}) = \vec{0}$$

For this case, the definition of a directional derivative is needed. This can be defined as:

$$D\vec{f}(\vec{x})\ [\vec{u}] = \frac{d}{d\epsilon}\bigg|_{\epsilon=0} \vec{f}(\vec{x} + \epsilon\vec{u}) \tag{6.2}$$

Therefore, the next guess for the solution is given by:

$$x^{k+1} = x^k + \Delta x^k \qquad \text{where} \qquad D\vec{f}\left(\vec{x}^k\right)\ \left[\Delta\vec{x}^k\right] = -\vec{f}\left(\vec{x}^k\right) \tag{6.3}$$

6.2 Application to Finite Elements

In order to apply the Newton-Raphson method to the finite element method, the equation to be solved is stated in 4.5. This means that the function to be solved is the virtual work of the system, and hence, the firts step is to compute the directional derivative of the virtual work with respect to a displacement increment $\Delta\vec{u}$:

$$
\begin{aligned}
&D\delta\mathcal{W}\left(\vec{\phi},\, \delta\vec{u}\right)\,[\Delta\vec{u}] = \\
&\quad = \underbrace{\int_V D\bar{\bar{\mathrm{P}}}\,[\Delta\vec{u}] : \bar{\bar{\nabla}}_0\delta\vec{u}\,\mathrm{dV}}_{D\delta\mathcal{W}^{int}\,[\Delta\vec{u}]} - \underbrace{\left(\int_V D\vec{f_0}\,[\Delta\vec{u}]\cdot\delta\vec{u}\,\mathrm{dV} + \int_S D\vec{t_0}\,[\Delta\vec{u}]\cdot\delta\vec{u}\,\mathrm{dS}\right)}_{D\delta\mathcal{W}^{ext}\,[\Delta\vec{u}]} = 0 \quad \forall\,\delta\vec{u}
\end{aligned}
\tag{6.4}
$$

To solve for the next step, the virtual work of the system is composed of the sum of the internal virtual work and the external virtual work. Then, the directional derivative of each of them is computed separately. In both cases, it will be written as follows:

$$
D\delta\mathcal{W}\,[\Delta\vec{u}] = \sum_a\sum_b \vec{U}_a\cdot\bar{\bar{K}}_{ik}^{(a,b)}\cdot\delta\vec{U}_b
$$

The goal with this section is to find the tangent tensor $\bar{\bar{K}}_{ik}^{(a,b)}$ for each node a and b. Once this is done, the next step is to solve for the increment of displacement $\Delta\vec{U}$ by solving the following system of equations:

$$
\sum_a\sum_b \vec{U}_a\cdot\bar{\bar{K}}_{ik}^{(a,b)}\cdot\delta\vec{U}_b = -\delta\mathcal{W} = \sum \quad \forall\,\delta\vec{u}
$$

6.2.1 Internal virtual work

$$
\int_V D\bar{\bar{\mathrm{P}}}\,[\Delta\vec{u}] : \bar{\bar{\nabla}}_0\delta\vec{u}\,\mathrm{dV} \tag{6.5}
$$

Discretization

Elementary Description

Numerical Integration

6.2.2 External virtual work

Discretization

Elementary Description

Numerical Integration

Chapter 7

The code

7.1 Geometry

7.2 Mesh

7.3 Material

7.4 Element

7.5 Model

7.6 Boundary Conditions

7.7 Post Processing