Instituto Federal de Educação, Ciência e Tecnologia do Ceará
Curso:Informática
Disciplina: SOR 2
Aluno: Gabriel Rodrigues Moreira

Atividade-Presença-02

Parte 1

1 etapa:

_____

2 etapa:

a) 0/24

b) 0/2

c) 0 4 e 5 15

d) show startup-config

e) as configurações de startup ainda não foram definidas

_____

Parte 2

etapa 1:

etapa 2:


```
line con 0
!
line vty 0 4
 login
line vty 5 15
 login
!
!
!
!
end


Switch#
Switch#show startup-config
startup-config is not present
Switch#
Switch#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#hostname S1
S1(config)#exit
S1#
%SYS-5-CONFIG_I: Configured from console by console

S1#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
S1(config)#line console 0
S1(config-line)#password letmein
S1(config-line)#login
S1(config-line)#exit
S1(config)#exit
S1#
%SYS-5-CONFIG_I: Configured from console by console

S1#
```

a) sem o login o usuário não pode acessar o router

etapa 3:

etapa 4:


```
                        IOS Command Line Interface
% Bad passwords




Press RETURN to get started!


User Access Verification

Password:

S1>enable
S1#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
S1(config)#enable password cl$c0
S1(config)#exit
S1#
%SYS-5-CONFIG_I: Configured from console by console

S1#
```

etapa 5:

```
S1                                                              —   □   ✕

 CLI

                        IOS Command Line Interface

 Press RETURN to get started!


 User Access Verification

 Password:

 S1>enable
 Password:
 S1#show running-config
 Building configuration...

 Current configuration : 1125 bytes
 !
 version 12.2
 no service timestamps log datetime msec
 no service timestamps debug datetime msec
 no service password-encryption
 !
 hostname S1
 !
 enable password cl$c0
 !
 !
 !
 !
 !
 spanning-tree mode pvst
 spanning-tree extend system-id
 !
 interface FastEthernet0/1
  --More--

 Ctrl+F6 to exit CLI focus              Copy        Paste

 ☐ Top
```

etapa 6:

```
S1                                                              —   □   ✕

CLI

                        IOS Command Line Interface

!
!
!
line con 0
 password letmein
 login
!
line vty 0 4
 login
line vty 5 15
 login
!
!
!
!
end


S1#
S1#config t
Enter configuration commands, one per line.   End with CNTL/Z.
S1(config)#enable secret itsasecret
S1(config)#sair
              ^
% Invalid input detected at '^' marker.

S1(config)#sair
              ^
% Invalid input detected at '^' marker.

S1(config)#exit
S1#
%SYS-5-CONFIG_I: Configured from console by console

S1#

Ctrl+F6 to exit CLI focus                        Copy      Paste


☐ Top
```

etapa 7:

a) 082D495A041C0C19

b) para que a senha não fique exposta.

etapa 8:

Parte 3

etapa 1:

a) quando alguém logar no switch.

b) porque as configurações são separadas.

Parte 4

etapa 1:

a) copy run start

b) show start

c) sim

Parte 5

etapa 1:

a)

b)

```
S2                                                    —   □   ✕

 CLI

                    IOS Command Line Interface

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/2, changed state to up

%LINK-5-CHANGED: Interface FastEthernet0/1, changed state to up

%LINEPROTO-5-UPDOWN: Line protocol on Interface FastEthernet0/1, changed state to up


Switch>enable
Switch#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
Switch(config)#host name S2
                     ^
% Invalid input detected at '^' marker.

Switch(config)#hostname S2
S2(config)#exit
S2#
%SYS-5-CONFIG_I: Configured from console by console

S2#line console 0
           ^
% Invalid input detected at '^' marker.

S2#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
S2(config)#line console 0
S2(config-line)#password letmain
S2(config-line)#login
S2(config-line)#exit
S2(config)#exit
S2#
%SYS-5-CONFIG_I: Configured from console by console

S2#

Ctrl+F6 to exit CLI focus                        Copy        Paste

□ Top
```

c)

```
S2#configure terminal
Enter configuration commands, one per line.  End with CNTL/Z.
S2(config)#enable password cl$c0
S2(config)#exit
S2#
%SYS-5-CONFIG_I: Configured from console by console

S2#
```

d)

```
S2#config t
Enter configuration commands, one per line.  End with CNTL/Z.
S2(config)#banner motd "Sistema Seguro somente, pessoal autorizado!"
S2(config)#exit
S2#
%SYS-5-CONFIG_I: Configured from console by console

S2#
```

e)
```
S2#configure t
Enter configuration commands, one per line.  End with CNTL/Z.
S2(config)#enable secret itsasecret
S2(config)#exit
S2#
%SYS-5-CONFIG_I: Configured from console by console

S2#
```

f)
```
S2#copy run start
Destination filename [startup-config]?
Building configuration...
[OK]
S2#
S2#
```