


# C Programming (part 2)

# Topics

- Intro to memory (Addressing)
- Pointers
  - Pass by value vs pass by reference
  - Pointer Arithmetic
- Arrays
- Strings
- Structs

# Intro to Memory

- C's memory model matches the underlying (virtual) memory system
  - Array of addressable bytes
- Variables are simply names for contiguous sequences of bytes
  - Number of bytes given by type of variable
- Compiler translates names to addresses
  - handles memory addressing for us




# Pointers

- A pointer simply an address
- Pointer Declaration
  - Data type followed by \*
  - Example:
    - `int *p; // p will point to an int`
    - You can think of it as "variable p will hold the address of a int"
- Pointer Operators
  - & (Address)
    - `&X` gives us the address of variable X
  - \* (De-referencing)
    - `*X` gives value stored at the address X

# Pointer (example)

```
int i;  
int *ptr;  
  
i = 4;  
ptr = &i;  
*ptr = *ptr + 1;
```




# Pointer (example)

```
int i;  
int *ptr;
```

```
i = 4;  
ptr = &i;  
*ptr = *ptr + 1;
```

store the value 4 into the memory location associated with i




# Pointer (example)

```
int i;  
int *ptr;
```

```
i = 4;  
ptr = &i; ←  
*ptr = *ptr + 1;
```

store the address of i into the  
memory location associated with ptr




# Pointer (example)

```
int i;  
int *ptr;
```

store the result into memory  
at the address stored in ptr

```
i = 4;  
ptr = &i;  
*ptr = *ptr + 1;
```

read the contents of memory  
at the address stored in ptr





# Parameter Passing

- Pointers give us an additional way of passing parameters
- Two ways of passing parameters to functions
- Pass by Value
  - Simply give the pass of the value of a variable
  - Example:
    - `int x = 5;`  
`SomeFunction(x);`
    - The function has a copy of x's value, 5
- Pass by Reference
  - Pass a pointer to a location
  - Example:
    - `int x = 5;`  
`int *y = &x;`  
`function(y);`
    - The function has the pointer to where x is stored
    - function manipulate what value is stored where x is

# Pass by Value (example)

- What does the following code produce? Why?

```
void Swap(int firstVal, int secondVal)
{
    int tempVal = firstVal;
    firstVal = secondVal;
    secondVal = tempVal;
}
```

...

```
int fv = 6, sv = 10;
Swap(fv, sv);
printf("Values: (%d, %d)\n", fv, sv);
```

# Pass by Value (example)

- What does the following code produce? Why?

```
void Swap(int firstVal, int secondVal)
{
    int tempVal = firstVal;
    firstVal = secondVal;
    secondVal = tempVal;
}
```

...

```
int fv = 6, sv = 10;
Swap(fv, sv);
printf("Values: (%d, %d)\n", fv, sv);
```

Answer: 6, 10

# Pass by Reference

- What does the following code produce? Why?

```
void Swap(int *firstVal, int *secondVal)
{
    int tempVal = *firstVal;
    *firstVal = *secondVal;
    *secondVal = tempVal;
}
```

```
...
int fv = 6, sv = 10;
Swap(&fv, &sv);
printf("Values: (%d, %d)\n", fv, sv);
```

# Pass by Reference

- What does the following code produce? Why?

```
void Swap(int *firstVal, int *secondVal)
{
    int tempVal = *firstVal;
    *firstVal = *secondVal;
    *secondVal = tempVal;
}
```

```
...
int fv = 6, sv = 10;
Swap(&fv, &sv);
printf("Values: (%d, %d)\n", fv, sv);
```

Answer: 10, 6

# Null Pointer

- Sometimes we want to know a pointer points to nothing
  - Example: So we don't try and access an invalid location or a pointer we haven't set yet
- Setting a pointer to Null
  - Use the NULL constant
  - Example:
    - ```
int *p;  
p = NULL;
```
- NULL is a predefined constant that contains a value that a non-null pointer should never hold
  - Often, `NULL = 0`, because address 0 is not legal for most platforms

# Arrays

- Arrays are contiguous sequences of data items
- All data items are of the same type
- Declaration of static array
  - Example:
    - `int x[10];`
    - `int y[10] = {1,2,3,4,5,6,7,8,9,0};`
- Array index always starts at 0
- The C compiler and runtime system do not check boundaries
  - The compiler will happily let you do the following:
    - `int a[10];`  
`a[12] = 5;`


# Array Storage

- Elements of an array are stored sequentially in memory
- First element (grid[0]) is at the lowest address of sequence

`char grid[10];`



- Variable grid is simply address of the beginning of sequence
- Knowing the location of the first element is good enough to access any element
  - Can access any element using starting address, index, and size of each element
  - Address of array element would simply be: starting address + (element size \* index)





# Arrays and Pointers

- An array name is essentially a pointer to the first element in array
- We can do the following:  
    char word[10];  
    char \*cptr = word;
- Getting first element would be
  - char x = word[0];  
        or  
    char x = \*cptr;
- Getting the 5<sup>th</sup> element would be
  - char x = word[4];  
        or  
    char x = \*(cptr + 4)    (we'll go over why this is in the next slide)

# Pointer Arithmetic

- We can manipulate pointers and calculate addresses by using pointer arithmetic
- Address calculations with pointers are dependent on the size of the data the pointers are pointing to
- Example:
  - size of type int is 4 bytes
  - `int *i;`  
`i++;`        `// equivalent to i = i + 4`  
`i--;`        `// i = i - 4`  
`i += 2;`    `// i = i + (2 * 4)`
- Another example:
  - `int x[10];`  
`int *y = x;`  
`*(y + 3) = 13`        `/* equal to x[3] = 13 */`

# Passing Arrays as Arguments

- Arrays are passed by reference
  - Ex. `function(array);`
- Array items are passed by value
  - Ex. `function(array[10]);`
- What will be the result?

```
void foo(int nums[], int x){  
    nums[0] = 5;  
    x = 5;  
}
```

```
int main(int argc, char **argv){  
    int z[2];  
    z[0] = 0;  
    z[1] = 0;  
    foo(z, z[1]);  
    printf("First number is %d, Second number is %d\n", z[0], z[1]);  
}
```

# Passing Arrays as Arguments

- Arrays are passed by reference
  - Ex. `function(array);`
- Array items are passed by value
  - Ex. `function(array[10]);`
- What will be the result?

```
void foo(int nums[], int x){  
    nums[0] = 5;  
    x = 5;  
}
```

```
int main(int argc, char **argv){  
    int z[2];  
    z[0] = 0;  
    z[1] = 0;  
    foo(z, z[1]);  
    printf("First number is %d, Second number is %d\n", z[0], z[1]);  
}
```

Answer: 5, 0

# Common Pitfalls with Arrays in C

- Overrun array limits
  - There is no checking at compile or run time to see whether you are within array bounds

Ex.

```
int array[10];  
for (int i = 0; i <= 10; i++){  
    array[i] = 0;  
}
```

- No such thing as declaration with variable size
  - Size of array must be known at compile time
  - The following will not work:
    - `int array[x];`

# Strings

- String are simply an array of characters
  - Can allocate like any other array  
char str[10]:
- Each string should end with a '\0' characters
  - '\0' (aka null terminator) lets the computer know that the string has ended
  - Functions like strlen() need this to work on arbitrary strings
  - Make sure there is enough space for the null terminator
- Special syntax for initializing string:
  - char str[16] = "Result";
  - equivalent to:  
    str[0] = 'R';  
    str[1] = 'e';  
    str[2] = 's';  
    ....  
    str[6] = '\0';

# Useful String Functions

- String library part of the standard C libraries
  - `#include <string.h>`
- `size_t strlen(char *s)`
  - computes the length of string `s`
- `char *strcpy(char *dest, char *src)`
  - copies string from `src` to `dest`
- `int strcmp(char *str1, char * str2)`
  - Compares `str1` to `str2`

# Structs

- A struct is a mechanism for grouped together related data items
- Example:
  - We might want to represent an airborne aircraft:

```
char flightNum[7];  
int altitude;  
int longitude;  
int latitude;  
int heading;  
double airSpeed;
```



# Declaring a Struct Type

- Define a new struct type to tell the compiler what our struct will look like:

```
struct flightType{  
    char flightNum[7];  
    int altitude;  
    int longitude;  
    int latitude;  
    int heading;  
    double airSpeed;  
};
```

- This tells the compiler what how big our struct is how the different data items are laid out in memory
- Declaration doesn't allocate any memory yet, memory will be allocated when a variable of struct flight is declared

# Using a Struct


- To use a struct, declare a variable using the new struct type

Ex. `struct flightType plane;`

- We can access the different members like the following

`plane.altitude = 10000;`  
`plane.airSpeed = 800.0;`

`foo(&(plane.airSpeed));`  
`/* pass the address of  
plane.airSpeed */`



# Array of Structs

- We can also declare arrays of struct items
  - `struct flightType planes[100];`
- Each array element is an item of type "struct flightType"
- To access members of a particular element:
  - `planes[34].altitude = 10000;`
- Because the `[]` and `.` Operators have the same precedence, this is the same as:
  - `(planes[34]).altitude = 10000;`

# Pointers to Structs

- We can declare and create a pointer to a struct:
  - `struct flightType *planePtr;`  
`planePtr = &planes[34];`
- To access a member of a struct addressed by a pointer:
  - `(*planePtr).altitude = 10000;`
- Because the operator has a higher precedence than `*`, this is NOT the same as:
  - `*planePtr.altitude = 10000;`
- Luckily C provides special syntax for accessing a struct member through a pointer:
  - `planePtr->altitude = 10000;`

# Passing Struct as Arguments

- It is possible to pass a struct by value however is not recommended
- Most of the time, you'll want to pass a pointer to a struct

```
int willcollide(struct flightType * planeA, struct flightType *planeB){  
    if(planeA->altitude == planeB->altitutde){  
        return 1;  
    }else{  
        return 0;  
    }  
}
```