

UNIVERSIDAD AUTÓNOMA DEL ESTADO DE MÉXICO

INGENIERÍA EN COMPUTACIÓN

CENTRO UNIVERSITARIO ZUMPANGO

Sistemas Operativos

“Comandos para listar servicios en ejecución (**running**)”

PROFESORA

Mtra. Hazem Alvarez Rodriguez

2225850-Gabriel Moctezuma Sánchez

Fecha:

Sep 2026

Muestra la ejecución del comando `systemctl | grep exited` por parte de un usuario normal mediante elevación de privilegios (`sudo su`). Su función es **filtrar y listar los servicios del sistema que ya han finalizado su ejecución (estado *exited*)**.

```
root@LAPTOP-7URH6061:/et x Ubuntu
gaby@LAPTOP-7URH6061:~$ cd .
gaby@LAPTOP-7URH6061:~$ sudo su
[sudo: authenticate] Password:
root@LAPTOP-7URH6061:/home/gaby# cd /etc
root@LAPTOP-7URH6061:/etc# systemctl | grep exited
console-setup.service
loaded active exited Set console font and keymap
keyboard-setup.service
loaded active exited Set the console keyboard layout
kmod-static-nodes.service
loaded active exited Create List of Static Device Nodes
netplan-config.service
loaded active exited Netplan Backend Configuration
setvtrgb.service
loaded active exited Set console scheme
snapd.seeded.service
loaded active exited Wait until snapd is fully seeded
systemd-binfmt.service
loaded active exited Set Up Additional Binary Formats
systemd-journal-flush.service
loaded active exited Flush Journal to Persistent Storage
systemd-modules-load.service
loaded active exited Load Kernel Modules
systemd-remount-fs.service
loaded active exited Remount Root and Kernel File Systems
systemd-sysctl.service
loaded active exited Apply Kernel Variables
systemd-tmpfiles-setup-dev-early.service
loaded active exited Create Static Device Nodes in /dev gracefully
systemd-tmpfiles-setup-dev.service
loaded active exited Create Static Device Nodes in /dev
systemd-tmpfiles-setup.service
loaded active exited Create System Files and Directories
systemd-udev-load-credentials.service
loaded active exited Load udev Rules from Credentials
systemd-udev-trigger.service
loaded active exited Coldplug All udev Devices
systemd-user-sessions.service
loaded active exited Permit User Sessions
user-runtime-dir@.service
loaded active exited User Runtime Directory /run/user/0
user-runtime-dir@1000.service
loaded active exited User Runtime Directory /run/user/1000
root@LAPTOP-7URH6061:/etc#
```

Muestra la misma consulta de servicios en estado `exited` ejecutada directamente desde la sesión de la cuenta del **usuario administrador (root)**.

```
root@LAPTOP-7URH6061:/et x Ubuntu
root@LAPTOP-7URH6061:/etc# systemctl | grep exited
console-setup.service
loaded active exited Set console font and keymap
keyboard-setup.service
loaded active exited Set the console keyboard layout
kmod-static-nodes.service
loaded active exited Create List of Static Device Nodes
netplan-config.service
loaded active exited Netplan Backend Configuration
setvtrgb.service
loaded active exited Set console scheme
snapd.seeded.service
loaded active exited Wait until snapd is fully seeded
systemd-binfmt.service
loaded active exited Set Up Additional Binary Formats
systemd-journal-flush.service
loaded active exited Flush Journal to Persistent Storage
systemd-modules-load.service
loaded active exited Load Kernel Modules
systemd-remount-fs.service
loaded active exited Remount Root and Kernel File Systems
systemd-sysctl.service
loaded active exited Apply Kernel Variables
systemd-tmpfiles-setup-dev-early.service
loaded active exited Create Static Device Nodes in /dev gracefully
systemd-tmpfiles-setup-dev.service
loaded active exited Create Static Device Nodes in /dev
systemd-tmpfiles-setup.service
loaded active exited Create System Files and Directories
systemd-udev-load-credentials.service
loaded active exited Load udev Rules from Credentials
systemd-udev-trigger.service
loaded active exited Coldplug All udev Devices
systemd-user-sessions.service
loaded active exited Permit User Sessions
user-runtime-dir@.service
loaded active exited User Runtime Directory /run/user/0
user-runtime-dir@1000.service
loaded active exited User Runtime Directory /run/user/1000
root@LAPTOP-7URH6061:/etc# systemctl | grep dead
root@LAPTOP-7URH6061:/etc#
```

Errores de sintaxis al ingresar `system control enable` y `systemctl control enable`.

La ejecución correcta del comando `systemctl enable ssh`, el cual **habilita el servicio SSH para que se inicie automáticamente** al arrancar el sistema operativo.

```
root@LAPTOP-7URH6061:/etc# system control enable
Command 'system' not found, did you mean:
  command 'system3' from deb simh (3.8.1-6.3)
Try: apt install <deb name>
root@LAPTOP-7URH6061:/etc# systemctl control enable
Unknown command verb 'control', did you mean 'cancel'?
root@LAPTOP-7URH6061:/etc# systemctl enable ssh
Synchronizing state of ssh.service with SysV service script with /usr/lib/systemd/systemd-sysv-install.
Executing: /usr/lib/systemd/systemd-sysv-install enable ssh
Created symlink '/etc/systemd/system/ssh.service' -> '/usr/lib/systemd/system/ssh.service'.
Created symlink '/etc/systemd/system/multi-user.target.wants/ssh.service' -> '/usr/lib/systemd/system/ssh.service'.
root@LAPTOP-7URH6061:/etc# |
```

Salida interactiva del comando **systemctl** desplegando la lista general de unidades de servicio activas en el sistema, destacando la línea del servicio **ssh.service** en estado **running** (en ejecución).

```
UNIT                                LOAD    ACTIVE SUB    DESCRIPTION
chrony.service                     loaded active running chrony, an NTP client/server
console-setup.service              loaded active exited Set console font and keymap
cron.service                       loaded active running Regular background program processing daemon
dbus.service                       loaded active running D-Bus System Message Bus
getty@tty1.service                 loaded active running Getty on tty1
keyboard-setup.service             loaded active exited Set the console keyboard layout
kmod-static-nodes.service          loaded active exited Create List of Static Device Nodes
mysql.service                      loaded active running MySQL Community Server
netplan-config.service             loaded active exited Netplan Backend Configuration
networkd-dispatcher.service        loaded active running Dispatcher daemon for systemd-networkd
polkit.service                     loaded active running Authorization Manager
rsyslog.service                   loaded active running System Logging Service
setvtrgb.service                  loaded active exited Set console scheme
snapd.seeded.service              loaded active exited Wait until snapd is fully seeded
ssh.service                        loaded active running OpenBSD Secure Shell server
systemd-binfmt.service             loaded active exited Set Up Additional Binary Formats
systemd-journal-flush.service      loaded active exited Flush Journal to Persistent Storage
systemd-journald.service           loaded active running Journal Service
systemd-logind.service             loaded active running User Login Management
systemd-modules-load.service        loaded active exited Load Kernel Modules
systemd-remount-fs.service          loaded active exited Remount Root and Kernel File Systems
systemd-resolved.service           loaded active running Network Name Resolution
systemd-sysctl.service             loaded active exited Apply Kernel Variables
systemd-tmpfiles-setup-dev-early.service loaded active exited Create Static Device Nodes in /dev gracefully
systemd-tmpfiles-setup-dev.service loaded active exited Create Static Device Nodes in /dev
systemd-tmpfiles-setup.service     loaded active exited Create System Files and Directories
systemd-udev-load-credentials.service loaded active exited Load udev Rules from Credentials
systemd-udev-trigger.service        loaded active running Coldplug All udev Devices
systemd-udevd.service              loaded active running Rule-based Manager for Device Events and Files
systemd-user-sessions.service       loaded active exited Permit User Sessions
unattended-upgrades.service         loaded active running Unattended Upgrades Shutdown
user-runtime-dir@0.service          loaded active exited User Runtime Directory /run/user/0
user-runtime-dir@1000.service       loaded active exited User Runtime Directory /run/user/1000
user@0.service                     loaded active running User Manager for UID 0
user@1000.service                  loaded active running User Manager for UID 1000
wsl-pro.service                    loaded activating auto-restart Bridge to Ubuntu Pro agent on Windows

Legend: LOAD -> Reflects whether the unit definition was properly loaded.
ACTIVE -> The high-level unit activation state, i.e. generalization of SUB.
lines 1-40
```

Uso del comando **systemctl status ssh** para **verificar el estado detallado del servicio SSH**, confirmando que se encuentra activo (**active (running)**) y configurado para iniciar con el sistema (**enabled**)

```
36 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: active (running) since Fri 2026-09-04 16:31:45 CST; 6min ago
   Invocation: 92cbe8a3a4e34b7481b811131fd555d6
   TriggeredBy: ● ssh.socket
   Docs: man:sshd(8)
        man:sshd_config(5)
   Main PID: 3994 (sshd)
   Tasks: 1 (limit: 4471)
   Memory: 3M (peak: 3.6M)
   CPU: 48ms
   CGroup: /system.slice/ssh.service
           └─3994 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Sep 04 16:31:45 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:31:45 LAPTOP-7URH6061 sshd[3994]: Server listening on 0.0.0.0 port 22.
Sep 04 16:31:45 LAPTOP-7URH6061 sshd[3994]: Server listening on :: port 22.
Sep 04 16:31:45 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# |
```

Ejecución del comando **systemctl stop ssh** para **detener el servicio SSH**, desplegando una advertencia del sistema que indica que sus unidades activadoras (**ssh.socket**) continúan activas.

```
36 loaded units listed. Pass --all to see loaded but inactive units, too.
To show all installed unit files use 'systemctl list-unit-files'.
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
  Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
  Active: active (running) since Fri 2026-09-04 16:31:45 CST; 6min ago
  Invocation: 92cbe8a3a4e34b7481b811131fd555d6
  TriggeredBy: ● ssh.socket
  Docs: man:sshd(8)
       man:sshd_config(5)
  Main PID: 3994 (sshd)
  Tasks: 1 (limit: 4471)
  Memory: 3M (peak: 3.6M)
  CPU: 48ms
  CGroup: /system.slice/ssh.service
          └─3994 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Sep 04 16:31:45 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:31:45 LAPTOP-7URH6061 sshd[3994]: Server listening on 0.0.0.0 port 22.
Sep 04 16:31:45 LAPTOP-7URH6061 sshd[3994]: Server listening on :: port 22.
Sep 04 16:31:45 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# systemctl stop ssh
Stopping 'ssh.service', but its triggering units are still active:
ssh.socket
root@LAPTOP-7URH6061:/etc# |
```

Se verifica el estado inactivo (**inactive (dead)**) tras haber detenido el servicio **ssh**.

Se ejecuta **systemctl start ssh** para volver a iniciar el servicio **SSH**.

Se verifica con **systemctl status ssh** que el servicio regresó exitosamente al estado **active (running)**

```
root@LAPTOP-7URH6061:/et x Ubuntu
Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
Active: inactive (dead) since Fri 2026-09-04 16:40:04 CST; 2min 4s ago
Duration: 0min 19.837s
Invocation: 92cbe8a3a4e34b7481b811131fd555d6
TriggeredBy: ● ssh.socket
Docs: man:sshd(8)
     man:sshd_config(5)
Process: 3994 ExecStart=/usr/sbin/sshd -D $SSH_OPTS (code=exited, status=0/SUCCESS)
Main PID: 3994 (code=exited, status=0/SUCCESS)
Mem peak: 3.6M
CPU: 55ms

Sep 04 16:31:45 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:31:45 LAPTOP-7URH6061 sshd[3994]: Server listening on 0.0.0.0 port 22.
Sep 04 16:31:45 LAPTOP-7URH6061 sshd[3994]: Server listening on :: port 22.
Sep 04 16:31:45 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
Sep 04 16:40:04 LAPTOP-7URH6061 systemd[1]: Stopping ssh.service - OpenBSD Secure Shell server...
Sep 04 16:40:04 LAPTOP-7URH6061 systemd[1]: ssh.service: Deactivated successfully.
Sep 04 16:40:04 LAPTOP-7URH6061 systemd[1]: Stopped ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# systemctl start ssh
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
  Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
  Active: active (running) since Fri 2026-09-04 16:47:51 CST; 6s ago
  Invocation: albe88649ae940bfa0557cdfd080749e
  TriggeredBy: ● ssh.socket
  Docs: man:sshd(8)
       man:sshd_config(5)
  Process: 4254 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
  Main PID: 4257 (sshd)
  Tasks: 1 (limit: 4471)
  Memory: 1.6M (peak: 2.2M)
  CPU: 180ms
  CGroup: /system.slice/ssh.service
          └─4257 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Sep 04 16:47:51 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:47:51 LAPTOP-7URH6061 sshd[4257]: Server listening on 0.0.0.0 port 22.
Sep 04 16:47:51 LAPTOP-7URH6061 sshd[4257]: Server listening on :: port 22.
Sep 04 16:47:51 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# |
```

Detención del servicio **SSH** mediante **systemctl stop ssh**, desplegando la advertencia de que la unidad de conexión **ssh.socket** permanece activa.

```
root@LAPTOP-7URH6061:/etc# systemctl stop ssh
Stopping 'ssh.service', but its triggering units are still active:
ssh.socket
root@LAPTOP-7URH6061:/etc# |
```

Historial completo de comprobación de estado, detención y reinicio consecutivo del servicio **SSH** mediante la combinación de comandos **systemctl stop ssh**, **systemctl start ssh** y **systemctl status ssh**

```
root@LAPTOP-7URH6061:/et x Ubuntu
Invocation: albe88649ae940bfa0557cdfd080749e
TriggeredBy: ● ssh.socket
Docs: man:sshd(8)
man:sshd_config(5)
Process: 4254 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
Main PID: 4257 (sshd)
Tasks: 1 (Limit: 4471)
Memory: 1.6M (peak: 2.2M)
CPU: 180ms
CGroup: /system.slice/ssh.service
└─4257 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Sep 04 16:47:51 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:47:51 LAPTOP-7URH6061 sshd[4257]: Server listening on 0.0.0.0 port 22.
Sep 04 16:47:51 LAPTOP-7URH6061 sshd[4257]: Server listening on :: port 22.
Sep 04 16:47:51 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# systemctl stop ssh
Stopping 'ssh.service', but its triggering units are still active:
ssh.socket
root@LAPTOP-7URH6061:/etc# systemctl start ssh
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: active (running) since Fri 2026-09-04 16:48:48 CST; 10s ago
 Invocation: 50f622f3e2654f319cf486bb0054df41
 TriggeredBy: ● ssh.socket
 Docs: man:sshd(8)
man:sshd_config(5)
Process: 4268 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
Main PID: 4270 (sshd)
Tasks: 1 (Limit: 4471)
Memory: 1.6M (peak: 2.2M)
CPU: 53ms
CGroup: /system.slice/ssh.service
└─4270 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Sep 04 16:48:48 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:48:48 LAPTOP-7URH6061 sshd[4270]: Server listening on 0.0.0.0 port 22.
Sep 04 16:48:48 LAPTOP-7URH6061 sshd[4270]: Server listening on :: port 22.
Sep 04 16:48:48 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc#
```

Muestra el estado del servicio SSH tras ser detenido nuevamente con `systemctl stop ssh`, confirmando que cambió a estado inactivo (**inactive (dead)**).

```
root@LAPTOP-7URH6061:/etc# systemctl stop ssh
Stopping 'ssh.service', but its triggering units are still active:
ssh.socket
root@LAPTOP-7URH6061:/etc# systemctl status ssh
o ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: inactive (dead) since Fri 2026-09-04 16:49:11 CST; 4s ago
 Duration: 22.706s
 Invocation: 50f622f3e2654f319cf486bb0054df41
 TriggeredBy: ● ssh.socket
 Docs: man:sshd(8)
man:sshd_config(5)
Process: 4268 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
Process: 4270 ExecStart=/usr/sbin/sshd -D $SSH_OPTS (code=exited, status=0/SUCCESS)
Main PID: 4270 (code=exited, status=0/SUCCESS)
Mem peak: 2.2M
CPU: 57ms

Sep 04 16:48:48 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:48:48 LAPTOP-7URH6061 sshd[4270]: Server listening on 0.0.0.0 port 22.
Sep 04 16:48:48 LAPTOP-7URH6061 sshd[4270]: Server listening on :: port 22.
Sep 04 16:48:48 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
Sep 04 16:49:11 LAPTOP-7URH6061 systemd[1]: Stopping ssh.service - OpenBSD Secure Shell server...
Sep 04 16:49:11 LAPTOP-7URH6061 sshd[4270]: Received signal 15; terminating.
Sep 04 16:49:11 LAPTOP-7URH6061 systemd[1]: ssh.service: Deactivated successfully.
Sep 04 16:49:11 LAPTOP-7URH6061 systemd[1]: Stopped ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc#
```

Muestra la ejecución en secuencia del reinicio del servicio (`systemctl start ssh`) y la verificación de su estado activo mediante `systemctl status ssh`.

```
root@LAPTOP-7URH6061:/et x Ubuntu
Duration: 22.706s
Invocation: 50f622f3e2654f319cf486bb0054df41
TriggeredBy: ssh.socket
Docs: man:sshd(8)
man:sshd_config(5)
Process: 4268 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
Process: 4270 ExecStart=/usr/sbin/sshd -D $SSHD_OPTS (code=exited, status=0/SUCCESS)
Main PID: 4270 (code=exited, status=0/SUCCESS)
Mem peak: 2.2M
CPU: 57ms

Sep 04 16:48:48 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:48:48 LAPTOP-7URH6061 sshd[4270]: Server listening on 0.0.0.0 port 22.
Sep 04 16:48:48 LAPTOP-7URH6061 sshd[4270]: Server listening on :: port 22.
Sep 04 16:48:48 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
Sep 04 16:49:11 LAPTOP-7URH6061 systemd[1]: Stopping ssh.service - OpenBSD Secure Shell server...
Sep 04 16:49:11 LAPTOP-7URH6061 sshd[4270]: Received signal 15; terminating.
Sep 04 16:49:11 LAPTOP-7URH6061 systemd[1]: ssh.service: Deactivated successfully.
Sep 04 16:49:11 LAPTOP-7URH6061 systemd[1]: Stopped ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# systemctl start ssh
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: active (running) since Fri 2026-09-04 16:49:28 CST; 2s ago
   Invocation: c7854c08c10d4fe991994f4c83dd6aa5
   TriggeredBy: ssh.socket
   Docs: man:sshd(8)
        man:sshd_config(5)
   Process: 4289 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
   Main PID: 4291 (sshd)
     Tasks: 1 (limit: 4471)
    Memory: 1.6M (peak: 2.2M)
       CPU: 41ms
   CGroup: /system.slice/ssh.service
           └─4291 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"

Sep 04 16:49:28 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:49:28 LAPTOP-7URH6061 sshd[4291]: Server listening on 0.0.0.0 port 22.
Sep 04 16:49:28 LAPTOP-7URH6061 sshd[4291]: Server listening on :: port 22.
Sep 04 16:49:28 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# |
```

Muestra la verificación final del estado del servicio SSH, confirmando que se encuentra **activo y ejecutándose** (active (running)).

```
root@LAPTOP-7URH6061:/et x Ubuntu
ssh.socket
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: inactive (dead) since Fri 2026-09-04 16:49:44 CST; 4s ago
   Duration: 15.945s
   Invocation: c7854c08c10d4fe991994f4c83dd6aa5
   TriggeredBy: ssh.socket
   Docs: man:sshd(8)
        man:sshd_config(5)
   Process: 4289 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
   Process: 4291 ExecStart=/usr/sbin/sshd -D $SSHD_OPTS (code=exited, status=0/SUCCESS)
   Main PID: 4291 (code=exited, status=0/SUCCESS)
   Mem peak: 2.2M
       CPU: 43ms

Sep 04 16:49:28 LAPTOP-7URH6061 systemd[1]: Starting ssh.service - OpenBSD Secure Shell server...
Sep 04 16:49:28 LAPTOP-7URH6061 sshd[4291]: Server listening on 0.0.0.0 port 22.
Sep 04 16:49:28 LAPTOP-7URH6061 sshd[4291]: Server listening on :: port 22.
Sep 04 16:49:28 LAPTOP-7URH6061 systemd[1]: Started ssh.service - OpenBSD Secure Shell server.
Sep 04 16:49:44 LAPTOP-7URH6061 systemd[1]: Stopping ssh.service - OpenBSD Secure Shell server...
Sep 04 16:49:44 LAPTOP-7URH6061 sshd[4291]: Received signal 15; terminating.
Sep 04 16:49:44 LAPTOP-7URH6061 systemd[1]: ssh.service: Deactivated successfully.
Sep 04 16:49:44 LAPTOP-7URH6061 systemd[1]: Stopped ssh.service - OpenBSD Secure Shell server.
root@LAPTOP-7URH6061:/etc# systemctl start ssh
root@LAPTOP-7URH6061:/etc# systemctl status ssh
● ssh.service - OpenBSD Secure Shell server
   Loaded: loaded (/usr/lib/systemd/system/ssh.service; enabled; preset: enabled)
   Active: active (running) since Fri 2026-09-04 16:49:57 CST; 4s ago
   Invocation: 7502001288f4411281e9025240188235
   TriggeredBy: ssh.socket
   Docs: man:sshd(8)
        man:sshd_config(5)
   Process: 4306 ExecStartPre=/usr/sbin/sshd -t (code=exited, status=0/SUCCESS)
   Main PID: 4308 (sshd)
     Tasks: 1 (limit: 4471)
    Memory: 1.6M (peak: 2.1M)
       CPU: 31ms
   CGroup: /system.slice/ssh.service
           └─4308 "sshd: /usr/sbin/sshd -D [listener] 0 of 10-100 startups"
```