

POD-based deflation techniques for the solution of two-phase flow problems in large and highly heterogeneous porous media.

G. B. Diaz Cortes

Abstract

Simulation of two-phase flow through highly heterogeneous porous media results in ill-conditioned large systems of linear equations for the pressure when using, e.g., sequential procedures. Solving the resulting linear system can be particularly time-consuming. Therefore, there have been extensive efforts finding effective ways to address this issue.

Iterative methods, together with preconditioning techniques [1, 2], are the most commonly chosen to solve this kind of problem. In the literature, we can also find Reduced Order Models (ROM) [3–5] and deflation methods [6, 7] where system information is reused to find a good approximation more quickly. For the deflation techniques, an optimal selection of deflation vectors is crucial for a good performance. These vectors are collected mainly via recycling deflation (vectors containing previous solutions); subdomain deflation (vectors constructed based on geometric properties); and restriction and prolongation matrices, obtained with multigrid and multilevel methods.

The construction of deflated vectors based on information captured with ROM, in particular, Proper Orthogonal Decomposition (POD) was presented by Diaz et al. [8, 9]. The goal of this work is to further explore the possibilities of combining POD and deflation techniques to speed-up the convergence of iterative methods. We propose selecting deflation vectors based on ROM methods; in particular, we focus on Proper Orthogonal Decomposition (POD).

The convergence properties of the resulting POD-based deflation method are studied for an incompressible two-phase flow problem in a highly heterogeneous porous medium. We compare the number of iterations required to solve the above-mentioned problem using the Conjugate Gradient method preconditioned with Incomplete Cholesky (ICCG), against the deflated (DICCG) version of the same method.

The efficiency of the method is illustrated with the SPE 10 benchmark problem, presenting a contrast in permeability coefficients of $\mathcal{O}(10^7)$ and containing $\mathcal{O}(10^6)$ cells. For this problem, the DICCG method requires only $\sim 30\%$ of the number of ICCG iterations.

References

- [1] Y. Saad. *Iterative Methods for Sparse Linear Systems*. Society for Industrial and Applied Mathematics Philadelphia, PA, USA. 2nd edition, 2003.
- [2] M. Benzi. Preconditioning techniques for large linear systems: a survey. *Journal of computational Physics*, 182(2):418–477, 2002.
- [3] P. Astrid, G. Papaioannou, J.C. Vink and J.D. Jansen. Pressure Preconditioning Using Proper Orthogonal Decomposition. In *2011 SPE Reservoir Simulation Symposium, The Woodlands, Texas, USA*, 2011.
- [4] R. Markovinović and J.D. Jansen. Accelerating iterative solution methods using reduced-order models as solution predictors. *International journal for numerical methods in engineering*, 68(5):525–541, 2006.
- [5] D. Pasetto, M. Ferronato and M. Putti. A reduced order model-based preconditioner for the efficient solution of transient diffusion equations. *International Journal for Numerical Methods in Engineering*, 109(8):1159–1179, 2017.
- [6] Yousef Saad, Manshung Yeung, Jocelyne Erhel, and Frédéric Guyomarc’h. A deflated version of the conjugate gradient algorithm. *SIAM Journal on Scientific Computing*, 21(5):1909–1926, 2000.
- [7] C. Vuik, A. Segal and J.A. Meijerink. An Efficient Preconditioned CG Method for the Solution of a Class of Layered Problems with Extreme Contrasts in the Coefficients. *Journal of Computational Physics*, 152:385, 1999.
- [8] G.B. Diaz Cortes, C. Vuik and J.D. Jansen. On POD-based Deflation Vectors for DPCG applied to porous media problems. *Journal of Computational and Applied Mathematics*, 330(Supplement C):193 – 213, 2018.
- [9] G.B. Diaz Cortes, C. Vuik and J.D. Jansen. Physics-based Pre-conditioners for Large-scale Subsurface Flow Simulation. In *Proceedings of the 15th European Conference on the Mathematics of Oil Recovery, ECMOR XV*, 2016.