Angular Modern Template Syntax Cheatsheet

1. Conditional Logic: `@if`

Replaces `*ngIf`. Supports multiple branches and type-narrowing.

```
@if (user.isLoggedIn()) {
  <app-dashboard />
} @else if (user.isGuest()) {
  <app-guest-view />
} @else {
  <app-login />
}

// Aliasing with "as" (useful for Observables/Complex Expressions)
@if (data$ | async; as data) {
  <p>{{ data.name }}</p>
}
```

2. Iteration: `@for`

Replaces `*ngFor`. Mandatory `track` for performance; built-in empty state handling.

```
@for (item of items; track item.id) {
  <li>{{ $index }}: {{ item.name }}</li>
} @empty {
  <p>No items found.</p>
}
```

Contextual Variables (inside `@for` block):

Variable	Variable	Variable
`$index`	`number`	Index of the current row.
`$count`	`number`	Total number of items in the collection.
`$first` / `$last`	`boolean`	True if item is the first or last in the list.
`$even` / `$odd`	`boolean`	True if the current index is even or odd.

3. Selection: `@switch`

Replaces `*ngSwitch`. Uses strict equality (`===`).

```
@switch (userRole) {
  @case ('admin') { <app-admin /> }
  @case ('editor') { <app-editor /> }
  @default { <app-viewer /> }
}
```

4. Local Variables: `@let`

Declare immutable, block-scoped variables directly in the template.

```
// Reusable async value (solves "Indentation Hell")
@let user = user$ | async;
@let theme = user?.prefs.theme?? 'light';

@if (user) {
  <div [class]="theme">Hello, {{ user.name }}</div>
}

// Complex calculations
@let discountedPrice = product.price * (1 - discount);
<span>Price: {{ discountedPrice | currency }}</span>
```

5. Deferrable Views: `@defer`

Declarative lazy loading for components, directives, and pipes.

```
@defer (on viewport; prefetch on idle) {
  <app-heavy-chart />
} @placeholder (minimum 500ms) {
  <app-skeleton />
} @loading (after 100ms; minimum 1s) {
  <app-spinner />
} @error {
  <p>Failed to load chart.</p>
}
```

Common Triggers (`on`):

- `idle` : (Default) Browser is idle.
- `viewport` : Content enters visible area.
- `interaction` : User clicks or focuses.
- `hover` : Mouseover or focus.
- `immediate` : After initial page render.
- `timer(500ms)` : After a specific delay.
- `when condition` : Custom boolean logic/Signal.

Brought to you by **certificates.dev**

Learn more at **certificates.dev/angular**

Creators of the **Angular Certification**

Angular Modern Template Syntax Cheatsheet

1. Conditional Logic: `@if`

Replaces `*ngIf`. Supports multiple branches and type-narrowing.

```
@if (user.isLoggedIn()) {
  <app-dashboard />
} @else if (user.isGuest()) {
  <app-guest-view />
} @else {
  <app-login />
}

// Aliasing with "as" (useful for Observables/Complex Expressions)
@if (data$ | async; as data) {
  <p>{{ data.name }}</p>
}
```

2. Iteration: `@for`

Replaces `*ngFor`. Mandatory `track` for performance; built-in empty state handling.

```
@for (item of items; track item.id) {
  <li>{{ $index }}: {{ item.name }}</li>
} @empty {
  <p>No items found.</p>
}
```

Contextual Variables (inside `@for`):

Variable	Variable	Variable
`$index`	`number`	Index of the current row.
`$count`	`number`	Total number of items in the collection.
`$first` / `$last`	`boolean`	True if item is the first or last in the list.
`$even` / `$odd`	`boolean`	True if the current index is even or odd.

3. Selection: `@switch`

Replaces `*ngSwitch`. Uses strict equality (`===`).

```
@switch (userRole) {
  @case ('admin') { <app-admin /> }
  @case ('editor') { <app-editor /> }
  @default { <app-viewer /> }
}
```

4. Local Variables: `@let`

Declare immutable, block-scoped variables directly in the template.

```
// Reusable async value (solves "Indentation Hell")
@let user = user$ | async;
@let theme = user?.prefs.theme?? 'light';

@if (user) {
  <div [class]="theme">Hello, {{ user.name }}</div>
}

// Complex calculations
@let discountedPrice = product.price * (1 - discount);
<span>Price: {{ discountedPrice | currency }}</span>
```

5. Deferrable Views: `@defer`

Declarative lazy loading for components, directives, and pipes.

```
@defer (on viewport; prefetch on idle) {
  <app-heavy-chart />
} @placeholder (minimum 500ms) {
  <app-skeleton />
} @loading (after 100ms; minimum 1s) {
  <app-spinner />
} @error {
  <p>Failed to load chart.</p>
}
```

Common Triggers (`on`):

- `idle` : (Default) Browser is idle.
- `viewport` : Content enters visible area.
- `interaction` : User clicks or focuses.
- `hover` : Mouseover or focus.
- `immediate` : After initial page render.
- `timer(500ms)` : After a specific delay.
- `when condition` : Custom boolean logic/Signal.

Brought to you by
certificates.dev

Learn more at certificates.dev/angular

Creators of the
Angular Certification