Article Recommender System

DS300.Q11 - Final Project

Presented by:
T. Nhat[1] L. M. Nhut[1] N. H. Phat[1]
Instructor: Master. Huynh Van Tin[1]

[1]Department of Computer Science
University of Information Technology

DS300 Final Project Report

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Motivation: Why News Recommendation?

In the digital era, news platforms face **Information Overload**:

- **User Experience:** Navigating thousands of daily articles is overwhelming.
- **Retention:** Personalized content increases user engagement and platform stickiness.
- **Monetization:** Better engagement leads to higher ad revenue and subscriptions.

Target: Build a system that understands both *Content semantics* and *User behavior*.

Research Objectives

Our goal is to develop a state-of-the-art recommendation engine for Vietnamese news:

- **Hybrid Logic:** Combine Collaborative Filtering (CF) with Content-Based (CB) techniques.
- **Graph Learning:** Leverage GNNs to model complex user-article interactions.
- **Multimodal Fusion:** Incorporate Social (replies) signals.
- **Vietnamese NLP:** Optimize PhoBERT embeddings for news semantics.

Problem Statement

Challenge: How to recommend relevant news articles to users?

Key Challenges:

1. **Cold Start:** New users/articles have no interaction history
2. **Sparse Data:** Most users read very few articles (99.9% sparsity)
3. **Vietnamese Language:** Limited NLP resources for Vietnamese text
4. **Dynamic Content:** News articles are time-sensitive

Our Approach: Graph-based Contrastive Learning with PhoBERT embeddings

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Dataset Overview (VnExpress)

Statistics:

- **Users:** 13,117
- **Articles:** 3,645
- **Interactions:** 38,505 (Comments/Replies)
- **Sparsity:** 99.92%

The dataset is highly sparse. **Note:** We treat users commenting on articles as "implicit interactions".



Experimental Settings: Graph Levels (G1-G3)

We construct three distinct graph topologies to test model robustness across different sparsity and heterogeneity levels:

Level 1 (G1): Baseline

User-Article Bipartite

- **Type:** Homogeneous/Bipartite.
- **Nodes:** Users, Articles.
- **Edges:** $U \leftrightarrow A$ (Comment/Interaction).
- **Purpose:** Standard

Level 2 (G2): Social

Full Heterogeneous Graph

- **Type:** Heterogeneous.
- **Edges:** Adds Social Signals:
  - $U \xrightarrow{reply} U$ (Social Trust)
  - $U \leftrightarrow U$ (Latent Similarity)
- **Purpose:** Advanced GNNs

Level 3 (G3): Abstract

User-Category Graph

- **Type:** Bipartite Abstract.
- **Nodes:** Users, Categories.
- **Edges:** $U \leftrightarrow C$ (Interest in Topic).
- **Purpose:** Modeling high-level user

Graph vs. Matrix Perspective

Mathematical Equivalence: A User-Item Graph is structurally identical to a Sparse User-Item Interaction Matrix.



Graph View

"Path-based reasoning"

$\Longleftrightarrow$

Matrix View

$$A = \begin{bmatrix} 1 & 1 \\ 0 & 1 \end{bmatrix}$$

"Algebraic operations"

Why this matters?

- **High-Order Connectivity:** Multiplying matrices ($A \times A^T$) simulates "walking" on the graph.
- **GNNs** generalize Matrix Factorization by performing convolution over this structure.

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Background: Content-Based Filtering (CB)

Core Idea: "Show me more of what I've read before."

- **Input:** Article Text (Title, Content, Tags).
- **Process:**
  1. Convert text to Vectors (TF-IDF / PhoBERT).
  2. Build **User Profile** by averaging history vectors.
  3. Recommend items with highest **Cosine Similarity** to Profile.

Pros & Cons:

Solves **Cold-Start** (works for new items).

Captures Semantic meaning.

× **Overspecialization:** Creates filter bubbles (only suggests same topics).

Feature Engineering: PCA & Dimensionality Reduction

Problem: Raw Text Features (TF-IDF) are extremely high-dimensional and sparse (10,000+ dimensions).

Solution: Truncated SVD (PCA)

- Linearly projects data to a lower-dimensional space with max variance.
- **Implementation:**

$$X_{dense} = SVD(X_{tfidf}, k = 256)$$

- Reduces 10,000 dims $\rightarrow$ 256 dims.



"Retains core info, removes noise"

Why use it in our Project?

- Makes **Content-Based** computation feasible.
- Acts as a baseline comparison against **Deep Semantic Embeddings**

Background: Collaborative Filtering (CF)

Core Idea: "Users similar to you also liked this."

- **Memory-Based (KNN) Implementation:**
  - **User-KNN (Pearson):** Find similar users v to target user u.

    $$sim(u, v) = \text{Pearson}(R_u, R_v)$$

    Why? Handles user bias (tough/easy raters).
  - **Item-KNN (Cosine):** Find items j similar to item i based on co-occurrence.

    $$sim(i, j) = \cos(\vec{i}, \vec{j})$$

    Why? Efficient for sparse

Pros & Cons:

- Serendipity (Discovers new interests).
- Domain independent.
- × **Sparsity:** Fails when interactions are few (99.9% sparsity).
- × **Cold-Start:** Cannot recommend to new users.

Current SOTA Approaches

We benchmark against three main categories of modern Recommender Systems:

1. **Graph Neural Networks (GNNs):**
   - **NGCF (2019):** First to encode collaborative signal into embeddings via graph propagation. High computational cost.
   - **LightGCN (2020):** Simplified GCN by removing non-linearities. Current industry standard for efficiency.
2. **Contrastive Learning (CL):**
   - **SimGCL (2022):** Augments graph structure with noise to learn robust representations. Handles sparsity better than pure GNNs.
3. **Content-Based & Hybrid:**
   - **PhoBERT:** State-of-the-art BERT model for Vietnamese, capturing deep semantic text features.

System Architecture



Pipeline: Crawl → Clean → Build Graph → Generate Embeddings → Train → Evaluate

Strategic Why: The Hybrid Synergy

Why combine **Content-Based** with **Graph Learning**?

- **Content-Based (NLP):**
  - Solves the **Cold-Start** problem (recommends new articles with 0 interactions).
  - Captures semantic similarity (PhoBERT).
- **Graph Learning (GNN):**
  - Captures **Collaborative Signals** (Users who like X also like Y).
  - Exploits **Social Signals** (Reply networks).

Hybrid Outcome

Content-Based provides "Freshness" while Graph Learning provides "Depth" and "Discovery".

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

VnExpress Data Crawling

Data Source: VnExpress.net (largest Vietnamese news portal)

Categories Crawled:

- 'Thế giới'
- 'Giáo dục'
- 'Thể thao'
- 'Thời sự'
- 'Kinh doanh'
- 'Khoa học công nghệ'

Collected Data:

- Articles: title, content, author, publish date
- Metadata: category, tags (per article)
- Comments: user ID, comment text, reactions, replies
- User profiles: user ID, username, join date

Data Collection Pipeline: 3-Step Workflow

Our crawler implements a resilient 3-stage architecture to handle high-volume news data:



Pipeline Orchestration & Efficiency

- **Parallelism:** `Step 2` (Selenium) is resource-intensive. We split the workload across N parallel browser instances using `multiprocessing`.
- **Resiliency:**
  - **Caching:** Avoids redundant HTTP requests for static content.
  - **Checkpointing:** Atomic writes to CSV allow resuming from the last article in case of failure.
  - **Headless Execution:** Minimizes resource overhead in production environments.
- **Tool Stack:**
  - **Requests:** High-speed metadata extraction.
  - **Selenium:** Handling complex JS (Load More buttons).
  - **Playwright:** Modern, fast engine for user history scraping.

Dataset Overview: High-Level Statistics

Raw Behavioral Data:

- **3,685** Articles
- **42,050** Comments
- **6** News Categories
- **19,842** User Profiles

Graph Interaction Set (G1-G3):

- **13,117** Unique Users
- **3,645** Active Articles
- **38,505** Total Interactions
- **Sparsity: 99.919%**

Data Sample: Interaction & Content

1. **Content Sample (Article)**
"Chinh phục loạt 'ông lớn' công nghệ sau hơn 500 lần bị từ chối"
→ **Tags:** [Meta, Amazon, Apple, Tesla, kĩ sư công nghệ]

2. **Social Sample (Comment/Reply)**
   - **User A:** "Nếu giỏi thì cố gắng mua lại mấy công ty này..."
   - **User B:** (Reply to A) "Mua lại Meta chắc cần nghìn tỷ USD..."
   ⇒ Social Connection detected

Feature Mapping

- **Article** → PhoBERT Embedding ($d = 64$) → Node Feature.
- **User** → Interaction aggregation → Node Embedding.
- **Reply** → User-User Edge in the Heterogeneous Graph.

Core Innovation: Social Fusion

Idea: Use the "Reply Network" to bridge gaps between users.



The Logic:

- **Direct:** User A likes Article 1.
- **Social:** User A replies to User B $\rightarrow$ *Shared Interest*.
- **Inference:** User A is likely to enjoy Article 2 (read by B).

Impact on Sparsity

By adding User-User edges, the GNN can propagate "interests" even if User A has only read 1 article.

The Sparsity Challenge: Mathematical Proof

Definition:
Sparsity measures the lack of interactions in the potential link space.

The Formula

$$\text{Sparsity} = 1 - \frac{|\mathcal{E}_{obs}|}{|\mathcal{V}_u| \times |\mathcal{V}_i|}$$

VnExpress Graph Calculation:

- Interactions ($|\mathcal{E}_{obs}|$): **38,505**
- Active Users ($|\mathcal{V}_u|$): **13,117**
- Active Articles ($|\mathcal{V}_i|$): **3,645**
- Total Possible Edges: $13,117 \times 3,645 = \mathbf{47,811,465}$

$$\Rightarrow \text{Sparsity} = 1 - \frac{38,505}{47,811,465} = \mathbf{99.919\%}$$

Category Distribution (VnExpress)





- **Thế giới** and **Thời sự** are the dominant categories.
- Skewed distribution reflects editorial priorities.

User Engagement Patterns (1/2)





Distribution Analysis

Article popularity follows Zipf's law. Top 10 users account for 15% of all interactions.

User Engagement Patterns (2/2)





Power Law Observation

Long-tail distribution: 80% of users have fewer than 10 interactions.

Engagement by Category





Graph Degree Distribution



- User degrees peak at very low values (high cold-start risk).
- Article degrees are more distributed but still sparse.

Graph Connectivity & Density



Graph Topology: A Heterogeneous Network



- **Blue Nodes:** Active Users
- **Green Nodes:** News Articles
- **Dashed Edges:** Social Reply interactions

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Inspiration & Theoretical Foundation

Where did this idea come from? Our architecture is an adaptation of the **HGNR** framework, optimized with LightGCN mechanics.

1. HGNR (arXiv:2009.00799)

Heterogeneous GNN for Recommendation

- **Key Idea:** Users and items have multiple types of relationships (e.g., Comment vs Reply).
- **Mechanism:** Use relation-specific aggregation steps.

2. LightGCN (He et al., SIGIR'20)

Simplified GCN for Recommendation

- **Key Idea:** Non-linearities (ReLU) are effectively redundant for collaborative filtering.
- **Mechanism:** Linear propagation + Layer averaging.

$\Rightarrow$ **MA-HGN = HGNR's Multi-Relation logic + LightGCN's**

Motivation: Why a Heterogeneous GNN?

The Problem with Standard GNNs (LightGCN, NGCF):

- They treat the graph as **Homogeneous**: All nodes are just "IDs", all edges are just "links".
- **Failure Case:** A "Reply" (social trust) is treated identically to a "Comment" (explicit interest).

The VnExpress Reality:

- **Multiple Node Types:** Users $\neq$ Items.
- **Multiple Edge Types:**
  - `User-Comment-Item`: Explicit Interest.
  - `User-Reply-User`: Social Influence / Trust.

The MA-HGN Solution

We need an architecture that aggregates **Social Signals** separately from **Content Signals** before fusing them.

MA-HGN: Multi-Aspect Heterogeneous GNN



Core Innovation: Dual-path Propagation

- **Path 1 (Interest):** history ($\mathcal{G}_{u-a}$) via **GATv2**.
- **Path 2 (Social):** friends ($\mathcal{G}_{u-u}$) via **GraphSAGE**.
- **Adaptive Fusion:** balances signal importance:

$$h_u = \alpha \cdot h_{int} + (1 - \alpha) \cdot h_{soc}$$

Alternative Component: MA-HCL (Failed Experiment)

Idea: Combine Heterogeneity (Social + Interest) with Contrastive Learning + LightGCN.
Result: Performance dropped (-48%), proving that **Graph Attention (GAT)** is crucial for this dataset, while simple LightGCN over-smooths the distinct social signals.



Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Benchmark 1: Mainstream Recommendation (LOO)

Protocol: Leave-One-Out (Test on latest interaction).
Focus: Accuracy on warm-start users.

Model	Type	R@10	N@10	Gain
MA-HGN (G2)	**Hetero**	**0.4364**	**0.2636**	**Best**
BIGCF (G1)	**CF**	**0.4015**	**0.2488**	**-8.0%**
LightGCL (G1)	Graph CL	0.3081	0.2021	-29.4%
XSimGCL (G2)	Graph CL	0.3036	0.2002	-30.4%
LightGCN (G1)	GNN	0.2812	0.1739	-35.6%
MA-HCL (G3)	Hetero CL	0.2260	0.1491	-48.2%
SimGCL (G3)	Graph CL	0.2181	0.1333	-50.0%

Result: MA-HGN outperforms standard GNNs by leveraging heterogeneous graph signals (User-User + User-Article), proving the value of social fusion.

Benchmark 2: Cold-Start / Zero-Shot (Full)

Protocol: 80/20 Split (Random).
Focus: Retrieving relevant content based strictly on content similarity (Handling new users/items).

Model	Type	R@10	N@10	Note
BGE-M3	**CB**	**0.0535**	**0.0315**	**Best Dense**
TF-IDF	CB	0.0508	0.0301	Best Sparse
VnDoc	CB	0.0485	0.0287	Document-level
PhoBERT	CB	0.0452	0.0253	Contextual
LightGCL	Graph CL	0.0436	0.0261	Best Graph CL
XSimGCL	Graph CL	0.0432	0.0248	Cross-layer
BIGCF	CF (GNN)	0.0413	0.0219	Generative
IGCL	Graph CL	0.0404	0.0235	Imbalanced
NGCF	CF (GNN)	0.0387	0.0223	Baseline GNN
MA-HGN	Hetero	0.0369	0.0201	Relation-focused
MA-HCL	Hetero CL	0.0320	0.0192	Hetero CL
LightGCN	GNN	0.0266	0.0151	Simple GNN
SimGCL	Graph CL	0.0228	0.0122	Baseline CL
User-KNN (Pearson)	Memory CF	0.0412	0.0235	Baseline
User-KNN (Jaccard)	Memory CF	0.0336	0.0178	Baseline
Item-KNN (Cosine)	Memory CF	0.0213	0.0113	Baseline
Item-KNN (Jaccard)	Memory CF	0.0110	0.0057	Baseline

Ablation Study: GNN Architecture

Question: Does the choice of aggregator matter? Comparing **GAT** (default), **GraphSAGE**, and **TransformerConv**.

Backbone	LOO Protocol (Warm)		Full Protocol (Cold)		Trend
	R@10	N@10	R@10	N@10	
GAT	0.3436	0.2074	0.0262	0.0163	Baseline
SAGE	0.3876	0.2322	0.0303	0.0182	Better (+12%)
TRANS	**0.4492**	**0.2700**	**0.0504**	**0.0266**	**Best (+30%)**

Analysis:

- **Transformer Superiority:** The multi-head attention mechanism in TransformerConv captures complex dependencies better than GAT's simple attention or SAGE's mean pooling.
- **GAT Underperformance:** Standard GAT struggles, possibly due to the "static" nature of its attention mechanism compared to Transformer's dynamic query-key value pairs.
- **Consistent Ranking:** The hierarchy (Transformer > SAGE > GAT) holds true for both Warm and Cold start scenarios.

Impact of Graph Structure (Ablation Study)

Question: Which graph topology yields the best performance?
Testing **MA-HGN** on different graph types:

Graph	Structure Stats	R@10	Impact
G1 (Base)	13k Users, 30k Edges Density: 0.06%	0.4015	**Baseline**. Sparse, cold-start prone.
G2	**+61k Social Edges** Density: **0.064%**	**0.4364**	**+8.7%**. Social wisdom (Homophily) helps
G3	+6 Categories 16k User-Cat Edges	0.2617	**-35%**. Categories are too broad (Noise).

Insight: Denser is not always better. **G2** succeeds because social edges provide *high-quality* signals, whereas **G3**'s category edges dilute specific user interests.

Ablation Study: GNN Depth (n-layers)

Question: Does going deeper help capture long-range dependencies?

Layers	R@10 (LOO)	NDCG@10	Trend
1	**0.4376**	**0.2611**	**Optimal**
2	0.4244	0.2578	Slight drop (-3%)
3	0.3423	0.1999	Significant drop (-21%)
4	0.3852	0.2207	Unstable

Analysis:

- **Shallow is Better:** Performance peaks at **1 layer**. Immediate social neighbors (friends/replies) provide the strongest signal.
- **Over-smoothing:** Deeper GNNs (3-4 layers) likely cause user representations to become indistinguishable (Laplacian smoothing), hurting ranking.
- **Noise Propagation:** In social graphs, distant connections (>2 hops) are often irrelevant, adding noise rather than signal.

The Power of Density: Effect of k-core Filtering

Insight: Recommendation difficulty scales with graph sparsity.

Regular Filtering (k=1)

- 13,117 Users
- 3,645 Articles
- many "cold" one-off users

G2 R@10: 0.2938 ↑ Best Model

Strict Filtering (k=2)

- 6,221 Users
- 2,583 Articles
- only recurring users

G2 R@10: 0.1917

- **Surprise Finding:** "Simple" Regular filtering outperforms "Complex" Strict filtering (0.29 vs 0.19).
- **Reason:** The "long tail" of one-off users acts as a bridge in the reply network. Removing them destroys valuable connectivity.

Valid Semantic Enrichment: Category Hubs (G3)

Solution: Instead of dense Article-Article edges, we introduce **Category Nodes** as middle-man hubs.

The G3 Architecture

- **Compact:** Only 6 Category nodes.
- **Efficient:** Adds ∼12k edges.
- **Dual Paths:**
  - $User \leftrightarrow Category \leftrightarrow Article$

Best Result: SimGCL on G3

- **Recall@10: 0.2127**
- **NDCG@10: 0.1391**
- **Impact:** Category node augmentation enables long-range collaborative signals without the noise of dense item-to-item edges.

Verdict: Category Hubs provide a scalable semantic alternative, capturing thematic interests without the "Density Trap".

Our Contribution: MA-HCL Model

MA-HCL = Multi-Aspect Heterogeneous Contrastive Learning

Architecture

- **Backbone:** LightGCN-style propagation
- **Loss:** BPR + SimCL contrastive
- **Fusion:** Multi-aspect (interest + social)

Results (G2)

- **Recall@10:** 0.1502
- **NDCG@10:** 0.1024
- **MRR:** 0.1165

- **+21%** better than SimMAHGN (attention-based)
- **Simpler architecture** = faster training, better generalization

Evaluation Methodology & Validity

Our evaluation follows strict scientific standards for Recommender Systems:

- **Metric Choice:**
  - *Recall@10*: Measures system coverage.
  - *NDCG@10*: Rewards models that rank true items higher.
  - **MRR**: Standard for single-target news retrieval.
- **Split Strategy:** Time-aware 80/10/10 split to prevent leakage.
- **Data Integrity: Temporal Leave-One-Out** strategy. We test on the latest interaction per user, ensuring **zero data leakage** from the future.

Investigation: The "Projection Trap"

Observed Paradox: Standalone PhoBERT performed 10x worse than expected.

The Problem

- **Random Projection:** PhoBERT embeddings (768-dim) were compressed via untrained random linear layers.
- **Noise Injection:** High-quality semantics were destroyed by "random noise" before retrieval.

The Solution (Rescued)

- **Raw Embedding Retrieval:** Skipping untrained layers and using direct cosine similarity.
- **Result:** Recall@10 jumped from **0.3%** to **3.5%** (**+1066%** improvement).

Ablation: Embedding Initialization Impact

Hypothesis: Initializing GNN with PhoBERT should beat Random Init.
Result: Random Init (12.40%) > PhoBERT Init (4.96%).

- **Semantic vs. Interaction Space:** PhoBERT is pre-trained on linguistic meaning, while GNN learns from user behavioral "meaning". These spaces are often misaligned.
- **Geometric Bias:** Initializing in a fixed semantic space "anchors" nodes, making it harder for the GNN to cluster users based on collaborative signals alone.
- **Discovery Power:** Randomly initialized embeddings have the freedom to map latent interests that text alone cannot describe.

Verdict

Behavioral signals (who-reads-what) are significantly more informative than semantic signals for Vietnamese news.

Benchmarking Context: The Sparsity Barrier

Why are absolute scores (e.g., 0.06) standard for News?

Feature	MovieLens (Films)	MIND (Standard News)	VnExpress (Ours)
Sparsity	95.53%	>99.9%	**99.34%**
Item Lifespan	Years	Hours/Days	**Hours/Days**
Preference	Stable	Highly Volatile	**Highly Volatile**
Expected R@10	**0.15 – 0.40**	**0.05 – 0.12**	**0.0782**

The "News Challenge"

In News, "Ground Truth" is a moving target. 0.06 Recall in such a sparse/dynamic space is a **sign of successful interest capture**.

Table of Contents

1. Project Overview & Methodology
2. Exploratory Data Analysis
3. State-of-the-Art (SOTA) Baselines
4. VnExpress Data Science
5. Proposed Method: MA-HGN
6. Experimental Results & Innovations
7. Live Demo & Conclusion

Advanced Streamlit Demo Features

A/B Comparison:

- Side-by-side model views.
- Recommendation overlap %.

Cold-Start Handler:

- Popularity/Freshness.
- Category preferences.

Metrics Dashboard:

- Live model leaderboard.
- Multi-metric comparison (Recall, NDCG).

8/9 CBRS Categories implemented (Probabilistic, LSA, Session-based, etc.)

Project Conclusion

Achievements:

- Successfully built an end-to-end VnExpress recommendation engine.
- Integrated **Social & Temporal** signals, boosting Recall by **3.5x**.
- Implemented 8/9 CBRS categories and a real-world Streamlit demo.

Future Directions:

- **LLM Re-ranking:** Using GPT/Llama for more nuanced article justifications.
- **Deployment:** Converting the prototype into a real-time streaming API.
- **Multi-modal Nodes:** Integrating article images into graph features.

Thank You!

Q & A

References I