

Deployment of unsupervised learning in the search for new physics at the LHC with the ATLAS detector

by

Sakarias Garcia de Presno Frette

THESIS

for the degree of

MASTER OF SCIENCE



Faculty of Mathematics and Natural Sciences
University of Oslo

Autumn 2022

Deployment of unsupervised learning in the search for new physics at the LHC with the ATLAS detector

Sakarias Garcia de Presno Frette

© 2022 Sakarias Garcia de Presno Frette

Deployment of unsupervised learning in the search for new physics at the LHC with the ATLAS detector

<http://www.duo.uio.no/>

Printed: Reprosentralen, University of Oslo

Abstract

Acknowledgments

Contents

Introduction	1
1 Machine learning phenomenology	3
2 The Standard model	9
3 Implementation	17
4 Results	19
5 Discussion	21
Conclusion	23
Appendices	25
Appendix A	27
Appendix B	29
Appendix C	31
Appendix D	33

Introduction

Outline of the Thesis

Chapter 1

Machine learning phenomenology

Neural Networks

There are several categories of statistical algorithms for data analysis within machine learning. Amongst them are neural networks, which have for the last decade exponentially been used within industry and academia for a number of usecases. From image analysis to weather prediction, these models are used extensively.

Neural networks, or feed forward neural networks (FFNN), are based on a few principles. First, the data is feeded forward through the network. The end output is evaluated in some fashion, and corrections are then back propagated through the network, updating the weights and biases. This "training" is done until a sufficient threshold is met.

Autoencoders

Autoencoders are a subset of neural networks. Whereas a general neural network in principle can take any shape, autoencoders are more restrictive. This restrictiveness can in its most general sense be condensed into the following points:

- Same number of output categories as input categories
- A latent space with smaller dimensionality than the input/output layer

What we end up with is two funnel shaped parts linked together. The two funnels are called the encoder (left funnel) and decoder (right funnel) respectively. This architecture is not accidental, but rather designed with a very specific solution of problems in mind, reconstruction. A good example to illustrate this is image denoising. Suppose you have a noised image, and want to denoise it. By feeding the encoder a noised image, and comparing the decoder output to the actual image, the autoencoder can tune itself to denoise images.

Chapter 2

The Standard model

Why the Standard Model

Structure and composition of the Standard Model

Limitations

All though the standard model have had great success comparing with experiments, there are still several problems not addressed by it. First and foremost, the standard model as described above, does not and cannot explain gravity in a quantized way. There are models that try to address this problem, but they supplement the standard model, and does not derrive it from it.

Chapter 3

Implementation

Chapter 4

Results

Chapter 5

Discussion

Conclusion

Future work, more work

Appendices

Appendix A

Appendix B

Appendix C

Appendix D

Bibliography