1, Basic Alert: <script>alert('XSS')</script>



What it does:

- Executes JavaScript
- Shows a popup alert saying **"XSS"**

Purpose:

- Simple test to check if XSS is possible

Expected Output:

- Alert popup appears

2, Image Tag Payload: <img src=x onerror=alert('XSS')>



What it does:

- Tries to load an invalid image (src=x)
- Triggers onerror event
- Executes JavaScript alert

Why important:

- Bypasses filters that block <script> tags

Expected Output:

- Alert popup appears

3, SVG Payload:<Svg/onload=alert('XSS')>



What it does:

- Uses SVG element
- Runs JavaScript when SVG loads

Why important:

- Another bypass technique
- Works even if <img> is blocked

Expected Output:

- Alert popup appears

4, Cookie Display Payload: <img src=x onerror=alert(document.cookie)>



What it does:

- Displays browser cookies

Why dangerous:

- Can **steal session cookies**
- Leads to **session hijacking**

Expected Output:

- Alert showing cookies (if not protected

5, DOM Manipulation :src=xonerror="document.body.innerHTML='HACKED'">



What it does:

- Replaces entire webpage content with **"HACKED"**

Why dangerous:

- Can deface website

- Can inject phishing content

Expected Output:

- Page becomes blank and shows "HACKED"

◈ Which Payload Worked Best: <img src=x onerror=alert(document.cookie)>

Reason:

- More dangerous than alert
- Shows **real sensitive data (cookies)**
- Demonstrates **actual attack impact**