

Electrical Engineering
IIT Madras



EE 3101 Digital Signal Processing

BS Electronic Systems programme

R. David Koilpillai

September – December 2024

Session # 19

November 19, 2024



19/11/24

Note Title

EE3101 Digital Signal Processing

EE3101

Session 19

03-01-2018

Session 19

Outline

Last session

- Intro to Ch 5
- $H(e^{j\omega})$ — magnitude, phase
 - Group delay
- Impact of G.D
- Pole-zero plots

Today

- First order systems
- Allpass systems, properties
- Relationship between Mag & Phase

Reading Assignment

O&S ch5 Transform Analysis of LTI systems

Week 9-10

O&S chapter 5

Frequency Domain Analysis of LTI Systems: Frequency response of systems with rational transfer function—definitions of magnitude and phase response—frequency response of single complex zero/pole—frequency response of simple configurations (second order resonator, notch filter, averaging filter, comb filter, allpass systems)—phase response—definition of principal phase—zero-phase response—conditions that have to be met for a filter to have generalized linear phase—four types of linear phase FIR filters—on the zero locations of a linear phase FIR filter—constrained zeros at $z = 1$ and at $z = -1$ and their implications on choice of filters Type I through Type IV (with focus on Type I)

Z Transform is a generalization of the DTFT

$$\text{Defn } X(z) \triangleq \sum_{n=-\infty}^{\infty} x[n] z^{-n} = \sum_{n=-\infty}^{\infty} [x[n] n^{-n}] e^{-j\omega n}$$

$$x[n] \xrightarrow{Z} X(z) \text{ ROC}$$
$$\xleftarrow{\text{Inv. ZT}}$$

$$x[n] = \frac{1}{2\pi j} \oint_C X(z) z^{n-1} dz$$

scale factor

Cauchy Integral Theorem

Contour

- Closed contour in ROC
- encircle $z=0$
- Traversed in counter-clockwise

$$X(z) = \frac{P(z)}{Q(z)}$$

Evaluate Inv ZT using
Cauchy Residue Theorem

Power Series

1 $\frac{1}{(1-x)^2} = 1 + 2x + 3x^2 + \dots$

2 $\ln(1+x) = x - \frac{x^2}{2} + \frac{x^3}{3} - \frac{x^4}{4} + \dots$

3 $e^z = \sum_{n=0}^{\infty} \frac{z^n}{n!} = 1 + z + \frac{z^2}{2!} + \frac{z^3}{3!} + \dots$

4 $\sin z = z - \frac{z^3}{3!} + \frac{z^5}{5!} - \dots$

ZT of periodic signal (period = N)

Commencing @ $n=0$

One period $X_1(z) = \sum_{n=0}^{N-1} x[n] z^{-n}$

$$X(z) = X_1(z) [1 + z^{-N} + z^{-2N} + \dots] = \frac{X_1(z)}{1 - z^{-N}} \quad |z| > 1$$

D&S Ch 5 Transform Analysis of LTI System

✓ 5.1 Freq response of LTI systems $h[n] \longleftrightarrow H(e^{j\omega})$

✓ 5.2 Systems characterized by LCCDE

✓ 5.3 Freq response of Rational Transfer Function

5.4 Relationship between magnitude and phase

→ ✓ 5.5 Allpass System

5.6 Min. phase system

5.7 Linear phase \Leftarrow


O&S ch 5

LTI system $h[n]$ $\xrightarrow{x[n]}$ $\boxed{h[n]}$ $\rightarrow y[n] = h[n] * x[n]$

Using DFT $Y(e^{j\omega}) = H(e^{j\omega}) X(e^{j\omega})$

$$H(e^{j\omega}) = \underbrace{|H(e^{j\omega})|}_{\text{Mag. resp.}} e^{j \underbrace{\arg[H(e^{j\omega})]}_{\text{phase response}}}$$


$$|Y(e^{j\omega})| = |H(e^{j\omega})| |X(e^{j\omega})|$$




Principal value of the Phase

$$-\pi < \text{ARG } H(e^{j\omega}) \leq \pi$$

$$\text{True phase } \underline{H(e^{j\omega})} = \text{ARG } H(e^{j\omega}) + 2\pi \pi(\omega)$$






Unwrapped Phase

$$\underbrace{\arg H(e^{j\omega})}_{\text{phase unwrapping}} = \text{ARG } H(e^{j\omega}) + 2\pi n(\omega)$$


$$n(\omega) = \pm K \quad K = 0, 1, 2, \dots$$

phase unwrapping



Principal value

= phase wrap around



(c)

$$\text{Group Delay} = \tau(\omega) = - \frac{d}{d\omega} \underbrace{\arg H(e^{j\omega})}_{\text{true phase or unwrapped phase}}$$


true phase or

unwrapped phase



Understand the GrD distortion introduced by LTI system

Choose LTI system with linear $\phi \Rightarrow$ constant GrD

\Rightarrow No GrD distortion



LTI



Rule of Thumb





- GD is derivative $\arg H(e^{j\omega})$
- regions of rapid phase change \Rightarrow large GD near poles or zeros
- \Rightarrow regions where change of magnitude

Ex

$$(1 - z_0 z^{-1}) \Rightarrow \text{zero @ } z_0$$

$$\frac{z - z_0}{z}$$

$$\left(\frac{1 - z_0 z^{-1}}{1 - z_1 z^{-1}} \right)$$



Magnitude response

1. Traverse the unit circle $\omega=0$ to $\omega=2\pi$
(counter clockwise)
2. At each point on unit circle, evaluate $|H(e^{j\omega})|$

Ideal LPP

$$H(e^{j\omega}) = \begin{cases} 1 & |\omega| < \omega_c \\ 0 & \text{otherwise} \end{cases}$$

$$\longleftrightarrow h[n] = \frac{\sin \omega_c n}{\pi n}$$



$H(e^{j\omega})$ = real-valued


$\arg H(e^{j\omega}) = 0 \quad \forall \omega \Rightarrow$ zero phase function

Zero-phase TF

→ non-causal
→ symmetry $\begin{cases} \text{even} \\ \text{odd} \end{cases}$

→ finite or inf duration


* LTI systems with linear phase are realizable



even symmetry $h[n] = h[-n]$

non-causal

infinite duration



$$h_{\text{prac}}[n] = \frac{\sin \cdot \omega_c (n - n_d)}{\pi (n - n_d)} [u[n] - u[n - (2n_d + 1)]]$$


Linear phase $-\omega n_d$

Group Delay n_d samples

Truncation + shift to make it realizable
(Windowing)

Application

Inverse System



$$H(z) H_{inv}(z) = 1 \quad \Rightarrow \quad H_{inv}(z) = \frac{1}{H(z)}$$

Suppose $H(z)$ causal & stable \rightarrow all poles inside unit circle $|z| > r_R$

$$r_R < 1$$

— What about $H_{inv}(z)$? \rightarrow no constraint on zeros

\rightarrow poles & zeros

poles of $H_{inv}(z)$ inside unit circle

zeros of $H(z)$ inside unit circle

$h[n]$ $\begin{cases} \text{finite length} & \text{Finite Impulse Response (FIR)} \\ \text{infinite length} & \text{Infinite Impulse Response (IIR)} \end{cases}$

Linear ϕ

① Can IIR system have linear ϕ ?

Yes. Ideal LPF

② Can FIR system have linear ϕ ? Yes.

Linear ϕ depends on the symmetry in $h[n]$

Causality

③ Can an IIR filter be causal? Yes

$$h[n] = a^n u[n]$$

④ Can a causal IIR filter have linear ϕ ? No.

BIBO stability

$$|H(e^{j\omega})| < \infty \quad \forall \omega$$

$$\Rightarrow \sum_{n=-\infty}^{\infty} |h[n]| < \infty \quad \text{Absolute summability}$$

\Rightarrow ZT having ROC that includes unit circle

Causal & stable \Rightarrow all poles inside the unit circle

BIBO stable

FIR system (causal) \Rightarrow poles are @ $z=0$

IIR system (causal) \Rightarrow poles inside unit circle

$$H(z) = \left(\frac{a_0}{b_0} \right) \frac{\prod_{k=1}^M (1 - c_k z^{-1})}{\prod_{k=1}^N (1 - d_k z^{-1})}$$

poles @ $z = d_k \quad k=1, \dots, N$

zeros @ $z = c_k \quad k=1, \dots, M$

$N \geq 1$ $h[n]$ will be IIR

Example

$$H(z) = \frac{Y(z)}{X(z)} = \frac{1}{1 - d_0 z^{-1}} \quad (1)$$


$$\rightarrow Y(z) - d_0 Y(z) z^{-1} = X(z) \quad (2)$$

(3) Recursive relation



$$Y(z) = d_0 Y(z) z^{-1} + X(z) \quad (3)$$

Substitute (3) in (2)

$$Y(z) = d_0^2 Y(z) z^{-2} + X(z) + d_0 X(z) z^{-1}$$



$$H(e^{j\omega}) \begin{cases} |H(e^{j\omega})| \\ \arg H(e^{j\omega}) \end{cases}$$



LTI System (IIR)

$$H(z) = \left(\frac{a_0}{b_0} \right) \frac{\prod_{k=1}^M (1 - c_k z^{-1})}{\prod_{k=1}^N (1 - d_k z^{-1})}$$

FIR if $N=0$

$$20 \log_{10} |H(e^{j\omega})| = 20 \log_{10} \left| \frac{a_0}{b_0} \right| + \sum_{k=1}^M 20 \log_{10} |1 - c_k e^{-j\omega}| - \sum_{k=1}^N 20 \log_{10} |1 - d_k e^{-j\omega}|$$

$$\arg H(e^{j\omega}) = \sum_{k=1}^M \arg (1 - c_k e^{-j\omega}) - \sum_{k=1}^N \arg (1 - d_k e^{-j\omega})$$

$$\text{Group delay } \tau(\omega) = - \frac{d}{d\omega} \left[\underbrace{\arg H(e^{j\omega})}_{\text{unwrapped phase}} \right]$$

$$H(z) = 1 - c_1 z^{-1}$$

c_1 is real

$$H(e^{j\omega}) = 1 - c_1 e^{-j\omega} = 1 - c_1 \cos \omega + j c_1 \sin \omega$$

$$|H(e^{j\omega})|^2 = \sqrt{(1 - c_1 \cos \omega)^2 + (c_1 \sin \omega)^2}$$

$$\arg H(e^{j\omega}) = \tan^{-1} \left[\frac{c_1 \sin \omega}{1 - c_1 \cos \omega} \right]$$

$$\tau(\omega) = - \frac{d}{d\omega} (\arg H(e^{j\omega})) = - \frac{d}{d\omega} \tan^{-1} \left(\frac{c_1 \sin \omega}{1 - c_1 \cos \omega} \right) = \frac{c_1^2 - c_1 \cos \omega}{1 + c_1^2 - 2 c_1 \cos \omega}$$

c_1 complex

$$c_1 = r_1 e^{j\theta_1}$$

$$H(e^{j\omega}) = 1 - r_1 e^{j\theta_1} e^{-j\omega} = 1 - r_1 e^{-j(\omega - \theta_1)}$$

$$= 1 - r_1 \cos(\omega - \theta_1) + j r_1 \sin(\omega - \theta_1)$$

$$|H(e^{j\omega})|$$

$$\arg H(e^{j\omega})$$

$$\tau(\omega) = \frac{|c_1|^2 - \operatorname{Re}\{c_1 e^{-j\omega}\}}{1 + |c_1|^2 - 2 \operatorname{Re}\{c_1 e^{-j\omega}\}}$$

Task to
Complete

5.5 Allpass Systems

$$H_{ap}(z) = \frac{z^{-1} - a^*}{1 - az^{-1}} = z^{-1} \frac{(1 - a^* z)}{(1 - az^{-1})}$$

$$H_{ap}(e^{j\omega}) = \frac{e^{-j\omega} (1 - a^* e^{j\omega})}{(1 - a e^{-j\omega})}$$

$$|H_{ap}(e^{j\omega})| = \underbrace{|e^{-j\omega}|}_{=1} \cdot \underbrace{\frac{|1 - a^* e^{j\omega}|}{|1 - a e^{-j\omega}|}}_{=1} = \frac{|N(e^{j\omega})|}{|D(e^{j\omega})|}$$

$$= \frac{|C^*|}{|C|} = 1$$

$$N(e^{j\omega}) = D^*(e^{j\omega})$$

$$|H_{ap}(e^{j\omega})| = 1 \quad \forall \omega \quad \text{Allpass filter}$$

$n=-1$	$n=0$	$n=1$
D_r	1	$-a$
N_r	$-a^*$	1

Time-reversed + conjugation

Gen form of Allpass Systems

$$H_{ap}(z) = \frac{b_N^* + b_{N-1}^* z^{-1} + b_{N-2}^* z^{-2} + \dots + b_1^* z^{-(N-1)} + z^{-N}}{1 + b_1 z^{-1} + b_2 z^{-2} + \dots + b_N z^{-N}} = z^{-N} \frac{[1 + b_1^* z + b_2^* z^2 + \dots + b_N^* z^N]}{[1 + b_1 z^{-1} + b_2 z^{-2} + \dots + b_N z^{-N}]}$$

$$\text{Verify } |H_{ap}(e^{j\omega})| = 1 \quad \forall \omega$$



Zeros & Poles of $H_{ap}(z)$

$H_{ap}(z)$ causal & stable \Rightarrow poles must be within unit circle

$$H_{ap}(z) = \frac{z^{-1} - a^*}{1 - az^{-1}}$$

pole @ $z = a$

zero @ $z = \frac{1}{a^*}$



$$H_1(z) = (1 - az^{-1})$$

$$H_2(z) = (z^{-1} - a^*)$$

$$H_{ap}(e^{j\omega}) = \overbrace{e^{-j\omega}}^{N_r} \underbrace{\frac{(1 - a^* e^{j\omega})}{(1 - a e^{-j\omega})}}_{D_r} \quad \boxed{a = r e^{j\theta}} \text{ location of pole}$$

Verify $|H_{ap}(e^{j\omega})| = 1 \quad \forall \omega$

$$\arg[H_{ap}(e^{j\omega})] = \underbrace{-\omega + \tan^{-1}\left[\frac{-r \sin(\omega - \theta)}{1 - r \cos(\omega - \theta)}\right]}_{N_r} \ominus \underbrace{\tan^{-1}\left[\frac{r \sin(\omega - \theta)}{1 - r \cos(\omega - \theta)}\right]}_{D_r}$$

Group delay $\tau(\omega) = -\frac{d}{d\omega} [\arg H_{ap}(e^{j\omega})] = +1 - 2 \frac{d}{d\omega} \tan^{-1}\left[\frac{r \sin(\omega - \theta)}{1 - r \cos(\omega - \theta)}\right]$

$$\tau(\omega) = \frac{1 - r^2}{1 + r^2 - 2r \cos(\omega - \theta)} \quad \text{Verify}$$

Causal, stable allpass

\Rightarrow all poles inside the unit circle

$$r < 1$$

$$\tau(\omega) = \frac{N_r}{D_r}$$

$$\tau(\omega) > 0 \quad \forall \omega$$

$$r < 1 \quad N_r > 0$$

$$r < 1 \quad D_r > 0$$


Smallest value of D_r
 $\cos(\omega - \theta) = +1$

$$D_r = 1 + r^2 - 2r = (1 - r)^2$$

$$\tau(\omega) = - \frac{d}{d\omega} \arg H_{ap}(e^{j\omega})$$

$$\tau(\omega) > 0 \quad \forall \omega$$


$\Rightarrow \arg H_{ap}(e^{j\omega})$ is a monotone decreasing function



General result

Causal, stable Allpass \Rightarrow all ^{strictly} poles inside unit circle
 \Rightarrow phase is ^{strictly} monotone decreasing.

Magnitude response of first order zero




$$\arg H(e^{j\omega}) = \angle v_3 - \angle v_1$$



$$H(z) = (1 - c_0 z^{-1}) = \frac{z - c_0}{z} = \frac{v_3}{v_1}$$




$$|H(e^{j\omega})| = \frac{|v_3|}{|v_1|}$$

compute at all points on the unit circle



$\arg H(e^{j\omega})$









$\pi = 1$
 $\pi = 0.9$
 $\pi = 0.7$
 $\pi = 0.5$

$\pi/2$

$$H(z) = (1 + z^{-1})$$


$$C_0 = -1$$



$$C_0 = -0.9$$




- ① Magnitude response
- ② Phase response
- ③ Group response

O&S Example 5.6





(b)



(c)

OKS Example 5.8

