

# Homework 5

Submission by : Gagan Ullas Nirgun , Viswadeep Mallarapu Bhaskar

Question 1 (a)

```
In [57]: import numpy as np
import matplotlib.pyplot as plt
from sklearn.datasets import fetch_openml
from sklearn.model_selection import train_test_split
from sklearn.preprocessing import StandardScaler
from sklearn.linear_model import LogisticRegression
from sklearn.metrics import accuracy_score, roc_curve, roc_auc_score, auc
from sklearn.ensemble import RandomForestClassifier
import warnings
warnings.filterwarnings('ignore')
```

```
In [58]: # Load data
X_train = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/Gisette/gise
y_train = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/Gisette/gise

X_test = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/Gisette/giset
y_test = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/Gisette/giset

# Convert labels to binary
y_train = (y_train + 1) // 2
y_test = (y_test + 1) // 2

scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)
```

```
In [59]: # Lorenz loss function
def lorenz_loss(x):
    return np.where(x > 1, 0, np.log1p(1 + ((x - 1) ** 2)))

# FSA algorithm
def fsa(X_train, y_train, X_test, y_test, k_values, s=0.001, mu=300, N_iter=300):

    n,p = X_train.shape
    # Initialize beta
    beta = np.zeros(p)

    # Lists to store training loss for each iteration
    train_loss = []

    for i in range(1, N_iter + 1):

        # Compute gradient of the loss function
        gradient = np.dot(X_train_scaled.T, (np.dot(X_train_scaled, beta) - y_train)) / len(y_train)

        # Update beta using gradient descent
        beta -= s * gradient

        # Variable selection
        mi = k + (X_train_scaled.shape[1] - k) * max(0, (N_iter - 2 * i) / (2 * i * mu + N_iter))
        top_k_indices = np.argsort(beta ** 2)[-int(mi):]

        loss = np.mean([lorenz_loss(1 - 2 * y_train[i] + 2 * y_train[i] * np.dot(X_train_scaled[i], beta)
        train_loss.append(loss)

    return top_k_indices,train_loss
```

```
In [60]: k_values = [10, 30, 100, 300, 500]
s = 0.001
mu = 300
N_iter = 300

train_errors = []
test_errors = []

for k in k_values:
    k_indices, train_loss = fsa(X_train, y_train, X_test, y_test, k_values, s, mu, N_iter)
    X_train_selected = X_train_scaled[:, k_indices]
    X_test_selected = X_test_scaled[:, k_indices]
    lr = LogisticRegression()
    lr.fit(X_train_selected, y_train)

    # Compute misclassification error on training set
    y_train_pred = lr.predict(X_train_selected)
    train_error = 1 - accuracy_score(y_train, y_train_pred)
    train_errors.append(train_error)

    # Compute misclassification error on test set
    y_test_pred = lr.predict(X_test_selected)
    test_error = 1 - accuracy_score(y_test, y_test_pred)
```

```
test_errors.append(test_error)

        # If k is 100, extract feature subset and plot ROC curves
    if k == 100:
        # Train logistic regression classifier with 100 selected features
        lr_100_features = LogisticRegression()
        lr_100_features.fit(X_train_selected, y_train)


        # Predict probabilities for training and test set
        y_train_proba = lr_100_features.predict_proba(X_train_selected)[: , 1]
        y_test_proba = lr_100_features.predict_proba(X_test_selected)[: , 1]


        # Compute ROC curve and ROC area for training set
        fpr_train, tpr_train, _ = roc_curve(y_train, y_train_proba)
        roc_auc_train = auc(fpr_train, tpr_train)

        # Compute ROC curve and ROC area for test set
        fpr_test, tpr_test, _ = roc_curve(y_test, y_test_proba)
        roc_auc_test = auc(fpr_test, tpr_test)

        # Plot ROC curve for training set
        plt.figure()
        plt.plot(fpr_train, tpr_train, color='darkorange', lw=2, label=f'Train ROC curve (AUC = {roc_auc_train:.2f})')
        plt.plot([0, 1], [0, 1], color='navy', lw=2, linestyle='--')
        plt.xlabel('False Positive Rate')
        plt.ylabel('True Positive Rate')
        plt.title('ROC Curve - Training Set (100 Features)')
        plt.legend(loc='lower right')
        plt.show()

        # Plot ROC curve for test set
        plt.figure()
        plt.plot(fpr_test, tpr_test, color='darkorange', lw=2, label=f'Test ROC curve (AUC = {roc_auc_test:.2f})')
        plt.plot([0, 1], [0, 1], color='navy', lw=2, linestyle='--')
        plt.xlabel('False Positive Rate')
        plt.ylabel('True Positive Rate')
        plt.title('ROC Curve - Test Set (100 Features)')
        plt.legend(loc='lower right')
        plt.show()
```






```
In [61]: plt.plot(k_values, train_errors, label='Train Error')
plt.plot(k_values, test_errors, label='Test Error')
plt.xlabel('Number of Features (k)')
plt.ylabel('Misclassification Error')
plt.title('Misclassification Error vs Number of Features (k)')
plt.legend()
plt.show()


print("Test and Train Misclassification Errors:")
print("k\tTrain Error\tTest Error")
for i, k in enumerate(k_values):
    print(f"{k}\t{train_errors[i]:.4f}\t\t{test_errors[i]:.4f}")

k_indices, train_loss = fsa(X_train, y_train, X_test, y_test, k_values, s, mu, N_iter)
plt.plot(range(1, 301), train_loss)
plt.xlabel('Iteration')
plt.ylabel('Training Loss')
plt.title('Training Loss vs Iteration Number for k = 100')
plt.show()
```



Test and Train Misclassification Errors:

k	Train Error	Test Error
10	0.1195	0.1300
30	0.0658	0.0730
100	0.0275	0.0360
300	0.0038	0.0180
500	0.0000	0.0160



Question 1 (b)

```
In [62]: # Load data
X_train = np.genfromtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_3/dexter/de
y_train = np.genfromtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_3/dexter/de

X_test = np.genfromtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_3/dexter/dex
y_test = np.genfromtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_3/dexter/dex

# Convert labels to binary
y_train = (y_train + 1) // 2
y_test = (y_test + 1) // 2

scaler = StandardScaler()
X_train_scaled = scaler.fit_transform(X_train)
X_test_scaled = scaler.transform(X_test)
```

```
In [63]: k_values = [10, 30, 100, 300, 500]
s = 0.001
mu = 300
N_iter = 300

train_errors = []
test_errors = []

for k in k_values:
    k_indices, train_loss = fsa(X_train, y_train, X_test, y_test, k_values, s, mu, N_iter)
    X_train_selected = X_train_scaled[:, k_indices]
    X_test_selected = X_test_scaled[:, k_indices]
    lr = LogisticRegression()
    lr.fit(X_train_selected, y_train)

    # Compute misclassification error on training set
    y_train_pred = lr.predict(X_train_selected)
    train_error = 1 - accuracy_score(y_train, y_train_pred)
    train_errors.append(train_error)

    # Compute misclassification error on test set
    y_test_pred = lr.predict(X_test_selected)
    test_error = 1 - accuracy_score(y_test, y_test_pred)
    test_errors.append(test_error)

    # If k is 100, extract feature subset and plot ROC curves
    if k == 100:
        # Train logistic regression classifier with 100 selected features
        lr_100_features = LogisticRegression()
        lr_100_features.fit(X_train_selected, y_train)

        # Predict probabilities for training and test set
        y_train_proba = lr_100_features.predict_proba(X_train_selected)[:, 1]
        y_test_proba = lr_100_features.predict_proba(X_test_selected)[:, 1]



        # Compute ROC curve and ROC area for training set
        fpr_train, tpr_train, _ = roc_curve(y_train, y_train_proba)
        roc_auc_train = auc(fpr_train, tpr_train)

        # Compute ROC curve and ROC area for test set
        fpr_test, tpr_test, _ = roc_curve(y_test, y_test_proba)
        roc_auc_test = auc(fpr_test, tpr_test)

        # Plot ROC curve for training set
        plt.figure()
        plt.plot(fpr_train, tpr_train, color='darkorange', lw=2, label=f'Train ROC curve (AUC = {roc_auc_train})')
        plt.plot([0, 1], [0, 1], color='navy', lw=2, linestyle='--')
        plt.xlabel('False Positive Rate')
        plt.ylabel('True Positive Rate')
```

```
plt.title('ROC Curve - Training Set (100 Features)')
plt.legend(loc='lower right')
plt.show()


# Plot ROC curve for test set
plt.figure()
plt.plot(fpr_test, tpr_test, color='darkorange', lw=2, label=f'Test ROC curve (AUC = {roc_auc_test:.2f})')
plt.plot([0, 1], [0, 1], color='navy', lw=2, linestyle='--')
plt.xlabel('False Positive Rate')
plt.ylabel('True Positive Rate')
plt.title('ROC Curve - Test Set (100 Features)')
plt.legend(loc='lower right')
plt.show()
```



```
In [64]: plt.plot(k_values, train_errors, label='Train Error')
plt.plot(k_values, test_errors, label='Test Error')
plt.xlabel('Number of Features (k)')
plt.ylabel('Misclassification Error')
plt.title('Misclassification Error vs Number of Features (k)')
plt.legend()
plt.show()


print("Test and Train Misclassification Errors:")
print("k\tTrain Error\tTest Error")
for i, k in enumerate(k_values):
    print(f"{k}\t{train_errors[i]:.4f}\t{test_errors[i]:.4f}")

k_indices, train_loss = fsa(X_train, y_train, X_test, y_test, k_values, s, mu, N_iter)
plt.plot(range(1, 301), train_loss)
plt.xlabel('Iteration')
plt.ylabel('Training Loss')
plt.title('Training Loss vs Iteration Number for k = 100')
plt.show()
```



Test and Train Misclassification Errors:

k	Train Error	Test Error
10	0.2033	0.2200
30	0.0567	0.1133
100	0.0133	0.1300
300	0.0000	0.0967
500	0.0000	0.0800



Question 1 (c)

```
In [68]: # Lorenz loss function
def lorenz_loss(x):
    return np.where(x > 1, 0, np.log1p(1 + ((x - 1) ** 2)))

# FSA algorithm
def fsa(X_train, y_train, X_test, y_test, k_values, s=0.001, mu=300, N_iter=300):
    train_errors = []
    test_errors = []
    train_losses = []

    for k in k_values:
        # Normalize features
        scaler = StandardScaler()
        X_train_scaled = scaler.fit_transform(X_train)
        X_test_scaled = scaler.transform(X_test)

        n,p = X_train.shape
        # Initialize beta
        beta = np.zeros(p)

        # Lists to store training loss for each iteration
        train_loss = []

        for i in range(1, N_iter + 1):

            # Compute gradient of the loss function
            gradient = np.dot(X_train_scaled.T, (np.dot(X_train_scaled, beta) - y_train)) / len(y_train)
```

```

# Update beta using gradient descent
beta -= s * gradient

# Variable selection
mi = k + (X_train_scaled.shape[1] - k) * max(0, (N_iter - 2 * i) / (2 * i * mu + N_iter))
top_k_indices = np.argsort(beta ** 2)[-int(mi):]
X_train_selected = X_train_scaled[:, top_k_indices]
X_test_selected = X_test_scaled[:, top_k_indices]

loss = np.mean([lorenz_loss(1 - 2 * y_train[i] + 2 * y_train[i] * np.dot(X_train_scaled[i], beta)
train_loss.append(loss)

# Train logistic regression classifier
lr = RandomForestClassifier(n_estimators=100, random_state=42)
lr.fit(X_train_selected, y_train)

# Compute misclassification error on training set
y_train_pred = lr.predict(X_train_selected)
train_error = 1 - accuracy_score(y_train, y_train_pred)
train_errors.append(train_error)

# Compute misclassification error on test set
y_test_pred = lr.predict(X_test_selected)
test_error = 1 - accuracy_score(y_test, y_test_pred)
test_errors.append(test_error)

# If k is 100, extract feature subset and plot ROC curves
if k == 100 and i == N_iter:
    # Train logistic regression classifier with 100 selected features
    lr_100_features = RandomForestClassifier(n_estimators=100, random_state=42)
    lr_100_features.fit(X_train_selected, y_train)

    # Predict probabilities for training and test set
    y_train_proba = lr_100_features.predict_proba(X_train_selected)[:, 1]
    y_test_proba = lr_100_features.predict_proba(X_test_selected)[:, 1]

    # Compute ROC curve and ROC area for training set
    fpr_train, tpr_train, _ = roc_curve(y_train, y_train_proba)
    roc_auc_train = auc(fpr_train, tpr_train)

    # Compute ROC curve and ROC area for test set
    fpr_test, tpr_test, _ = roc_curve(y_test, y_test_proba)
    roc_auc_test = auc(fpr_test, tpr_test)

    # Plot ROC curve for training set
    plt.figure()
    plt.plot(fpr_train, tpr_train, color='darkorange', lw=2, label=f'Train ROC curve (AUC = {roc_auc_train})')
    plt.plot([0, 1], [0, 1], color='navy', lw=2, linestyle='--')
    plt.xlabel('False Positive Rate')
    plt.ylabel('True Positive Rate')
    plt.title('ROC Curve - Training Set (100 Features)')
    plt.legend(loc='lower right')
    plt.show()

    # Plot ROC curve for test set
    plt.figure()
    plt.plot(fpr_test, tpr_test, color='darkorange', lw=2, label=f'Test ROC curve (AUC = {roc_auc_test})')
    plt.plot([0, 1], [0, 1], color='navy', lw=2, linestyle='--')
    plt.xlabel('False Positive Rate')
    plt.ylabel('True Positive Rate')
    plt.title('ROC Curve - Test Set (100 Features)')
    plt.legend(loc='lower right')
    plt.show()

train_losses.append(train_loss)

return train_losses, train_errors, test_errors

# Load data
X_train = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/MADELON/made
y_train = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/MADELON/made

X_test = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/MADELON/madel
y_test = np.loadtxt("/Users/gaganullas19/Documents/Spring2024/AppliedMachineLearning/Homework_4/MADELON/madel

# Convert labels to binary
y_train = (y_train + 1) // 2
y_test = (y_test + 1) // 2

# Define parameters
k_values = [10, 30, 100, 300, 500]
s = 0.001
mu = 300
N_iter = 300

# Run FSA algorithm
train_losses, train_errors, test_errors = fsa(X_train, y_train, X_test, y_test, k_values, s, mu, N_iter)

# Plot training loss vs iteration number for k=100
plt.plot(range(1, N_iter + 1), train_losses[2])
plt.xlabel('Iteration Number')
plt.ylabel('Training Loss')
plt.title('Training Loss vs Iteration Number (k=100)')

```





```
plt.show()


# Report misclassification errors for different k values
print("k\tTrain Error\tTest Error")
for i, k in enumerate(k_values):
    train_error = round(train_errors[i], 4)
    test_error = round(test_errors[i], 4)
    print(f"{k}\t{train_error}\t{test_error}")

# Aggregate misclassification errors for each k value
avg_train_errors = [np.mean(train_errors[i::len(k_values)]) for i in range(len(k_values))]
avg_test_errors = [np.mean(test_errors[i::len(k_values)]) for i in range(len(k_values))]


# Plot misclassification error vs k
plt.plot(k_values, avg_train_errors, label='Train Error')
plt.plot(k_values, avg_test_errors, label='Test Error')
plt.xlabel('Number of Features (k)')
plt.ylabel('Misclassification Error')
plt.title('Misclassification Error vs Number of Features')
plt.legend()
plt.show()
```







k	Train Error	Test Error
10	0.0	0.2817
30	0.0	0.225
100	0.0	0.2283
300	0.0	0.2083
500	0.0	0.195



In [ ]: