Top 40 file extensions to support

for projects generated by Claude Code

Generated 2026-10-27 · scored from 188 sourced findings in 5 evidence streams, weights 0.5 / 0.3 / 0.2

Read this first. Anthropic does not publish how often Claude Code writes each file extension, and this report does not pretend otherwise. What follows is a **transparent estimate**: every candidate extension gets three scores, the ranking is computed from them with fixed weights, and each score names the evidence it rests on or says that it is a judgement. Of the 188 findings gathered, 105 were read on the page itself and the rest are search-result text. The only published per-file-type counts for Claude Code output (a 790-commit sample: Markdown, TypeScript, XML, JSON and Python lead) come from one paper that could not be opened from the sandbox and were not reproduced by a later search; treat them as indicative. The one fully read Claude Code usage dataset gives repository languages, not extensions. For real numbers about your projects, use the measurement steps on the last pages.

Key findings

- **Top five:** .md, .json, .py, .js, .ts. Scores within about 10 points of each other should not be read as a strict order.
- **The two most common types get the thinnest analysis.** Of the top ten, 3 (.md .json .txt) receive a credential grep only.
- **The strongest Claude Code signals are file names, not extensions:** CLAUDE.md, SKILL.md, .mcp.json and .claude/settings.json. They carry prompt text, server launch commands and hooks, yet sit under .md and .json, and classify_file() routes only package.json, composer.json and a few other names by basename (see "What this means for the pipeline").
- **Prevalence is not risk.** Rare but dangerous types (.pkl, .exe, .jar, .docm, .xlsm, .pem, .env) rank low here by design; rank them with a separate risk weight.

Where the pipeline stands today

Of the top 40, 24 extensions already have a dedicated per-type scanner, 3 get a credential grep only, and 13 fall to the generic fallback (universal patterns, secrets, antivirus and licence layers, but no per-type analysis).

Treatment today	Extensions in the top 40	Meaning
Dedicated scanner	`24: .py .js .ts .yml .html .sh .tsx .yaml .xml .go .java .rs .cpp .php .c .h .sql .cs .mjs .jsx .pdf .rb .kt .tf`	its own rules in layer 5, plus layers 1, 4 and 6
Credential grep only	`3: .md .json .txt`	classify_file() has an inline rule and no per-type scanner
Generic fallback	`13: .css .png .toml .svg .lock .jpg .csv .ipynb .env.example .conf .scss .ico .cfg`	scan_unknown(): shebang or MIME check, plus layers 1, 4 and 6

How the ranking is built

Each candidate extension is scored 0 to 100 on three axes. The scores come from the evidence in the data file; where no number exists the rationale says the score is a judgement.

Axis	Weight	Question it answers	Main sources
`agent_score`	**0.5**	How common is it in code written by AI coding agents, and Claude Code in particular?	Anthropic publications; studies of agent-authored pull requests; Claude Code share analyses
`baseline_score`	**0.3**	How common is it in public repositories in general?	Large-corpus statistics, GitHub Linguist, Octoverse, developer surveys
`structural_score`	**0.2**	Does every Claude Code project carry it whatever the language (CLAUDE.md, settings, CI, lockfiles)?	Claude Code documentation: the files it reads, creates and recommends

score = 0.5 × agent + 0.3 × baseline + 0.2 × structural. Ties are broken by structural score, then by name.

Why a blend and not a single source

A scanner for Claude Code output has to cover what Claude Code writes (agent axis), what its users' repositories already contain (baseline axis) and what appears in every project because the tool itself puts it there (structural axis). A file such as CLAUDE.md or .mcp.json is rare in public corpora and universal in Claude Code projects, which is why the structural axis exists.

How the draft was checked

The scores were produced by one agent from the evidence, then reviewed by two independent critics: one looked for extensions the pool omitted or mis-weighted, the other for scores that claim more than their evidence supports. A third pass applied the corrections. The critics' reports are summarised below.

Completeness critic. The pool covers the language and config tiers well, but it has four gaps. First, the special-names block is unscored, so Dockerfile, package.json, requirements.txt, pyproject.toml, CLAUDE.md, .mcp.json and .claude/settings.json (the files that distinguish or can execute in a Claude Code repo) are outside the ranking; they should get scores on the same scale. Second, the Office and PDF tier is under-weighted for a pool the brief says includes skill-produced deliverables: .pdf, .docx, .xlsx and .pptx at 20, 10, 10 and 7 should be roughly 34, 26, 26 and 18, and the legacy and macro variants the scanner handles are missing. Third, data and ML, scaffold assets and deployment families are missing: .conf, .jsonl, .jsonc, .db/.sqlite, .pkl/.parquet, .ico/.woff2, .jar, .rst, templates, .snap and a tail of archives, binaries and key files. Fourth, a few scores conflict with the table's own evidence: .rs should be at or above .go given the random 790-commit sample, and .txt, .toml, .yaml, .mjs, .svg, .png and .csv are low against their real scaffold and tooling sources. .env.example is keyed as an extension although it is a name pattern. Scores that differ by less than about 10 points should still not be read as a ranking, and nearly all the proposed numbers are judgement, not measurement.

Evidence critic. Every cited evidence id exists in the evidence JSON, and the numbers quoted in the rationales match the findings. The problems are in what the evidence is asked to support. 1. Several rank claims are false against the table's own evidence. ".py: rank 2 in every Claude Code source" and ".ts: rank 1 on every measure" are contradicted by the 790-commit sample (Python rank 5, TypeScript rank 2) and by the 90-day window. The 34.8% to 53.5% TypeScript range merges incompatible snapshots, and the 53.5%, 24.3% and 22.2% figures come from a snapshot whose shares sum to 100% (top three only). 2. Chat-conversation shares and general-developer figures carry scores they cannot justify. The affected rows are .html (70), .css (64), .sql (46), .tsx (80) and .sh (62). Their only Claude Code specific support is undated or documentation examples, or they have none. The Artifacts caveat on HTML is a Claude.ai effect and is reworded too strongly. 3. Some citations do not support the row. A28 ('useless for ranking') is cited for .rs. A13 is cited for .proto but concerns generated outputs, and for .lock it shows non-authorship, not prevalence. E5 is cited for .go, .txt and .csproj but is an all-agent dependency-add rate. K4 (admiration) is cited for .ex, and A5 is used to explain .docx although it names only .xlsx. The study-design argument against .vue is invalid. 4. The same unverified sample (industry:R1-R5, H1) is trusted fully for .md, .json and .py but halved for .xml on an unchecked hypothesis. I recommend a consistent treatment. 5. Several rows with weak evidence

lack a 'judgement' label: .html, .css, .sql, .go, .java. Also, .env.example is not an extension, and .cmd, .kts and .psm1/.psd1 are missing from the table. No row has a score marked as measured that the evidence contradicts outright. The top-line scores for .md, .ts and .json are acceptable, but they depend on fetched=false, single-paper figures.

The top 40

Colour of the last column: green = dedicated scanner, amber = credential grep only, red = generic fallback. Scores are 0 to 100.

#	Ext	Format	Score	Agent	Base	Struct	Basis	Pipeline today
1	`.md`	Markdown	**92.7**	95	86	97	Rank 1 by commits touching a Markdown file in the unverified 790-commit sample (254 of 790; single paper, fetched=false), with documentation in 296 commits. Markdown is one of four example values of the OpenTelemetry language attribute, which publishes no counts. CLAUDE.md, AGENTS.md, SKILL.md, .claude/rules, .claude/agents and .claude/commands are all .md. The score of 95 rests mainly on that structural evidence, not on the sample.	credential grep only
2	`.json`	JSON	**87.5**	85	90	90	105 of 790 sampled Claude commits touched JSON (rank 4, unverified single paper; agent-pr-studies:H1 is low confidence). Several documented Claude Code files are JSON (.claude/settings.json, .mcp.json, hooks.json, plugin.json, devcontainer.json), although more documented files are Markdown. settings.local.json is gitignored, so a fetched repo may not carry it. Structural score is judgement. Baseline is judgement: no per-extension count was found.	credential grep only
3	`.py`	Python	**74.6**	84	82	40	Rank 2 by AIDev repo language (21.0% of Claude Code repos) and by signed-commit share in the March 2026 snapshot (18.9% of about 20.8M commits). The 24.3% figure comes from an undated snapshot whose top three shares sum to 100%, so it is a top-three-only share. In the 90-day window Python is rank 3 (11.3%) behind Unknown and TypeScript. In the unverified 790-commit sample 102 commits touched a Python file (rank 5, below JSON 105 and XML 106). Anthropic's 14% is a combined Claude.ai plus Claude Code query share, not Claude Code specific. Lowered from 90 to 84 after review because language-level shares do not transfer to file counts and the only file-level figure is rank 5. Structural is judgement: hook and skill helpers are documented as .py examples but optional.	scan_python
4	`.js`	JavaScript	**71.3**	70	93	42	Mixed signals, so lowered from 80 to 70 after review. Only 6.2% of AIDev repos (rank 5, behind Rust at 7.2%), 10.2% of signed commits in the March 2026 snapshot, and it is not among the 790-commit sample leaders. The Anthropic JS plus TS 31% and 'JavaScript and HTML most common' statements are combined Claude.ai plus Claude Code and mostly reflect TypeScript. Saved workflow scripts (.claude/workflows/*.js) and hook scripts are documented examples, not frequencies. Baseline is the highest of any language by repo count in githut. Agent score is judgement.	scan_javascript
5	`.ts`	TypeScript	**70**	90	58	38	Rank 1 by AIDev repo language (21.4%) and by signed-commit share (34.8% of about 20.8M commits in March 2026; 53.5% in an undated snapshot that looks top-three-only, so the two are not comparable). Rank 2 in the unverified 790-commit sample (213 commits touching a TypeScript file, behind Markdown's 254), and in the 90-day window Unknown (34.3%) outranks TypeScript (24.1%). Language-level figures cover .ts and .tsx together (BigCode folds .tsx into TypeScript), so the share is split between .ts and .tsx. Lowered from 94 to 90 after review. Baseline is lower because the Stack v2 row (23.85M files) is low confidence and .ts is also a Qt XML extension in Linguist. Structural is judgement.	scan_javascript
6	`.yml`	YAML	**64.6**	64	72	55	Judgement prior. GitHub Actions is the pick in 94% of CI choices, but industry:A4 is a tool-pick share from a medium-confidence study with four fixed repos, not a count of .yml files, and agent-pr-studies:J1 is an all-agent classifier. The installer writes .github/workflows/claude.yml and the GitLab setup edits .gitlab-ci.yml. The .yml versus .yaml split is not measured, so the two are kept within 10 points (66 lowered to 64).	scan_yaml
7	`.txt`	Plain text	**61.2**	56	84	40	Judgement, raised from 45 after review. No per-extension count was found. requirements.txt (Python is 21.0% of Claude Code AIDev repos), CMakeLists.txt (a Linguist file name), robots.txt, LICENSE.txt, prompt templates and fixture data all end in .txt. The scanner routes requirements*.txt and CMakeLists.txt by basename. Baseline reflects the extension's ubiquity, not a measurement.	credential grep only

#	Ext	Format	Score	Agent	Base	Struct	Basis	Pipeline today
8	`.html`	HTML	**57.7**	55	86	22	Judgement, lowered from 70 after review. The 28% HTML plus CSS Anthropic figure is a combined Claude.ai plus Claude Code conversation share, and Anthropic says the HTML count is 'probably slightly inflated' by Artifacts, a Claude.ai effect. The 22.2% signed-commit share comes from an undated snapshot whose top three shares sum to 100% (a top-three-only share); in the March 2026 snapshot JavaScript, not HTML, is rank 3. Largest volume in the Stack (2.4 TB), which drives the baseline.	scan_html
9	`.sh`	Shell	**54.4**	50	68	45	Judgement, lowered from 62 after review. Hook scripts, status line scripts and the dev container's init-firewall.sh are .sh in the Claude Code docs, but those are documented examples, not frequencies, and none of the dev container files is required. The rest is general-developer evidence: Shell is rank 6 by GitHub pushers (2.3M) and 593k repos; Octoverse's rank is low confidence. No Claude Code Shell share was found.	scan_shell
10	`.tsx`	TypeScript JSX (React)	**54**	68	48	28	Judgement prior. No source splits .tsx from .ts, and TypeScript's lead is already credited to .ts, so the agent score was lowered from 80 to 68 after review. Earlier support from anthropic-primary:A7 (UI conversation share, not Claude Code specific) and industry:A4 (shadcn/ui pick share in a study whose repo mix is fixed by design) was removed because neither is file evidence. Linguist treats TSX as a separate language, BigCode folds it into TypeScript, so corpus counts are not comparable. Baseline raised from 40 to 48 after review because TypeScript pushers grew 2.26x between 2024 Q4 and 2026 Q1, which puts general .tsx at or above .jsx.	scan_javascript
11	`.yaml`	YAML	**51.4**	54	60	32	Judgement, raised from 48 after review. No source separates .yaml from .yml. .yaml is the official spelling for compose.yaml, Kubernetes manifests, OpenAPI documents, .pre-commit-config.yaml and pnpm-lock.yaml, and workflows may use either spelling, so an 18-point gap on no data over-ranked .yml.	scan_yaml
12	`.css`	CSS	**50.5**	45	80	20	Judgement, lowered from 64 after review. There is no CSS-only figure for Claude Code. It leans on the combined 28% HTML plus CSS and 12% UI cluster conversation shares (neither Claude Code specific) and on general-developer corpus counts, which cannot justify a high agent score. 745k repos contain CSS in githut (second only to JavaScript).	generic (scan_unknown)
13	`.xml`	XML	**50**	48	72	22	Held at 48 because reviewers disagreed: one proposed 40 (real XML is mainly pom.xml, Android files and .csproj, tied to Java, Kotlin and C#), another 62 (the same unverified sample is trusted fully for .md, .json and .py, so a half discount on a hypothesis is inconsistent). 106 of 790 sampled commits (rank 3) is a surprising figure resting on one unverified sample. Linguist's XML category covers 112 extensions and .ts, .tsx and .rs are also listed there; whether the paper counted that way is a hypothesis, not checked, though Linguist resolves ambiguous extensions by content heuristics. Treat as a flagged anomaly.	scan_xml
14	`.png`	PNG image	**49**	38	90	15	Judgement, held at 38 because reviewers disagreed (46 versus 25). Docs only show Read returns PNG as visual content. Plausible sources: matplotlib or plotly savefig charts, Playwright MCP screenshots (written into a .playwright-mcp/ directory), and README screenshots; agents otherwise rarely generate PNGs. Baseline is not measured.	generic (scan_unknown)
15	`.toml`	TOML	**47.6**	52	42	45	Judgement, held at 52 because reviewers disagreed (one proposed 58 on pyproject.toml and Cargo.toml, another 45 because no TOML count exists). pyproject.toml and Cargo.toml follow from Python and Rust being 21.0% and 7.2% of Claude Code AIDev repos. The Innovation Graph shows TOML as almost absent only because Linguist classes it as data (corpora:C21). Structural raised from 38 to 45 after review because every uv, poetry or hatch Python project and every Rust crate carries one.	generic (scan_unknown)
16	`.go`	Go	**46**	58	42	22	Lowered from 66 after review. Rank 3 AIDev repo language for Claude Code (9.8%), above its Innovation Graph rank of 21 but only slightly above the all-agent AIDev share (8.6%). Only 35 of 790 sampled commits (4.4%) touched Go, fewer than Rust's 57, so Go is scored below Rust. Judgement.	scan_go

#	Ext	Format	Score	Agent	Base	Struct	Basis	Pipeline today
17	`.java`	Java	**44.8**	32	88	12	Judgement, lowered from 40 after review so it sits below .cpp: Java is 3.0% of Claude Code AIDev repos (rank 7) against C++ at 3.6% (rank 6), and Java is not among languages reported in the 790-commit sample. Largest file count in Stack v2 Table 1 (154M files) drives the baseline.	scan_java
18	`.svg`	SVG	**41.2**	42	58	14	Judgement prior, held at 42 because reviewers disagreed (52 versus 28). No evidence in any stream. Mechanisms on both sides: scaffolders (create-next-app, create-vite) write SVG files and agents author icons and logos as text since they cannot produce rasters, but none of it is measured. Relevant to a scanner because SVG can carry script. Structural raised from 12 to 14 for the scaffolder case.	generic (scan_unknown)
19	`.lock`	Lockfile	**40.8**	40	36	50	Judgement, lowered from 55 after review. Anthropic's analytics exclude lock files (package-lock.json, yarn.lock, Cargo.lock) from attribution because they are tool-generated, which shows they are not authored, not that agents produce them more than other developers. BigCode maps .lock to JSON; Linguist lists Pipfile.lock, composer.lock, bun.lock, deno.lock, flake.lock, pixi.lock, yarn.lock, Cargo.lock, poetry.lock and uv.lock by name. package-lock.json is .json, not .lock.	generic (scan_unknown)
20	`.rs`	Rust	**40.8**	62	18	22	Rank 4 AIDev repo language for Claude Code (7.2%, ahead of JavaScript) and 57 sampled commits, more than Go's 35 in the same random sample. Rust is over-represented against the general baseline (2.22M Stack v2 files, a low confidence row). Evidence anthropic-primary:A28 (one compiler project) was removed as it is useless for ranking.	scan_rust
21	`.cpp`	C++	**39.4**	36	66	8	Rank 6 AIDev repo language for Claude Code (3.6%). 43.18M Stack v2 files and 267k repos give a high baseline.	scan_c_cpp
22	`.php`	PHP	**39**	34	68	8	Rank 8 AIDev repo language for Claude Code (2.5%). 46.03M Stack v2 files and 329k repos.	scan_php
23	`.c`	C	**37.8**	28	74	8	Judgement for the agent score: no C figure for Claude Code. Baseline is high (20.78M Stack v2 files, 286k repos).	scan_c_cpp
24	`.jpg`	JPEG image (also .jpeg)	**37.2**	22	82	8	Judgement. Evidence is only that Read returns JPEG visually. Agents rarely produce photos; baseline reflects ubiquity in public repositories, not a measurement.	generic (scan_unknown)
25	`.csv`	CSV	**36.4**	34	58	10	Judgement, raised from 25 after review. No evidence in any stream. CSV is the standard test fixture, export format and sample dataset in Python and data projects (Python is 21.0% of Claude Code AIDev repos). Also the usual carrier of spreadsheet formula injection, which the scanner lists as an unrouted gap. The family enum has no data category, so it stays config-data.	generic (scan_unknown)
26	`.h`	C/C++ header	**36.2**	26	72	8	Judgement. Ambiguous extension shared by C, C++ and Objective-C in Linguist; it follows C and C++ prevalence (C++ is 3.6% of Claude Code AIDev repos).	scan_c_cpp
27	`.sql`	SQL	**35.9**	35	52	14	Judgement, lowered from 46 after review. SQL was 6% of combined Claude.ai plus Claude Code queries (April 2025), a conversation share that is not Claude Code specific, and is used by 61.4% of professional developers. Migrations and schema files are plausible in agent projects but not evidenced. .sql is shared by five Linguist languages.	scan_sql
28	`.cs`	C#	**35.2**	28	64	10	Claude Code under-indexes on C#: 1.7% of its AIDev repos against 8.0% for Copilot. General baseline is large (51.23M Stack v2 files).	scan_csharp
29	`.mjs`	JavaScript ES module	**35**	44	30	20	Judgement, raised from 38 after review. Scaffolders write config files as .mjs without being asked (create-next-app writes eslint.config.mjs and postcss.config.mjs, Astro and Vite templates write astro.config.mjs). Only the Linguist extension mapping is evidenced; the scaffolder claim is a mechanism, not a measurement.	scan_javascript
30	`.jsx`	JavaScript JSX	**34.8**	42	38	12	Judgement. No source gives a .jsx count. It is listed as a JavaScript extension in Linguist. Claude Code's lean to TypeScript suggests it writes fewer .jsx than .tsx. Baseline lowered from 42 to 38 after review so it sits below .tsx, consistent with TypeScript pushers growing 2.26x.	scan_javascript

#	Ext	Format	Score	Agent	Base	Struct	Basis	Pipeline today
31	`.ipynb`	Jupyter Notebook	**33.8**	36	46	10	Claude Code has a dedicated NotebookEdit tool and special Read handling for notebooks. 889,811 pushers in 2026 Q1 (rank 11). Python is used for data analysis in the Anthropic sample. How often agents create notebooks is not measured.	generic (scan_unknown)
32	`.pdf`	PDF	**33**	34	48	8	Judgement, raised from 20 after review. Read handles PDFs in 20-page ranges, which says nothing about how many land in repositories, but PDF-generation libraries (ReportLab, WeasyPrint, headless Chrome print-to-PDF) write them by script, and this repository itself ships ReportLab builders for its guides. Unmeasured. A PDF is also an active-content container (/OpenAction, /Launch, /EmbeddedFile), so scanner priority exceeds prevalence.	scan_pdf
33	`.env.example`	Environment template (name pattern .env*)	**31.4**	30	38	25	Prior only, lowered from 45 after review. This is a file name pattern, not an extension (the true extension is .example; .env.sample, .env.template, .env.local, .env.production and .env.development behave the same), so it also appears in special_names as .env*. The row is kept because candidates may not be dropped. claude-code-artifacts:A36 was removed: it concerns .env and .env.local in .worktreeinclude and never mentions a template. Scanner relevance is high, as the template is where placeholder secrets live.	generic (scan_unknown)
34	`.conf`	Config file (nginx, redis, supervisord)	**30**	24	52	12	Added after review. Judgement, no evidence in any stream. nginx.conf, redis.conf, supervisord.conf and systemd drop-ins are standard in deployment work for self-hosted proxies, which the Vercel and Railway picks do not cover.	generic (scan_unknown)
35	`.rb`	Ruby	**28.4**	20	56	8	Judgement. No Claude Code Ruby figure surfaced. Baseline from 365k githut repos and 17.79M Stack v2 files (low confidence row).	scan_ruby
36	`.kt`	Kotlin	**26.8**	28	36	10	Judgement. No Claude Code Kotlin figure was found. 433,614 pushers in 2026 Q1. Android and Gradle projects explain most use.	scan_kotlin
37	`.scss`	SCSS	**26.8**	26	42	6	Judgement. 570,968 pushers in 2026 Q1 (rank 14) is the only evidence, and it is general GitHub. No indication that agents favour it.	generic (scan_unknown)
38	`.tf`	Terraform (HCL)	**26.6**	32	30	8	Agents modify Terraform module skeleton files more often than humans (low confidence, all-agent study). HCL ranks ninth in Octoverse per a low confidence secondary source. Judgement for the numbers.	scan_terraform
39	`.ico`	Icon file	**25.6**	24	40	8	Added after review. Judgement. create-next-app writes src/app/favicon.ico and Vite templates write favicon files; with .png and .svg these are the bulk of binary files in a Claude Code front end.	generic (scan_unknown)
40	`.cfg`	Config (INI-style)	**24**	20	40	10	Judgement. setup.cfg and tox.ini-style files in Python projects. .cfg is shared by HAProxy and INI in Linguist.	generic (scan_unknown)

What this means for the pipeline

Extensions in the top 40 that lack a dedicated scanner, in ranking order. These are candidates for new per-type scanners, not a statement that they are unscanned: layers 1, 4 and 6 and the universal patterns run on every file.

Rank	Ext	Format	Today	Basis for the score (shortened; full text in the top-40 table)
1	`.md`	Markdown	credential grep only	Rank 1 by commits touching a Markdown file in the unverified 790-commit sample (254 of 790; single paper, fetched=false), with documentation in 296 commits. Markdown is one of four example values of the OpenTe…
2	`.json`	JSON	credential grep only	105 of 790 sampled Claude commits touched JSON (rank 4, unverified single paper; agent-pr-studies:H1 is low confidence). Several documented Claude Code files are JSON (.claude/settings.json, .mcp.json, hooks.j…
7	`.txt`	Plain text	credential grep only	Judgement, raised from 45 after review. No per-extension count was found. requirements.txt (Python is 21.0% of Claude Code AIDev repos), CMakeLists.txt (a Linguist file name), robots.txt, LICENSE.txt, prompt t…
12	`.css`	CSS	generic (scan_unknown)	Judgement, lowered from 64 after review. There is no CSS-only figure for Claude Code. It leans on the combined 28% HTML plus CSS and 12% UI cluster conversation shares (neither Claude Code specific) and on gen…
14	`.png`	PNG image	generic (scan_unknown)	Judgement, held at 38 because reviewers disagreed (46 versus 25). Docs only show Read returns PNG as visual content. Plausible sources: matplotlib or plotly savefig charts, Playwright MCP screenshots (written…
15	`.toml`	TOML	generic (scan_unknown)	Judgement, held at 52 because reviewers disagreed (one proposed 58 on pyproject.toml and Cargo.toml, another 45 because no TOML count exists). pyproject.toml and Cargo.toml follow from Python and Rust being 21…
18	`.svg`	SVG	generic (scan_unknown)	Judgement prior, held at 42 because reviewers disagreed (52 versus 28). No evidence in any stream. Mechanisms on both sides: scaffolders (create-next-app, create-vite) write SVG files and agents author icons a…
19	`.lock`	Lockfile	generic (scan_unknown)	Judgement, lowered from 55 after review. Anthropic's analytics exclude lock files (package-lock.json, yarn.lock, Cargo.lock) from attribution because they are tool-generated, which shows they are not authored,…
24	`.jpg`	JPEG image (also .jpeg)	generic (scan_unknown)	Judgement. Evidence is only that Read returns JPEG visually. Agents rarely produce photos; baseline reflects ubiquity in public repositories, not a measurement.
25	`.csv`	CSV	generic (scan_unknown)	Judgement, raised from 25 after review. No evidence in any stream. CSV is the standard test fixture, export format and sample dataset in Python and data projects (Python is 21.0% of Claude Code AIDev repos). A…
31	`.ipynb`	Jupyter Notebook	generic (scan_unknown)	Claude Code has a dedicated NotebookEdit tool and special Read handling for notebooks. 889,811 pushers in 2026 Q1 (rank 11). Python is used for data analysis in the Anthropic sample. How often agents create no…
33	`.env.example`	Environment template (name pattern .env*)	generic (scan_unknown)	Prior only, lowered from 45 after review. This is a file name pattern, not an extension (the true extension is .example; .env.sample, .env.template, .env.local, .env.production and .env.development behave the…
34	`.conf`	Config file (nginx, redis, supervisord)	generic (scan_unknown)	Added after review. Judgement, no evidence in any stream. nginx.conf, redis.conf, supervisord.conf and systemd drop-ins are standard in deployment work for self-hosted proxies, which the Vercel and Railway pic…
37	`.scss`	SCSS	generic (scan_unknown)	Judgement. 570,968 pushers in 2026 Q1 (rank 14) is the only evidence, and it is general GitHub. No indication that agents favour it.
39	`.ico`	Icon file	generic (scan_unknown)	Added after review. Judgement. create-next-app writes src/app/favicon.ico and Vite templates write favicon files; with .png and .svg these are the bulk of binary files in a Claude Code front end.
40	`.cfg`	Config (INI-style)	generic (scan_unknown)	Judgement. setup.cfg and tox.ini-style files in Python projects. .cfg is shared by HAProxy and INI in Linguist.

Important files that have no extension

They cannot appear in an extension ranking but belong in any support list. The pipeline routes some of them by name (Dockerfile*, Makefile*, package.json, requirements*.txt, setup.py, gradle files).

Name	Why it matters
`Dockerfile`	No extension, so it cannot be ranked as one. Scores (judgement, from review): agent 58 / baseline 76 / structural 38. 1.90M files in Stack v2 and 1,732,771 GitHub pushers in 2026 Q1 (corpora:C15, C18); the Claude Code dev container reference includes one (claude-code-artifacts:A40).
`Makefile`	No extension. Scores (judgement, from review): agent 36 / baseline 60 / structural 20. 824,208 pushers in 2026 Q1 (corpora:C19); Linguist also lists GNUmakefile and BSDmakefile (corpora:C38). The .mk extension covers only includes.
`.gitignore`	Present in nearly every repository. Scores (judgement, from review): agent 90 / baseline 92 / structural 90. Claude Code gitignores settings.local.json and CLAUDE.local.md (claude-code-artifacts:A10, A14) and docs tell users to add the latter by hand. No count in any stream.
`.env`	Local secrets file; the pattern .env* is scored in its own entry below. Docs name .env and .env.local as the gitignored files that .worktreeinclude copies into worktrees (claude-code-artifacts:A36). High scanner relevance, because it appears in a fetched repo only when it was committed by mistake.
`.env*`	Name pattern covering .env, .env.example, .env.sample, .env.template, .env.local, .env.production and .env.development, which cannot be matched as an extension. Scores (judgement): agent 30 / baseline 38 / structural 25, the same as the .env.example candidate row. Scanner-priority credential carrier; usually gitignored.
`.npmrc`	Credential-carrying dotfile (registry auth tokens). Scores (judgement, from review): agent 14 / baseline 20 / structural 8. Rare but scanner priority.
`.pypirc`	Credential-carrying dotfile (PyPI upload credentials). Agent score 3 (judgement, from review); baseline and structural not scored. Rare but scanner priority.
`.netrc`	Credential-carrying dotfile. Agent score 2 (judgement, from review); baseline and structural not scored. Rare but scanner priority.
`.git-credentials`	Credential-carrying dotfile. Agent score 2 (judgement, from review); baseline and structural not scored. Rare but scanner priority.
`LICENSE`	Linguist lists LICENSE and COPYING as plain-text names (corpora:C39). Not scored; not measured for agent repositories; ScanCode layer reads it for licence detection.
`.worktreeinclude`	Claude Code-specific dotfile in the project root listing gitignored files to copy into new worktrees (claude-code-artifacts:A36). Not scored.
`.dockerignore`	Judgement. Usual companion of Dockerfile; no evidence in any stream. Review gave agent 38; baseline 45 and structural 15 are my judgement.
`.gitattributes`	Judgement. Common in public repositories; no evidence in any stream. Not scored.
`Jenkinsfile`	Linguist lists it as a Groovy file name (corpora:C38). Judgement on prevalence in agent output. Not scored.
`Gemfile`	Linguist lists Gemfile, Rakefile and Podfile as Ruby names (corpora:C36). Ruby has no Claude Code figure. Not scored.
`Procfile`	Judgement. Small deployment file for Railway-style hosts; Railway was the pick for 82% of Python backend deployments in one study (industry:A5). Review gave agent 8; baseline 8 and structural 3 are my judgement.
`package.json`	Routed by basename; present in nearly every JS/TS project (TypeScript is 21.4% and JavaScript 6.2% of Claude Code AIDev repos: agent-pr-studies:A1, A5). Scores (judgement, from review): agent 84 / baseline 88 / structural 80. Runs install hooks, so it needs its own rules.
`requirements.txt`	Routed by basename (requirements*.txt, constraints*.txt); present in most Python projects (Python is 21.0% of Claude Code AIDev repos: agent-pr-studies:A2). Scores (judgement, from review): agent 58 / baseline 60 / structural 40. Also counted under .txt.
`pyproject.toml`	Present in uv, poetry and hatch Python projects (agent-pr-studies:A2). Scores (judgement, from review): agent 56 / baseline 44 / structural 45. Also counted under .toml.

Name	Why it matters
`docker-compose.yml / compose.yaml`	Deployment files. Scores (judgement, from review): agent 40 / baseline 40 / structural 20. Also counted under .yml and .yaml.
`go.mod`	Present in every Go module (Go is 9.8% of Claude Code AIDev repos: agent-pr-studies:A3). Scores (judgement, from review): agent 50 / baseline 28 / structural 25. Cannot execute anything.
`Cargo.toml`	Present in every Rust crate (Rust is 7.2% of Claude Code AIDev repos: agent-pr-studies:A4). Scores (judgement, from review): agent 48 / baseline 16 / structural 25.
`.mcp.json`	Team-shared MCP server config at project root, committed to version control (claude-code-artifacts:A17). It can launch stdio server processes when a project is opened, so it needs stricter rules than generic .json. Scores (judgement, from review): agent 26 / baseline 3 / structural 80.
`.claude/settings.json`	Project settings holding hooks, env, permissions and apiKeyHelper (claude-code-artifacts:A13); these can start processes. Scores (judgement, from review): agent 40 / baseline 3 / structural 85. The sibling settings.local.json is gitignored (claude-code-artifacts:A14) and scored low: agent 5 / baseline 2 / structural 5.
`.claude-plugin/plugin.json and hooks/hooks.json`	Plugin manifest and plugin hook configuration (claude-code-artifacts:A28, A29). Scores (judgement, from review): agent 8 / baseline 2 / structural 60.
`.claude/hooks/*`	Hook scripts (.sh, .py, .ps1) documented in claude-code-artifacts:A24, A25, A26. They ride on the .sh, .py and .ps1 rows; the review asked for a path-based boost instead of a separate entry. Not scored separately.
`CLAUDE.md`	The best-attested Claude Code file name: 922 to 1,640 files in AIDev-scale studies (agent-pr-studies:I1, I2, I3, I4) and documented in claude-code-artifacts:A8, A9. It feeds an LLM's instructions, so it is a prompt-injection surface. Scores (judgement, from review): agent 72 / baseline 4 / structural 95.
`AGENTS.md`	Read in place of CLAUDE.md (claude-code-artifacts:A11); counted together with CLAUDE.md in a census (agent-pr-studies:I5). Prompt-injection surface. Scores (judgement, from review): agent 30 / baseline 6 / structural 70.
`SKILL.md`	Required file of every skill (claude-code-artifacts:A7, A18). Prompt-injection surface. Scores (judgement, from review): agent 24 / baseline 2 / structural 60.
`.claude/commands/*.md`	Single-file slash commands (claude-code-artifacts:A20). Scores (judgement, from review): agent 24 / baseline 2 / structural 55.
`.claude/agents/*.md`	Subagent definitions (claude-code-artifacts:A21). Scores (judgement, from review): agent 18 / baseline 2 / structural 50.
`gradle-wrapper.jar and gradlew`	Committed to nearly every Gradle project; the wrapper runs before any code the repository declares and the scanner has a dedicated handler. Agent score 20 (judgement, from review); see also the .jar row.
`.playwright-mcp/`	Name pattern: a directory the Playwright MCP writes into the working tree (PNG screenshots, YAML snapshots, logs), often committed by accident; the .yml and .log files inside are generated. Judgement from review; not scored.
`Caddyfile and nginx.conf`	Self-hosted proxy configs with no extension or a .conf one. Agent score 10 (judgement, from review); see also the .conf row.

The evidence behind the scores

45 of the findings cited by the top 20, grouped by source stream (read pages first), of 188 gathered. All 188 are in the data file with their quotes. Findings about Claude Code itself that were read on the page come first. "read" means the page was opened; "snippet" means the figure was seen only in a search result and could not be checked.

Id	Subject	Figure	It counts	CC	Read	Source
anthropic-primary:A13	Files Anthropic excludes from Claude Code contribution attribution: l…	list of excluded file classes, no numbers	documentation of the analytics dashboard's PR attribution rules, counts nothing. Shows which generated file classes Anthropic itself treats as non-authored	yes	read	Track team usage with analytics (Claude Code docs) (code.claude.com)
anthropic-primary:A8	OpenTelemetry 'language' attribute on claude_code.code_edit_tool.deci…	4 example values only ('such as'), no exhaustive list and no extension-to-langu…	documentation of an attribute on a customer-side OpenTelemetry counter (metric, not a log event) that increments when a user accepts or rejects an Edit, Write or NotebookEdit call. This is telemetry exported to the customer's own…	yes	read	Monitoring (Claude Code docs, OpenTelemetry) (code.claude.com)
anthropic-primary:A1	JavaScript + TypeScript (language group)	**31%**	share of queries in a sample of 500,000 coding-related interactions, Claude.ai (Free/Pro) and Claude Code sessions weighted equally, 6-13 April 2025. Combined figure, no Claude Code only split	no	read	Anthropic Economic Index: AI's impact on software deve… (anthropic.com)
anthropic-primary:A2	HTML + CSS (language group)	**28%**	share of queries, same 500,000-interaction sample (Claude.ai + Claude Code, 6-13 April 2025). Anthropic's footnote says the Claude.ai HTML count is probably slightly inflated because Artifacts use HTML	no	read	Anthropic Economic Index: AI's impact on software deve… (anthropic.com)
anthropic-primary:A3	Python	**14%**	share of queries, same combined Claude.ai + Claude Code sample (April 2025). Anthropic notes Python serves both back-end work and data analysis	no	read	Anthropic Economic Index: AI's impact on software deve… (anthropic.com)
anthropic-primary:A5	JavaScript and HTML (web-development languages)	rank 1 (most common languages; no percentage given for this sentence)	qualitative ranking over the same 500,000 coding-related interactions (Claude.ai + Claude Code, April 2025)	no	read	Anthropic Economic Index: AI's impact on software deve… (anthropic.com)
anthropic-primary:A7	Task clusters 'UI/UX Component Development' and 'Web & Mobile App Dev…	**12% and 8%**	share of conversations falling in each cluster, same combined Claude.ai + Claude Code sample (April 2025)	no	read	Anthropic Economic Index: AI's impact on software deve… (anthropic.com)
agent-pr-studies:A1	TypeScript (repository language)	**21.4% (2,977 of 13,934 repos), rank 1**	distinct AIDev-pop repositories (>100 stars) in which Claude Code opened at least one PR, grouped by GitHub primary repository language (v5). Repo language, not file extension.	yes	read	AI_Teammates_in_SE3 analysis/language_usage.ipynb (out… (github.com)

Id	Subject	Figure	It counts	CC	Read	Source
agent-pr-studies:A2	Python (repository language)	**21.0% (2,929 of 13,934 repos), rank 2**	distinct AIDev-pop repositories in which Claude Code opened at least one PR, by GitHub primary repository language (v5)	yes	read	AI_Teammates_in_SE3 analysis/language_usage.ipynb (out... (github.com)
agent-pr-studies:A3	Go (repository language)	**9.8% (1,368 repos), rank 3**	distinct AIDev-pop repositories with at least one Claude Code PR, by repository language (v5)	yes	read	AI_Teammates_in_SE3 analysis/language_usage.ipynb (out... (github.com)
agent-pr-studies:A4	Rust (repository language)	7.2% (999 repos), rank 4 (ahead of JavaScript for Claude Code)	distinct AIDev-pop repositories with at least one Claude Code PR, by repository language (v5)	yes	read	AI_Teammates_in_SE3 analysis/language_usage.ipynb (out... (github.com)
agent-pr-studies:A5	JavaScript (repository language)	**6.2% (865 repos), rank 5**	distinct AIDev-pop repositories with at least one Claude Code PR, by repository language (v5)	yes	read	AI_Teammates_in_SE3 analysis/language_usage.ipynb (out... (github.com)
agent-pr-studies:A7	Java (repository language)	**3.0% (414 repos), rank 7**	distinct AIDev-pop repositories with at least one Claude Code PR, by repository language (v5)	yes	read	AI_Teammates_in_SE3 analysis/language_usage.ipynb (out... (github.com)
agent-pr-studies:I1	CLAUDE.md	922 CLAUDE.md files (of 2,303 context files in 1,925 repos; 694 AGENTS.md, 687...	agent context files found in AIDev repositories with at least 5 stars, from Chatlatanagulchai et al.	yes	snippet	Agent READMEs: An Empirical Study of Context Files for... (arxiv.org)
agent-pr-studies:I2	CLAUDE.md	1,640 files (34.4% of 4,768 context files); in 1,187 repos (45.9%)	context files across 2,853 repositories; CLAUDE.md is the most common type. A different search result gave 1,658 (34.2%), so versions of the paper may differ.	yes	snippet	Configuring Agentic AI Coding Tools: An Exploratory St... (arxiv.org)
agent-pr-studies:H1	Markdown, TypeScript, XML, JSON, Python (order as given)	top five by changed-file count in a sample of 790 Claude Code commits	changed files by language category in 790 Claude Code commits (Robbes et al.). This claim came from one search summary only. A second, more specific search could not confirm it, so treat it as unverified.	yes	snippet	Agentic Much? Adoption of Coding Agents on GitHub (arX... (arxiv.org)
agent-pr-studies:J1	code vs documentation vs config (.json .yaml .toml) vs build (.tf .sh...	63.2% of 29,669 AI PRs change code without any documentation update	AIDev PRs (2,585 repositories, all agents), with changed files sorted into code, configuration and build categories. The extension groups are the paper's classifier, not counts. Another summary described labels as code, documenta...	no	snippet	Documentation Drift in AI-Generated Pull Requests (arX... (arxiv.org)
industry:A4	GitHub Actions workflows (.yml / .yaml), Stripe, shadcn/ui	GitHub Actions 94%; Stripe 91%; shadcn/ui 90%	share of primary picks in their category among parsed responses; the tools Claude Code picks most decisively	yes	snippet	What Claude Code Actually Chooses (Amplifying) (amplifying.ai)
industry:C1	TypeScript (languages of Claude Code signed commits, all-time homepag...	**53.5% (22.2M commits), rank 1**	public GitHub commits signed by Claude Code (author field or trailer), tracked since Feb 2025; undated cached homepage snapshot. The top three shares sum to 100.0%, so the denominator may be only the top three languages	yes	snippet	Claude's Code (claudescode.dev dashboard) (claudescode.dev)

Id	Subject	Figure	It counts	CC	Read	Source
industry:C2	Python (languages of Claude Code signed commits, all-time homepage sn…	**24.3% (10M commits), rank 2**	public GitHub commits signed by Claude Code; same undated homepage snapshot as C1	yes	snippet	Claude's Code (claudescode.dev dashboard) (claudescode.dev)
industry:C3	HTML (languages of Claude Code signed commits, all-time homepage snap…	**22.2% (9.21M commits), rank 3**	public GitHub commits signed by Claude Code; same undated homepage snapshot as C1. HTML replaces JavaScript at rank 3 compared with the March snapshot (C5-C7)	yes	snippet	Claude's Code (claudescode.dev dashboard) (claudescode.dev)
industry:C4	language ranking, 90-day window (claudescode.dev)	Unknown 34.3% (18.8M commits); TypeScript 24.1% (13.2M); Python 11.3% (6.17M)	public GitHub commits signed by Claude Code in the trailing 90-day window. A third of commits have no detected language, and this window's implied total is larger than the all-time snapshot's, so the two snapshots were taken at d…	yes	snippet	Interesting Observations - Claude's Code (90-day windo… (claudescode.dev)
industry:C5	TypeScript (languages of Claude Code signed commits, March 2026 snaps…	**34.8% (7.25M commits), rank 1**	public GitHub commits signed by Claude Code, out of about 20.8M total at that snapshot (the share is of all commits, unknown language included); reported by WinBuzzer around 26 Mar 2026 citing claudescode.dev	yes	snippet	90% of Claude Code Output Lands in Low-Star GitHub Rep… (winbuzzer.com)
industry:C6	Python (languages of Claude Code signed commits, March 2026 snapshot)	**18.9% (3.92M commits), rank 2**	public GitHub commits signed by Claude Code, share of about 20.8M total at that snapshot; WinBuzzer citing claudescode.dev	yes	snippet	90% of Claude Code Output Lands in Low-Star GitHub Rep… (winbuzzer.com)
industry:C7	JavaScript (languages of Claude Code signed commits, March 2026 snaps…	**10.2% (2.13M commits), rank 3**	public GitHub commits signed by Claude Code, share of about 20.8M total at that snapshot; WinBuzzer citing claudescode.dev	yes	snippet	90% of Claude Code Output Lands in Low-Star GitHub Rep… (winbuzzer.com)
industry:R1	Markdown (.md) in changed files	254 commits (rank 1 of the listed languages)	commits, within a randomly sampled 790 of 90,321 Claude-authored commits (identified by the Co-authored-by trailer), with a changed file in that language; raw counts, not percentages	yes	snippet	Agentic Much? Adoption of Coding Agents on GitHub (Rob… (arxiv.org)
industry:R2	TypeScript in changed files	**213 commits (rank 2)**	commits, in the same 790-commit sample of Claude-authored commits, with a changed file in that language; raw counts	yes	snippet	Agentic Much? Adoption of Coding Agents on GitHub (Rob… (arxiv.org)
industry:R3	XML in changed files	**106 commits (rank 3)**	commits, in the same 790-commit sample of Claude-authored commits, with a changed file in that language; raw counts	yes	snippet	Agentic Much? Adoption of Coding Agents on GitHub (Rob… (arxiv.org)
industry:R4	JSON in changed files	**105 commits (rank 4)**	commits, in the same 790-commit sample of Claude-authored commits, with a changed file in that language; raw counts	yes	snippet	Agentic Much? Adoption of Coding Agents on GitHub (Rob… (arxiv.org)

Id	Subject	Figure	It counts	CC	Read	Source
corpora:C22	JavaScript, CSS, HTML, Shell, Python, Ruby, Java, PHP, C, C++ (reposi…	JavaScript 1006022; CSS 745573; HTML 663315; Shell 593461; Python 492715; Ruby…	number of rows in bigquery-public-data:github_repos.languages per language name, i.e. repositories that contain the language (any language in the repo, not only the primary one). Snapshot date not stated in the README.	no	read	githut README, GitHub Language Statistics (madnight/gi… (raw.githubusercontent.com)
corpora:C35	The Stack v1.1 language-to-extension mapping	370 languages mapped to extensions, e.g. Python [.py .bzl .gyp .lmi .pyde .pyp…	entries in the language_selection mapping BigCode used to build The Stack v1.1. It is a mapping, not a count. It differs from Linguist: .tsx belongs to TypeScript and .lock to JSON, and it has no Terraform entry (HCL covers .tf).	no	read	bigcode-project/bigcode-dataset, language_selection/pr… (raw.githubusercontent.com)
corpora:C38	Linguist extensions: build, Windows and infrastructure languages	Makefile [.mak .d .make .makefile .mk .mkfile; names Makefile GNUmakefile BSDma…	extension and file-name lists in Linguist's languages.yml for build and infrastructure languages, including ones just outside the top 25 by pushers. GitHub's popular.yml also lists PowerShell and Shell among its 'popular' languag…	no	read	github-linguist/linguist lib/linguist/languages.yml (raw.githubusercontent.com)
corpora:C39	Linguist extensions: data, config and prose types (JSON, YAML, Markdo…	JSON [.json plus 21 others incl. .geojson .jsonl .har .sarif .webmanifest .tfst…	extension and file-name lists in Linguist's languages.yml (type data or prose). XML alone has 112 extensions. Linguist classes these as data or prose, which is why they are missing from repository language statistics (see C21).	no	read	github-linguist/linguist lib/linguist/languages.yml (raw.githubusercontent.com)
corpora:C40	Extensions that Linguist assigns to more than one language	.h [C, C++, Objective-C]; .ts [TypeScript, XML]; .tsx [TSX, XML]; .rs [RenderSc…	extensions claimed by more than one language in languages.yml, computed by me. languages.yml has 836 entries, 789 with extensions, 1,749 extension listings and 1,489 distinct extension strings. Linguist resolves the ambiguity by…	no	read	github-linguist/linguist lib/linguist/languages.yml (raw.githubusercontent.com)
corpora:C16	HTML, JavaScript, CSS, Python, TypeScript, Shell, Dockerfile, Java, C…	HTML 6,700,107; JavaScript 5,662,372; CSS 5,363,826; Python 4,109,495; TypeScri…	DERIVED by me: sum over the 184 economies reporting in 2026 Q1 of the published per-economy num_pushers (unique developers with at least one git push in the quarter to a repository containing the language). A developer pushing to…	no	read	GitHub Innovation Graph, data/languages.csv (and docs/… (raw.githubusercontent.com)
corpora:C17	Shell (.sh/.bash)	2,319,832 pushers in 2026 Q1 (rank 6); 1,924,701 in 2025 Q4; 1,353,992 in 2024…	DERIVED by me: sum over economies of published num_pushers for repositories containing Shell, GitHub Innovation Graph. Lower bound because small economies are suppressed.	no	read	GitHub Innovation Graph, data/languages.csv (raw.githubusercontent.com)
corpora:C20	TypeScript vs Python vs JavaScript trend	TypeScript pushers 1,062,491 (2024 Q1) -> 1,232,206 (2024 Q4) -> 2,175,422 (202…	DERIVED by me: sum over economies of published num_pushers per quarter, GitHub Innovation Graph. TypeScript grew 2.26x between 2024 Q4 and 2026 Q1, Python 1.79x, JavaScript 1.61x.	no	read	GitHub Innovation Graph, data/languages.csv (raw.githubusercontent.com)
claude-code-artifacts:A1	image files: .png .jpg/.jpeg .gif .webp (Read tool)	PNG, JPEG, GIF and WebP returned as visual content; Read refuses an image file…	files the Read tool treats specially (documented behaviour, not a usage frequency)	yes	read	Tools reference (Read tool behavior) (code.claude.com)

Id	Subject	Figure	It counts	CC	Read	Source
claude-code-artifacts:A11	AGENTS.md	read in place of CLAUDE.md; location project root, .claude/ or any directory	file Claude Code reads (documented, structural)	yes	read	How Claude remembers your project (code.claude.com)
claude-code-artifacts:A12	.claude/rules/*.md	topic-scoped instructions, optional paths frontmatter, discovered recursively	files Claude Code reads (documented, structural)	yes	read	How Claude remembers your project (code.claude.com)
claude-code-artifacts:A13	.claude/settings.json and ~/.claude/settings.json	JSON settings: permissions, hooks, env vars, model defaults; strict JSON, no co…	files Claude Code reads and writes (documented, structural)	yes	read	Settings files and precedence (code.claude.com)
claude-code-artifacts:A14	.claude/settings.local.json	personal per-project overrides; Claude Code writes it when you choose 'Yes, and…	file Claude Code creates (documented, structural)	yes	read	Explore the .claude directory (code.claude.com)
claude-code-artifacts:A17	.mcp.json	team-shared MCP servers at project root, committed to version control	file Claude Code reads (documented, structural)	yes	read	Connect Claude Code to tools via MCP (code.claude.com)
claude-code-artifacts:A19	skill supporting files: reference.md, examples.md, scripts/helper.py…	skills may bundle reference docs and scripts in any language; the doc layout sh…	files shipped inside skill directories (documented example layout, not a frequency)	yes	read	Extend Claude with skills (code.claude.com)
claude-code-artifacts:A21	.claude/agents/*.md (subagents)	Markdown with YAML frontmatter, project and user scope	files Claude Code reads (documented, structural)	yes	read	Create custom subagents (code.claude.com)

Looked for and not found (first four per stream)

anthropic-primary: Any Anthropic-published breakdown of Claude Code usage by programming language: none found. The only language shares Anthropic ha… · Any Anthropic-published breakdown by file extension or file name (.py, .ts, .json, .md, Dockerfile, package.json etc.): none foun… · Language or file-type shares in the Economic Index editions of Feb 2025, Mar 2025 (Claude 3.7 Sonnet), Sep 2025, Jan 2026, Mar 20… · Language or file-type shares in the Dec 2025 'How AI is transforming work at Anthropic' and Jun 2026 'Agentic coding and persiste…

agent-pr-studies: Any per-extension or per-file-type count for Claude Code pull requests or commits that I opened myself. The AIDev pr_commit_detai… · The SE3 paper (arXiv 2507.15003) per-agent, per-language table for Claude Code. I could only see the all-agents language figure,… · Any file-type or language breakdown in Watanabe et al. (arXiv 2509.14745), and a GitHub replication package for it. · Confirmation of the 790 Claude Code commits with Markdown, TypeScript, XML, JSON, Python (arXiv 2601.18341); the first search gav…

industry: Any primary-source page opened: WebFetch failed with ENOTFOUND on every host, and curl through the proxy was refused (403 on CONN… · Amplifying: an overall JavaScript/TypeScript vs Python share of Claude Code's default project language or stack picks (none seen;… · SemiAnalysis: the original newsletter text, its methodology detail, and any per-language breakdown of the 4% share. · Amplifying Coding Agents Index: the per-language (segments / languages page) figures for Claude Code.

corpora: Per-language file counts from the Hugging Face language stats table of bigcode/the-stack-v2 or bigcode/the-stack: huggingface.co… · StarCoder2 Table 1 rows for Shell with usable values (the search summary's v1 Shell numbers were internally inconsistent), SQL, S… · Any published per-extension file count for JSON, YAML (.yml/.yaml), TOML, XML, .txt, .lock or .sh from The Stack, GitHub BigQuery… · A ranked list of file extensions by file count for the BigQuery github_repos dataset (searches found only the .go and .py counts)

claude-code-artifacts: Any statistic in the official Claude Code documentation on how often each file extension or language appears in Claude Code proje… · A complete list of extensions the Read tool refuses as binary (the tools reference gives four examples after 'such as' and no ful… · A fixed list of allowed file extensions for skill supporting files (the skills page shows .md and .py in an example layout and sa… · A statement in the NotebookEdit section that names the .ipynb extension (it says 'Jupyter notebook'; the extension appears only i…

Limits of this estimate

• No public per-extension Claude Code telemetry exists. Anthropic has published no breakdown by file extension or file name (anthropic-primary not_found). The OpenTelemetry 'language' attribute is customer-side, gives four example values and no counts (anthropic-primary:A8, A10), and the Analytics API has no language field (anthropic-primary:A12). Every extension score is therefore an inference from language data, commit samples and documentation.

• Language is not extension. The AIDev numbers (agent-pr-studies:A1-A10) are shares of distinct repositories by GitHub primary language over repositories with more than 100 stars. A TypeScript repository also holds .md, .json, .yml, .css and .lock files, so those percentages do not transfer to file counts. The Innovation Graph rows (corpora:C16-C21) are developer counts, not file counts, and show Markdown, YAML, JSON and XML near zero only because Linguist classes them as data or prose (corpora:C21).

• The only language shares Anthropic has published (JS/TS 31%, HTML/CSS 28%, Python 14%, SQL 6%) are from one week in April 2025, blend Claude.ai and Claude Code 50/50, and are about 18 months old. Anthropic itself says the HTML share is probably slightly inflated by Artifacts (anthropic-primary:A1-A6). They are conversation shares, not Claude Code specific and not file shares, so they support the .py, .js, .html, .css and .sql rows only weakly. The two Claude Code-only Anthropic studies report task types and no languages (anthropic-primary:A14-A19).

• The industry stream returned no fetched page: all of its findings are search-result text (fetched=false, no quotes), and most agent-pr-studies arXiv findings are the same. The 790-commit Markdown/TypeScript/XML/JSON/Python counts (industry:R1-R8, agent-pr-studies:H1) are commits touching a file in that language, come from a single paper and the same search summaries, so their agreement is not independent confirmation. A later query could not reproduce them. The Markdown rank 1 and XML rank 3 scores rest on it.

• The 790-commit sample is not treated uniformly across rows: it is used at face value for .md, .json and .ts, but the .xml count is discounted on an unchecked hypothesis, and .py was lowered after review because its file-level rank (5) is below the language-level ranking. Reviewers disagreed on .xml (40 versus 62) and the score was held at 48.

• The claudescode.dev snapshots are mutually inconsistent: the undated 'all-time' top three sums to exactly 100% (so it is a top-three-only share) and ranks HTML third, the March 2026 snapshot ranks JavaScript third of about 20.8M commits, and the 90-day window has 34.3% of commits with no detected language (industry:C1-C8). They mix methodology and dates and cannot be combined into one ranking.

• Sampling bias. AIDev-pop covers repositories above 100 stars, while about 90% of Claude Code commits land in repositories with fewer than two stars (industry:C9, low confidence). Trailer-based detection also misses private repositories and users who disable attribution (industry:S1, S2). AIDev v3 and v5 differ a lot (459 PRs versus 13,934 repositories for Claude Code). A scanned enterprise repository may look different from either.

• The corpora stream gives no Claude Code data at all. Stack v2 Table 1 covers only 32 programming and markup languages and has no rows for JSON, YAML, TOML, XML, .txt, .lock, SVG or any binary type. All Stack v2, github-code, Octoverse and Software Heritage rows are search summaries (fetched=false); the TypeScript, Ruby and Rust rows are low confidence and the Shell row was discarded as inconsistent. Baseline scores for config, data, image and office extensions are judgement, not measurement.

• The claude-code-artifacts stream is documentation, not usage: it names files and extensions Claude Code reads or writes, with no frequency or rank. Several of them are gitignored or live outside the repository (settings.local.json, CLAUDE.local.md, ~/.claude.json, keybindings.json: claude-code-artifacts:A10, A14, A15, A34), so a fetched repository will not carry them. Structural scores are therefore judgement about what is typically committed.

- Several extension ranks rest on no evidence: .dart, .svelte, .graphql, .csv, .svg, .docx, .pptx, .r, .lua, .scala, .mdx, .prisma, .proto, .ex and .env.example have empty or minimal evidence_ids and their scores are priors. Every row added after review is likewise a judgement prior unless its rationale cites an id. Scores differing by less than about 10 points should not be read as a ranking.
- Ambiguous or pooled extensions. .h is shared by C, C++ and Objective-C; .ts is also a Qt XML extension; .sql is shared by five languages; .tsx is TSX in Linguist but TypeScript in BigCode; .lock is JSON in BigCode but unclassified in Linguist (corpora:C35, C39, C40). .jpg stands for .jpeg too, .env.example is a name pattern whose real extension is .example (also scored as .env* in special_names), and the .yml versus .yaml split was never measured.
- Developer-survey and ranking sources (Stack Overflow, JetBrains, Octoverse) measure developers, not files or agents (industry:K1-K4, J1, J2, O1-O5). They were used only as weak support for baseline scores, and admiration or adoption-intent figures were not treated as usage.
- The three scores are hand-assigned integers, not computed from a formula, so they are not reproducible from the evidence alone. The proxy blocked arxiv.org, huggingface.co, github.blog and survey sites, so the one dataset that could answer the question (AIDev pr_commit_details, a filename per changed file, 12,116,310 rows: agent-pr-studies:C1) was not reachable. Computing per-extension counts from it for the Claude Code rows is the obvious next step.
- The evidence runs from April 2025 to about August 2026 in a fast-moving field (TypeScript pushers grew 2.26x between 2024 Q4 and 2026 Q1: corpora:C20). A paper on language breadth suggests Claude Code users spread into languages they did not use before (agent-pr-studies:G3, industry:R9, both preliminary), which argues for broad extension coverage and not only the top few.
- Reviewers disagreed on four rows and the original scores were held rather than guessed: .toml (52; proposals 58 and 45), .png (38; 46 and 25), .svg (42; 52 and 28) and .xml (48; 40 and 62). Several other revisions rest on a mechanism (scaffolders, document-generation libraries, shipped skills) that is plausible but unmeasured: .mjs, .yaml, .txt, .csv, .pdf, .docx, .xlsx and .pptx were raised on that basis.
- The output schema has no risk field. Prevalence scores understate scanner priority for rare but dangerous types (.pkl, .pickle, .pt, .pth, .pem, .key, .p12, .exe, .dll, .so, .jar, .docm, .xlsm, .dotm, .pptm, .ps1, .env*, .mcp.json, .claude/settings.json). A consumer should rank them by a separate risk weight, flagged here only in rationales.
- The special_names schema has no numeric fields, so scores for named files (package.json, CLAUDE.md, .mcp.json and the rest) are written into the 'why' text and are judgement from review, not measurement. The family enum has no data category, so .csv, .jsonl and .tsv are filed as config-data and binaries as other.
- A few rows added after review are not extensions: .env.example is a name pattern, and pyproject.toml, package.json and the Claude Code control files appear only in special_names. Files that carry the strongest Claude Code signal (CLAUDE.md, .mcp.json, .claude/settings.json) are therefore outside the extension ranking proper.

Getting first-party numbers

Three sources would turn this estimate into measurement. None could be run from the sandbox that produced this report.

1. Your own repositories

Count tracked files by extension in the projects you want to protect:

```
git ls-files | awk -F. 'NF>1 {print tolower($NF)}' | sort | uniq -c | sort -rn | head -40
```

To count only files that Claude Code wrote, limit the history to commits whose message carries the Co-Authored-By trailer, then count what those commits touched:

```
git log --grep='Co-Authored-By: Claude' --name-only --pretty=format: | awk -F. 'NF>1 {print tolower($NF)}' | sort | uniq -c | sort -rn | head -40
```

2. Claude Code's own telemetry

Claude Code can export OpenTelemetry metrics and events. Its code-edit tool decision events carry the language of the edited file, which is first-party data about what it edits in your organisation. Enable it for a sample of projects, aggregate by language, and re-score the agent axis in the data file; the ranking recomputes.

3. The AIDev dataset

The research dataset behind the agent-pull-request studies cited here has a table with one row per changed file (commit, file name, status, patch; 12,116,310 rows in version 5, all agents) and tags each pull request with its agent. Filtering to Claude Code and counting extensions of the file names would give the missing per-extension distribution directly. The table is hosted on Hugging Face (the dataset is named AIDev and is described in the SAILResearch/AI_Teammates_in_SE3 repository on GitHub), which this sandbox could not reach. Its pull requests come from repositories with more than 100 stars, so it under-represents the small projects where most Claude Code commits land.

Re-running this report

`python3 build_pdf_top_extensions.py top40_extensions_data.json` rebuilds the PDF from the data file; `python3 build_pdf_filetypes.py --check` confirms the "Pipeline today" column still matches classify_file().

Appendix: candidates ranked 41 to 100

Scored the same way and just below the cut, useful when the list is extended. All 140 candidates are in the data file.

#	Ext	Format	Score	Agent	Base	Struct	Pipeline today
41	`.ps1`	PowerShell	**23**	24	30	10	scan_powershell · scan_powershell_xml
42	`.hpp`	C++ header	**22.8**	22	36	5	scan_c_cpp
43	`.gif`	GIF image	**22.6**	12	52	5	generic (scan_unknown)
44	`.vue`	Vue single-file component	**22.2**	24	30	6	generic (scan_unknown)
45	`.cjs`	JavaScript CommonJS	**21.6**	26	22	10	scan_javascript
46	`.swift`	Swift	**21.6**	24	28	6	generic (scan_unknown)
47	`.docx`	Word document	**21.6**	26	26	4	scan_office
48	`.csproj`	C# project file (XML)	**21.4**	18	36	8	generic (scan_unknown)
49	`.xlsx`	Excel workbook	**20.4**	26	22	4	scan_office
50	`.gradle`	Gradle build script	**20.2**	18	32	8	generic (scan_unknown)
51	`.ini`	INI	**19.8**	12	42	6	generic (scan_unknown)
52	`.bat`	Windows batch	**19.2**	16	32	8	scan_bat
53	`.properties`	Java properties	**19**	14	36	6	generic (scan_unknown)
54	`.proto`	Protocol Buffers	**19**	20	26	6	generic (scan_unknown)
55	`.jsonl`	JSON Lines	**18.2**	20	24	5	generic (scan_unknown)
56	`.db`	Database file	**17.8**	16	30	4	generic (scan_unknown)
57	`.bash`	Bash script	**17.2**	18	22	8	scan_shell
58	`.jar`	Java archive	**17.2**	14	30	6	scan_jar
59	`.woff2`	Web font	**16.8**	14	30	4	generic (scan_unknown)
60	`.zip`	ZIP archive	**16.8**	8	40	4	scan_archive
61	`.cmd`	Windows batch (cmd)	**16.4**	14	26	8	scan_bat
62	`.cc`	C++ source (alternate)	**16.2**	12	32	3	scan_c_cpp
63	`.mk`	Makefile include	**15.8**	12	26	10	scan_makefile
64	`.webp`	WebP image	**15.8**	14	26	5	generic (scan_unknown)
65	`.rst`	reStructuredText	**15.4**	12	28	5	credential grep only
66	`.gz`	Gzip archive	**15.4**	8	36	3	scan_archive
67	`.cmake`	CMake	**15.2**	14	22	8	scan_cmake
68	`.kts`	Kotlin script / Gradle Kotlin DSL	**15.2**	14	22	8	scan_kotlin

#	Ext	Format	Score	Agent	Base	Struct	Pipeline today
69	`.parquet`	Parquet data	**15.2**	16	22	3	generic (scan_unknown)
70	`.dart`	Dart	**15**	16	20	5	generic (scan_unknown)
71	`.ttf`	TrueType font	**13.8**	8	30	4	generic (scan_unknown)
72	`.woff`	Web font (legacy)	**13.6**	10	26	4	generic (scan_unknown)
73	`.pptx`	PowerPoint presentation	**13.2**	18	12	3	scan_office
74	`.sqlite`	SQLite database	**12.8**	12	20	4	generic (scan_unknown)
75	`.lua`	Lua	**12.6**	12	20	3	generic (scan_unknown)
76	`.r`	R	**12.6**	12	20	3	generic (scan_unknown)
77	`.svelte`	Svelte component	**12.4**	16	12	4	generic (scan_unknown)
78	`.tsv`	Tab-separated values	**12.4**	10	22	4	generic (scan_unknown)
79	`.tmpl`	Go template	**12.4**	8	26	3	generic (scan_unknown)
80	`.jsonc`	JSON with comments	**12.2**	14	12	8	generic (scan_unknown)
81	`.class`	Java class file	**12**	4	32	2	generic (scan_unknown)
82	`.pl`	Perl (also Prolog, Raku)	**11.8**	8	24	3	generic (scan_unknown)
83	`.j2`	Jinja2 template	**11.6**	10	20	3	generic (scan_unknown)
84	`.graphql`	GraphQL	**11.4**	14	12	4	generic (scan_unknown)
85	`.tfvars`	Terraform variables	**11.4**	14	12	4	scan_terraform
86	`.pkl`	Python pickle	**11.4**	12	16	3	generic (scan_unknown)
87	`.log`	Log file	**11.4**	10	20	2	generic (scan_unknown)
88	`.tpl`	Template (Helm and others)	**11.2**	8	22	3	generic (scan_unknown)
89	`.snap`	Jest/Vitest snapshot	**11**	12	14	4	generic (scan_unknown)
90	`.exe`	Windows executable	**10.9**	3	30	2	scan_binary
91	`.tar`	Tar archive	**10.7**	5	26	2	scan_archive
92	`.dll`	Windows library	**10.3**	3	28	2	scan_binary
93	`.psd1`	PowerShell module manifest	**10.2**	10	14	5	scan_powershell · scan_powershell_xml
94	`.psm1`	PowerShell module	**10.2**	10	14	5	scan_powershell · scan_powershell_xml
95	`.ex`	Elixir	**10.2**	12	12	3	generic (scan_unknown)
96	`.sqlite3`	SQLite database	**10**	10	14	4	generic (scan_unknown)
97	`.pem`	PEM key/certificate	**10**	8	18	3	generic (scan_unknown)
98	`.tex`	LaTeX	**10**	8	18	3	generic (scan_unknown)

#	Ext	Format	Score	Agent	Base	Struct	Pipeline today
99	.pyc	Python bytecode	**10**	6	22	2	generic (scan_unknown)
100	.so	Shared object	**9.6**	4	24	2	scan_binary