# What the AI Transit Pipeline checks, file type by file type

30 scanner slides covering every extension the pipeline routes, and one on unknown extensions.

Each slide: the extensions · the tools that run · the rules that FAIL · the rules that only WARN · the known limits.

Source of truth: classify_file() in scan_pipeline.sh. python3 build_pdf_filetypes.py --check fails if this deck drifts from it.

# What every file gets

Layer 5 is the part that varies by type. The other layers do not look at the extension.

| | | | |
|---|---|---|---|
| L1 | **Global** | Whole directory | betterleaks · detect-secrets · ClamAV · YARA |
| L2 | **Semgrep** | Whole directory | p/owasp-top-ten · p/cwe-top-25 · p/security-audit · p/secrets |
| L3 | **Dependencies** | Manifests | trivy · pip-audit · safety · npm audit |
| L4 | **Universal patterns** | EVERY file | Credentials · 18 known token formats · PEM keys · traversal · SSRF · weak crypto / PRNG |
| L5 | **Per-type scanner** | By type | One slide per type in this deck |
| L6 | **ScanCode** | Whole directory | Licences (GPL / AGPL / LGPL / SSPL / BUSL → WARN) · CVE HIGH / CRITICAL → FAIL |

WARN = logged, the pipeline continues.  FAIL = the repository is quarantined and no ZIP is produced.  .transit-allow.json downgrades a named FAIL to WARN; .transitignore removes a file from every scan.

# How a file is routed

classify_file() decides in this order; the first match wins.

| | | |
|---|---|---|
| 0 | **Excluded?** | .transitignore patterns and the default pruned directories (node_modules, .git, vendor, dist, build, target, coverage …) never reach a scanner. |
| 1 | **Basename** | Dockerfile*, Makefile*, CMakeLists.txt, package.json, composer.json, requirements*.txt, constraints*.txt, *.gradle, *.gradle.kts, gradle*.properties, setup.py, conanfile.py. |
| 2 | **Extension** | Lower-cased first, so .PS1 and .JAR are treated like .ps1 and .jar. One slide per family in this deck. |
| 3 | **Shebang** | No known extension: the first line decides — python, bash / sh / zsh / ksh, ruby, node, php, pwsh / powershell. |
| 4 | **MIME type** | Still nothing: file --mime-type. An executable type (x-executable, x-sharedlib, x-dosexec) → FAIL. |
| 5 | **Default** | Anything else passes Layer 5 untouched. See "Unknown extensions". |

# Python

`scan_python`

`.py`

also by shebang: #!...python

## TOOLS APPLIED

### Bandit

bandit -q -l -i. Any MEDIUM or HIGH issue → FAIL (bandit:<severity>:<test id>). Not installed → WARN.

## FAIL — blocks the repository

- CWE-78 os.system, subprocess.call, subprocess.Popen, commands.getoutput
- CWE-95 eval( or exec(
- CWE-502 pickle.load(s), marshal.loads, yaml.load( without a Loader
- CWE-89 execute / executemany with an f-string, +, % or .format() query
- CWE-703 assert is_admin / is_authenticated / has_perm / user.is...

## WARN — reported, does not block

- CWE-601 redirect( or HttpResponseRedirect( fed from request....
- bandit missing

Note: Broad by design: eval, exec and os.system fail even with a literal argument. setup.py and conanfile.py are routed to the install-time scanner instead.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Install-time Python — setup.py, conanfile.py

`scan_setup_py`

`setup.py` `conanfile.py`

**TOOLS APPLIED**

**— none —**

Replaces scan_python for these two names: Bandit and the generic eval / exec / os.system FAILs do not run on them.

**FAIL — blocks the repository**

- A download piped into a shell
- exec / eval of a network response
- A blob decoded and executed in the same file (whole-file test)
- A socket handed to a shell, or a pty
- Writing authorized_keys, a crontab or a systemd unit

**WARN — reported, does not block**

- Overriding install / develop / egg_info
- Downloading at install time
- Running a program

Note: setup.py runs on a source pip install and a Conan recipe on conan install, so both fire before anything is imported. 36 real setup.py: 4 FAIL → 0 FAIL, 3 WARN.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# JavaScript / TypeScript

`scan_javascript`

`.js` `.ts` `.jsx` `.tsx` `.mjs` `.cjs`

also by shebang: #!...node

## TOOLS APPLIED

### Semgrep p/javascript

Run per file. Any finding → FAIL (semgrep:js:N_findings). Not installed → WARN.

## FAIL — blocks the repository

- CWE-79 innerHTML / outerHTML / document.write / insertAdjacentHTML assignment
- CWE-78 child_process, exec(, execSync(, spawn(
- CWE-95 eval( or new Function(
- CWE-1321 __proto__, constructor[prototype], Object.assign({}
- CWE-915 Object.assign / _.merge / deepmerge( with req.... as the source
- CWE-89 SQL in a template literal (query / raw / knex.raw / sequelize.query)

## WARN — reported, does not block

- CWE-611 DOMParser, parseXML, libxmljs.parseXml
- semgrep missing

Note: package.json is routed to the manifest scanner, not here.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Java source

scan_java

.java

## TOOLS APPLIED

**— none per file —**

Semgrep covers Java at Layer 2 (whole directory).

## FAIL — blocks the repository

- CWE-78 Runtime.getRuntime().exec( or ProcessBuilder(
- CWE-89 createQuery / createNativeQuery / prepareStatement with "…" +
- CWE-502 ObjectInputStream, XMLDecoder, XStream
- CVE-2021-44228 jndi:, ldap://, rmi://, ${jndi (Log4Shell)
- CWE-295 TrustAllCerts / an empty X509TrustManager

## WARN — reported, does not block

- CWE-79 request.getParameter written to the response
- CWE-611 DocumentBuilderFactory.newInstance() — check the entity configuration

Note: Compiled Java is a different file type: .jar .war .ear .aar have their own scanner.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# PHP

scan_php

.php

also by shebang: #!...php

## TOOLS APPLIED

**— none per file —**

Semgrep covers PHP at Layer 2 (whole directory).

## FAIL — blocks the repository

- CWE-78 shell_exec, exec, system, passthru, popen, proc_open
- CWE-89 mysql_query / mysqli_query / pg_query concatenating a variable
- CWE-79 echo $_GET / $_POST / $_REQUEST / $_COOKIE / $_SERVER
- CWE-22 include / require with a variable path
- CWE-502 unserialize( of $_GET / $_POST / $_COOKIE / $_REQUEST

## WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: Every rule here is a FAIL: PHP has no reviewable tier.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Ruby

`scan_ruby`

`.rb`

also by shebang: #!...ruby

## TOOLS APPLIED

**— none per file —**

Semgrep covers Ruby at Layer 2 (whole directory).

## FAIL — blocks the repository

- CWE-78 system, exec, Kernel.exec, %x{ or a backtick command
- CWE-95 eval( / eval {
- CWE-89 where / find_by_sql / execute with "...#{...}" interpolation
- CWE-22 File.read / File.open / IO.read of params[...]

## WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: A Rakefile is not routed to this scanner: it was measured and rejected (8 of 62 false positives on markdown backticks).

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Go

scan_go

.go

## TOOLS APPLIED

**— none per file —**

Semgrep covers Go at Layer 2 (whole directory).

## FAIL — blocks the repository

- CWE-89 fmt.Sprintf building SELECT / INSERT / UPDATE / DELETE

## WARN — reported, does not block

- CWE-78 exec.Command(
- CWE-22 os.Open / ioutil.ReadFile / http.ServeFile of r.URL or path
- CWE-338 "math/rand" imported
- CWE-326 tls.Config{ without MinVersion

Note: Mostly reviewable-tier: only SQL built by fmt.Sprintf blocks.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# C / C++

`scan_c_cpp`

`.c` `.cpp` `.cc` `.h` `.hpp`

## TOOLS APPLIED

### cppcheck

--enable=all. Any error: or warning: line → FAIL (cppcheck:<first>). Not installed → WARN.

## FAIL — blocks the repository

- CWE-120 gets, gets_s, strcpy, strcat, sprintf, vsprintf
- CWE-78 system, popen, execl / execle / execlp / execv / execve / execvp
- CWE-134 printf-family call with argv, getenv, user_input or stdin as the format
- CWE-377 tmpnam, tempnam, mktemp (TOCTOU temp file)

## WARN — reported, does not block

- CWE-190 malloc(a * b) — possible integer overflow
- CWE-415 two free() calls on one line — possible double free
- CWE-338 rand()

Note: CERT STR31 / MEM30 / INT30 / ENV33 / FIO45 / MSC30 are the reference points.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Rust

`scan_rust`

`.rs`

## TOOLS APPLIED

**— none —**

Three built-in rules, deliberately small.

## FAIL — blocks the repository

- CWE-119 unsafe { block — needs human review
- CWE-78 std::process::Command
- CWE-798 password / secret / api_key / token assigned a 4+ character literal

## WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: Known gap: a build.rs legitimately uses std::process::Command (how pkg-config and cc run), so it over-fires. No build.rs existed on the host to calibrate a better rule.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Kotlin

`scan_kotlin`

`.kt` `.kts`

### TOOLS APPLIED

**— none —**

*.gradle.kts is a Gradle build script, not Kotlin source: it goes to the Gradle scanner.

### FAIL — blocks the repository

- CWE-78 Runtime.getRuntime().exec(
- CWE-798 password / secret / apiKey / api_key / token assigned a 4+ character literal
- CWE-327 MessageDigest.getInstance("MD5") or "SHA-1"

### WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: foo.main.kts and other non-Gradle Kotlin scripts still come here.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# C#

`scan_csharp`

`.cs`

## TOOLS APPLIED

**— none —**
Four built-in rules.

## FAIL — blocks the repository

- CWE-78 Process.Start(
- CWE-798 password / secret / apiKey / api_key / token assigned a 4+ character literal
- CWE-327 new MD5CryptoServiceProvider()
- CWE-89 a "SELECT …" literal followed by + (concatenation)

## WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: Only SELECT is matched for SQL concatenation.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Shell

`scan_shell`

`.sh` `.bash` `.zsh` `.ksh`

also by shebang: #!.../bash  #!.../sh  #!.../zsh  #!.../ksh  #!/usr/bin/env bash|sh

### TOOLS APPLIED

**ShellCheck**
shellcheck -S warning. Any warning → FAIL (shellcheck:warnings). Not installed → WARN.

### FAIL — blocks the repository

- CWE-78 curl ... | bash / sh and wget ... | bash / sh
- CWE-88 eval $variable

### WARN — reported, does not block

- CWE-426 export PATH= starting with a relative directory
- CWE-377 predictable temp name (/tmp/$$, /tmp/<name>tmp)
- IFS manipulation
- shellcheck missing

Note: Makefile recipes, PowerShell and batch files have their own scanners.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# PowerShell

`scan_powershell · scan_powershell_xml`

`.ps1` `.psm1` `.psd1` `.pssc` `.psrc` `.ps1xml` `.psc1` `.cdxml`

also by shebang: #!…pwsh  #!…powershell

### TOOLS APPLIED

**— none —**

One shared rule set (_ps_rules). The XML types (.ps1xml .psc1 .cdxml) also get scan_xml's external-entity check.

### FAIL — blocks the repository

- Fetch then execute: irm … | iex, DownloadString + iex, or a download piped to a shell
- -EncodedCommand and its abbreviations (-enc, -e) followed by a base64 blob
- FromBase64String with iex / ScriptBlock::Create / Assembly::Load / VirtualAlloc (whole file)
- A backtick inside the command name, an AMSI bypass, Defender disabled
- Persistence: Run key, WMI event consumer, Startup folder; socket fed to a shell; VirtualAlloc + CreateThread
- A literal $Password, or ConvertTo-SecureString "…" -AsPlainText
- A plaintext http:// download that is then run

### WARN — reported, does not block

- Invoke-Expression alone (a deliberate relaxation)
- Start-Process / cmd /c, an https download then run
- Execution-policy bypass, hidden window, Defender exclusion
- Scheduled task, certificate validation off, local account creation
- ScriptsToProcess in a manifest; wildcard VisibleCmdlets in a role capability

Note: Matching is case-insensitive, and so is the extension (UPPER.PS1 used to bypass the scanner). 32 real scripts: 8 FAIL (all false positives) → 0. None of the module, manifest or XML types exists on the host, so those routes rest on fixtures. Legacy .msh is not routed.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Windows batch

`scan_bat`

`.bat` `.cmd`

### TOOLS APPLIED

**— none —**

Works on a normalised view: CR stripped, REM / :: comment lines dropped, ^ continuations joined. Case-insensitive.

### FAIL — blocks the repository

- certutil -urlcache, bitsadmin /transfer, a PowerShell DownloadString cradle, curl -k
- powershell -enc <base64> (any abbreviation); certutil -decode into an executable
- Download then execute on one line; carets inside a command name
- A Run / RunOnce / Winlogon / IFEO key, or a file copied into the Startup folder
- UAC, Defender or the firewall turned off; a new member of local Administrators
- A delete aimed exactly at a drive root or the profile; format; set …PASSWORD=<literal>

### WARN — reported, does not block

- net user /add, schtasks /create, certutil -decode of anything else
- Fetch and run in one script; a plaintext http:// download
- -ExecutionPolicy Bypass, hidden PowerShell window
- mshta / wscript / rundll32 / regsvr32; wmic process call create; a remote UNC path
- A command assembled from adjacent %v:~n,1% extractions

Note: 116 real files, all clean — but they are npm shims, virtualenv and Maven wrappers, with no Windows-native automation, so that says little about recall. .btm and the 4DOS family are not routed.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Makefile

`scan_makefile`

`.mk` `.mak` `.make` `Makefile*` `makefile*` `GNUmakefile*`

### TOOLS APPLIED

**— none —**

$(shell …) runs when make merely reads the file, before any target; recipe lines are shell.

### FAIL — blocks the repository

- A download piped into a shell; a parse-time fetch $(shell curl …)
- A base64-decoded payload executed; a reverse shell
- A hardcoded credential (assignments are unquoted, so the universal rule cannot see them)
- TLS verification disabled
- A setuid / setgid bit; cron or authorized_keys persistence
- rm -rf of exactly /, ~ or $HOME

### WARN — reported, does not block

- sudo in a recipe
- chmod 777
- A plaintext http:// download
- Clone-and-build from a remote

Note: 88 real Makefiles: no finding of any kind. No rule for a bare $(eval …): it fired on 7 of 88 as ordinary metaprogramming.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# CMake

`scan_cmake`

`.cmake` `CMakeLists.txt` `CMakeLists.*.txt`

## TOOLS APPLIED

**— none —**

file(DOWNLOAD) and execute_process() run at configure time: cmake . is enough.

## FAIL — blocks the repository

- A credential in set(NAME "value") — a function call the universal rule cannot see
- A plaintext http:// download, or TLS_VERIFY OFF
- A download piped into a shell
- Hardening removed: -fno-stack-protector, _FORTIFY_SOURCE=0, execstack
- file(WRITE …) into /etc, ~/.ssh or cron

## WARN — reported, does not block

- A build step that fetches
- COMMAND sh -c
- install(CODE | SCRIPT)
- GIT_TAG on a moving branch

Note: 1 of 1116 real files fails: a plaintext archive URL in CMake's own ExternalProject documentation. execute_process appears in 106 of 1116, so it is not a finding by itself.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Gradle

`scan_gradle`

`gradle.properties` `gradle-wrapper.properties` `*.gradle` `*.gradle.kts`

### TOOLS APPLIED

**— none —**

A Gradle script is a program, evaluated in full at configuration time (gradle tasks, --dry-run, an IDE import). settings.gradle runs first.

### FAIL — blocks the repository

- Build scripts: apply from 'http(s)://...', allowInsecureProtocol = true
- Build scripts: a process started from a literal or list, a ProcessBuilder (matched without new, so Kotlin is covered), Runtime.exec
- gradle.properties: a literal *.password / *.secret / *.apiKey
- gradle.properties: dependency verification off or lenient; -javaagent / -agentpath in org.gradle.jvmargs
- gradle-wrapper.properties: a plaintext distributionUrl

### WARN — reported, does not block

- A configuration-time remote fetch
- exec / commandLine / javaexec
- A trustStore override
- validateDistributionUrl=false

Note: 6413 real files, 99.6% pass; the 26 FAILs are credentials in Gradle's own docs and tests, one doc snippet, two genuine spawns. A missing distributionSha256Sum is deliberately not reported (20 of 26 omit it). gradle-wrapper.jar is a jar: see Java archives.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Package manifests

`scan_package_json · scan_requirements`

`package.json` `composer.json` | `requirements*.txt` `constraints*.txt`

**TOOLS APPLIED**

**trivy · pip-audit · npm audit**

At Layer 3, whole directory: CVEs in the dependencies a manifest names. This slide is about what the manifest itself can run.

**FAIL — blocks the repository**

- npm: preinstall / install / postinstall (and prepare) that pipe a download into a shell, decode base64, open /dev/tcp or use nc -e
- npm: a dependency on http://, git:// or git+http://
- Composer: the same hook rules; secure-http false; an http:// repository
- pip: an index, -f or requirement over http:// or git://; credentials embedded in a URL

**WARN — reported, does not block**

- An install-time hook being present
- A non-lifecycle script that pipes or fetches
- A git or tarball dependency
- --trusted-host; --extra-index-url (dependency confusion)
- A VCS requirement not pinned to a commit

Note: JSON is parsed, not grepped: "post\u0069nstall" is postinstall to npm. Calibration is weak: 0 of 1193 real package.json fail, but they are mostly published packages. Lockfiles, go.mod and meson_options.txt are not covered.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# XML, Maven and Ant

`scan_xml`

`.xml` `.pom`

**TOOLS APPLIED**

**— none —**

Matches on a newline-folded, comment-stripped view. pom.xml and build.xml get Maven / Ant rules by name.

**FAIL — blocks the repository**

- XXE: <!ENTITY … SYSTEM pointing at file:, expect:, php:, gopher:, jar:, netdoc:, ftp:, http(s): or an absolute path
- An entity expansion bomb: 4+ named references in one entity value
- A credential in <password> / <token> / <secret> / <apiKey> / <privateKey> with a 6+ character literal
- Maven: a <repository> whose <url> is http://; exec-maven-plugin / antrun running sh, bash, cmd, powershell, curl, wget
- Ant: <get> over http://; <exec> of a shell or downloader; <sshexec> / <scp> with a literal password=

**WARN — reported, does not block**

- A relative SYSTEM include (DocBook) or a PUBLIC DTD reference
- The exec or antrun plugin being present; system scope
- Any Ant <exec>

Note: A bare <!DOCTYPE failed 736 of 3362 real XML files, so it is no longer a rule: 0 of 3362 fail now. The Ant half rests on only 22 real files. No -SNAPSHOT rule (176 of 221 real poms use one).

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# YAML / CI / Kubernetes

`scan_yaml`

`.yml` `.yaml`

### TOOLS APPLIED

**— none per file —**
checkov covers Terraform, not YAML; Semgrep runs at Layer 2.

### FAIL — blocks the repository

- OWASP A08 uses: owner/action with no @ref — an unpinned GitHub Action
- CWE-798 password / secret / token / key / api_key: followed by a literal
- OWASP A05 privileged: true
- OWASP A05 hostNetwork / hostPID / hostIPC: true

### WARN — reported, does not block

- CWE-94 {{ request.... / user.... / .env.... }} — possible template injection

Note: Known weak spot: the bare key: rule flags about 7% of real YAML files.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Terraform / HCL

`scan_terraform`

`.tf` `.tfvars` `.hcl`

### TOOLS APPLIED

**checkov**
checkov -f --quiet (--skip-download when offline). Any failed check → FAIL (checkov:N_CIS_IaC_findings). Not installed → WARN.

### FAIL — blocks the repository

- CWE-798 password / secret / token = "..."
- OWASP A05 acl = "public-read" (S3)
- OWASP A02 encrypted = false

### WARN — reported, does not block

- OWASP A05 cidr_blocks = ["0.0.0.0/0"]

Note: Offline, checkov must be pointed at staged data or it silently contributes nothing.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Dockerfile

`scan_docker`

`Dockerfile*`

### TOOLS APPLIED

**hadolint**
Any lint issue → FAIL (hadolint:dockerfile_issue). Not installed → WARN.

### FAIL — blocks the repository

- OWASP A05 a :latest base image
- CWE-494 ADD of an http(s):// URL — no integrity check
- CWE-78 RUN curl | bash or wget | sh
- CWE-798 ENV PASSWORD / SECRET / TOKEN / API_KEY / PRIVATE_KEY baked into a layer

### WARN — reported, does not block

- CWE-250 no non-root USER directive

Note: Matched by basename: Dockerfile.dev and Dockerfile.prod count.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# HTML

`scan_html`

`.html` `.htm` `.xhtml`

## TOOLS APPLIED

**— none —**

Inline <script> is ordinary, so every rule targets a construct with no innocent reading. Each was counted on 388 real files.

## FAIL — blocks the repository

- eval(); a percent-encoded payload in unescape(); document.write() fed from a decoder
- <script src="http://…">; <base href="http://">; <form action="http://">
- A hidden iframe: display:none, visibility:hidden, zero width or height
- A credential in a name / value attribute pair or a <meta content>
- A cookie read wired to a network sink (matched in both orders)

## WARN — reported, does not block

- innerHTML / outerHTML / insertAdjacentHTML
- new Function(; a bare atob(
- A protocol-relative <script src="//…">
- An external meta refresh; a javascript: URI

Note: 2 of 388 real files fail: both genuine eval() calls in the bundled Go trace viewer (vendoring it needs a .transit-allow.json entry). build/, dist/, coverage/ and node_modules/ are pruned first.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# PDF

`scan_pdf`

`.pdf`

### TOOLS APPLIED

**— stdlib decoder —**
Decodes Flate, LZW, ASCIIHex, ASCII85 and RunLength filter chains (64 MB ceiling) and #xx name escapes; two views, so prose cannot fire a key rule.

### FAIL — blocks the repository

- CWE-94 /JavaScript, /JS, /OpenAction, /AA — also hex-escaped (/J#61vaScript) and inside compressed object streams
- CWE-78 /Launch
- CWE-506 /EmbeddedFile, or an embedded Windows executable
- Rich media; /SubmitForm, /ImportData
- Known exploit APIs (util.printf, collab.getIcon, media.newPlayer …) and unescape shellcode shapes

### WARN — reported, does not block

- Encrypted (/Encrypt) — reported, not decrypted
- A stream behind an undecodable filter, named
- XFA forms; remote or embedded destinations (/GoToR, /GoToE)
- Incremental updates (several %%EOF)

Note: The five PDFs this project ships are the acceptance test: scan them and expect PASS with no finding. Image filters are excluded — they carry pixels, never dictionaries.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# SQL

`scan_sql`

`.sql`

### TOOLS APPLIED

**— none —**

Four built-in rules.

### FAIL — blocks the repository

- CWE-78 xp_cmdshell, sp_OACreate, OPENROWSET, BULK INSERT
- CWE-89 DROP TABLE / DATABASE / SCHEMA / VIEW / FUNCTION / PROCEDURE
- CWE-89 injection patterns: ; --, '--, OR 1=1, AND 1=1
- CWE-89 UNION [ALL] SELECT

### WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: A migration that legitimately drops a table fails: use .transit-allow.json.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# JSON

`classify_file (inline rule)`

`.json`

## TOOLS APPLIED

**— none —**

One built-in rule. package.json and composer.json are routed to the manifest scanner by name.

## FAIL — blocks the repository

- CWE-798 "password" / "secret" / "token" / "api_key" / "private_key": "<4+ character literal>"

## WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: After the bracket-expression fix this rule sees values containing an "s": 12 of 2252 real JSON files flag (9 before).

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Documentation and text

`classify_file (inline rule)`

`.md` `.txt` `.rst`

### TOOLS APPLIED

**— none —**

One built-in rule. CMakeLists.txt and requirements*.txt end in .txt but are routed by name first.

### FAIL — blocks the repository

- CWE-798 password / secret / api_key followed by : or = and a literal value

### WARN — reported, does not block

No reviewable tier: every rule here blocks.

Note: A README that quotes an attack string (a credential or a traversal example) fails: INSTALL.md and CLAUDE.md of this project do. That is what .transit-allow.json is for.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Native binaries

`scan_binary`

`.so` `.dll` `.dylib` `.exe` `.elf` `.bin`

**TOOLS APPLIED**

### strings

Extracts readable strings and looks for http://, https://, /etc/passwd, /bin/sh, exec, shell, reverse, c2server.

**FAIL — blocks the repository**

- binary:unexpected_binary_in_AI_repo — EVERY file of these types, whatever it contains
- binary:IOC_strings_detected — in addition, when the strings search hits

**WARN — reported, does not block**

No reviewable tier: every rule here blocks.

Note: .bin is blocked, not analysed: a harmless weights file fails exactly like an ELF, while the same pickle named .pkl or .pt passes (see Unknown extensions). Content-based routing would fix both.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Archives

`scan_archive`

`.zip` `.tar` `.gz` `.tgz` `.bz2` `.xz`

**TOOLS APPLIED**

**unzip -l**
.zip only: lists the entries and looks for '..' in a path.

**FAIL — blocks the repository**

- archive:requires_dedicated_rescan — EVERY archive
- CWE-22 a .zip entry whose path contains '..' (zip-slip)

**WARN — reported, does not block**

No reviewable tier: every rule here blocks.

Note: An archive is not opened: it must be extracted in an isolated environment and rescanned. Java archives are the exception (next slide).

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Java archives

`scan_jar`

`.jar` `.war` `.ear` `.aar`

**TOOLS APPLIED**

### stdlib zipfile helper

Opened in place, never extracted. Reads entries like the JVM does; bounded by entry, byte, text, size, time and depth limits — each one reached is reported.

**FAIL — blocks the repository**

- Zip-slip: a path with .., a leading / or a drive letter; a symlink out of the archive; a local record the central directory does not list
- A .class that is not bytecode; a PE / ELF / Mach-O under a non-native name or glued in front of the archive
- A manifest Class-Path naming an http(s):// or ftp:// jar
- curl | sh, a reverse shell, encoded PowerShell, certutil -urlcache — in a resource, UTF-16 text, a class constant or attribute
- A PEM private key at any line width; any of the 18 known credential formats
- gradle-wrapper.jar / maven-wrapper.jar with entries outside the expected tree or no main class

**WARN — reported, does not block**

- EVERY jar: its bytecode is not reviewed, so a clean jar still warns
- Java agents; native libraries; scripts; nested archives; symlinks; duplicate names
- Encrypted or unreadable entries; any limit reached (inspection_incomplete)
- Every wrapper jar: verify its SHA-256 yourself

Note: 365 real jars: one FAIL, a genuine embedded test key. .war / .ear / .aar are routed but unmeasured. Bytecode is not decompiled. A jar under build/, dist/, target/ or vendor/ is pruned and never scanned.

Also applied to every file: L1 betterleaks · detect-secrets · ClamAV · YARA | L2 Semgrep | L4 universal patterns (credentials, key material, traversal, SSRF, weak crypto) | L6 ScanCode

# Unknown extensions — what is allowed

Anything not routed above. It is not skipped: it still passes every layer except Layer 5.

### HOW IT IS HANDLED

| | |
|---|---|
| `#!…python` | → **scan_python** |
| `#!…/bash, /sh, /zsh, /ksh, env bash\|sh` | → **scan_shell** |
| `#!…ruby` | → **scan_ruby** |
| `#!…node` | → **scan_javascript** |
| `#!…php` | → **scan_php** |
| `#!…pwsh, powershell` | → **scan_powershell** |

- No shebang: file --mime-type. x-executable, x-sharedlib or x-dosexec → FAIL (binary:unexpected_executable_mime).
- Any other type → PASS. That is "allowed".
- If the file command is not installed the MIME check is skipped and the file passes.

### STILL APPLIED

- L1 betterleaks, detect-secrets, ClamAV and YARA — whole directory
- L2 Semgrep rulesets — whole directory
- L4 universal patterns on this very file: hardcoded credentials, the 18 known token formats, PEM private keys, path traversal in three contexts, SSRF, weak crypto and PRNG, debug artefacts, logging suppression
- L6 ScanCode licences and CVEs
- Examples that land here: .png .jpg .csv .toml .ini .cfg .conf .lock .env .svg .proto .safetensors

### WHAT PASSES UNEXAMINED

- Source in a language with no scanner: Perl, Lua, VBScript, Groovy (outside Gradle), Scala, Swift, Dart, Elixir … — no per-language rule runs, only Layer 4.
- Pickled models and weights: .pkl .pickle .pt .pth .ckpt .joblib. A pickle that runs os.system PASSED when tested; loading one executes it.
- A .bin pickle is the opposite case: blocked with every other .bin, harmlessly or not.
- Content disguised by name: a script saved as .txt gets only the document rule.
- Remedy for a legitimate file: .transit-allow.json (FAIL → WARN, with a reason) or .transitignore.

# Index — every routed extension and basename

Extension → slide number.


| | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|
| `*.gradle` | p. 20 | `.elf` | p. 31 | `.make` | p. 18 | `.sh` | p. 15 | `CMakeLists.*.txt` | p. 19 |
| `*.gradle.kts` | p. 20 | `.exe` | p. 31 | `.md` | p. 30 | `.so` | p. 31 | `CMakeLists.txt` | p. 19 |
| `.aar` | p. 33 | `.go` | p. 10 | `.mjs` | p. 6 | `.sql` | p. 28 | `composer.json` | p. 21 |
| `.bash` | p. 15 | `.gz` | p. 32 | `.mk` | p. 18 | `.tar` | p. 32 | `conanfile.py` | p. 5 |
| `.bat` | p. 17 | `.h` | p. 11 | `.pdf` | p. 27 | `.tf` | p. 24 | `constraints*.txt` | p. 21 |
| `.bin` | p. 31 | `.hcl` | p. 24 | `.php` | p. 8 | `.tfvars` | p. 24 | `Dockerfile*` | p. 25 |
| `.bz2` | p. 32 | `.hpp` | p. 11 | `.pom` | p. 22 | `.tgz` | p. 32 | `GNUmakefile*` | p. 18 |
| `.c` | p. 11 | `.htm` | p. 26 | `.ps1` | p. 16 | `.ts` | p. 6 | `gradle-wrapper.properties` | p. 20 |
| `.cc` | p. 11 | `.html` | p. 26 | `.ps1xml` | p. 16 | `.tsx` | p. 6 | `gradle.properties` | p. 20 |
| `.cdxml` | p. 16 | `.jar` | p. 33 | `.psc1` | p. 16 | `.txt` | p. 30 | `Makefile*` | p. 18 |
| `.cjs` | p. 6 | `.java` | p. 7 | `.psd1` | p. 16 | `.war` | p. 33 | `makefile*` | p. 18 |
| `.cmake` | p. 19 | `.js` | p. 6 | `.psm1` | p. 16 | `.xhtml` | p. 26 | `package.json` | p. 21 |
| `.cmd` | p. 17 | `.json` | p. 29 | `.psrc` | p. 16 | `.xml` | p. 22 | `requirements*.txt` | p. 21 |
| `.cpp` | p. 11 | `.jsx` | p. 6 | `.pssc` | p. 16 | `.xz` | p. 32 | `setup.py` | p. 5 |
| `.cs` | p. 14 | `.ksh` | p. 15 | `.py` | p. 4 | `.yaml` | p. 23 | | |
| `.dll` | p. 31 | `.kt` | p. 13 | `.rb` | p. 9 | `.yml` | p. 23 | | |
| `.dylib` | p. 31 | `.kts` | p. 13 | `.rs` | p. 12 | `.zip` | p. 32 | | |
| `.ear` | p. 33 | `.mak` | p. 18 | `.rst` | p. 30 | `.zsh` | p. 15 | | |


**Unknown extensions: p. 34**