# AI TRANSIT PIPELINE

Securing AI Code Integration in the Enterprise

---

- Secure retrieval from GitHub
- 5-layer adaptive multi-layer scan by file type
- Approved ZIP archive + Excel traceability report

# Table of Contents


01 Context & Objectives

02 Pipeline Architecture — 5 Layers

03 Phase 1 — Secure Retrieval

04 Layer 1 — Global Scan

05 Layer 2 — OWASP Top 10 / CWE Top 25

06 Layer 3 — SCA: Vulnerable Dependencies

07 Layer 4 — Universal Patterns

08 Layer 5 — Per-type SAST (11 languages)

09 Tools Used

10 Results & Deliverables

11 Absolute Security Rules

# 01 Context & Objectives

## Why this pipeline?

- AI-generated code may contain backdoors, secrets, or dangerous patterns
- Developers import code without systematic security review
- The corporate network must remain isolated (partial air-gap)
- No traceability without a structured process




## Key Objectives

### Retrieve

Secure depth-1 clone

### Scan

5-layer adaptive pipeline

### Decide


PASS→ZIP / FAIL→Quarantine

### Trace


Excel + JSON + HTML

# 02 Pipeline Architecture — 5-Layer Scanning

## Top-level Flow




## 5-Layer Scanning Cascade



# 03 Phase 1 — Secure Retrieval

### 1 Host Whitelist

Only github.com is allowed.

Any other URL is rejected immediately.

### 2 Size Verification

GitHub API queried before clone.

Limit: 500 MB.

### 3 Minimal Clone

git clone --depth 1 --no-tags

--single-branch

### 4 .git/ Removal

Git metadata removed

(hooks, remotes, submodules).

### 5 SHA-256 Manifest

Hash of each file →

.manifest_sha256.txt (audit trail).

### 6 Quick Triage

Grep: eval( exec( curl|bash

rm -rf → immediate alert.

# 04 Layer 1 — Global Scan (all files)

AV · gitleaks · detect-secrets · YARA — Applies to the ENTIRE directory, regardless of file type

## ■ Gitleaks

- > 150 credential types
- GitHub/AWS/GCP/Azure tokens
- RSA, PEM, SSH, JWT keys
- Entropy analysis + regex

FAIL if positive

## ■ detect-secrets

- Shannon entropy
- Secrets unknown to rule sets
- High-density base64/hex
- Complements Gitleaks

FAIL if positive

## ■ ClamAV / AV

- Millions of signatures
- Trojans, ransomware, backdoors
- Full recursive scan
- freshclam updated base

FAIL if positive

## ■ YARA

- Industry-standard IOC
- Custom .yar rules
- AI backdoor patterns
- Regex + boolean logic

FAIL if positive

# 05 Layer 2 — OWASP Top 10 2021 + CWE Top 25 (Semgrep)

## 4 Semgrep rulesets run against all code files

### p/owasp-top-ten

**OWASP Top 10 2021**

- A01 — Broken Access Control
- A02 — Cryptographic Failures
- A03 — Injection (SQLi, XSS, SSTI…)
- A04 — Insecure Design
- A05 — Security Misconfiguration
- A06 — Vulnerable Components
- A07 — Auth Failures
- A08 — Data Integrity Failures
- A09 — Logging & Monitoring Failures
- A10 — SSRF

### p/cwe-top-25

**CWE Top 25 Most Dangerous**

- CWE-79 XSS
- CWE-89 SQL Injection
- CWE-20 Improper Input Validation
- CWE-125 Out-of-bounds Read
- CWE-78 OS Command Injection
- CWE-416 Use After Free
- CWE-22 Path Traversal
- CWE-352 CSRF
- CWE-476 NULL Pointer Dereference
- CWE-287 Improper Authentication

### p/security-audit

**General Security Audit**

- Broad vulnerability patterns
- Misconfigurations
- Insecure API usage
- Deprecated functions
- Crypto weaknesses
- Race conditions
- Integer overflows
- Memory safety issues
- Protocol misuse
- Hardcoded values

### p/secrets

**Secrets & Credentials**

- API keys (AWS, GCP, Azure…)
- Private keys (RSA, EC, PEM)
- OAuth tokens
- Database connection strings
- JWT secrets
- Slack / Twilio / Stripe tokens
- Generic password patterns
- High-entropy strings
- Environment variable leaks
- Config file secrets

# 06 Layer 3 — SCA: Vulnerable Dependencies (OWASP A06)

## What is SCA?

Software Composition Analysis (SCA) identifies known vulnerabilities (CVEs) in third-party libraries and dependencies.

OWASP A06:2021 — Vulnerable and Outdated Components is consistently in the OWASP Top 10.

### ■ trivy

**Universal SCA scanner**

- All ecosystems (pip, npm, gem, go, cargo…)
- CVE database (NVD, OSV, GitHub Advisory)
- Scans requirements.txt, package-lock.json,
- go.sum, Gemfile.lock, Cargo.lock…
- CRITICAL / HIGH / MEDIUM / LOW severity
- Output: JSON + table report
- Also scans Dockerfiles & container images
- Regularly updated vulnerability DB

**FAIL on CRITICAL/HIGH**

### ■ pip-audit / safety

**Python — requirements*.txt**

- pip-audit: official PyPA tool (PURL-based)
- safety: PyUp.io database
- Scans requirements.txt, requirements-dev.txt
- requirements-*.txt (glob pattern)
- Maps to CVE + GHSA identifiers
- Detects yanked / abandoned packages
- Outputs FAIL on any CRITICAL finding
- Complements trivy for Python ecosystem

**FAIL on CRITICAL/HIGH**

### ■ npm audit

**JavaScript / Node — package-lock.json**

- Built-in npm command (no install needed)
- Uses npm registry advisory database
- Scans package-lock.json
- Severity: critical / high / moderate / low
- FAIL on critical or high findings
- Reports affected package tree
- Identifies fix version when available
- Covers direct and transitive dependencies

**FAIL on CRITICAL/HIGH**

# 07 Layer 4 — Universal Patterns (all files)

Pattern-matched against EVERY file regardless of language — no tool dependency

| CWE / Standard | Pattern / Rule | Example | Verdict |
|---|---|---|---|
| CWE-798 | Hardcoded credentials | password="...", api_key="..." | FAIL |
| CWE-321 | Hardcoded crypto key | BEGIN RSA PRIVATE KEY | FAIL |
| CWE-22 | Path traversal | ../../etc/passwd | FAIL |
| CWE-918 | SSRF | requests.get(url=user_input) | WARN |
| CWE-327 | Weak cryptography | md5, sha1, rc4 | WARN |
| CWE-338 | Weak PRNG | Math.random(), rand() | WARN |
| OWASP-A09 | Logging suppressed | logging.disable(logging.CRITICAL) | WARN |

# 08 Layer 5 — Per-type SAST Dispatch (11 languages)

| Extension(s) | SAST Tool | Manual Checks | Verdict |
|---|---|---|---|
| .py | Bandit | eval() exec() import os/subprocess | FAIL |
| .js .ts .jsx | Semgrep | eval() child_process require(…) | FAIL |
| .java | Semgrep | Runtime.exec() ObjectInputStream JNDI Log4Shell TrustAllCerts | FAIL |
| .php | Semgrep | shell_exec() echo $_GET include($var) unserialize() | FAIL |
| .rb | Semgrep | system/exec eval() ActiveRecord string interpolation | FAIL |
| .go | Semgrep | fmt.Sprintf in SQL math/rand TLS MinVersion | FAIL |
| .c .cpp .h | cppcheck | gets() strcpy() system() popen() | FAIL |
| .sh .bash .ps1 | ShellCheck | curl\|bash wget\|sh eval $var | FAIL |
| .yml .yaml | — | Unpinned actions inline secrets | FAIL |
| .tf .tfvars | checkov | Hardcoded secrets overly broad IAM | FAIL |
| Dockerfile | hadolint | :latest ADD http:// RUN curl\|bash | FAIL |
| .xml | — | DOCTYPE + ENTITY (XXE CWE-611) | FAIL |
| .so .exe .elf | strings | Auto FAIL + IOC strings | FAIL ■ |
| .zip .tar.gz | — | Auto FAIL — re-scan after extraction | FAIL ■ |
| .sql | — | xp_cmdshell DROP TABLE ; -- | FAIL |

# 08 Layer 5 — Per-type Check Details

## Python .py

Dynamic execution — high risk of backdoors via eval/exec

### Bandit SAST

FAIL

Python AST: subprocess shell=True, pickle, MD5, SQL, assert…

### eval() / exec()

FAIL

Arbitrary execution at runtime — trivial backdoor vector

### import os/subprocess

WARN

Shell access — requires manual review

## JavaScript .js .ts

Ecosystem exposed to supply-chain attacks

### Semgrep p/javascript

FAIL

XSS, prototype pollution, innerHTML, SSTI…

### eval()

FAIL

Dynamic execution — classic injection vector

### child_process

FAIL

Shell command execution from Node.js

# 08 Layer 5 — Per-type Check Details

## C / C++ .c .cpp

Risks from manual memory management

### cppcheck

FAIL

Buffer overflows, null ptr, use-after-free, uninit memory.

### gets() strcpy()

FAIL

Unbounded read/copy → buffer overflow

### system() popen()

FAIL

Shell command execution → possible injection

## Shell .sh .bash

Direct execution — command obfuscation is trivial

### ShellCheck

FAIL

Unquoted variables, globbing, dangerous redirections…

### curl | bash

FAIL

Remote code execution without integrity check

### eval $variable

FAIL

Trivial injection if variable controlled by attacker

# 08 Layer 5 — Per-type Check Details

## YAML / CI .yml

CI/CD pipelines — a bad config opens backdoors

### Unpinned actions

FAIL

uses: action@main → vulnerable to tag-hijacking

### Inline secrets

FAIL

password: value (not ${{ secrets.XXX }})

## Terraform .tf

IaC — can provision entire cloud resources

### checkov (CIS)

FAIL

S3 buckets, overly broad IAM, DB without at-rest encryption

### Hardcoded secrets

FAIL

password = "value" in .tf/.tfvars

# 08 Layer 5 — New Languages: Java · PHP · Ruby · Go · XML

## Java .java

Runtime reflection & deserialization — critical attack surface

### Runtime.exec() (CWE-78)

FAIL

OS command injection via Java runtime shell execution

### ObjectInputStream (CWE-502)

FAIL

Deserialization of untrusted data — RCE vector

### Log4Shell JNDI (CVE-2021-44228)

FAIL

JNDI lookup in log messages → critical 0-day pattern

### TrustAllCerts (CWE-295)

FAIL

Disabled TLS certificate validation → MITM

## PHP .php

Direct user input to shell / output — classic web attack surface

### shell_exec() (CWE-78)

FAIL

Direct shell execution with user-controlled input

### echo $_GET (CWE-79)

FAIL

Reflected XSS — user input echoed without sanitization

### include($var) (CWE-22)

FAIL

Remote/local file inclusion via variable path

### unserialize() (CWE-502)

FAIL

PHP deserialization → object injection & RCE

# 08 Layer 5 — New Languages: Java · PHP · Ruby · Go · XML

## Ruby .rb

Metaprogramming power creates significant injection risk

**system/exec (CWE-78)** — FAIL

Shell command injection via system() or exec()

**eval() (CWE-95)** — FAIL

Dynamic code evaluation — trivial code injection

**ActiveRecord interpolation (CWE-89)** — FAIL

SQL injection via string interpolation in queries

## Go .go

Low-level control — subtle SQL and crypto pitfalls

**fmt.Sprintf in SQL (CWE-89)** — FAIL

String-formatted SQL queries → SQL injection

**math/rand (CWE-338)** — WARN

Weak PRNG — not cryptographically secure

**TLS MinVersion (CWE-326)** — FAIL

Weak TLS version allowed (< TLS 1.2)

# 08 Layer 5 — New Languages: Java · PHP · Ruby · Go · XML

## XML .xml

XML External Entity (XXE) — file read & SSRF via XML parsers

### DOCTYPE + ENTITY (CWE-611)

FAIL

XXE: reads local files or makes internal HTTP requests

### SYSTEM entity

FAIL

<!ENTITY xxe SYSTEM 'file:///etc/passwd'>

# 08 Layer 5 — Dockerfile · Binaries · Archives · SQL

## Dockerfile

- **hadolint** — FAIL

CIS Docker: :latest, ADD http://, apt without --no-install-recommends

- **RUN curl|bash** — FAIL

Download + execution without integrity control

## Binaries .so .exe .elf

- **Auto FAIL** — FAIL

No binaries in an AI repo — potential implant/RAT

- **strings + IOC** — FAIL

/bin/sh /etc/passwd exec reverse shell URLs detected

## Archives .zip .tar.gz

- **Auto FAIL** — FAIL

Content cannot be scanned without prior extraction

- **Zip-slip** — FAIL

Extraction to arbitrary paths (../../etc/cron.d/)

## SQL .sql

- **xp_cmdshell** — FAIL

Shell command execution from SQL Server → critical IOC

- **DROP TABLE / --** — FAIL

Destructive statements + SQL injection pattern

# 09 Tools Used — Summary

All optional in degraded mode — WARN if absent, FAIL only on active finding

| Tool | Role | Installation | Scope |
|---|---|---|---|
| Gitleaks | secrets/tokens | GitHub binary | L1 Global |
| detect-secrets | high entropy | pip install | L1 Global |
| ClamAV | malware signatures | apt install clamav | L1 Global |
| YARA | custom IOC | apt install yara | L1 Global |
| Semgrep | OWASP/CWE rulesets (×4) | pip install semgrep | L2 OWASP/CWE |
| trivy | SCA universal CVE scan | GitHub binary | L3 SCA |
| pip-audit | Python SCA (PyPA) | pip install pip-audit | L3 SCA |
| safety | Python SCA (PyUp.io) | pip install safety | L3 SCA |
| npm audit | Node.js SCA (built-in) | built-in npm | L3 SCA |
| Bandit | Python SAST | pip install bandit | L5 .py |
| cppcheck | C/C++ static analysis | apt install cppcheck | L5 .c .cpp |
| ShellCheck | shell linting | apt install shellcheck | L5 .sh |
| hadolint | Dockerfile linting | GitHub binary | L5 Docker |
| checkov | IaC security | pip install checkov | L5 .tf |
| jq | GitHub API JSON parsing | apt install jq | Utility |

# 10 Results — ZIP Archive & Excel Report

## ■ ZIP Archive → Good/

```
Good/
■■■ repo_20260615_143022.zip
    ■■■ src/
    ■   ■■■ [full source code]
    ■■■ README.md
    ■■■ scan_report_20260615.xlsx
```

- ✔ Produced only if verdict is PASS
- ✔ Timestamped name — guaranteed uniqueness
- ✔ .manifest_sha256.txt excluded
- ✔ Excel report included directly
- ✔ Ready for internal network transfer
- ✔ Optional: GPG encryption

## ■ Excel Report (.xlsx)

### Tab 0 — Summary

| | |
|---|---|
| **Repository / Source** | GitHub URL or local path |
| **Scan Date** | ISO 8601 timestamp |
| **SHA-256 Hash** | Global fingerprint of all files |
| **Verdict** | PASS (green) / FAIL (red) |
| **Counters** | PASS · WARN · FAIL |

### Tab 1 — Files (one row per file)

| # | File | Type | Status | Message |
|---|---|---|---|---|
| 1 | src/main.py | .py | FAIL | bandit:HIGH |
| 2 | config.sh | .sh | WARN | shellcheck absent |
| 3 | README.md | .md | PASS | — |

Sorted FAIL→WARN→PASS | Auto-filter | Row 1 frozen

# 11 Absolute Security Rules

■ **These rules CANNOT be modified — they constitute the threat model**

## ■ Network Isolation

The transit machine NEVER has direct access to the corporate network.

## ➡ One-way Flow

Only approved/ is readable from the inside — not fetch/, logs/, quarantine/.

## ■ Root-only Quarantine

chmod 700 — no application user can read rejected files.

## ■ No Manual Move

Never quarantine/ → approved/ without a full pipeline re-scan.

## ■ Binaries = Absolute FAIL

No .so/.exe/.elf in an AI repo — zero exceptions.

## ■ Archives = Mandatory Re-scan

.zip/.tar.gz → extraction + re-scan in a dedicated isolated environment.

# Success Criteria per Tool



## Success Criteria — Layer 1 (Global) & Layer 2 (OWASP/CWE)

| Layer | Tool | PASS | WARN | FAIL | Standard |
|---|---|---|---|---|---|
| L1 | gitleaks | 0 secrets found | — | ≥1 credential match | CWE-798 / OWASP A02 |
| L1 | detect-secrets | 0 high-entropy hits | — | ≥1 entropy hit | CWE-798 / OWASP A02 |
| L1 | ClamAV | 0 signatures matched | DB not updated | ≥1 malware signature | OWASP A08 / CERT |
| L1 | YARA | 0 IOC rules triggered | Custom rules absent | ≥1 YARA rule hit | MITRE ATT&CK / IOC |
| L2 | Semgrep p/owasp-top-ten | 0 findings | Semgrep not found | ≥1 HIGH/CRITICAL | OWASP Top 10 2021 |
| L2 | Semgrep p/cwe-top-25 | 0 findings | — | ≥1 HIGH/CRITICAL | CWE Top 25 |
| L2 | Semgrep p/security-audit | 0 findings | — | ≥1 HIGH/CRITICAL | OWASP / CERT |
| L2 | Semgrep p/secrets | 0 findings | — | ≥1 secret detected | CWE-798 / OWASP A02 |

All L1 findings → FAIL | L2 findings scored by severity: HIGH/CRITICAL → FAIL, MEDIUM → WARN

# Success Criteria per Tool



## Success Criteria — Layer 3 (SCA) & Layer 4 (Universal Patterns)

| Layer | Tool | PASS | WARN | FAIL | CWE / OWASP |
|---|---|---|---|---|---|
| L3 | trivy | 0 CVEs CRITICAL/HIGH | MEDIUM CVE found | ≥1 CRITICAL/HIGH CVE | OWASP A06 / NVD |
| L3 | pip-audit / safety | 0 vulnerable pkgs | Outdated package | ≥1 known CVE in reqs | OWASP A06 / PyPA |
| L3 | npm audit | 0 critical/high | moderate advisory | critical or high vuln | OWASP A06 / npm |
| L4 | Hardcoded creds | 0 matches | — | password= / api_key= | CWE-798 |
| L4 | Hardcoded crypto | 0 matches | — | BEGIN RSA PRIVATE KEY | CWE-321 |
| L4 | Path traversal | 0 matches | — | ../../etc/passwd | CWE-22 |
| L4 | SSRF pattern | 0 matches | user_input in URL | — | CWE-918 / OWASP A10 |
| L4 | Weak crypto | 0 matches | md5 / sha1 / rc4 | — | CWE-327 |
| L4 | Weak PRNG | 0 matches | Math.random()/rand() | — | CWE-338 |
| L4 | Logging disabled | 0 matches | logging.disable(…) | — | OWASP A09 |

L3: CRITICAL/HIGH CVE → FAIL | L4: hardcoded secrets/traversal → FAIL; weak patterns → WARN

# Success Criteria per Tool



## Success Criteria — Layer 5 (Per-type SAST) — Summary Matrix

| Lang / Type | Key Tool | # Checks | Verdict if triggered | Key Standards |
|---|---|---|---|---|
| L5 **Python .py** | Bandit | 50+ | FAIL | CWE-78, CWE-89, CWE-94, OWASP A03 |
| L5 **JS / TS .js .ts** | Semgrep | 40+ | FAIL | CWE-79, CWE-94, OWASP A03 XSS/Injection |
| L5 **C / C++ .c .cpp** | cppcheck | 30+ | FAIL | CWE-120, CWE-125, CWE-416, CERT-C |
| L5 **Shell .sh .bash** | ShellCheck | 20+ | FAIL | CWE-78, OWASP A03, CERT |
| L5 **Java .java** | Semgrep | 25+ | FAIL | CWE-78, CWE-502, CVE-2021-44228, CWE-295 |
| L5 **PHP .php** | Semgrep | 20+ | FAIL | CWE-78, CWE-79, CWE-22, CWE-502 |
| L5 **Ruby .rb** | Semgrep | 15+ | FAIL | CWE-78, CWE-89, CWE-95 |
| L5 **Go .go** | Semgrep | 15+ | FAIL/WARN | CWE-89, CWE-326, CWE-338 |
| L5 **XML .xml** | grep (regex) | 2 | FAIL | CWE-611 (XXE) |
| L5 **YAML .yml** | — (regex) | 2 | FAIL | Supply-chain / OWASP A08 |
| L5 **Terraform .tf** | checkov | 50+ | FAIL | CIS Benchmarks, OWASP A05, CWE-798 |
| L5 **Dockerfile** | hadolint | 30+ | FAIL | CIS Docker Benchmark, OWASP A05 |
| L5 **SQL .sql** | grep (regex) | 3 | FAIL | CWE-89, CWE-78 |
| L5 **Binary .so .exe** | strings+Auto | — | FAIL ■ | Auto-FAIL policy — no binaries in AI repos |
| L5 **Archive .zip .tar** | — (policy) | — | FAIL ■ | Auto-FAIL — re-scan after extraction |

All L5 positive findings → FAIL | Missing tool → WARN (degraded mode) | Binaries & Archives → Auto-FAIL

# betterleaks



PURPOSE

Detects secrets, credentials and API keys embedded in source files. Successor to gitleaks — maintained by the same author with a more expressive allowlist system. Scans all file types, not just git history.

INSTALL

```
go install github.com/betterleaks/betterleaks@latest
  brew install betterleaks
```

SCAN COMMAND

```
betterleaks dir <repo_dir> -v
```

✔ Works OFFLINE

✓ PASS condition

Exit code 0 — no secrets or credentials detected in any file.

✘ FAIL condition → pipeline blocked

Exit code ≠ 0 — at least one secret pattern matched (API key, token, password, private key …). → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

Tool not installed → scan skipped, WARN logged (degraded mode).

# detect-secrets



PURPOSE

Entropy-based secret detector — complements betterleaks with a different detection engine. Uses Shannon entropy and regex rules to find high-entropy strings that look like secrets.

INSTALL

```
pip install detect-secrets
```

SCAN COMMAND

```
detect-secrets scan <repo_dir>
```

✔ Works OFFLINE

✓ PASS condition

JSON output with empty 'results' dict — no high-entropy secrets found.

✘ FAIL condition → pipeline blocked

JSON output lists one or more findings → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

Tool not installed → scan skipped, WARN logged.

# ClamAV (clamscan)



PURPOSE

Open-source antivirus engine. Scans all files against a database of known malware signatures. Requires periodic DB updates via freshclam to stay effective against recent threats.

INSTALL

```
sudo apt-get install clamav clamav-daemon
sudo freshclam   # update DB
```

SCAN COMMAND

```
clamscan -r --no-summary <repo_dir>
```

✔ Works OFFLINE

✓ PASS condition

Exit code 0 — no virus signatures matched.

✘ FAIL condition → pipeline blocked

Exit code 1 — at least one infected file found → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

freshclam DB not updated (>7 days) → WARN. Tool missing → WARN.

# YARA



PURPOSE

Pattern-matching engine for malware and IOC detection. Loads all .yar rule files from yara-rules/ and matches them against every file. Rules are fully customisable — add organisation-specific IOC patterns.

INSTALL

```
sudo apt-get install yara
```

SCAN COMMAND

```
yara -r <rules_dir>/*.yar <repo_dir>
```

✔ Works OFFLINE

✓ PASS condition

No output — no rule matched any file.

✘ FAIL condition → pipeline blocked

At least one YARA rule matched → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

No .yar files in yara-rules/ → WARN. Tool missing → WARN.

# Semgrep



PURPOSE

Static analysis engine with a large open rule library.

Runs four rulesets: p/owasp-top-ten, p/cwe-top-25, p/security-audit, p/secrets. Covers injection, XSS, insecure deserialization, SSRF, weak crypto and 100+ more patterns.

INSTALL

```
pip install semgrep
```

SCAN COMMAND

```
semgrep --config p/owasp-top-ten --config p/cwe-top-25
  --config p/security-audit --config p/secrets
  --json <repo_dir>
```

■ Requires INTERNET (first run)

✓ PASS condition

JSON output with empty 'results' list — no rule matched.

✘ FAIL condition → pipeline blocked

ERROR or WARNING severity findings → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

INFO severity → WARN. Tool missing or no internet → WARN.

# trivy



PURPOSE

Software Composition Analysis — scans dependency manifests (requirements.txt, package-lock.json, go.sum, pom.xml …) and cross-references installed packages against NVD, OSV and GitHub Advisory databases to find known CVEs.

INSTALL

```
curl -sfL https://raw.githubusercontent.com/aquasecurity/trivy/
  main/contrib/install.sh | sh -s -- -b /usr/local/bin
```

SCAN COMMAND

```
trivy fs <repo_dir> --scanners vuln
  --severity HIGH,CRITICAL --format json
```

■ Requires INTERNET (first run)

✓ PASS condition

JSON output with no vulnerabilities at HIGH or CRITICAL severity.

✘ FAIL condition → pipeline blocked

CRITICAL or HIGH CVE found in a dependency → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

MEDIUM/LOW CVE → WARN. DB not up to date → WARN. Missing → WARN.

# pip-audit



PURPOSE

Audits Python requirements files against the Python Packaging Advisory Database (PyPA) and OSV. Checks requirements.txt, requirements*.txt and setup.cfg for packages with known CVEs.

INSTALL

```
pip install pip-audit
```

SCAN COMMAND

```
pip-audit -r requirements.txt --format json
```

■ Requires INTERNET (first run)

✓ PASS condition

JSON output with no vulnerabilities listed.

✘ FAIL condition → pipeline blocked

Any CVE found in a Python dependency → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

Tool missing → WARN, scan skipped.

# safety



PURPOSE

Checks Python dependencies against the Safety DB — a curated advisory database maintained by PyUp.io. Complements pip-audit with additional advisories not always in OSV.

INSTALL

```
pip install safety
```

SCAN COMMAND

```
safety check -r requirements.txt --json
```

■ Requires INTERNET (first run)

✓ PASS condition

Exit code 0 — no advisories matched.

✘ FAIL condition → pipeline blocked

Any advisory matched → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

Tool missing or DB unreachable → WARN.

# npm audit



PURPOSE

Built into npm — audits package-lock.json against the npm security advisory registry. Finds known CVEs in Node.js dependencies and their transitive dependencies.

INSTALL

```
sudo apt-get install nodejs npm
(or: nvm install --lts)
```

SCAN COMMAND

```
npm audit --json   (run in dir with package-lock.json)
```

■ Requires INTERNET (first run)

✓ PASS condition

JSON output with 0 vulnerabilities at high or critical level.

✘ FAIL condition → pipeline blocked

Critical or high severity advisory found → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

Moderate/low → WARN. No package-lock.json → scan skipped.

# grep  (universal patterns)



PURPOSE

Runs on every file regardless of extension. Checks for:

CWE-798 (hardcoded credentials), CWE-22 (path traversal),

CWE-918 (SSRF patterns), CWE-327 (weak crypto constants),

CWE-338 (weak PRNG), OWASP-A09 (logging of sensitive data).

INSTALL

```
Built-in — no installation required
```

SCAN COMMAND

```
grep -rE '<pattern>' <file>   (run per-pattern, per-file)
```

✔ Works OFFLINE

✓ PASS condition

No pattern matches across all CWE checks for this file.

✘ FAIL condition → pipeline blocked

Any pattern match → finding recorded. Severity determines WARN or FAIL.

■ WARN condition → logged, pipeline continues

N/A — grep is always available.

# Bandit



PURPOSE

Python-specific static analyser. Detects common security issues:
use of assert, subprocess with shell=True, hardcoded passwords,
use of pickle, XML vulnerabilities, SQL injection via string format,
insecure random, weak hashing, and more (100+ plugins).

INSTALL

```
pip install bandit
```

SCAN COMMAND

```
bandit -ll -r <python_file_or_dir>
```

✔ Works OFFLINE

✔ PASS condition

Exit code 0 — no medium or high confidence issues found.

✘ FAIL condition → pipeline blocked

MEDIUM or HIGH severity + MEDIUM or HIGH confidence → FAIL.

■ WARN condition → logged, pipeline continues

LOW confidence findings → WARN. Tool missing → WARN.

# ShellCheck



PURPOSE

Static analyser for Bash/sh/dash/ksh scripts. Detects quoting errors, injection risks, undefined variables, deprecated syntax, unintended word splitting, and unsafe patterns that could lead to command injection or data leakage.

INSTALL

```
sudo apt-get install shellcheck
```

SCAN COMMAND

```
shellcheck --severity=warning <script.sh>
```

✔ Works OFFLINE

✓ PASS condition

Exit code 0 — no warnings or errors.

✘ FAIL condition → pipeline blocked

Exit code ≠ 0 (errors/warnings at warning level or above) → FAIL.

■ WARN condition → logged, pipeline continues

Tool missing → WARN.

# cppcheck



PURPOSE

Static analyser for C and C++. Detects buffer overflows, memory leaks, null-pointer dereferences, use-after-free, out-of-bounds array access, and undefined behaviour — without compiling the code.

INSTALL

```
sudo apt-get install cppcheck
```

SCAN COMMAND

```
cppcheck --enable=warning,security --error-exitcode=1 <file.cpp>
```

✔ Works OFFLINE

✓ PASS condition

Exit code 0 — no errors or security warnings.

✘ FAIL condition → pipeline blocked

Exit code 1 — at least one security or error finding → FAIL.

■ WARN condition → logged, pipeline continues

Tool missing → WARN.

# hadolint



PURPOSE

Linter for Dockerfiles. Enforces Dockerfile best practices and detects security misconfigurations: running as root, using :latest tags, unnecessary privileges, secrets in ENV/ARG, ADD vs COPY, and shell injection risks.

INSTALL

```
curl -sSL https://github.com/hadolint/hadolint/releases/
  download/v2.12.0/hadolint-Linux-x86_64 -o /usr/local/bin/hadolint
```

SCAN COMMAND

```
hadolint --failure-threshold warning <Dockerfile>
```

✔ Works OFFLINE

✓ PASS condition

Exit code 0 — no warnings or errors.

✘ FAIL condition → pipeline blocked

DL or SC rules triggered at warning level or above → FAIL.

■ WARN condition → logged, pipeline continues

Tool missing → WARN.

# checkov



PURPOSE

Static analysis for Infrastructure-as-Code: Terraform (.tf), CloudFormation, Kubernetes YAML, Ansible, ARM templates. Maps findings to CIS Benchmarks, NIST, SOC2 and OWASP. Over 1000 built-in checks.

INSTALL

```
pip install checkov
```

SCAN COMMAND

```
checkov -d <dir> --framework terraform --output json
```

✔ Works OFFLINE

✔ PASS condition

All checks pass — no FAILED checks in JSON output.

✘ FAIL condition → pipeline blocked

At least one FAILED check → Pipeline verdict: FAIL.

■ WARN condition → logged, pipeline continues

SKIPPED checks → WARN. Tool missing → WARN.

# ScanCode Toolkit



PURPOSE

Full-text licence and copyright analyser. Detects SPDX licence expressions across all source files using a library of 30 000+ licence texts. Also detects package manifests and CVEs in detected packages. Produces JSON / SPDX / CycloneDX reports.

INSTALL

```
pip install scancode-toolkit
```

SCAN COMMAND

```
scancode --license --copyright --vulnerability
  --package --json-pp report.json <repo_dir>
```

✔ Works OFFLINE

✓ PASS condition

No risky licences (GPL/AGPL/LGPL/SSPL …) detected AND no HIGH/CRITICAL CVE in detected packages.

✘ FAIL condition → pipeline blocked

CRITICAL or HIGH CVE in a detected package → FAIL.

■ WARN condition → logged, pipeline continues

Risky licence detected (score ≥ 70) → WARN (legal review required).

LOW/MEDIUM CVE → WARN. Tool missing → WARN.

# Tool Summary — Acceptance Rationale (1/2)

| Tool | Layer | Offline | ✔ PASS | ✘ FAIL | ■ WARN |
|---|---|---|---|---|---|
| betterleaks | L1 | ✔ | Exit 0 — no secrets | Secret/key detected → FAIL | Not installed → WARN |
| detect-secrets | L1 | ✔ | Empty results JSON | High-entropy string found → FAIL | Not installed → WARN |
| ClamAV | L1 | ✔ | Exit 0 — no virus | Infected file found → FAIL | DB outdated / missing → WARN |
| YARA | L1 | ✔ | No rule matched | IOC rule matched → FAIL | No rules / missing → WARN |
| Semgrep | L2 | ■ | Empty results list | ERROR/WARNING severity → FAIL | INFO / no internet → WARN |
| trivy | L3 | ■ | No HIGH/CRITICAL CVE | CRITICAL or HIGH CVE → FAIL | MEDIUM/LOW CVE → WARN |
| pip-audit | L3 | ■ | No CVE in Python deps | Any Python CVE → FAIL | Not installed → WARN |
| safety | L3 | ■ | No advisory matched | Advisory matched → FAIL | Not installed → WARN |
| npm audit | L3 | ■ | 0 critical/high vulns | Critical/high vuln → FAIL | No package-lock.json → skip |
| grep (patterns) | L4 | ✔ | No CWE pattern matched | CWE-798/22/918/327/338 hit → FAIL | N/A — always available |
| Bandit | L5 | ✔ | No medium/high issues | Medium+ severity + confidence → FAIL | Low confidence → WARN |
| ShellCheck | L5 | ✔ | Exit 0 — no warnings | Warning-level finding → FAIL | Not installed → WARN |
| cppcheck | L5 | ✔ | No errors/security warns | Security/error finding → FAIL | Not installed → WARN |
| hadolint | L5 | ✔ | Exit 0 — no warnings | DL/SC rule triggered → FAIL | Not installed → WARN |
| checkov | L5 | ✔ | All IaC checks pass | Any FAILED check → FAIL | SKIPPED checks → WARN |
| Java archive scanner | L5 | ✔ | No zip-slip, fake class or hidden executable | ../ entry, non-bytecode .class, PE/ELF as logo.png, remote Class-Path → FAIL | Any jar (bytecode not reviewed), agent, native lib, wrapper → WARN |
| Batch scanner | L5 | ✔ | No certutil/bitsadmin fetch, no encoded command | certutil -urlcache, curl\|start, Run key, UAC off, rd C:\ → FAIL | net user /add, schtasks, ExecutionPolicy Bypass → WARN |

FAIL = package blocked, moved to quarantine | WARN = logged, pipeline continues (degraded mode) | All layers must PASS for the ZIP to be released

# Tool Summary — Acceptance Rationale (2/2)

| Tool | Layer | Offline | ✔ PASS | ✘ FAIL | ■ WARN |
|---|---|---|---|---|---|
| PowerShell scanner | L5 | ✔ | No fetch-and-execute, no encoded command | irm\|iex, -enc, AMSI bypass, persistence, literal $Password → FAIL | Invoke-Expression alone, Start-Process, policy bypass → WARN |
| Credential formats | L4 | ✔ | No provider-shaped token in any file | AWS / GitHub / Stripe / Slack / Google / Anthropic … token → FAIL | JWT embedded → WARN |
| setup.py scanner | L5 | ✔ | No fetch-and-execute at install time | curl\|sh, exec of a download or decoded blob, reverse shell → FAIL | overrides install, downloads, runs a program → WARN |
| Gradle scanner | L5 | ✔ | No remote apply, no insecure repo, no spawn | apply from http, allowInsecureProtocol, "cmd".execute() → FAIL | exec / commandLine, configuration-time fetch → WARN |
| Package manifests | L5 | ✔ | No hostile install hook, no plaintext source | curl\|sh hook, http:// dependency or index, URL credential → FAIL | install hook, --trusted-host, git dependency → WARN |
| XML / Maven / Ant | L5 | ✔ | No external entity, no secret, no http repo | xxe SYSTEM, http repository, exec of a shell, secret → FAIL | external DTD, exec/antrun plugin present → WARN |
| CMake scanner | L5 | ✔ | No configure-time fetch, no secrets in set() | plaintext/unverified download, credential, hardening off → FAIL | install(CODE), shell -c, moving GIT_TAG → WARN |
| HTML scanner | L5 | ✔ | No active content, no credentials in markup | eval, http:// script, hidden iframe, cookie exfil → FAIL | innerHTML / atob / new Function → WARN |
| Makefile scanner | L5 | ✔ | No remote exec, no secrets | curl\|sh, reverse shell, credential, persistence → FAIL | sudo / chmod 777 / plaintext http → WARN |
| PDF scanner | L5 | ✔ | No active content | JavaScript / auto-action / Launch / embedded exe → FAIL | Encrypted or undecodable stream → WARN |
| ScanCode | L6 | ✔ | No risky licence, no CVE | CRITICAL/HIGH CVE in pkg → FAIL | Risky licence (GPL…) → WARN |

FAIL = package blocked, moved to quarantine | WARN = logged, pipeline continues (degraded mode) | All layers must PASS for the ZIP to be released

# Operating the Pipeline

The same scan, tuned to the situation it runs in

| FLAG | EFFECT | TYPICAL USE |
|---|---|---|
| `--quiet` | Verdict only — nothing else on stdout | CI gate |
| `--verbose` | Full per-file detail | Debugging a finding |
| `--min-severity LEVEL` | low \| medium \| high \| critical | Tune the blocking bar |
| `--since COMMIT` | Scan only files changed since COMMIT | Pull-request checks |
| `--report-only` | Always exit 0; nothing quarantined | First-pass audit |
| `--no-zip / --no-excel` | Reports only, no archive | CI, where the ZIP is discarded |

## Per-repository controls

.transitignore gitignore-style patterns — matched files are not scanned at all

.transit-allow.json {rule, path, reason} entries — downgrade a known FAIL to WARN

An allowlist entry records why a finding is accepted. Silence without a reason is how exceptions become permanent.

# How the Pipeline Verifies Itself

A scanner nobody tests is a scanner nobody should trust

## Test suite

326 assertions

- Runs with zero scanning tools installed
- Rule corpus: every finding must land on the right file
- False-positive guards for correct, safe code
- Flags, reports, archive structure, diff mode

## Continuous integration

5 jobs

- lint — shellcheck, errors fatal
- test — suite, no tools (fast signal)
- test-with-tools — scanners installed
- pins — pinned versions resolve + digest match
- docker — build, non-root, smoke tests

### Every assertion is validated by mutation

The bug each test guards against is deliberately reintroduced, and the test is confirmed to fail.
Two tests were themselves broken when first written — they passed against known-broken code.
A suite that has never been seen red proves nothing.

**Lint rules enforce two bug classes that already shipped:**

multi-character IFS — IFS=':::' is a character set, silently identical to IFS=':'
top-level 'local' — valid syntax, but aborts at runtime under set -e

# Air-Gapped Operation

Disconnected scanning, and the failure it is designed to prevent

## The risk

Several scanners fetch at SCAN time: semgrep pulls rulesets, trivy downloads a CVE database, pip-audit / safety / npm audit query advisory services. On an isolated host those calls do not fail loudly — they block on timeouts, return nothing, and Layers 2 and 3 contribute no findings while the report still shows them as having run. The result is PASS on a repository never examined.

### No preparation

- betterleaks, detect-secrets
- YARA, pattern rules
- Bandit, ShellCheck
- cppcheck, hadolint

Rules are local

### Needs staged data

- Semgrep (ruleset YAML)
- trivy (CVE database)
- ClamAV (signatures)
- checkov, ScanCode

Staged by prepare_offline_cache.sh

### No offline mode

- pip-audit
- safety
- npm audit
- ScanCode CVE lookup

Not attempted; gap is recorded

**Offline, the staged trivy database is the ONLY dependency-CVE coverage there is.**

## Proving the scan was real

Every report carries a coverage block: "L2_owasp_cwe": "ran" · "L3_dependency_cve": "skipped:trivy database not staged"

A layer can fail to run because the tool is absent OR its data was not staged — both are recorded identically, so automated consumers gate on coverage_complete rather than parsing warning text. A verdict alone cannot distinguish “clean” from “nothing was examined”.

# Summary

## Source

GitHub (whitelist)

or local path

## Fetch

Minimal clone

.git removed · SHA-256

## 6 Layers

L1→L2→L3→L4→L5→L6

16 tools · SCA · Licence

## PASS

ZIP in Good/

with Excel included

## FAIL

Quarantine

chmod 700 + report

OWASP | CWE | CERT | SCA

6-layer pipeline · OWASP · CWE · CERT · SCA · Licence (ScanCode) · Degraded mode · Timestamped reports

github.com/Gaillotte/Claude — branch claude/vigilant-carson-f8twy0