Sample Project: Writer Integration

Anonymous

Abstract

We compare baseline, main and ablation conditions using the approved smoke-task evidence. The main and baseline C1 means are 0.779900 and 0.694233, with 3 and 3 runs respectively. The observations motivate cautious follow-up within the recorded scope.

1 Introduction

We compare baseline, main and ablation methods on the approved smoke task. Pretraining and parameter-efficient adaptation motivate the comparison [1, 2]. This literature motivation does not establish that the smoke implementation reproduces those methods.

2 Related Work

BERT describes pretraining and downstream fine-tuning [1]. LoRA studies low-rank adaptation [2]. Only the supplied abstracts are available; detailed experimental settings are not inferred.

3 Method

The approved comparison contains baseline, main and ablation conditions. The bundled plan and approved process log define the scope; unavailable implementation details remain unspecified.

4 Experimental Setup

The bundled final-condition C1 score observations contain 3 main and 3 baseline runs. C2 contains 3 ablation runs. Comparisons C1 and C2 retain the supplied uncertainty and contrast statistics. Hardware details are not supplied in the evidence context.

5 Results

For C1, the mean scores for main and baseline are 0.779900 and 0.694233. The supplied 95% intervals are [0.758428, 0.801372] and [0.660009, 0.728458]. The mean difference is 0.085667 with reported p = 0.0017. For C2, the ablation mean is 0.737100 and the main-minus-ablation difference is 0.042800 (p = 0.0343). These are observations under the recorded final condition, rather than causal explanations.

6 Discussion

The observed differences may motivate further evaluation; they do not establish a general causal effect.

6.1 Limitations

The evidence covers the smoke task, with C1 group counts 3 and 3. Exclusions and suspicious-run annotations retain their recorded meaning. Local offline citation checks do not verify scientific claims online, and abstract-only access does not support reconstruction of unavailable experimental details.

7 Conclusion

The supplied C1 and C2 observations suggest further investigation within the recorded scope; they do not establish performance on new tasks.

References

[1] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *NAACL*, 2019.

[2] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. Lora: Low-rank adaptation of large language models. In *ICLR*, 2022.