



Authentication	none
Source Code	shell

# Solar

```
# Install the command line client
$ pip install coreapi-cli
```

## app

### v2 > app\_flights > list

GET

/api/app/v2/app\_flights/

App相关架次的创建、查询、删除、更新

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > app_flights > list
```

### v2 > app\_flights > create

POST

/api/app/v2/app\_flights/

App相关架次的创建、查询、删除、更新

⇌ INTERACT

#### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	架次名/任务名
project_id <div>required</div>	项目id
operator_id <div>required</div>	执行人id
flight_plan_config	规划配置
flight_plan_start_time	计划执行时间
is_auto_upload <div>required</div>	是否自动上传

Parameter	Description
flight_type	飞行模式（类型）
drone_id	选用无人机id
address <div>required</div>	飞行地址
app_plan_config	app配置
location	架次坐标
status_desc	
status	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > app_flights > create -p name=... -p project_id=... -p operato
```

v2 > app\_flights > read

⇌ INTERACT

GET

 /api/app/v2/app\_flights/{id}/  
App相关架次的创建、查询、删除、更新

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > app_flights > read -p id=...
```

v2 > app\_flights > update

⇌ INTERACT

PUT

 /api/app/v2/app\_flights/{id}/  
App相关架次的创建、查询、删除、更新

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
operator_id	
data_url	
flight_plan_config	
flight_plan_start_time	计划执行时间
flight_exec_report_url	
is_auto_upload	
flight_type	
flight_exec_start_time	架次执行时间
flight_exec_end_time	架次结束时间
is_deleted	
status	
status_desc	
report_url	
app_plan_config	
location	
drone_id	选用无人机id

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > app_flights > update -p id=... -p name=... -p operator_id=...
```

v2 > app\_flights > partial\_update

App相关架次的创建、查询、删除、更新

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
operator_id	
data_url	
flight_plan_config	
flight_plan_start_time	计划执行时间
flight_exec_report_url	
is_auto_upload	
flight_type	
flight_exec_start_time	架次执行时间
flight_exec_end_time	架次结束时间
is_deleted	
status	
status_desc	
report_url	
app_plan_config	
location	
drone_id	选用无人机id

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > app_flights > partial_update -p id=... -p name=... -p operation=...
```

v2 > app\_flights > delete

DELETE

 /api/app/v2/app\_flights/{id}/ 

⇌ INTERACT

App相关架次的创建、查询、删除、更新

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > app_flights > delete -p id=...
```

v2 > company > projects > list

GET

 /api/app/v2/company/projects/ 

⇌ INTERACT

app项目 与web创建项目不一致只有智飞套件一种应用

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
p	A page number within the paginated result set.
page_size	Number of results to return per page.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > company > projects > list -p p=... -p page_size=...
```

v2 > company > projects > read

GET

 /api/app/v2/company/projects/{id}/ 

⇌ INTERACT

app项目 与web创建项目不一致只有智飞套件一种应用

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > company > projects > read -p id=...
```

v2 > company\_drone\_info > list

⇌ INTERACT

GET

 /api/app/v2/company\_drone\_info/  
app端连接无人机后获取无人机信息，以便更新状态对接直播

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > company_drone_info > list
```

v2 > company\_drone\_update > update

⇌ INTERACT

PUT

 /api/app/v2/company\_drone\_update/{id}/  
app更新无人机状态

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
status_code	
location	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > company_drone_update > update -p id=... -p status_code=... -p
```

v2 > company\_drone\_update > partial\_update

PATCH

/api/app/v2/company\_drone\_update/{id}/

app更新无人机状态

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
status_code	
location	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > company_drone_update > partial_update -p id=... -p status_coc
```

v2 > login > create

POST

/api/app/v2/login/

登录

⇌ INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
phone_num <div>required</div>	手机号
password <div>required</div>	密码

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > login > create -p phone_num=... -p password=...
```

v2 > smart\_flight\_resources > list

GET

/api/app/v2/smart\_flight\_resources/

智飞套件资源管理

⇌ INTERACT

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > smart_flight_resources > list -p name=... -p project_id=...
```

v2 > smart\_flight\_resources > create

POST

/api/app/v2/smart\_flight\_resources/

智飞套件资源管理

⇌ INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
project_id <div>required</div>	项目id
name	资源名称
resources_type <div>required</div>	资源类型
resources_url <div>required</div>	资源地址
resources_size <div>required</div>	资源大小
accuracy	



Parameter	Description
difference	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > smart_flight_resources > create -p project_id=... -p name=...
```

v2 > smart\_flight\_resources > read

⇌ INTERACT

**GET** /api/app/v2/smart\_flight\_resources/{id}/  
智飞套件资源管理

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > smart_flight_resources > read -p id=... -p name=... -p project_id=...
```

v2 > smart\_flight\_resources > update

⇌ INTERACT

**PUT** /api/app/v2/smart\_flight\_resources/{id}/  
智飞套件资源管理

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
resources_url	
resources_size	
is_deleted	
difference	
accuracy	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > smart_flight_resources > update -p id=... -p name=... -p res...
```

v2 > smart\_flight\_resources > partial\_update

PATCH

 /api/app/v2/smart\_flight\_resources/{id}/  
智飞套件资源管理

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
-----------	-------------

Parameter	Description
id <div>required</div>	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
resources_url	
resources_size	
is_deleted	
difference	
accuracy	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > smart_flight_resources > partial_update -p id=... -p name=...
```

v2 > task\_flights > create

POST

 /api/app/v2/task\_flights/  
app 任务列表信息

⇌ INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
-----------	-------------

Parameter	Description
project_id <div>required</div>	项目id
p	页数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action app v2 > task_flights > create -p project_id=... -p p=...
```

# auto

## v2 > auto\_queue\_pv\_detection\_tasks > list

GET

 /api/auto/v2/auto\_queue\_pv\_detection\_tasks 

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action auto v2 > auto_queue_pv_detection_tasks > list
```

## v2 > pv\_detection > update

PUT

 /api/auto/v2/pv\_detection/{id}/ 

⇌ INTERACT

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
raw_data_url	原始数据地址
model_url	模型地址
model_format	模型格式
proceed_time	

Parameter	Description
proceed_duration_time	处理时长
proceed_summary	总结
status	状态
status_desc	状态描述
report_url	报告地址
is_deleted	是否删除
raw_data_config	原始数据配置
station_name	电站名称
defect_num	缺陷数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action auto v2 > pv_detection > update -p id=... -p raw_data_url=... -p model=...
```

v2 > pv\_detection > partial\_update

⇌ INTERACT

PATCH /api/auto/v2/pv\_detection/{id}/

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
raw_data_url	原始数据地址
model_url	模型地址
model_format	模型格式
proceed_time	

Parameter	Description
proceed_duration_time	处理时长
proceed_summary	总结
status	状态
status_desc	状态描述
report_url	报告地址
is_deleted	是否删除
raw_data_config	原始数据配置
station_name	电站名称
defect_num	缺陷数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action auto v2 > pv_detection > partial_update -p id=... -p raw_data_url=...
```

# web

## v2 > app\_config > create

⇌ INTERACT

**POST** /api/web/v2/app\_config/  
创建应用配置

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
app_id <b>required</b>	appld

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > app_config > create -p app_id=...
```

## v2 > applications > list

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > applications > list
```

## v2 > applications > create

POST

/api/web/v2/applications/应用

⇌ INTERACT

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
brief	
keywords	
contents	
price	
sale_price	
price_date_period	
load_url	
is_auto	
is_private	
application_step	
pre_data_type	
pre_applications_ids	
owner_id	
industry_id	行业id
output_data_type	
logo	

Parameter	Description
is_deleted	是否删除
version	
version_date	
version_desc	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > applications > create -p name=... -p brief=... -p keywords=...
```

v2 > applications > read

GET

/api/web/v2/applications/{id}/

应用

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > applications > read -p id=...
```

v2 > applications > update

PUT

/api/web/v2/applications/{id}/

应用

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.



Parameter	Description
name	
brief	
keywords	
contents	
price	
sale_price	
price_date_period	
load_url	
is_auto	
is_private	
application_step	
pre_data_type	
pre_applications_ids	
owner_id	
industry_id	行业id
output_data_type	
logo	
is_deleted	是否删除
version	
version_date	
version_desc	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > applications > update -p id=... -p name=... -p brief=... -p k
```

v2 > applications > partial\_update

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
brief	
keywords	
contents	
price	
sale_price	
price_date_period	
load_url	
is_auto	
is_private	
application_step	
pre_data_type	
pre_applications_ids	
owner_id	
industry_id	行业id
output_data_type	
logo	
is_deleted	是否删除
version	

Parameter	Description
version_date	
version_desc	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > applications > partial_update -p id=... -p name=... -p brief=...
```

v2 > base64 > create

⇌ INTERACT

**POST** /api/web/v2/base64/  
图片转64码

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > base64 > create
```

v2 > check\_verifycode > create

⇌ INTERACT

**POST** /api/web/v2/check\_verifycode/

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > check_verifycode > create
```

v2 > codes > create

⇌ INTERACT

**POST** /api/web/v2/codes/  
发送短信验证码

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
phone_num <b>required</b>	手机号
send_type	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > codes > create -p phone_num=... -p send_type=...
```

v2 > common\_flights > list

⇌ INTERACT

**GET** /api/web/v2/common\_flights/  
架次的创建、修改、查询、删除（web）

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > common_flights > list
```

v2 > common\_flights > create

⇌ INTERACT

**POST** /api/web/v2/common\_flights/  
架次的创建、修改、查询、删除（web）

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
task_id <b>required</b>	任务id
project_id <b>required</b>	项目id
operator_id	执行人id
flight_plan_config	规划配置
flight_plan_start_time	计划执行时间
is_auto_upload <b>required</b>	是否自动上传
flight_type	飞行模式（类型）
drone_id	选用无人机id
task_application_id <b>required</b>	任务应用id
app_plan_config	app_config

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > common_flights > create -p task_id=... -p project_id=... -p c
```

v2 > common\_flights > read

GET

/api/web/v2/common\_flights/{id}/

⇌ INTERACT

架次的创建、修改、查询、删除（web）

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > common_flights > read -p id=...
```

v2 > common\_flights > update

PUT

/api/web/v2/common\_flights/{id}/

⇌ INTERACT

架次的创建、修改、查询、删除（web）

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
operator_id	
data_url	
flight_plan_config	

Parameter	Description
flight_plan_start_time	计划执行时间
flight_exec_report_url	
is_auto_upload	
flight_type	
flight_exec_start_time	架次执行时间
flight_exec_end_time	架次结束时间
is_deleted	
status	
status_desc	
report_url	
app_plan_config	
location	
drone_id	选用无人机id

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > common_flights > update -p id=... -p name=... -p operator_id=...
```

v2 > common\_flights > partial\_update

⇌ INTERACT

**PATCH** /api/web/v2/common\_flights/{id}/  
架次的创建、修改、查询、删除（web）

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
operator_id	
data_url	
flight_plan_config	
flight_plan_start_time	计划执行时间
flight_exec_report_url	
is_auto_upload	
flight_type	
flight_exec_start_time	架次执行时间
flight_exec_end_time	架次结束时间
is_deleted	
status	
status_desc	
report_url	
app_plan_config	
location	
drone_id	选用无人机id

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > common_flights > partial_update -p id=... -p name=... -p oper
```

v2 > company > app\_temp\_config > create

POST

/api/web/v2/company/app\_temp\_config/

创建应用配置

INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
-----------	-------------

Parameter	Description
app_id <div>required</div>	appld

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > app_temp_config > create -p app_id=...
```

v2 > company > apps > list

GET

 /api/web/v2/company/apps/ 

⇌ INTERACT

获取用户能使用的app

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > apps > list
```

v2 > company > apps > read

GET

 /api/web/v2/company/apps/{id}/ 

⇌ INTERACT

获取用户能使用的app

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this 系统应用.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > apps > read -p id=...
```

v2 > company > defects > list

GET

 /api/web/v2/company/defects/ 

⇌ INTERACT

缺陷



```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > defects > list
```

v2 > company > defects > create

⇌ INTERACT

**POST** /api/web/v2/company/defects/  
缺陷

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
pv_detection_id <b>required</b>	缺陷检测id
defect_data <b>required</b>	缺陷数据

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > defects > create -p pv_detection_id=... -p defect_c
```

v2 > company > defects > update

⇌ INTERACT

**PUT** /api/web/v2/company/defects/{id}/  
缺陷

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
defect_type	缺陷类型
name	
light_name	

Parameter	Description
light_url	
infrared_name	
infrared_url	
longitude	
latitude	
altitude	
region	
status	
is_deleted	
create_date	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > defects > update -p id=... -p defect_type=... -p na
```

v2 > company > defects > partial\_update

PATCH /api/web/v2/company/defects/{id}/

缺陷

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
defect_type	缺陷类型
name	

Parameter	Description
light_name	
light_url	
infrared_name	
infrared_url	
longitude	
latitude	
altitude	
region	
status	
is_deleted	
create_date	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > defects > partial_update -p id=... -p defect_type=.
```

v2 > company > destroy\_user > update

**PUT** /api/web/v2/company/destroy\_user/{id}/  
公司管理员移除用户

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
is_deleted <b>required</b>	删除

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > destroy_user > update -p id=... -p is_deleted=...
```

v2 > company > destroy\_user > partial\_update

PATCH

/api/web/v2/company/destroy\_user/{id}/

公司管理员移除用户

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
is_deleted	删除

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > destroy_user > partial_update -p id=... -p is_delet
```

v2 > company > drones > list

GET

/api/web/v2/company/drones/

公司无人机管理

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > drones > list
```

v2 > company > drones > create

POST

/api/web/v2/company/drones/

公司无人机管理

⇌ INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <span>required</span>	无人机名称
drone_id <span>required</span>	无人机id
the_drone_sn <span>required</span>	无人机系列号
control_sn	飞控序列号
purchaser	购买人
purchase_time	购买时间

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > drones > create -p name=... -p drone_id=... -p the_

```

v2 > company > drones > read

⇌ INTERACT

GET /api/web/v2/company/drones/{id}/  
公司无人机管理

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > drones > read -p id=...

```

v2 > company > drones > update

⇌ INTERACT

PUT /api/web/v2/company/drones/{id}/  
公司无人机管理

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
-----------	-------------

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
purchase_time	购买时间
drone_name	
drone_model	
drone_brand	
drone_sn	
fly_control_sn	
register_date	
is_deleted	
status_code	
location	
push_url	
live_url	
pilot_id	
purchaser	
register_user	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > drones > update -p id=... -p purchase_time=... -p c
```

v2 > company > drones > partial\_update

PATCH

/api/web/v2/company/drones/{id}/

公司无人机管理

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
purchase_time	购买时间
drone_name	
drone_model	
drone_brand	
drone_sn	
fly_control_sn	
register_date	
is_deleted	
status_code	
location	
push_url	
live_url	
pilot_id	
purchaser	
register_user	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > drones > partial_update -p id=... -p purchase_time=...
```

v2 > company > get\_task\_applications\_info > create

⇌ INTERACT

POST

/api/web/v2/company/get\_task\_applications\_info/

任务应用信息

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
project_id <div>required</div>	项目id
p	页数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > get_task_applications_info > create -p project_id=.
```

v2 > company > mobile\_device > list

⇌ INTERACT

GET

/api/web/v2/company/mobile\_device/

公司移动设备

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > mobile_device > list
```

v2 > company > mobile\_device > create

⇌ INTERACT

POST

/api/web/v2/company/mobile\_device/

公司移动设备

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <div>required</div>	公司移动设备名称
device_id <div>required</div>	移动设备id
the_device_sn <div>required</div>	移动设备系列号
purchaser	购买人
purchase_time	购买时间



```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > mobile_device > create -p name=... -p device_id=...
```

v2 > company > mobile\_device > read

GET

/api/web/v2/company/mobile\_device/{id}/

公司移动设备

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > mobile_device > read -p id=...
```

v2 > company > mobile\_device > update

PUT

/api/web/v2/company/mobile\_device/{id}/

公司移动设备

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
purchase_time	购买时间
device_name	
device_model	
device_brand	

Parameter	Description
device_sn	
register_date	
is_deleted	
purchaser	
register_user	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > mobile_device > update -p id=... -p purchase_time=...
```

v2 > company > mobile\_device > partial\_update

PATCH /api/web/v2/company/mobile\_device/{id}/  
公司移动设备

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
purchase_time	购买时间
device_name	
device_model	
device_brand	
device_sn	
register_date	
is_deleted	

Parameter	Description
purchaser	
register_user	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > mobile_device > partial_update -p id=... -p purchaser
```

v2 > company > payloads > list

⇌ INTERACT

**GET** /api/web/v2/company/payloads/  
公司挂载管理

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > payloads > list
```

v2 > company > payloads > create

⇌ INTERACT

**POST** /api/web/v2/company/payloads/  
公司挂载管理

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <b>required</b>	公司挂载名称
payload_id <b>required</b>	挂载id
payload_sn <b>required</b>	无人机系列号SN
purchaser	购买人
purchase_time	购买时间

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > payloads > create -p name=... -p payload_id=... -p
```

v2 > company > payloads > read

GET

/api/web/v2/company/payloads/{id}/

公司挂载管理

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > payloads > read -p id=...
```

v2 > company > payloads > update

PUT

/api/web/v2/company/payloads/{id}/

公司挂载管理

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
payload_name	
payload_brand	
payload_model	
payload_sn	

Parameter	Description
register_date	
is_deleted	
purchaser	
purchase_time	
register_user	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > payloads > update -p id=... -p payload_name=... -p
```

v2 > company > payloads > partial\_update

⇌ INTERACT

PATCH

 /api/web/v2/company/payloads/{id}/  
公司挂载管理

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
payload_name	
payload_brand	
payload_model	
payload_sn	
register_date	
is_deleted	
purchaser	

Parameter	Description
purchase_time	
register_user	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > payloads > partial_update -p id=... -p payload_name=...
```

v2 > company > pilot > create

⇌ INTERACT

**POST** /api/web/v2/company/pilot/  
公司用户飞手认证

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <b>required</b>	飞手姓名
appointed_course <b>required</b>	课程名称
aircraft_type <b>required</b>	培训机型
certificate_date <b>required</b>	
certificate_no <b>required</b>	证书编号
certificate_institutions <b>required</b>	证书机构
User_id <b>required</b>	用户id
certificate_image	证书图片地址

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > pilot > create -p name=... -p appointed_course=...
```

v2 > company > pilot > update

⇌ INTERACT

**PUT** /api/web/v2/company/pilot/{id}/  
公司用户飞手认证

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this 飞手信息.

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	飞手姓名
appointed_course	课程名称
aircraft_type	培训机型
certificate_date	
certificate_no	证书编号
certificate_institutions	证书机构
certificate_image	证书图片地址

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > pilot > update -p id=... -p name=... -p appointed_c
```

## v2 > company > pilot > partial\_update

PATCH

/api/web/v2/company/pilot/{id}/

公司用户飞手认证

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this 飞手信息.

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
-----------	-------------

Parameter	Description
name	飞手姓名
appointed_course	课程名称
aircraft_type	培训机型
certificate_date	
certificate_no	证书编号
certificate_institutions	证书机构
certificate_image	证书图片地址

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > pilot > partial_update -p id=... -p name=... -p app
```

v2 > company > project\_info > create

POST

/api/web/v2/company/project\_info

项目已完成数, 未完成数, 项目人数

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > project_info > create
```

v2 > company > projects > list

GET

/api/web/v2/company/projects/

项目

⇌ INTERACT

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
p	A page number within the paginated result set.
page_size	Number of results to return per page.



```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > projects > list -p p=... -p page_size=...
```

v2 > company > projects > create

POST

/api/web/v2/company/projects/

项目

⇌ INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <div>required</div>	项目名称
industry_id <div>required</div>	行业id
members	项目成员
admins	管理员
brief	项目描述

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > projects > create -p name=... -p industry_id=... -p
```

v2 > company > projects > read

GET

/api/web/v2/company/projects/{id}/

项目

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > projects > read -p id=...
```

v2 > company > projects > update

PUT

/api/web/v2/company/projects/{id}/

项目

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
industry_id	行业id
brief	
name	
cover_url	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > projects > update -p id=... -p industry_id=... -p b
```

v2 > company > projects > partial\_update

PATCH

/api/web/v2/company/projects/{id}/

项目

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
industry_id	行业id

Parameter	Description
brief	
name	
cover_url	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > projects > partial_update -p id=... -p industry_id=...
```

v2 > company > projects > delete

DELETE

/api/web/v2/company/projects/{id}/

项目

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > projects > delete -p id=...
```

v2 > company > pv\_detection > list

GET

/api/web/v2/company/pv\_detection/

光伏检测

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > pv_detection > list
```

v2 > company > pv\_detection > update

PUT

/api/web/v2/company/pv\_detection/{id}/

光伏检测

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
raw_data_url	原始数据地址
model_url	模型地址
model_format	模型格式
proceed_time	
proceed_duration_time	处理时长
proceed_summary	总结
status	状态
status_desc	状态描述
report_url	报告地址
is_deleted	是否删除
raw_data_config	原始数据配置
station_name	电站名称
defect_num	缺陷数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > pv_detection > update -p id=... -p raw_data_url=...
```

## v2 > company > pv\_detection > partial\_update

PATCH

 /api/web/v2/company/pv\_detection/{id}/  
光伏检测

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
raw_data_url	原始数据地址
model_url	模型地址
model_format	模型格式
proceed_time	
proceed_duration_time	处理时长
proceed_summary	总结
status	状态
status_desc	状态描述
report_url	报告地址
is_deleted	是否删除
raw_data_config	原始数据配置
station_name	电站名称
defect_num	缺陷数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > pv_detection > partial_update -p id=... -p raw_data...
```

v2 > company > task\_templates > list

GET

 /api/web/v2/company/task\_templates/  
公司任务模板

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > task_templates > list
```

v2 > company > task\_templates > create

⇌ INTERACT

**POST** /api/web/v2/company/task\_templates/  
公司任务模板

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <b>required</b>	模板名称
industry_id <b>required</b>	行业id
is_private <b>required</b>	是否私有
task_config <b>required</b>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > task_templates > create -p name=... -p industry_id=...
```

v2 > company > task\_templates > read

⇌ INTERACT

**GET** /api/web/v2/company/task\_templates/{id}/  
公司任务模板

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > task_templates > read -p id=...
```

# v2 > company > task\_templates > update

PUT

/api/web/v2/company/task\_templates/{id}/

公司任务模板

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
is_private	
task_config	
is_deleted	
industry	
company	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > task_templates > update -p id=... -p name=... -p is...
```

# v2 > company > task\_templates > partial\_update

PATCH

/api/web/v2/company/task\_templates/{id}/

公司任务模板

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
is_private	
task_config	
is_deleted	
industry	
company	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > task_templates > partial_update -p id=... -p name=.
```

v2 > company > task\_templates > delete

⇔ INTERACT

**DELETE** /api/web/v2/company/task\_templates/{id}/  
公司任务模板

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > task_templates > delete -p id=...
```

v2 > company > tasks > list

⇔ INTERACT

**GET** /api/web/v2/company/tasks/  
公司项目任务

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > tasks > list
```



# v2 > company > tasks > create

⇌ INTERACT

**POST** /api/web/v2/company/tasks/  
公司项目任务

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name <b>required</b>	任务名称
address <b>required</b>	任务地址
start_date <b>required</b>	任务开始时间
owner_id <b>required</b>	任务负责人id
project_id <b>required</b>	任务所属项目id
task_config <b>required</b>	任务配置
industry_id <b>required</b>	行业id
task_application_counts	任务应用数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > tasks > create -p name=... -p address=... -p start_
```

# v2 > company > tasks > read

⇌ INTERACT

**GET** /api/web/v2/company/tasks/{id}/  
公司项目任务

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > tasks > read -p id=...
```

v2 > company > tasks > update

PUT

/api/web/v2/company/tasks/{id}/

⇌

INTERACT

:param request: :param args: :param kwargs: :return:

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
project <div>required</div>	
address	
start_date <div>required</div>	任务开始时间
task_config	
owner <div>required</div>	
task_status	
task_application_current	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > tasks > update -p id=... -p name=... -p project=...
```

v2 > company > tasks > partial\_update

PATCH

/api/web/v2/company/tasks/{id}/

⇌

INTERACT

公司项目任务

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	任务名称
address	任务地址
start_date	任务开始时间
owner_id	任务负责人id
task_config	任务配置
industry_id	行业id
task_application_current	任务当前应用
process_status	当前应用状态
task_status	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > tasks > partial_update -p id=... -p name=... -p address=...
```

## v2 > company > tasks > delete

DELETE

 /api/web/v2/company/tasks/{id}/  
公司项目任务

⇌ INTERACT

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company > tasks > delete -p id=...
```

## v2 > company\_register\_code > list

GET

/api/web/v2/company\_register\_code/

公司级别邀请码

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company_register_code > list
```

## v2 > company\_register\_code > create

POST

/api/web/v2/company\_register\_code/

公司级别邀请码

⇌ INTERACT

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
phone_num <div>required</div>	手机号
days	有效天数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company_register_code > create -p phone_num=... -p days=...
```

## v2 > company\_register\_code > read

GET

/api/web/v2/company\_register\_code/{id}/

公司级别邀请码

⇌ INTERACT

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company_register_code > read -p id=...
```

## v2 > company\_register\_code > update

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
code_status	
is_deleted	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company_register_code > update -p id=... -p code_status=... -p is_deleted=...
```

v2 > company\_register\_code > partial\_update

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
code_status	
is_deleted	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > company_register_code > partial_update -p id=... -p code_stat
```

v2 > drone\_insurance > create

⇌ INTERACT

**POST** /api/web/v2/drone\_insurance/

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
insurance_type <b>required</b>	保险类别
name <b>required</b>	保险名称
insurance_company <b>required</b>	保险公司
insurance_num <b>required</b>	保单号
expire_date <b>required</b>	有效期
insurance_amount <b>required</b>	保额
insurance_image	
drone_id <b>required</b>	无人机id

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drone_insurance > create -p insurance_type=... -p name=... -p
```

v2 > drone\_insurance > update

⇌ INTERACT

**PUT** /api/web/v2/drone\_insurance/{id}/

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
insurance_type	
name	
insurance_company	
insurance_num	
expire_date	
insurance_amount	
insurance_image	
is_deleted	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drone_insurance > update -p id=... -p insurance_type=... -p r
```

v2 > drone\_insurance > partial\_update

⇌ INTERACT

PATCH /api/web/v2/drone\_insurance/{id}/

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
insurance_type	
name	
insurance_company	
insurance_num	

Parameter	Description
expire_date	
insurance_amount	
insurance_image	
is_deleted	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drone_insurance > partial_update -p id=... -p insurance_type=...
```

v2 > drone\_living > update

⇌ INTERACT

PUT

 /api/web/v2/drone\_living/{id}/  
web端无人机直播

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this 公司无人机.

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
push_url	
live_url	
status_code	
location	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drone_living > update -p id=... -p push_url=... -p live_url=...
```



# v2 > drone\_living > partial\_update

PATCH

/api/web/v2/drone\_living/{id}/

web端无人机直播

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this 公司无人机.

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
push_url	
live_url	
status_code	
location	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drone_living > partial_update -p id=... -p push_url=... -p li
```

# v2 > drones > common > list

GET

/api/web/v2/drones/common/

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drones > common > list
```

# v2 > drones > common > read

GET

/api/web/v2/drones/common/{id}/

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	A unique integer value identifying this 无人机信息.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > drones > common > read -p id=...
```

v2 > flying\_drones > list

GET /api/web/v2/flying\_drones/ 

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > flying_drones > list
```

v2 > get\_fly\_safe\_info > create

POST /api/web/v2/get\_fly\_safe\_info/ 

⇌ INTERACT

查询禁飞区信息

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
lng <div>required</div>	经度
lat <div>required</div>	纬度
country	国家/地区
search_radius	搜索半径
drone	无人机型号
level	层级
zones_mode	分带模式

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > get_fly_safe_info > create -p lng=... -p lat=... -p country=...
```

## v2 > get\_project\_tasks > create

⇌ INTERACT

**POST** /api/web/v2/get\_project\_tasks/

查询项目内所有的任务

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
project_id <b>required</b>	项目id
p	页数

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > get_project_tasks > create -p project_id=... -p p=...
```

## v2 > get\_users > list

⇌ INTERACT

**GET** /api/web/v2/get\_users/

查询公司员工

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > get_users > list
```

## v2 > industries > list

⇌ INTERACT

**GET** /api/web/v2/industries/

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > industries > list
```

# v2 > industries > read

GET /api/web/v2/industries/{id}/

⇌ INTERACT

## Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	A unique integer value identifying this 行业.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > industries > read -p id=...
```

# v2 > login > create

POST /api/web/v2/login/

⇌ INTERACT

登录

## Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
phone_num <span>required</span>	手机号
password <span>required</span>	密码

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > login > create -p phone_num=... -p password=...
```

# v2 > logout > list

GET /api/web/v2/logout/

⇌ INTERACT

登出

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > logout > list
```

## v2 > member\_register\_code > create

**POST** /api/web/v2/member\_register\_code

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > member_register_code > create
```

## v2 > mobile\_device > common > list

**GET** /api/web/v2/mobile\_device/common/

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > mobile_device > common > list
```

## v2 > payloads > common > list

**GET** /api/web/v2/payloads/common/

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > payloads > common > list
```

## v2 > payloads > common > read

**GET** /api/web/v2/payloads/common/{id}/

⇌ INTERACT

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	A unique integer value identifying this 挂载.

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > payloads > common > read -p id=...
```

## v2 > register > create

POST

/api/web/v2/register/

注册类

⇌ INTERACT

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
phone_num <div>required</div>	手机号
phone_code <div>required</div>	验证码
password <div>required</div>	密码
name <div>required</div>	姓名
email	邮箱
register_code <div>required</div>	邀请码

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > register > create -p phone_num=... -p phone_code=... -p passw
```

v2 > smart\_flight\_resources > list

GET

/api/web/v2/smart\_flight\_resources/

智飞套件资源管理

⇌ INTERACT

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > smart_flight_resources > list -p name=... -p project_id=... -
```

v2 > smart\_flight\_resources > create

⇌ INTERACT

**POST** /api/web/v2/smart\_flight\_resources/  
智飞套件资源管理

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
project_id <b>required</b>	项目id
name	资源名称
resources_type <b>required</b>	资源类型
resources_url <b>required</b>	资源地址
resources_size <b>required</b>	资源大小
accuracy	
difference	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > smart_flight_resources > create -p project_id=... -p name=...
```

v2 > smart\_flight\_resources > read

⇌ INTERACT

**GET** /api/web/v2/smart\_flight\_resources/{id}/  
智飞套件资源管理

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <b>required</b>	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号

Parameter	Description
resources_type	资源类型

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > smart_flight_resources > read -p id=... -p name=... -p project_id=...
```

v2 > smart\_flight\_resources > update

PUT

/api/web/v2/smart\_flight\_resources/{id}/

智飞套件资源管理

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
resources_url	
resources_size	
is_deleted	
difference	



Parameter	Description
accuracy	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > smart_flight_resources > update -p id=... -p name=... -p resco
```

v2 > smart\_flight\_resources > partial\_update

PATCH

/api/web/v2/smart\_flight\_resources/{id}/

智飞套件资源管理

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Query Parameters

The following parameters should be included as part of a URL query string.

Parameter	Description
name	资源名称
project_id	项目编号
resources_type	资源类型

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	
resources_url	
resources_size	
is_deleted	
difference	

Parameter	Description
accuracy	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > smart_flight_resources > partial_update -p id=... -p name=...
```

## v2 > task\_app\_status > create

[⇌ INTERACT](#)

**POST** /api/web/v2/task\_app\_status/  
根据task\_application\_code查询应用状态

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
task_app_code <b>required</b>	任务应用code

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > task_app_status > create -p task_app_code=...
```

## v2 > update > company > list

[⇌ INTERACT](#)

**GET** /api/web/v2/update/company/

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > company > list
```

## v2 > update > company > read

[⇌ INTERACT](#)

**GET** /api/web/v2/update/company/{id}/

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
-----------	-------------

Parameter	Description
id <div>required</div>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > company > read -p id=...
```

v2 > update > company > update

PUT

 /api/web/v2/update/company/{id}/

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	公司名称
industry_id	行业
contact_address	公司地址
contact_cellphone	联系电话
contact_email	联系邮箱
tax_number	税号
tax_title	发票抬头
tax_tel	发票电话
tax_bank	开户行
tax_bank_account	开户行账号
tax_address	发票地址
register_date	公司注册日期

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > company > update -p id=... -p name=... -p industry_id=...
```

v2 > update > company > partial\_update

PATCH

 /api/web/v2/update/company/{id}/ 

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
name	公司名称
industry_id	行业
contact_address	公司地址
contact_cellphone	联系电话
contact_email	联系邮箱
tax_number	税号
tax_title	发票抬头
tax_tel	发票电话
tax_bank	开户行
tax_bank_account	开户行账号
tax_address	发票地址
register_date	公司注册日期

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > company > partial_update -p id=... -p name=... -p ir
```

## v2 > update > password > list

**GET** /api/web/v2/update/password/

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > password > list
```

## v2 > update > password > create

**POST** /api/web/v2/update/password/

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > password > create
```

## v2 > update > user\_info > list

**GET** /api/web/v2/update/user\_info/

用戶基本信息更改

⇌ INTERACT

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > user_info > list
```

## v2 > update > user\_info > read

**GET** /api/web/v2/update/user\_info/{id}/

用戶基本信息更改

⇌ INTERACT

### Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
-----------	-------------

Parameter	Description
id <span>required</span>	

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > user_info > read -p id=...
```

v2 > update > user\_info > update

PUT

/api/web/v2/update/user\_info/{id}/

用戶基本信息更改

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <span>required</span>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
avatar_url	用戶头像
cel_tel	用戶座机
email	邮箱
name	用戶姓名

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > user_info > update -p id=... -p avatar_url=... -p ce
```

v2 > update > user\_info > partial\_update

PATCH

/api/web/v2/update/user\_info/{id}/

用戶基本信息更改

⇌ INTERACT

Path Parameters

The following parameters should be included in the URL path.

Parameter	Description
id <div>required</div>	

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
avatar_url	用户头像
cel_tel	用户座机
email	邮箱
name	用户姓名

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update > user_info > partial_update -p id=... -p avatar_url=...
```

v2 > update\_task\_app > create

⇌ INTERACT

POST

 /api/web/v2/update\_task\_app/  
更新任务所选应用信息 2018-11-1这个接口目前没有调用

Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
task_id <div>required</div>	任务id
application_id <div>required</div>	应用id
task_application_code	任务应用关系
process_status <div>required</div>	处理进度

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update_task_app > create -p task_id=... -p application_id=...
```

## v2 > update\_task\_app\_status > create

⇌ INTERACT

**POST** /api/web/v2/update\_task\_app\_status/  
根据task\_app\_code 更改应用任务状态

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
process_status <b>required</b>	应用状态
task_app_code <b>required</b>	任务应用code

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > update_task_app_status > create -p process_status=... -p task
```

## v2 > upload\_file > list

⇌ INTERACT

**GET** /api/web/v2/upload\_file/  
通过blob上传文件

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > upload_file > list
```

## v2 > upload\_file > create

⇌ INTERACT

**POST** /api/web/v2/upload\_file/  
通过blob上传文件

### Request Body

The request body should be a "application/json" encoded object, containing the following items.

Parameter	Description
file_path <b>required</b>	文件绝对路径

```
# Load the schema document
$ coreapi get http://127.0.0.1:8000/docs/

# Interact with the API endpoint
$ coreapi action web v2 > upload_file > create -p file_path=...
```