```
use store;

create table customers_back as select * from customers;
create table orders_back as select * from orders;
create table order_items_back as select * from order_items;

insert into customers_back
select * from customers c
where c.id not in (select id from customers_back);


use invoicing;

create table clients_back as select * from clients;
create table INVOICES_ARCHIVED as select c.id, c.name from clients c;

insert into clients_back
select * from clients c
where c.id not in (select id from INVOICES_ARCHIVED);
```

#	Time	Action	Message	Duration / Fetch
1	19:11:31	use store	0 row(s) affected	0.016 sec
2	19:11:33	create table customersBack as select * from customers	10 row(s) affected Records: 10 Duplicates: 0 Warnings: 0	0.813 sec
3	19:12:16	use store	0 row(s) affected	0.000 sec
4	19:12:18	create table customers_back as select * from customers	10 row(s) affected Records: 10 Duplicates: 0 Warnings: 0	0.031 sec
5	19:12:18	create table orders_back as select * from orders	10 row(s) affected Records: 10 Duplicates: 0 Warnings: 0	0.141 sec
6	19:12:18	create table order_items_back as select * from order_items	18 row(s) affected Records: 18 Duplicates: 0 Warnings: 0	0.109 sec
7	19:14:43	insert into customers_back select * from customers c where c.id not in (select id from customers_back)	0 row(s) affected Records: 0 Duplicates: 0 Warnings: 0	0.063 sec
8	19:20:14	use invoicing	0 row(s) affected	0.000 sec
9	19:20:17	create table INVOICES_ARCHIVED as select c.id, c.name from clients c	5 row(s) affected Records: 5 Duplicates: 0 Warnings: 0	0.156 sec
10	19:21:28	create table INVOICES_ARCHIVED as select c.id, c.name from clients c	Error Code: 1050. Table 'INVOICES_ARCHIVED' already exists	0.016 sec
11	19:24:58	use store	0 row(s) affected	0.000 sec