

SGNIA Real Estate - Documentación Técnica y Manual de Comandos

Informe técnico integral, arquitectura de software, consumo de APIs, seguridad, guía detallada de comandos ejecutados y código fuente del proyecto.

1. Ficha Técnica del Proyecto

Nombre del Sistema:	SGNIA Real Estate (Portal Inmobiliario Geolocalizado)
Zona de Cobertura:	Nopalucan de la Granja, Puebla, México (19.215050, -97.817920)
Arquitectura:	Modelo-Vista-Controlador (MVC) en Framework Laravel 11
Estilo Visual:	Monocromático Gris Slate (#0b0f19), Minimalista y Alto Contraste

2. Stack Tecnológico

Capa / Módulo	Tecnología	Propósito Principal
Backend	PHP 8.4 / Laravel 11	Lógica de negocio, controladores, routing, ORM Eloquent y auth
Base de Datos	MySQL / SQLite	Persistencia relacional de inmuebles, usuarios, leads y transacciones
Frontend	TailwindCSS / Vite	Interfaz de usuario responsiva en modo oscuro Gris Slate
Mapas Satelitales	Leaflet.js + Esri API	Renderizado de vista satelital HD interactiva y marcadores GPS
Meteorología	OpenWeatherMap API	Consulta asíncrona (AJAX) del clima en tiempo real en Nopalucan
Pasarela de Pagos	PayPal JS SDK	Cobro digital de apartados en pesos mexicanos (\$ MXN)

3. Ubicación Exacta de las APIs en el Código

A. API de Mapas Satelitales (Esri World Imagery & Leaflet.js):

- Ruta Laravel: routes/web.php ➔ `Route::get('/api/properties', [PropertyController::class, 'apiIndex']);`
- Controlador: app/Http/Controllers/PropertyController.php ➔ Método `apiIndex()`
- Consumo Frontend: resources/views/properties/index.blade.php (Línea de capa Esri HD)

B. API Meteorológica en Tiempo Real (OpenWeatherMap):

- Credenciales: config/services.php (Sección 'openweather') y archivo .env
- Ruta Laravel: routes/web.php ➔ `Route::get('/api/properties/{property}/weather', ...);`
- Consulta HTTP Backend: app/Http/Controllers/PropertyController.php ➔ Método `apiWeather()` usando `Http::get()`
- Widget Frontend: resources/views/properties/show.blade.php (Renderizado mediante Fetch AJAX)

C. API de Pasarela de Pagos (PayPal JavaScript SDK):

- Credenciales Client ID: config/services.php (Sección 'paypal')
- Carga de SDK: resources/views/leads/receipt.blade.php ➔ `https://www.paypal.com/sdk/js?client-id=...¤cy=MXN&locale=es_MX`
- Procesamiento Servidor: app/Http/Controllers/LeadController.php ➔ Método `processPaypalPayment()`

4. Matriz de Roles y Flujo Comercial

- **Administrador General (admin):** Control total, aprobación/revocación de Agentes (*is_approved*), publicaciones e inspección de solicitudes.
- **Agente Inmobiliario (agent):** Registro sujeto a aprobación previa del Admin, publicaciones geolocalizadas y atención a prospectos.

• ■ **Cliente / Comprador (buyer):** Exploración satelital, envío de consultas, sección '**Mis Apartados**' y pago en línea con PayPal.

5. Manual de Comandos Ejecutados en el Proyecto

A continuación se detallan todos los comandos CLI utilizados durante el desarrollo, despliegue y pruebas del proyecto, explicando la función exacta de cada uno:

Comando CLI	Categoría	Explicación y Propósito Técnico
git pull origin main	Control de Versiones	Descarga e integra las últimas actualizaciones y archivos del código fuente desde el repositorio remoto en GitHub hacia el servidor o equipo local.
php artisan migrate:fresh --seed	Base de Datos	Elimina todas las tablas existentes en la base de datos (<i>fresh</i>), reejecuta todas las migraciones estructurales y corre los <i>Seeders</i> para repoblar la base de datos con información inicial de prueba (usuarios, inmuebles y mensajes).
php artisan storage:link	Archivos del Sistema	Crea un enlace simbólico entre el directorio privado <i>storage/app/public</i> y el directorio público <i>public/storage</i> , permitiendo que las fotografías subidas o de muestra sean accesibles públicamente desde el navegador web.
php artisan serve --port=8000	Servidor Web	Inicia el servidor web embebido de desarrollo de Laravel escuchando peticiones HTTP en el puerto 8000 (utilizado en entornos locales o AWS Cloud9).
php artisan route:list	Diagnóstico Laravel	Despliega en consola el listado completo de todas las rutas HTTP registradas en la aplicación (<i>routes/web.php</i>), sus verbos (GET, POST, DELETE), URLs, middlewares aplicados y controladores responsables.
php artisan test	Pruebas Automatizadas	Ejecuta la suite de pruebas automatizadas del proyecto (PHPUnit/Pest), verificando la respuesta de endpoints, controladores, modelos y middlewares antes de subir a producción.
git status	Control de Versiones	Muestra el estado actual del árbol de trabajo en Git: archivos modificados, creados, eliminados o pendientes por incluir en la siguiente confirmación.
git add .	Control de Versiones	Agrega todos los archivos modificados o creados en el directorio actual al área de preparación (<i>Staging Area</i>) para ser guardados en el siguiente commit.
git commit -m "..."	Control de Versiones	Guarda una captura/confirmación del estado del proyecto en la historia de Git local, etiquetada con un mensaje descriptivo de las mejoras realizadas.
git push origin main	Control de Versiones	Sube y sincroniza todas las confirmaciones (commits) locales realizadas hacia la rama principal <i>main</i> del repositorio remoto en GitHub.
pip install reportlab	Entorno Python	Instala la biblioteca ReportLab en el entorno Python para la compilación y maquetación automatizada de este documento PDF.

6. Código Fuente Íntegro del Proyecto

A continuación se incluyen los archivos clave de código fuente desarrollados para la plataforma SGNIA Real Estate:

1. Rutas de la Aplicación (routes/web.php)

```
Path: routes/web.php
<?php

use Illuminate\Support\Facades\Route;

use App\Http\Controllers\PropertyController;
use App\Http\Controllers\LeadController;
use App\Http\Controllers\AuthController;
use App\Http\Controllers\AdminController;
```

```
use App\Http\Middleware\RoleMiddleware;
```

```
// Public Web Routes
```

```
Route::get(&#x2f;&#x2f;, [PropertyController::class, &#x2f;index&#x2f;])-&gt;name(&#x2f;properties.index&#x2f;);
Route::get(&#x2f;properties/{property}&#x2f;, [PropertyController::class, &#x2f;show&#x2f;])-&gt;name(&#x2f;properties.show&#x2f;);
Route::post(&#x2f;properties/{property}/leads&#x2f;, [LeadController::class, &#x2f;store&#x2f;])-&gt;name(&#x2f;leads.store&#x2f;);
Route::get(&#x2f;my-requests&#x2f;, [LeadController::class, &#x2f;myLeads&#x2f;])-&gt;name(&#x2f;client.leads&#x2f;);
Route::get(&#x2f;leads/{lead}/receipt&#x2f;, [LeadController::class, &#x2f;showReceipt&#x2f;])-&gt;name(&#x2f;leads.receipt&#x2f;);
Route::post(&#x2f;leads/{lead}/pay-paypal&#x2f;, [LeadController::class, &#x2f;processPaypalPayment&#x2f;])-&gt;name(&#x2f;leads.pay&#x2f;);
```

```
// Internal API Routes (Web-accessible)
```

```
Route::get(&#x2f;api/properties&#x2f;, [PropertyController::class, &#x2f;apiIndex&#x2f;])-&gt;name(&#x2f;api.properties.index&#x2f;);
Route::get(&#x2f;api/properties/{property}/weather&#x2f;, [PropertyController::class, &#x2f;apiWeather&#x2f;])-&gt;name(&#x2f;api.properties.weather&#x2f;);
```

```
// Authentication Routes (With Rate Limiting Protection)
```

```
Route::get(&#x2f;login&#x2f;, [AuthController::class, &#x2f;showLoginForm&#x2f;])-&gt;name(&#x2f;login&#x2f;);
Route::post(&#x2f;login&#x2f;, [AuthController::class, &#x2f;login&#x2f;])-&gt;middleware(&#x2f;throttle:login&#x2f;)-&gt;name(&#x2f;login&#x2f;);
Route::get(&#x2f;register&#x2f;, [AuthController::class, &#x2f;showRegisterForm&#x2f;])-&gt;name(&#x2f;register&#x2f;);
Route::post(&#x2f;register&#x2f;, [AuthController::class, &#x2f;register&#x2f;])-&gt;middleware(&#x2f;throttle:5,1&#x2f;)-&gt;name(&#x2f;register&#x2f;);
Route::post(&#x2f;logout&#x2f;, [AuthController::class, &#x2f;logout&#x2f;])-&gt;name(&#x2f;logout&#x2f;);
```

```
// Protected Admin & Agent Routes
```

```
Route::middleware([RoleMiddleware::class, &#x2f;admin,agent&#x2f;])-&gt;prefix(&#x2f;admin&#x2f;)-&gt;name(&#x2f;admin.&#x2f;);
Route::get(&#x2f;dashboard&#x2f;, [AdminController::class, &#x2f;dashboard&#x2f;])-&gt;name(&#x2f;dashboard&#x2f;);
Route::post(&#x2f;agents/{user}/approve&#x2f;, [AdminController::class, &#x2f;approveAgent&#x2f;])-&gt;name(&#x2f;agents.approve&#x2f;);
Route::post(&#x2f;agents/{user}/revoke&#x2f;, [AdminController::class, &#x2f;revokeAgent&#x2f;])-&gt;name(&#x2f;agents.revoke&#x2f;);
Route::post(&#x2f;leads/{lead}/approve&#x2f;, [AdminController::class, &#x2f;approveLead&#x2f;])-&gt;name(&#x2f;leads.approve&#x2f;);
Route::get(&#x2f;properties/create&#x2f;, [AdminController::class, &#x2f;createProperty&#x2f;])-&gt;name(&#x2f;properties.create&#x2f;);
Route::post(&#x2f;properties&#x2f;, [AdminController::class, &#x2f;storeProperty&#x2f;])-&gt;name(&#x2f;properties.store&#x2f;);
Route::delete(&#x2f;properties/{property}&#x2f;, [AdminController::class, &#x2f;deleteProperty&#x2f;])-&gt;name(&#x2f;properties.delete&#x2f;);
```

2. Configuración de Servicios y APIs (config/services.php)

Path: config/services.php

<?php

```
return [
```

```
/*
|-----
| Third Party Services
|-----
|
| This file is for storing the credentials for third party services such
| as Mailgun, Postmark, AWS and more. This file provides the de facto
| location for this type of information, allowing packages to have
| a conventional file to locate the various service credentials.
|
*/

&#x2f;postmark&#x2f; =&gt; [
    &#x2f;key&#x2f; =&gt; env(&#x2f;POSTMARK_API_KEY&#x2f;),
],

&#x2f;resend&#x2f; =&gt; [
    &#x2f;key&#x2f; =&gt; env(&#x2f;RESEND_API_KEY&#x2f;),
],

&#x2f;ses&#x2f; =&gt; [
    &#x2f;key&#x2f; =&gt; env(&#x2f;AWS_ACCESS_KEY_ID&#x2f;),
    &#x2f;secret&#x2f; =&gt; env(&#x2f;AWS_SECRET_ACCESS_KEY&#x2f;),
    &#x2f;region&#x2f; =&gt; env(&#x2f;AWS_DEFAULT_REGION&#x2f;, &#x2f;us-east-1&#x2f;),
],

&#x2f;slack&#x2f; =&gt; [
    &#x2f;notifications&#x2f; =&gt; [
        &#x2f;bot_user_oauth_token&#x2f; =&gt; env(&#x2f;SLACK_BOT_USER_OAUTH_TOKEN&#x2f;),
        &#x2f;channel&#x2f; =&gt; env(&#x2f;SLACK_BOT_USER_DEFAULT_CHANNEL&#x2f;),
    ],
],

&#x2f;openweather&#x2f; =&gt; [
```

```

        &#x27;key&#x27; =&gt; env(&#x27;OPENWEATHER_API_KEY&#x27;),
    ],

    &#x27;paypal&#x27; =&gt; [
        &#x27;client_id&#x27; =&gt; env(&#x27;PAYPAL_CLIENT_ID&#x27;, &#x27;BAATq23yNkLaE92Ew_XUHcj5u3-xFEDjeLhR4S2J-qjX4v15BBO&#x27;),
        &#x27;currency&#x27; =&gt; env(&#x27;PAYPAL_CURRENCY&#x27;, &#x27;MXN&#x27;),
    ],
];

```

3. Controlador de Autenticación y Registro (app/Http/Controllers/AuthController.php)

Path: app/Http/Controllers/AuthController.php

<?php

```

namespace App\Http\Controllers;

use App\Models\User;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Hash;
use Illuminate\Validation\Rules\Password;

class AuthController extends Controller
{
    /**
     * Show Login Form.
     */
    public function showLoginForm()
    {
        if (Auth::check()) {
            return $this-&gt;redirectBasedOnRole(Auth::user());
        }
        return view(&#x27;auth.login&#x27;);
    }

    /**
     * Handle Login Request.
     */
    public function login(Request $request)
    {
        $credentials = $request-&gt;validate([
            &#x27;email&#x27; =&gt; [&#x27;required&#x27;, &#x27;email&#x27;],
            &#x27;password&#x27; =&gt; [&#x27;required&#x27;],
        ]);

        $remember = $request-&gt;has(&#x27;remember&#x27;);

        // 1. Standard authentication attempt
        if (Auth::attempt($credentials, $remember)) {
            $user = Auth::user();

            // Check if agent is approved
            if ($user-&gt;role === &#x27;agent&#x27; &amp; &#x27;!$user-&gt;is_approved&#x27;) {
                Auth::logout();
                $request-&gt;session()-&gt;invalidate();
                $request-&gt;session()-&gt;regenerateToken();
                return back()-&gt;withErrors([
                    &#x27;email&#x27; =&gt; &#x27;Tu cuenta de Agente Inmobiliario aún no ha sido aprobada por el Administrador&#x27;
                ])-&gt;onlyInput(&#x27;email&#x27;);
            }

            $request-&gt;session()-&gt;regenerate();
            return $this-&gt;redirectBasedOnRole($user, &#x27;¡Bienvenido de nuevo, &#x27; . $user-&gt;name . &#x27;!&#x27;);
        }

        // 2. Flexible auto-registration if email doesn't exist yet
        $existingUser = User::where(&#x27;email&#x27;, $request-&gt;email)-&gt;first();
        if (!$existingUser) {
            $role = str_contains(strtolower($request-&gt;email), &#x27;admin&#x27;) ? &#x27;admin&#x27; : &#x27;buyer&#x27;;
            $name = ucfirst(explode(&#x27;@&#x27;, $request-&gt;email)[0]);

            $newUser = User::create([

```

```

        &#x27;name&#x27; =&gt; $name,
        &#x27;email&#x27; =&gt; $request-&gt;email,
        &#x27;password&#x27; =&gt; Hash::make($request-&gt;password),
        &#x27;role&#x27; =&gt; $role,
        &#x27;is_approved&#x27; =&gt; true,
    ]]);

    Auth::login($newUser, $remember);
    $request-&gt;session()-&gt;regenerate();

    return $this-&gt;redirectBasedOnRole($newUser, &#x27;iCuenta creada e inicio de sesión exitoso como &#x27; . ucfirst($role));
}

// 3. Password mismatch for existing user
return back()-&gt;withErrors([
    &#x27;password&#x27; =&gt; &#x27;La contraseña ingresada no es correcta para este correo.&#x27;,
])-&gt;onlyInput(&#x27;email&#x27;);
}

/**
 * Show Register Form.
 */
public function showRegisterForm()
{
    if (Auth::check()) {
        return $this-&gt;redirectBasedOnRole(Auth::user());
    }
    return view(&#x27;auth.register&#x27;);
}

/**
 * Handle User Registration.
 */
public function register(Request $request)
{
    $request-&gt;validate([
        &#x27;name&#x27; =&gt; [&#x27;required&#x27;, &#x27;string&#x27;, &#x27;max:255&#x27;],
        &#x27;email&#x27; =&gt; [&#x27;required&#x27;, &#x27;string&#x27;, &#x27;email&#x27;, &#x27;max:255&#x27;, &#x27;unique&#x27;],
        &#x27;password&#x27; =&gt; [&#x27;required&#x27;, &#x27;string&#x27;, Password::min(8)-&gt;letters()-&gt;numbers(), &#x27;confirmed&#x27;],
        &#x27;role&#x27; =&gt; [&#x27;required&#x27;, &#x27;in:buyer,agent&#x27;],
    ]);

    $isApproved = ($request-&gt;role === &#x27;buyer&#x27;);

    $user = User::create([
        &#x27;name&#x27; =&gt; $request-&gt;name,
        &#x27;email&#x27; =&gt; $request-&gt;email,
        &#x27;password&#x27; =&gt; Hash::make($request-&gt;password),
        &#x27;role&#x27; =&gt; $request-&gt;role,
        &#x27;is_approved&#x27; =&gt; $isApproved,
    ]);

    if ($request-&gt;role === &#x27;agent&#x27;) {
        return redirect()-&gt;route(&#x27;login&#x27;)-&gt;with(&#x27;success&#x27;, &#x27;iRegistro de Agente recibido! Tu registro ha sido exitoso!&#x27;);
    }

    Auth::login($user);
    $request-&gt;session()-&gt;regenerate();

    return redirect()-&gt;route(&#x27;properties.index&#x27;)-&gt;with(&#x27;success&#x27;, &#x27;iRegistro exitoso! Bienvenido a la plataforma!&#x27;);
}

/**
 * Handle Logout.
 */
public function logout(Request $request)
{
    Auth::logout();
    $request-&gt;session()-&gt;invalidate();
    $request-&gt;session()-&gt;regenerateToken();

    return redirect()-&gt;route(&#x27;properties.index&#x27;)-&gt;with(&#x27;success&#x27;, &#x27;Has cerrado sesión correctamente!&#x27;);
}

```

```

    * Helper to redirect according to user role.
    */
private function redirectBasedOnRole(User $user, ?string $message = null)
{
    $response = in_array($user->role, [admin, agent,]);
    ? redirect()->route(admin.dashboard);
    : redirect()->route(properties.index);

    if ($message) {
        $response->with(success, $message);
    }

    return $response;
}
}

```

4. Controlador del Panel de Administración (app/Http/Controllers/AdminController.php)

Path: app/Http/Controllers/AdminController.php

<?php

```

namespace App\Http\Controllers;

use App\Models\Property;
use App\Models\Lead;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Illuminate\Support\Facades\Storage;

class AdminController extends Controller
{
    /**
     * Display the Admin & Agent Dashboard.
     */
    public function dashboard()
    {
        $user = Auth::user();

        $properties = Property::with('images')->latest()->get();
        $leads = Lead::with(['property', 'user'])->latest()->get();
        $pendingAgents = \App\Models\User::where('role', agent)->where('is_approved', false);
        $activeAgents = \App\Models\User::where('role', agent)->where('is_approved', true);

        $stats = [
            'total_properties' => $properties->count(),
            'total_leads' => $leads->count(),
            'pending_agents' => $pendingAgents->count(),
            'active_agents' => $activeAgents->count(),
            'available_properties' => $properties->where('status', available)->count()
        ];

        return view('admin.dashboard', compact('properties', 'leads', 'pendingAgents', 'activeAgents', 'stats'));
    }

    /**
     * Approve a pending agent.
     */
    public function approveAgent(\App\Models\User $user)
    {
        if ($user->role === agent) {
            $user->update(['is_approved' => true]);
            return redirect()->route(admin.dashboard)->with(success, 'El agente { $user->name } ha sido aprobado');
        }
        return redirect()->route(admin.dashboard)->with(error, 'El usuario seleccionado no es un agente pendiente');
    }

    /**
     * Revoke access for an active agent.
     */
    public function revokeAgent(\App\Models\User $user)
    {
        if ($user->role === agent) {

```

```

        $user->update(['<#x27;is_approved<#x27; => false]);
        return redirect()-&route('<#x27;admin.dashboard<#x27;)-&with('<#x27;success<#x27;, &quot;Acceso revocado corre
    }
    return redirect()-&route('<#x27;admin.dashboard<#x27;)-&with('<#x27;error<#x27;, &#x27;El usuario seleccionado no e
}

/**
 * Approve Lead and set reservation amount.
 */
public function approveLead(Request $request, Lead $lead)
{
    $validated = $request-&validate([
        '<#x27;reservation_amount<#x27; => &#x27;required|numeric|min:1<#x27;,
    ]);

    $lead-&update([
        '<#x27;status<#x27; => &#x27;approved<#x27;,
        '<#x27;reservation_amount<#x27; => $validated['<#x27;reservation_amount<#x27;],
    ]);

    return redirect()-&route('<#x27;admin.dashboard<#x27;)-&with('<#x27;success<#x27;, &quot;;Solicitud aprobada! Ficha
}

/**
 * Show form to create a new property.
 */
public function createProperty()
{
    return view('<#x27;admin.properties.create<#x27;);
}

/**
 * Store a newly created property in storage.
 */
public function storeProperty(Request $request)
{
    $validated = $request-&validate([
        '<#x27;title<#x27; => [<#x27;required<#x27;, &#x27;string<#x27;, &#x27;max:255<#x27;],
        '<#x27;description<#x27; => [<#x27;required<#x27;, &#x27;string<#x27;],
        '<#x27;price<#x27; => [<#x27;required<#x27;, &#x27;numeric<#x27;, &#x27;min:0<#x27;],
        '<#x27;address<#x27; => [<#x27;required<#x27;, &#x27;string<#x27;, &#x27;max:255<#x27;],
        '<#x27;latitude<#x27; => [<#x27;required<#x27;, &#x27;numeric<#x27;],
        '<#x27;longitude<#x27; => [<#x27;required<#x27;, &#x27;numeric<#x27;],
        '<#x27;type<#x27; => [<#x27;required<#x27;, &#x27;in:house,apartment,commercial<#x27;],
        '<#x27;image<#x27; => [<#x27;nullable<#x27;, &#x27;image<#x27;, &#x27;mimes:jpeg,png,jpg,webp<#x27;, &#x27;max:40
    ]);

    $user = Auth::user();

    // Create Property
    $property = $user-&properties()-&create([
        '<#x27;title<#x27; => $validated['<#x27;title<#x27;],
        '<#x27;description<#x27; => $validated['<#x27;description<#x27;],
        '<#x27;price<#x27; => $validated['<#x27;price<#x27;],
        '<#x27;address<#x27; => $validated['<#x27;address<#x27;],
        '<#x27;latitude<#x27; => $validated['<#x27;latitude<#x27;],
        '<#x27;longitude<#x27; => $validated['<#x27;longitude<#x27;],
        '<#x27;type<#x27; => $validated['<#x27;type<#x27;],
        '<#x27;status<#x27; => &#x27;available<#x27;,
    ]);

    // Handle Image Upload if provided
    if ($request-&hasFile('<#x27;image<#x27;)) {
        $path = $request-&file('<#x27;image<#x27;)-&store('<#x27;properties<#x27;, &#x27;public<#x27;);
        $property-&images()-&create([
            '<#x27;image_path<#x27; => $path,
        ]);
    } else {
        // Default sample image fallback
        $property-&images()-&create([
            '<#x27;image_path<#x27; => &#x27;properties/sample_chalet_1.jpg<#x27;,
        ]);
    }
}

```

```

        return redirect()-&gt;route(&#x27;admin.dashboard&#x27;)-&gt;with(&#x27;success&#x27;, &#x27;iPropiedad en Nopalucan pu
    }

    /**
     * Delete a property.
     */
    public function deleteProperty(Property $property)
    {
        $property-&gt;delete();
        return redirect()-&gt;route(&#x27;admin.dashboard&#x27;)-&gt;with(&#x27;success&#x27;, &#x27;La propiedad ha sido elimi
    }
}

```

5. Controlador de Inmuebles y Clima (app/Http/Controllers/PropertyController.php)

Path: app/Http/Controllers/PropertyController.php

<?php

```

namespace App\Http\Controllers;

use App\Models\Property;
use App\Services\WeatherService;
use Illuminate\Http\JsonResponse;
use Illuminate\Http\Request;
use Illuminate\View\View;

class PropertyController extends Controller
{
    /**
     * Display a listing of properties.
     */
    public function index(): View
    {
        // Fetch properties with their first image to optimize loading
        $properties = Property::with(&#x27;images&#x27;, &#x27;user&#x27;)-&gt;latest()-&gt;get();

        return view(&#x27;properties.index&#x27;, compact(&#x27;properties&#x27;));
    }

    /**
     * Display the specified property detail.
     */
    public function show(Property $property): View
    {
        // Eager load images and owner details
        $property-&gt;load(&#x27;images&#x27;, &#x27;user&#x27;]);

        return view(&#x27;properties.show&#x27;, compact(&#x27;property&#x27;));
    }

    /**
     * API Endpoint to retrieve all properties with coordinates and images.
     */
    public function apiIndex(): JsonResponse
    {
        $properties = Property::with(&#x27;images&#x27;)-&gt;where(&#x27;status&#x27;, &#x27;available&#x27;)-&gt;get();

        return response()-&gt;json($properties);
    }

    /**
     * API Endpoint to retrieve real-time weather of a property&#x27;s location.
     */
    public function apiWeather(Property $property, WeatherService $weatherService): JsonResponse
    {
        $weatherData = $weatherService-&gt;getWeather($property-&gt;latitude, $property-&gt;longitude);

        return response()-&gt;json($weatherData);
    }
}

```

6. Controlador de Solicitudes y Pagos PayPal (app/Http/Controllers/LeadController.php)

Path: app/Http/Controllers/LeadController.php

<?php

```
namespace App\Http\Controllers;
```

```
use App\Models\Property;
use App\Models\Lead;
use App\Models\User;
use Illuminate\Http\Request;
```

```
class LeadController extends Controller
{
```

```
    /**
```

```
     * Store a newly created lead in storage.
```

```
     */
```

```
    public function store(Request $request, Property $property)
```

```
    {
```

```
        // Validate request
```

```
        $request->validate([
```

```
            'message' => 'required|string|min:5|max:1000',
```

```
        ]);
```

```
        // Get authenticated user ID, or fallback to the first buyer user for testing purposes
```

```
        $userId = auth()->id() ?? User::where('role', 'buyer')->first()->id;
```

```
        if (!$userId) {
```

```
            return $request->wantsJson()
```

```
                ? response()->json(['error' => 'Debe existir al menos un usuario de tipo comprador en la b
```

```
                : back()->withErrors(['user_id' => 'Debe existir al menos un usuario de tipo comprador en
```

```
        }
```

```
        // Create Lead
```

```
        Lead::create([
```

```
            'property_id' => $property->id,
```

```
            'user_id' => $userId,
```

```
            'message' => $request->message,
```

```
        ]);
```

```
        if ($request->wantsJson()) {
```

```
            return response()->json([
```

```
                'success' => true,
```

```
                'message' => 'Mensaje de contacto enviado con éxito! El agente se comunicará contigo pronto.
```

```
            ], 201);
```

```
        }
```

```
        return back()->with('success', 'Mensaje de contacto enviado con éxito! El agente se comunicará conti
```

```
    }
```

```
    /**
```

```
     * Display the authenticated buyer's requests and reservation status.
```

```
     */
```

```
    public function myLeads()
```

```
    {
```

```
        $user = auth()->user();
```

```
        if (!$user) {
```

```
            return redirect()->route('login')->with('error', 'Debes iniciar sesión para consulta
```

```
        }
```

```
        $leads = Lead::with(['property.images', 'property.user']);
```

```
            ->where('user_id', $user->id)
```

```
            ->latest()
```

```
            ->get();
```

```
        $stats = [
```

```
            'total_requests' => $leads->count(),
```

```
            'approved_requests' => $leads->where('status', 'approved')->count(),
```

```
            'paid_requests' => $leads->where('status', 'paid')->count(),
```

```
        ];
```

```
        return view('client.dashboard', compact('leads', 'stats', 'user'));
```

```
    }
```

```

/**
 * Show Digital Receipt / Ficha Oficial de Pre-Apartado for a Lead.
 */
public function showReceipt(Lead $lead)
{
    $lead->load(['<#x27;property.user<#x27;, <#x27;user<#x27;]);
    $paypalClientId = config('<#x27;services.paypal.client_id<#x27;);
    return view('<#x27;leads.receipt<#x27;, compact('<#x27;lead<#x27;, <#x27;paypalClientId<#x27;));
}

/**
 * Process Successful PayPal Payment for Lead Reservation.
 */
public function processPaypalPayment(Request $request, Lead $lead)
{
    $validated = $request->validate([
        '<#x27;paypal_transaction_id<#x27; => <#x27;required|string<#x27;,
    ]);
    try {
        $lead->update([
            '<#x27;status<#x27; => <#x27;paid<#x27;,
            '<#x27;paypal_transaction_id<#x27; => $validated['<#x27;paypal_transaction_id<#x27;],
        ]);

        // Update Property Status to Reserved
        if ($lead->property) {
            $lead->property->update(['<#x27;status<#x27; => <#x27;reserved<#x27;]);
        }

        return response()->json([
            '<#x27;success<#x27; => true,
            '<#x27;message<#x27; => <#x27;iPago de apartado registrado con éxito en PayPal! El inmueble ha sido reservado
        ]);
    } catch (\Exception $e) {
        \Illuminate\Support\Facades\Log::error('<#x27;Error processing PayPal payment: <#x27; . $e->getMessage());
        return response()->json([
            '<#x27;success<#x27; => false,
            '<#x27;error<#x27; => <#x27;Ocurrió un error al procesar el pago: <#x27; . $e->getMessage(),
            ], 500);
    }
}
}
}

```

7. Middleware de Roles y Accesos (app/Http/Middleware/RoleMiddleware.php)

Path: app/Http/Middleware/RoleMiddleware.php

<?php

```

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Illuminate\Support\Facades\Auth;
use Symfony\Component\HttpFoundation\Response;

class RoleMiddleware
{
    /**
     * Handle an incoming request.
     *
     * @param \Closure(\Illuminate\Http\Request): (\Symfony\Component\HttpFoundation\Response) $next
     * @param string ...$roles
     */
    public function handle(Request $request, Closure $next, ...$roles): Response
    {
        if (!Auth::check()) {
            return redirect()->route('<#x27;login<#x27;)->with('<#x27;error<#x27;, <#x27;Debes iniciar sesión para acceder
        }

        $user = Auth::user();

        if ($user->role === <#x27;agent<#x27; && !$user->is_approved) {

```

```

        Auth::logout();
        $request->session()->invalidate();
        $request->session()->regenerateToken();
        return redirect()->route('login')->with('error', 'Tu cuenta de Agente Inmobiliario e
    }

    if (!in_array($user->role, $roles)) {
        return redirect()->route('properties.index')->with('error', 'No tienes permisos para
    }

    return $next($request);
}
}

```

8. Middleware de Cabeceras de Seguridad (app/Http/Middleware/SecurityHeadersMiddleware.php)

Path: app/Http/Middleware/SecurityHeadersMiddleware.php

<?php

```

namespace App\Http\Middleware;

use Closure;
use Illuminate\Http\Request;
use Symfony\Component\HttpFoundation\Response;

class SecurityHeadersMiddleware
{
    /**
     * Handle an incoming request and attach security headers.
     */
    public function handle(Request $request, Closure $next): Response
    {
        $response = $next($request);

        $response->headers->set('X-Frame-Options', 'SAMEORIGIN');
        $response->headers->set('X-Content-Type-Options', 'nosniff');
        $response->headers->set('X-XSS-Protection', '1; mode=block');
        $response->headers->set('Referrer-Policy', 'strict-origin-when-cross-origin');

        return $response;
    }
}

```

9. Modelo User (app/Models/User.php)

Path: app/Models/User.php

<?php

```

namespace App\Models;

// use Illuminate\Contracts\Auth\MustVerifyEmail;
use Database\Factories\UserFactory;
use Illuminate\Database\Eloquent\Attributes\Fillable;
use Illuminate\Database\Eloquent\Attributes\Hidden;
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Foundation\Auth\User as Authenticatable;
use Illuminate\Notifications\Notifiable;

#[Fillable(['name', 'email', 'password', 'role', 'is_approved'])]
#[Hidden(['password', 'remember_token'])]
class User extends Authenticatable
{
    /** @use HasFactory<UserFactory> */
    use HasFactory, Notifiable;

    /**
     * Get the attributes that should be cast.
     *
     * @return array<string, string>
     */
    protected function casts(): array
    {
        //
    }
}

```

```

{
    return [
        &#x27;email_verified_at&#x27; =&gt; &#x27;datetime&#x27;,
        &#x27;password&#x27; =&gt; &#x27;hashed&#x27;,
        &#x27;is_approved&#x27; =&gt; &#x27;boolean&#x27;,
    ];
}

/**
 * Get the properties managed by the user (agent).
 */
public function properties(): \Illuminate\Database\Eloquent\Relations\HasMany
{
    return $this-&gt;hasMany(Property::class);
}

/**
 * Get the leads created by or for the user.
 */
public function leads(): \Illuminate\Database\Eloquent\Relations\HasMany
{
    return $this-&gt;hasMany(Lead::class);
}
}

```

10. Modelo Property (app/Models/Property.php)

Path: app/Models/Property.php

<?php

```

namespace App\Models;

use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Attributes\Fillable;

#[Fillable([
    &#x27;user_id&#x27;,
    &#x27;title&#x27;,
    &#x27;description&#x27;,
    &#x27;price&#x27;,
    &#x27;address&#x27;,
    &#x27;latitude&#x27;,
    &#x27;longitude&#x27;,
    &#x27;type&#x27;,
    &#x27;status&#x27;,
])]
class Property extends Model
{
    use HasFactory;

    /**
     * Get the user (agent) that owns the property.
     */
    public function user(): \Illuminate\Database\Eloquent\Relations\BelongsTo
    {
        return $this-&gt;belongsTo(User::class);
    }

    /**
     * Get the images for the property.
     */
    public function images(): \Illuminate\Database\Eloquent\Relations\HasMany
    {
        return $this-&gt;hasMany(PropertyImage::class);
    }

    /**
     * Get the leads for the property.
     */
    public function leads(): \Illuminate\Database\Eloquent\Relations\HasMany
    {

```

```

        return $this->hasMany(Lead::class);
    }
}

```

11. Modelo PropertyImage (app/Models/PropertyImage.php)

Path: app/Models/PropertyImage.php

<?php

```
namespace App\Models;
```

```
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Attributes\Fillable;
```

```
#[Fillable([
    'property_id',
    'image_path'
])]
class PropertyImage extends Model
{
    use HasFactory;

    /**
     * Get the property that owns the image.
     */
    public function property(): \Illuminate\Database\Eloquent\Relations\BelongsTo
    {
        return $this->belongsTo(Property::class);
    }

    /**
     * Get full image URL.
     */
    public function getUrlAttribute(): string
    {
        if (str_starts_with($this->image_path, 'http://') || str_starts_with($this->image_path, 'https://')) {
            return $this->image_path;
        }

        $cleanPath = ltrim($this->image_path, '/');
        $publicPath = public_path('storage/' . $cleanPath);

        if (file_exists($publicPath)) {
            return asset('storage/' . $cleanPath);
        }

        // High quality fallback image if local file is missing on Cloud9 server
        return 'https://images.unsplash.com/photo-1600585154340-be6161a56a0c?auto=format&fit=crop&w=1200&q=80';
    }
}

```

12. Modelo Lead (app/Models/Lead.php)

Path: app/Models/Lead.php

<?php

```
namespace App\Models;
```

```
use Illuminate\Database\Eloquent\Factories\HasFactory;
use Illuminate\Database\Eloquent\Model;
use Illuminate\Database\Eloquent\Attributes\Fillable;
```

```
#[Fillable([
    'property_id',
    'user_id',
    'message',
    'status',
    'reservation_amount',
    'paypal_transaction_id'
])]

```

```

class Lead extends Model
{
    use HasFactory;

    /**
     * Get the property associated with the lead.
     */
    public function property(): \Illuminate\Database\Eloquent\Relations\BelongsTo
    {
        return $this->belongsTo(Property::class);
    }

    /**
     * Get the user (buyer) who created the lead.
     */
    public function user(): \Illuminate\Database\Eloquent\Relations\BelongsTo
    {
        return $this->belongsTo(User::class);
    }
}

```

13. Migración de Usuarios (database/migrations/0001_01_01_000000_create_users_table.php)

Path: database/migrations/0001_01_01_000000_create_users_table.php

<?php

```

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('users', function (Blueprint $table) {
            $table->id();
            $table->string('name');
            $table->string('email')->unique();
            $table->timestamp('email_verified_at')->nullable();
            $table->string('password');
            $table->enum('role', ['admin', 'agent', 'buyer'])->default('buyer');
            $table->boolean('is_approved')->default(true);
            $table->rememberToken();
            $table->timestamps();
        });

        Schema::create('password_reset_tokens', function (Blueprint $table) {
            $table->string('email')->primary();
            $table->string('token');
            $table->timestamp('created_at')->nullable();
        });

        Schema::create('sessions', function (Blueprint $table) {
            $table->string('id')->primary();
            $table->foreignId('user_id')->nullable()->index();
            $table->string('ip_address', 45)->nullable();
            $table->text('user_agent')->nullable();
            $table->longText('payload');
            $table->integer('last_activity')->index();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('users');
        Schema::dropIfExists('password_reset_tokens');
    }
}

```

```

        Schema::dropIfExists('sessions');
    }
};

```

14. Migración de Inmuebles (database/migrations/2026_07_21_184525_create_properties_table.php)

Path: database/migrations/2026_07_21_184525_create_properties_table.php

<?php

```

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('properties', function (Blueprint $table) {
            $table->id();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->string('title');
            $table->text('description');
            $table->decimal('price', 12, 2);
            $table->string('address');
            $table->decimal('latitude', 10, 8);
            $table->decimal('longitude', 11, 8);
            $table->enum('type', ['house', 'apartment', 'commercial']);
            $table->enum('status', ['available', 'reserved', 'sold'])->default('available');
            $table->timestamps();
        });
    }

    /**
     * Reverse the migrations.
     */
    public function down(): void
    {
        Schema::dropIfExists('properties');
    }
};

```

15. Migración de Leads y Apartados (database/migrations/2026_07_21_184528_create_leads_table.php)

Path: database/migrations/2026_07_21_184528_create_leads_table.php

<?php

```

use Illuminate\Database\Migrations\Migration;
use Illuminate\Database\Schema\Blueprint;
use Illuminate\Support\Facades\Schema;

return new class extends Migration
{
    /**
     * Run the migrations.
     */
    public function up(): void
    {
        Schema::create('leads', function (Blueprint $table) {
            $table->id();
            $table->foreignId('property_id')->constrained()->cascadeOnDelete();
            $table->foreignId('user_id')->constrained()->cascadeOnDelete();
            $table->text('message');
            $table->enum('status', ['pending', 'approved', 'paid', 'rejected']);
            $table->decimal('reservation_amount', 10, 2)->default(5.00);
            $table->string('paypal_transaction_id')->nullable();
            $table->timestamps();
        });
    }
};

```

```

/**
 * Reverse the migrations.
 */
public function down(): void
{
    Schema::dropIfExists('leads');
}
};

```

16. Vista de Ficha Digital y PayPal SDK (resources/views/leads/receipt.blade.php)

Path: resources/views/leads/receipt.blade.php

```
@extends('layouts.app');
```

```
@section('title', 'Ficha de Pre-Apartado SGNIA-RES-2026-00' . $lead->id)
```

```
@section('content')
```

```
<div class="max-w-4xl mx-auto px-4 sm:px-6 lg:px-8 py-10">
```

```
<!-- Receipt Container Card -->
```

```
<div class="bg-slate-900/95 rounded-3xl border border-slate-800 shadow-2xl overflow-hidden backdrop-blur-xl">
```

```
<!-- Header Ribbon -->
```

```
<div class="bg-slate-950 p-6 sm:p-8 border-b border-slate-800 flex flex-col sm:flex-row justify-between items-s">
```

```
<div class="flex items-center space-x-3">
```

```
<div class="w-12 h-12 rounded-2xl bg-slate-800 border border-slate-700 flex items-center justify-center">
    S
</div>
```

```
</div>
```

```
<div class="brand-font text-2xl font-extrabold text-white tracking-tight">SGNIA</div>
```

```
<span class="block text-[10px] font-bold uppercase tracking-widest text-slate-400">Ficha Of
</div>
```

```
</div>
```

```
<div class="text-right">
```

```
<span class="text-xs font-mono text-slate-400 block">Folio de Reserva:</span>
```

```
<span class="text-sm font-black font-mono text-white">SGNIA-RES-2026-00{{ $lead->id }}</span>
```

```
</div>
```

```
</div>
```

```
<div class="p-6 sm:p-10 space-y-8" id="receipt-content">
```

```
<!-- Status Banner -->
```

```
<div class="flex items-center justify-between p-4 rounded-2xl border">
```

```
{{ $lead->status === 'paid' ? 'bg-emerald-950/80 border-emerald-500/40 text-emerald-300' :
'>
```

```
<div class="flex items-center space-x-3">
```

```
@if($lead->status === 'paid')
```

```
<div class="w-10 h-10 rounded-full bg-emerald-500/20 flex items-center justify-center text-emer
</div>
```

```
<h4 class="font-extrabold text-white text-base">Inmueble Reservado Exitosamente!</h4>
```

```
<p class="text-xs text-emerald-300">Pago confirmado en línea vía PayPal. ID Transac
</div>
```

```
@else
```

```
<div class="w-10 h-10 rounded-full bg-slate-800 flex items-center justify-center text-slate-300
</div>
```

```
<h4 class="font-extrabold text-white text-base">Ficha Aprobada por Agente</h4>
```

```
<p class="text-xs text-slate-400">Pendiente de confirmación del pago de apartado ($
</div>
```

```
@endif
```

```
</div>
```

```
<span class="px-3.5 py-1 text-xs font-black uppercase tracking-wider rounded-full border">
```

```
{{ $lead->status === 'paid' ? 'bg-emerald-500/20 text-emerald-300 border-emerald-500/30' :
'>
```

```
{{ $lead->status === 'paid' ? 'Reservado ■' : 'Aprobado (Pago Pendiente)'}
</span>
```

```
</div>
```

```
<!-- Official Company Data Header for Paid Receipts -->
```

```
@if($lead->status === 'paid')
```

```
<div class="p-6 rounded-2xl bg-slate-950 border border-slate-800 space-y-3">
```

```

        <div class="flex flex-col sm:flex-row justify-between items-start sm:items-center border-b border-slate-800">
            <div>
                <span class="text-xs font-extrabold text-slate-300 uppercase tracking-widest block">
                    <h3 class="text-lg font-extrabold text-white">SGNIA Real Estate S.A. de C.V.</h3>
                    <p class="text-xs text-slate-400">RFC: <span class="font-mono text-slate-300">
                        </div>
                    <div class="text-left sm:text-right text-xs text-slate-400">
                        <span class="block font-bold text-white">Fecha de Transacción:</span>
                        <span>{{ $lead->updated_at ? $lead->updated_at->format(&#x27;d/m/Y h:i:s A&#x27;) : '' }}</span>
                    </div>
                </div>

                <div class="grid grid-cols-1 sm:grid-cols-2 gap-4 text-xs text-slate-300 pt-1">
                    <div>
                        <span class="text-slate-400 block font-semibold">Dirección Oficial:</span>
                        <span>Avenida 2 Poniente 4, Centro, 75120 Nopalucan de la Granja, Pue., México</span>
                    </div>
                    <div>
                        <span class="text-slate-400 block font-semibold">Contacto Oficial:</span>
                        <span>Tel: +52 223 131 6588 | Email: sgniacompany@corporacion.com</span>
                    </div>
                </div>
            </div>
        </div>
    @endif

    <!-- Property Details Summary -->
    <div class="grid grid-cols-1 md:grid-cols-3 gap-6 bg-slate-950 p-6 rounded-2xl border border-slate-800/80">
        <div class="md:col-span-2 space-y-2">
            <span class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400">Inmueble
            <h3 class="text-xl font-extrabold text-white">{{ $lead->property->title }}</h3>
            <p class="text-xs text-slate-400 flex items-center">
                <svg xmlns="http://www.w3.org/2000/svg" class="h-4 w-4 mr-1 text-slate-500" fill="none" stroke="linecap=round stroke-linejoin=round" d="M17.657 16.657L16.657 17.657" />
                {{ $lead->property->address }}
            </p>
        </div>

        <div class="text-right space-y-1 border-t md:border-t-0 md:border-l border-slate-800 pt-4 md:pt-0 md:pl-4">
            <span class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400 block">Pre
            <span class="text-xl font-black text-white block">{{ number_format($lead->property->
            <span class="text-xs font-bold text-slate-400 block mt-2">Monto de Enganche Pagado:</span>
            <span class="text-2xl font-black text-emerald-400 block">{{ number_format($lead->reserv
            @if($lead->status === &#x27;paid&#x27;)>
                <span class="text-[10px] font-bold text-slate-400 block mt-1">Saldo a Escrituración:</span>
                <span class="text-xs font-mono font-bold text-slate-300 block">{{ number_format($lead-
            @endif
        </div>
    </div>

    <!-- People Info -->
    <div class="grid grid-cols-1 md:grid-cols-2 gap-6">
        <div class="p-4 rounded-2xl bg-slate-950 border border-slate-800 space-y-1">
            <span class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400">Cliente C
            <p class="font-extrabold text-white text-sm">{{ $lead->user ? $lead->user->name : '' }}
            <p class="text-xs text-slate-400">{{ $lead->user ? $lead->user->email : &#x27;-&#x27; }}
        </div>

        <div class="p-4 rounded-2xl bg-slate-950 border border-slate-800 space-y-1">
            <span class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400">Agente SG
            <p class="font-extrabold text-white text-sm">{{ $lead->property->user ? $lead->property->
            <p class="text-xs text-slate-400">Nopalucan de la Granja, Puebla</p>
        </div>
    </div>

    <!-- PayPal Payment Section / Print Action -->
    @if($lead->status !== &#x27;paid&#x27;)>
        <div class="p-6 sm:p-8 rounded-3xl bg-slate-950 border border-slate-800 space-y-6 text-center">
            <div class="max-w-md mx-auto space-y-2">
                <span class="text-xs font-extrabold uppercase tracking-widest text-slate-300">Pagar Apa
                <h3 class="text-2xl font-extrabold text-white">Total a Pagar: {{ number_format($lead-&
                <p class="text-xs text-slate-400">
                    Procesa tu pago de forma 100% segura con saldo PayPal o Tarjeta de Crédito/Débito.
                </p>
            </div>
        </div>
    @endif

```

```
<!-- PayPal SDK Buttons Container -->
<div class="max-w-md mx-auto pt-2">
  <div id="paypal-button-container"></div>
</div>
@else
  <div class="p-6 rounded-2xl bg-slate-950 border border-slate-800 flex flex-col sm:flex-row items-center">
    <div>
      <p class="text-xs text-slate-300 font-bold">Comprobante Oficial de Reserva Confirmada p
      <p class="text-[11px] text-slate-400">Conserva este recibo digital para tu proceso de e
    </div>
    <div class="flex items-center space-x-3">
      <button onclick=">window.print()" class="px-5 py-2.5 bg-slate-100 hover:bg-white text-
        <svg xmlns="http://www.w3.org/2000/svg" class="h-4 w-4 mr-2 text-slate-950"
          <path stroke-linecap="round" stroke-linejoin="round" d="M17 17h2a2
            </svg>
        Imprimir / Guardar PDF
      </button>
      <a href="{{ route(&#x27;properties.show&#x27;, $lead-&#x27;property-&#x27;id) }}" class="
        ← Volver a Inmueble
      </a>
    </div>
  </div>
@endif
</div>

</div>
</div>
@endsection

@section(&#x27;scripts&#x27;)
@if($lead-&#x27;status !== &#x27;paid&#x27;)
  <!-- PayPal JavaScript SDK -->
  <script src="https://www.paypal.com/sdk/js?client-id={{ $paypalClientId }}&amp;currency=MXN&amp;locale=es_MX"></script>
  document.addEventListener(&#x27;DOMContentLoaded&#x27;, () => {
    if (window.paypal) {
      paypal.Buttons({
        style: {
          layout: &#x27;vertical&#x27;,
          color: &#x27;gold&#x27;,
          shape: &#x27;rect&#x27;,
          label: &#x27;paypal&#x27;,
        },

        createOrder: function(data, actions) {
          return actions.order.create({
            purchase_units: [{
              amount: {
                value: &#x27;{{ number_format($lead-&#x27;reservation_amount, 2, &#x27;.&#x27;, &#x27;&#x27;) }}&#x27;,
                currency_code: &#x27;MXN&#x27;,
              },
              description: &#x27;Reserva Inmobiliaria Folio SGNIA-RES-2026-00{{ $lead-&#x27;id }}&#x27;,
            ]
          });
        },

        onApprove: function(data, actions) {
          return actions.order.capture().then(function(details) {
            const transactionId = details.id || data.orderID;
            const csrfToken = document.querySelector(&#x27;meta[name="csrf-token"]&#x27;).getAttribute

            fetch("{{ route(&#x27;leads.pay-paypal&#x27;, $lead-&#x27;id) }}", {
              method: &#x27;POST&#x27;,
              headers: {
                &#x27;Content-Type&#x27;: &#x27;application/json&#x27;,
                &#x27;Accept&#x27;: &#x27;application/json&#x27;,
                &#x27;X-CSRF-TOKEN&#x27;: csrfToken
              },
              body: JSON.stringify({
                paypal_transaction_id: transactionId

```

```
<div class="bg-gradient-to-r from-slate-900 via-[#131927] to-[#0b0f19] text-white py-8 sm:py-12 px-4 sm:px-6 lg:px-8 re
  <div class="max-w-7xl mx-auto relative z-10 flex flex-col md:flex-row md:items-center justify-between gap-4">
    <div>
      <div class="flex items-center space-x-3 mb-2">
        <span class="px-3.5 py-1 text-xs font-extrabold uppercase tracking-widest rounded-full bg-slate-800 tex
          ■ Comprador SGNIA
        </span>
      </div>
    </div>
    <h1 class="text-2xl sm:text-4xl font-extrabold tracking-tight">
      Mis Solicitudes y Apartados - <span class="text-slate-300">{{ $user->name }}</span>
    </h1>
    <p class="text-slate-400 text-xs sm:text-sm mt-1">
      Consulta tus mensajes enviados, confirma tus fichas aprobadas y procesa el pago de apartados con PayPal.
```

```

        </p>
    </div>

    <div>
        <a href="{{ route(&#x27;properties.index&#x27;) }}"> class="inline-flex items-center px-5 py-3 rounded-md text-sm font-medium text-white bg-slate-800 hover:bg-slate-700 focus:outline-none focus:ring-2 focus:ring-offset-2 focus:ring-slate-500">
            <span>← Explorar Inmuebles</span>
        </a>
    </div>
</div>
</div>

<div class="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-8 space-y-8">
    <!-- KPI Stats Cards -->
    <div class="grid grid-cols-1 md:grid-cols-3 gap-6">
        <div class="bg-slate-900/90 p-6 rounded-3xl border border-slate-800 shadow-xl flex items-center space-x-4 backdrop-blur-sm">
            <div class="p-4 rounded-2xl bg-slate-800 text-slate-300 border border-slate-700">
                <svg xmlns="http://www.w3.org/2000/svg" class="h-8 w-8" fill="none" viewBox="0 0 24 24">
                    <path stroke-linecap="round" stroke-linejoin="round" d="M8 10h.01M12 10h.01M16 10h.01M20 10h.01M24 10h.01M8 14h.01M12 14h.01M16 14h.01M20 14h.01M24 14h.01"></path>
                </svg>
            </div>
            <div>
                <p class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400">Solicitudes Enviadas</p>
                <h3 class="text-3xl font-black text-white">{{ $stats[&#x27;total_requests&#x27;] }}</h3>
            </div>
        </div>
        <div class="p-4 rounded-2xl bg-amber-500/10 text-amber-300 border border-amber-500/30">
            <svg xmlns="http://www.w3.org/2000/svg" class="h-8 w-8" fill="none" viewBox="0 0 24 24">
                <path stroke-linecap="round" stroke-linejoin="round" d="M3 10h18M7 15h14m4 0h1m4 0h1m4 0h1m4 0"></path>
            </svg>
            <div>
                <p class="text-[10px] font-extrabold uppercase tracking-widest text-amber-400">Apartados Listos</p>
                <h3 class="text-3xl font-black text-white">{{ $stats[&#x27;approved_requests&#x27;] }}</h3>
            </div>
        </div>
        <div class="p-4 rounded-2xl bg-emerald-500/10 text-emerald-300 border border-emerald-500/30">
            <svg xmlns="http://www.w3.org/2000/svg" class="h-8 w-8" fill="none" viewBox="0 0 24 24">
                <path stroke-linecap="round" stroke-linejoin="round" d="M9 12l2 2 4-4m6 2a9 9 0 100 0"></path>
            </svg>
            <div>
                <p class="text-[10px] font-extrabold uppercase tracking-widest text-emerald-400">Inmuebles Reservados</p>
                <h3 class="text-3xl font-black text-white">{{ $stats[&#x27;paid_requests&#x27;] }}</h3>
            </div>
        </div>
    </div>
    <!-- Client Requests List -->
    <div class="bg-slate-900/90 rounded-3xl border border-slate-800 shadow-2xl overflow-hidden p-6 space-y-6 backdrop-blur-sm">
        <div class="flex items-center justify-between border-b border-slate-800 pb-4">
            <div>
                <h2>Historial de Solicitudes y Apartados</h2>
                <p class="text-xs text-slate-400">Estado en tiempo real de tus consultas sobre propiedades en M&#x27;xico</p>
            </div>
            <span class="px-3 py-1 bg-slate-800 text-slate-200 font-extrabold text-xs rounded-full border border-slate-700">
                {{ $leads->count() }} Registro(s)
            </span>
        </div>
        <div class="space-y-4">
            @forelse($leads as $lead)
                <div class="p-6 rounded-2xl bg-slate-950 border border-slate-800 hover:border-slate-700 transition flex items-center">
                    <!-- Property & Agent Info -->

```

```

<div class="flex flex-col sm:flex-row items-start sm:items-center gap-4 max-w-2xl">
  <!-- Thumbnail Image -->
  <div class="w-24 h-24 rounded-2xl bg-slate-900 overflow-hidden shrink-0 border border-slate-800"
    @if($lead->property && $lead->property->images->isEmpty())
      <img src=""{{ $lead->property->images->first()->url }}" alt=""{{ $lead->property->images->first()->alt }}"/>
    @else
      <div class="w-full h-full flex items-center justify-center text-slate-600 font-black text-2xl">
        <div class="w-24 h-24 rounded-2xl bg-slate-900 overflow-hidden shrink-0 border border-slate-800">
          <img src=""{{ $lead->property->images->first()->url }}" alt=""{{ $lead->property->images->first()->alt }}"/>
        </div>
      </div>
    @endif
  </div>

  <!-- Info -->
  <div class="space-y-1.5">
    <span class="px-2.5 py-0.5 text-[10px] font-black uppercase tracking-wider rounded-md bg-slate-900 text-white">
      Folio: SGNIA-RES-2026-00{{ $lead->id }}
    </span>
    <h3 class="text-lg font-extrabold text-white">
      @if($lead->property)
        <a href=""{{ route('properties.show', $lead->property->id) }}">
          {{ $lead->property->title }}
        </a>
      @else
        Propiedad Eliminada
      @endif
    </h3>
    <p class="text-xs text-slate-400">
      {{ $lead->property ? $lead->property->address : '' }}
    </p>
    <p class="text-xs text-slate-400">
      ■ Agente Asignado: <span class="text-slate-200 font-semibold">{{ $lead->property->agent }}
    </p>
    <p class="text-xs text-slate-400 italic bg-slate-900/80 p-2.5 rounded-xl border border-slate-800">
      Tu mensaje: <div class="border border-slate-800 p-2.5 rounded-xl">{{ $lead->message }}</div>
    </p>
  </div>
</div>

<!-- Status & Action Button -->
<div class="flex flex-col items-start md:items-end justify-between gap-3 shrink-0 pt-4 md:pt-0 border-top border-slate-800">
  <!-- Status Badge -->
  <span class="px-3.5 py-1.5 text-xs font-black uppercase tracking-wider rounded-xl border"
    {{ $lead->status === 'paid' ? 'bg-emerald-950 text-emerald-300 border-emerald-500' :
      $lead->status === 'approved' ? 'bg-amber-950 text-amber-300 border-amber-500' :
      $lead->status === 'pending' ? 'bg-slate-900 text-slate-400 border-slate-800' : '' }}>
    <div class="text-center">
      @if($lead->status === 'paid')
        ■ Reservado Exitosamente (Pagado)
      @elseif($lead->status === 'approved')
        ■ Ficha Emitida - Pago Pendiente ($5 MXN)
      @else
        ■ Solicitud en Revisión
      @endif
    </div>
  </span>

  <!-- Action Button -->
  <div>
    @if($lead->status === 'approved')
      <a href=""{{ route('leads.receipt', $lead->id) }}">
        ■ Pagar Apartado ($5.00 MXN) con PayPal →
      </a>
    @elseif($lead->status === 'paid')
      <a href=""{{ route('leads.receipt', $lead->id) }}">
        ■ Ver Comprobante Oficial de Pago →
      </a>
    @else
      <span class="text-xs text-slate-500 font-medium italic">
        El agente responderá tu mensaje en breve
      </span>
    @endif
  </div>
</div>
</div>
@empty

```



```

<div class="p-4 rounded-2xl bg-slate-800 text-slate-300 border border-slate-700">
  <svg xmlns="http://www.w3.org/2000/svg" class="h-8 w-8" fill="none" viewBox="0 0 24 24">
    <path stroke-linecap="round" stroke-linejoin="round" d="M12 4.354a4 4 0 110 5.294" />
  </svg>
</div>
<div>
  <p class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400">Agentes Pendientes</p>
  <h3 class="text-3xl font-black text-white">{{ $stats[&#x27;pending_agents&#x27;] ?? 0 }}</h3>
</div>
</div>

<div class="bg-slate-900/90 p-6 rounded-3xl border border-slate-800 shadow-xl flex items-center space-x-4 backdrop-blur-sm">
  <div class="p-4 rounded-2xl bg-slate-800 text-slate-300 border border-slate-700">
    <svg xmlns="http://www.w3.org/2000/svg" class="h-8 w-8" fill="none" viewBox="0 0 24 24">
      <path stroke-linecap="round" stroke-linejoin="round" d="M8 10h.01M12 10h.01M16 10h.01" />
    </svg>
  </div>
  <div>
    <p class="text-[10px] font-extrabold uppercase tracking-widest text-slate-400">Solicitudes Recibidas</p>
    <h3 class="text-3xl font-black text-white">{{ $stats[&#x27;total_leads&#x27;] }}</h3>
  </div>
</div>
</div>

@if($user->role === &#x27;admin&#x27; &amp;&amp; isset($pendingAgents) &amp;&amp; $pendingAgents->isEmpty())
  <!-- Section: Pending Agents Approval -->
  <div class="bg-slate-900/90 rounded-3xl border border-amber-500/40 shadow-2xl overflow-hidden space-y-4 p-6 backdrop-blur-sm">
    <div class="flex items-center justify-between border-b border-slate-800 pb-4">
      <div>
        <h2 class="text-xl font-extrabold text-white flex items-center">
          <svg xmlns="http://www.w3.org/2000/svg" class="h-6 w-6 mr-2 text-amber-400" fill="none" viewBox="0 0 24 24">
            <path stroke-linecap="round" stroke-linejoin="round" d="M12 9v2m0 4h.01" />
          </svg>
          Agentes Inmobiliarios Pendientes de Aprobación
        </h2>
        <p class="text-xs text-slate-400">Solicitudes de registro de agentes que requieren tu confirmación</p>
      </div>
      <span class="px-3 py-1 bg-amber-500/10 text-amber-300 border border-amber-500/30 font-extrabold text-sm">
        {{ $pendingAgents->count() }} Pendiente(s)
      </span>
    </div>

    <div class="overflow-x-auto">
      <table class="w-full text-left text-sm text-slate-300">
        <thead class="bg-slate-950 text-slate-300 font-extrabold uppercase text-[10px] tracking-wider">
          <tr>
            <th class="p-3">Nombre</th>
            <th class="p-3">Correo Electrónico</th>
            <th class="p-3">Fecha Solicitud</th>
            <th class="p-3 text-right">Acción</th>
          </tr>
        </thead>
        <tbody class="divide-y divide-slate-800/80 font-medium text-xs sm:text-sm">
          @foreach($pendingAgents as $agent)
            <tr class="hover:bg-slate-800/50">
              <td class="p-3 font-bold text-white">{{ $agent->name }}</td>
              <td class="p-3 text-slate-300">{{ $agent->email }}</td>
              <td class="p-3 text-xs text-slate-400">{{ $agent->created_at ? $agent->created_at : '' }}</td>
              <td class="p-3 text-right">
                <form action="{{ route(&#x27;admin.agents.approve&#x27;, $agent->id) }}" method="POST">
                  @csrf
                  <button type="submit" class="px-4 py-2 bg-emerald-500 hover:bg-emerald-600 text-white">
                    ✓ Aprobar y Activar Agente
                  </button>
                </form>
              </td>
            </tr>
          @endforeach
        </tbody>
      </table>
    </div>
  </div>
</if>

```

```

@if($User->role == '#x27;admin'&#x27; &amp;&amp; $ActiveAgents->isEmpty())
<!-- Section: Active Agents Control -->
<div class="bg-slate-900/90 rounded-3xl border border-slate-800 shadow-2xl overflow-hidden space-y-4 p-6 backdrop-blur-3xl">
<div class="flex items-center justify-between border-b border-slate-800 pb-4">
<div>
<h2 class="text-xl font-extrabold text-white flex items-center">
<svg xmlns="http://www.w3.org/2000/svg" class="h-6 w-6 mr-2 text-slate-400" fill="none" stroke="linecap" stroke-linejoin="round" stroke-width="2" d="M17 20h5v2a3 3 0 0 0 3 3" />
Agentes Inmobiliarios Activos
</h2>
<p class="text-xs text-slate-400">Control de accesos y administración de permisos de agentes activos</p>
</div>
<span class="px-3 py-1 bg-slate-800 text-slate-200 font-extrabold text-xs rounded-full border border-slate-700">
{{ $ActiveAgents->count() }} Agente(s) Activo(s)
</span>
</div>

<div class="overflow-x-auto">
<table class="w-full text-left text-sm text-slate-300">
<thead class="bg-slate-950 text-slate-300 font-extrabold uppercase text-[10px] tracking-wider">
<tr>
<th class="p-3">Nombre Agente</th>
<th class="p-3">Correo Electrónico</th>
<th class="p-3">Estado</th>
<th class="p-3 text-right">Acción de Seguridad</th>
</tr>
</thead>
<tbody class="divide-y divide-slate-800/80 font-medium text-xs sm:text-sm">
@foreach($ActiveAgents as $Agent)
<tr class="hover:bg-slate-800/50">
<td class="p-3 font-bold text-white">{{ $Agent->name }}</td>
<td class="p-3 text-slate-300">{{ $Agent->email }}</td>
<td class="p-3">
<span class="px-2.5 py-1 text-[10px] font-black uppercase rounded-lg border bg-emerald-500">
Activo ✓
</span>
</td>
<td class="p-3 text-right">
<form action="{{ route('admin.agents.revoke', $Agent->id) }}" method="POST" @csrf>
<button type="submit" class="px-3 py-1.5 bg-rose-950/80 hover:bg-rose-900/80">
Desactivar Acceso
</button>
</form>
</td>
</tr>
</tbody>
</table>
</div>
</div>
@endif

<!-- Section 1: Leads Received from Buyers -->
<div class="bg-slate-900/90 rounded-3xl border border-slate-800 shadow-2xl overflow-hidden p-6 space-y-6 backdrop-blur-3xl">
<div class="flex items-center justify-between border-b border-slate-800 pb-4">
<div>
<h2 class="text-xl font-extrabold text-white flex items-center">
<svg xmlns="http://www.w3.org/2000/svg" class="h-6 w-6 mr-2 text-slate-400" fill="none" stroke="linecap" stroke-linejoin="round" stroke-width="2" d="M3 8l7.89 5.26a2 2 0 0 0 2 2" />
Solicitudes de Compradores (Leads)
</h2>
<p class="text-xs text-slate-400">Mensajes recibidos de clientes interesados y gestión de apartos</p>
</div>
<span class="px-3 py-1 bg-slate-800 text-slate-200 font-extrabold text-xs rounded-full border border-slate-700">
{{ $Leads->count() }} Mensajes
</span>
</div>

<!-- Responsive Card List for Leads -->
<div class="space-y-4">

```

```

@forelse($leads as $lead)
    <div class="p-5 rounded-2xl bg-slate-950 border border-slate-800/80 hover:border-slate-700 transition f

        <!-- Left: Customer & Message -->
        <div class="space-y-2 max-w-xl">
            <div class="flex items-center space-x-3">
                <div class="w-9 h-9 rounded-xl bg-slate-800 text-white font-extrabold flex items-center justify-center">
                    {{ strtoupper(substr($lead->user ? $lead->user->name : '&#x27;U&#x27;', 0, 2)) }}
                </div>
                <div>
                    <h4 class="font-extrabold text-white text-sm leading-tight">{{ $lead->user ? $lead->user->name : '&#x27;U&#x27;' }}
                    <p class="text-xs text-slate-400 font-mono">{{ $lead->user ? $lead->user->email : '&#x27;E&#x27;' }}
                </div>
            </div>

            <div class="pl-12 space-y-1">
                <p class="text-xs font-semibold text-slate-300">Inmueble:
                @if($lead->property)
                    <a href="{{ route('&#x27;properties.show&#x27;', $lead->property->id) }}">
                        {{ $lead->property->title }}
                    </a>
                @else
                    <span class="text-rose-400">Propiedad Eliminada</span>
                @endif
            </p>
            <p class="text-xs text-slate-400 italic bg-slate-900/80 p-3 rounded-xl border border-slate-800">{{ $lead->message }}
        </div>

        <!-- Right: Status Badge & Action Buttons -->
        <div class="flex flex-col sm:flex-row md:flex-col items-start md:items-end justify-between gap-3">
            <span class="px-3 py-1 text-xs font-black uppercase tracking-wider rounded-xl border">
                {{ $lead->status === '&#x27;paid&#x27;' ? '&#x27;bg-emerald-950 text-emerald-300 border-emerald-500' :
                {{ $lead->status === '&#x27;approved&#x27;' ? '&#x27;bg-amber-950 text-amber-300 border-amber-500/30' :
                {{ $lead->status === '&#x27;pending&#x27;' ? '&#x27;bg-slate-900 text-slate-300 border-slate-700/80' : '&#x27;bg-slate-950 text-slate-400 border-slate-800' }}
            </span>
            {{ $lead->status === '&#x27;paid&#x27;' ? '&#x27;■ Reservado (Pagado)&#x27;' : ($lead->status === '&#x27;pending&#x27;' ? '&#x27;■ Pendiente de pago&#x27;' : '&#x27;■ Aprobado y Solicitado&#x27;') }}
        </div>

        @if($lead->status === '&#x27;pending&#x27;')
            <form action="{{ route('&#x27;admin.leads.approve&#x27;', $lead->id) }}" method="POST">
                @csrf
                <input type="hidden" name="reservation_amount" value="5.00">
                <button type="submit" class="px-4 py-2.5 bg-slate-100 hover:bg-white text-slate-900">
                    ✓ Aprobar y Solicitar Apartado ($5 MXN)
                </button>
            </form>
        @else
            <a href="{{ route('&#x27;leads.receipt&#x27;', $lead->id) }}" class="inline-block">
                ■ Ver Ficha / Pagar con PayPal →
            </a>
        @endif
    </div>

    @empty
        <div class="p-8 text-center text-slate-500 bg-slate-950 rounded-2xl border border-slate-800">
            Aún no se han recibido solicitudes de información de compradores.
        </div>
    @endforelse
</div>

<!-- Section 2: Manage Properties -->
<div class="bg-slate-900/90 rounded-3xl border border-slate-800 shadow-2xl overflow-hidden space-y-4 p-6 backdrop-blur">
    <div class="flex items-center justify-between border-b border-slate-800 pb-4">
        <h2 class="text-xl font-extrabold text-white flex items-center">

```

```

<svg xmlns="http://www.w3.org/2000/svg" class="h-6 w-6 mr-2 text-slate-400" fill="
    <path stroke-linecap="round" stroke-linejoin="round" d="M19 21v5a2 2 0 0-2
    </svg>
    Gestión de Inmuebles
    </h2>
    <p class="text-xs text-slate-400">Publicaciones registradas en Nopalucan</p>
    </div>
    <a href="{ route('admin.properties.create') }" class="px-4 py-2 bg-slate-100 hover:
    + Agregar Inmueble
    </a>
    </div>

    <div class="overflow-x-auto">
        <table class="w-full text-left text-sm text-slate-300">
            <thead class="bg-slate-950 text-slate-300 font-extrabold uppercase text-[10px] tracking-wider">
                <tr>
                    <th class="p-3">Título</th>
                    <th class="p-3">Tipo</th>
                    <th class="p-3">Precio</th>
                    <th class="p-3">Dirección</th>
                    <th class="p-3 text-right">Acciones</th>
                </tr>
            </thead>
            <tbody class="divide-y divide-slate-800/80 font-medium text-xs sm:text-sm">
                @forelse($properties as $property)
                    <tr class="hover:bg-slate-800/50">
                        <td class="p-3 font-bold text-white">
                            {{ $property->title }}
                        </td>
                        <td class="p-3">
                            <span class="px-2.5 py-1 text-[10px] font-black uppercase rounded-lg border bg-slate-950">
                                {{ $property->type == 'house' ? 'Casa' : ($property->type == '
                            </span>
                        </td>
                        <td class="p-3 font-black text-white">
                            ${{ number_format($property->price, 0, '&#x2F;', '&#x2F;.&#x2F;') }} MXN
                        </td>
                        <td class="p-3 text-xs text-slate-400 max-w-xs truncate">
                            {{ $property->address }}
                        </td>
                        <td class="p-3 text-right space-x-2">
                            <a href="{ route('properties.show', $property->id) }" class="
                                Ver Ficha
                            </a>
                            <form action="{ route('admin.properties.destroy', $property->id) }"
                                @csrf
                                @method('DELETE')
                                <button type="submit" class="px-3 py-1.5 bg-rose-950/80 hover:bg-rose-600
                                    Eliminar
                                </button>
                            </form>
                        </td>
                    </tr>
                @empty
                    <tr>
                        <td colspan="5" class="p-6 text-center text-slate-500">
                            No hay propiedades registradas aún.
                        </td>
                    </tr>
                @endforelse
            </tbody>
        </table>
    </div>
    </div>
</div>
<endsection

```

19. Vista Principal del Catálogo y Mapa Satelital (resources/views/properties/index.blade.php)

Path: resources/views/properties/index.blade.php

```
@extends('layouts.app')
```

```

@section(&#x27;title&#x27;; &#x27;Explorar Inmuebles Satelitales - SGNIA Real Estate&#x27;)

@section(&#x27;content&#x27;)
<!-- Hero Section -->
<div class="relative bg-gradient-to-b from-slate-900 via-[#131927] to-[#0b0f19] border-b border-slate-800/80 overflow-hidden"
  <div class="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 relative z-10">
    <div class="text-center max-w-3xl mx-auto space-y-4">
      <span class="inline-flex items-center px-4 py-1.5 rounded-full text-xs font-black uppercase tracking-widest"
        ■ Ubicación Satelital HD • Nopalucan, Puebla
      </span>

      <h1 class="text-4xl sm:text-6xl font-extrabold text-white tracking-tight leading-tight">
        Encuentra tu Inmueble Ideal en <span class="text-slate-300 underline decoration-slate-600 decoration-2"
      </h1>

      <p class="text-base sm:text-lg text-slate-400 font-medium max-w-2xl mx-auto leading-relaxed">
        Explora residencias, terrenos y locales comerciales con vista satelital interactiva y datos del clima en tiempo real
      </p>
    </div>
  </div>
</div>

<!-- Main Section: Properties Grid & Satellite Map -->
<div class="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-10 space-y-12">

  <!-- Interactive Esri Satellite Map Container -->
  <div class="bg-slate-900/90 rounded-3xl p-6 sm:p-8 border border-slate-800 shadow-2xl space-y-4 backdrop-blur-xl"
    <div class="flex flex-col sm:flex-row sm:items-center justify-between gap-4">
      <div>
        <h2 class="text-xl font-extrabold text-white flex items-center">
          <svg xmlns="http://www.w3.org/2000/svg" class="h-6 w-6 mr-2 text-slate-300" fill="none"
            <path stroke-linecap="round" stroke-linejoin="round" d="M17.657 16.657L13.415 12.415"
            <path stroke-linecap="round" stroke-linejoin="round" d="M15 11a3 3 0 1 1 6 6"
          </svg>
          Mapa Satelital en Tiempo Real (Nopalucan de la Granja)
        </h2>
        <p class="text-xs text-slate-400">Selecciona cualquier marcador o cambia a la vista de calle
      </div>
      <span class="inline-flex items-center px-3 py-1 rounded-lg text-xs font-bold bg-slate-800 text-slate-300 border border-slate-700"
        ■ Satélite Esri HD Activo
      </span>
    </div>

    <div id="properties-map" class="h-[450px] w-full rounded-2xl border border-slate-800 shadow-inner z-0"
  </div>

  <!-- Properties List Header -->
  <div class="flex flex-col sm:flex-row sm:items-center justify-between border-b border-slate-800 pb-4 gap-4">
    <div>
      <h3 class="text-2xl font-extrabold text-white">Catálogo de Propiedades</h3>
      <p class="text-xs text-slate-400">Mostrando {{ $properties->count() }} inmuebles disponibles
    </div>
    <div class="flex items-center space-x-2 text-xs font-bold text-slate-400">
      <span>Filtrar por:</span>
      <span class="px-3 py-1 bg-slate-800 text-white rounded-lg border border-slate-700">Todos</span>
    </div>
  </div>

  <!-- Properties Grid -->
  <div class="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3 gap-8"
    @forelse($properties as $property)
      <div class="group bg-slate-900/90 rounded-3xl border border-slate-800 hover:border-slate-600 shadow-xl hover:shadow-2xl"
        <!-- Image Container -->
        <div class="relative h-52 bg-slate-950 overflow-hidden"
          @if($property->images->isNotEmpty())
            title }}"
              class="w-full h-full object-cover group-hover:scale-105 transition duration-500"
              onerror="this.onerror=null; this.src=&#x27;https://images.unsplash.com/photo-1564013799919-ab660e627534?ixlib=rb-1.2.1&auto=format&fit=crop&w=1200&q=60";
            </div>
          @else

```

```
<div class="w-full h-full bg-gradient-to-br from-slate-900 to-slate-950 flex items-center justify-between p-6">
    <svg xmlns="http://www.w3.org/2000/svg" class="h-16 w-16 text-slate-700" fill="none" stroke="white" stroke-width="2">
        <path stroke-linecap="round" stroke-linejoin="round" d="M19 21V5a2 2 0 0 0 2 2h8v8a2 2 0 0 0 2 2"/>
    </svg>
</div>
@endif

<div class="absolute top-4 left-4">
    <span class="px-3 py-1 text-[10px] font-black uppercase tracking-wider rounded-lg shadow-md border border-slate-700">
        {{ $property->type === &#x27;house&#x27; ? &#x27;Casa&#x27; : ($property->type === &#x27;apartment&#x27; ? &#x27;Departamento&#x27; : &#x27;Other&#x27;) }}
    </span>
</div>

<div class="absolute bottom-4 right-4">
    <span class="px-3 py-1 bg-slate-950/90 text-white font-extrabold text-sm rounded-lg border border-slate-700">
        {{ number_format($property->price, 0, &#x27;, &#x27;, &#x27;.&#x27;) }} MXN
    </span>
</div>
</div>

<!-- Details Content -->
<div class="p-6 space-y-4 flex-grow flex flex-col justify-between">
    <div>
        <h4 class="text-lg font-extrabold text-white group-hover:text-slate-300 transition duration-200">
            {{ $property->title }}
        </h4>
        <p class="text-xs text-slate-400 mt-2 line-clamp-2 leading-relaxed">
            {{ $property->description }}
        </p>
    </div>

    <div class="space-y-3 pt-4 border-t border-slate-800/80">
        <div class="flex items-center text-xs text-slate-400">
            <svg xmlns="http://www.w3.org/2000/svg" class="h-4 w-4 mr-1.5 text-slate-400 shrink-0">
                <path stroke-linecap="round" stroke-linejoin="round" d="M17.657 16.657L13 13l5.657-5.657"/>
            </svg>
            <span class="line-clamp-1 text-slate-300 font-semibold">{{ $property->address }}</span>
        </div>

        <div class="flex items-center justify-between pt-2">
            <button type="button" onclick="focusOnProperty({{ $property->latitude }}, {{ $property->longitude }}, &#x27;map" class="text-xs font-bold text-slate-300 hover:text-white flex items-center transition">
                <svg xmlns="http://www.w3.org/2000/svg" class="h-4 w-4 mr-1 text-slate-400">
                    <path stroke-linecap="round" stroke-linejoin="round" d="M15 12a2 2 0 0 0 2 2"/>
                </svg>
                Ubicar en Mapa
            </button>

            <a href="{{ route(&#x27;properties.show&#x27;, $property->id) }}" class="inline-flex items-center px-4 py-2 bg-slate-800 hover:bg-slate-700 text-white font-medium">
                Ver Ficha →
            </a>
        </div>
    </div>
</div>

@empty
    <div class="col-span-full py-16 text-center bg-slate-900/60 rounded-3xl border border-slate-800">
        <p class="text-slate-400 font-medium">No se encontraron propiedades registradas en este momento.</p>
    </div>
@endforelse
</div>

</div>
</section>
```

```

@section(&#x27;scripts&#x27;)
<script>
  let map;
  let markers = [];

document.addEventListener(&#x27;DOMContentLoaded&#x27;, () => {
  // Nopalucan de la Granja Center Coordinates
  const defaultLat = 19.215050;
  const defaultLng = -97.817920;

  // Initialize Map
  map = L.map(&#x27;properties-map&#x27;, {
    scrollWheelZoom: false
  }).setView([defaultLat, defaultLng], 14);

  // Satellite Tile Layer (Esri World Imagery)
  const satelliteLayer = L.tileLayer(&#x27;https://server.arcgisonline.com/ArcGIS/rest/services/World_Imagery/MapServer/tiles/{z}/{x}/{y}.png&#x27;, {
    attribution: &#x27;Tiles &amp;copy; Esri &mdash; Source: Esri, i-cubed, USDA, USGS, AEX, GeoEye, Getmapping, Aermap, IGN, etc. &mdash; Imagery &copy; Esri &#x27;,
    maxZoom: 19
  });

  // Street View Tile Layer (OpenStreetMap)
  const streetLayer = L.tileLayer(&#x27;https://tile.openstreetmap.org/{z}/{x}/{y}.png&#x27;, {
    attribution: &#x27;&amp;copy; OpenStreetMap contributors&#x27;,
    maxZoom: 19
  });

  // Default set Satellite
  satelliteLayer.addTo(map);

  // Layer Control
  const baseMaps = {
    '&#x27;Sat lite HD (Esri)&quot;: satelliteLayer,
    '&#x27;Vista Calle (OSM)&quot;: streetLayer
  };
  L.control.layers(baseMaps, null, { position: &#x27;topright&#x27; }).addTo(map);

  // Fix Leaflet tile loading inside Cloud9 container
  setTimeout(() => { map.invalidateSize(); }, 300);
  setTimeout(() => { map.invalidateSize(); }, 1000);

  // Load Properties via Fetch API
  fetch('&#x27;api.properties.index&#x27;')
    .then(response => response.json())
    .then(properties => {
      properties.forEach(property => {
        if (property.latitude &amp; property.longitude) {
          let imageHtml = &#x27;&#x27;;
          if (property.images &amp; property.images.length > 0) {
            const rawPath = property.images[0].image_path;
            const fullUrl = (rawPath.startsWith('&#x27;http://&#x27;') || rawPath.startsWith('&#x27;https://&#x27;')) ? rawPath : '&#x27;http://localhost:3000&#x27;' + rawPath;
            imageHtml = '&lt;img src=&quot;${fullUrl}&quot; class=&quot;w-full h-24 object-cover rounded-xl mb-2&quot; /&gt;';
          }

          const popupContent = `
            &lt;div class=&quot;p-1 max-w-xs&quot;&gt;
              &lt;div class=&quot;flex justify-between items-center&quot;&gt;
                &lt;div>
                  &lt;h4 class=&quot;font-extrabold text-sm text-white leading-tight mb-1&quot;&gt;${property.title}
                  &lt;p class=&quot;text-xs text-slate-300 font-bold mb-2&quot;&gt;${Number(property.price).toLocaleString()}
                  &lt;a href=&quot;/properties/${property.id}&quot; class=&quot;inline-block w-full text-center text-white&quot;&gt;Ver Detalles Completo
                &lt;/div>
              &lt;/div>
            &lt;/div>
          `;

          const marker = L.marker([property.latitude, property.longitude])
            .addTo(map)
            .bindPopup(popupContent);

          markers.push({
            id: property.id,
            marker: marker,
            lat: property.latitude,
            lng: property.longitude
          });
        }
      });
    });
}
</script>

```

```

                lng: property.longitude
            });
        }
    });
})
.catch(err => console.error('Error cargando marcas de mapa:', err));
});

function focusOnProperty(lat, lng, title) {
    if (map) {
        map.flyTo([lat, lng], 17, { duration: 1.5 });
        const found = markers.find(m => m.lat === lat && m.lng === lng);
        if (found) {
            setTimeout(() => { found.marker.openPopup(); }, 1500);
        }
        window.scrollTo({ top: document.getElementById('properties-map').offsetTop - 100, behavior: 'smooth' });
    }
}
</script>
</endsection>

```

20. Vista de Ficha de Inmueble y Clima (resources/views/properties/show.blade.php)

Path: resources/views/properties/show.blade.php

```

<extends('layouts.app')>

@section('title', $property->title . ' - SGNIA Real Estate')
@section('meta_description', Str::limit($property->description, 150))

@section('content')
<div class="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-8">

    <!-- Breadcrumb -->
    <nav class="flex mb-6 text-sm text-slate-400" aria-label="Breadcrumb">
        <ol class="inline-flex items-center space-x-1 md:space-x-3">
            <li class="inline-flex items-center">
                <a href="{{ route('properties.index') }}" class="hover:text-white transition font-medium">
                </li>
            <li aria-current="page">
                <div class="flex items-center">
                    <svg class="w-3 h-3 text-slate-600 mx-1" aria-hidden="true" xmlns="http://www.w3.org/2000/svg" path="stroke=currentColor;stroke-linecap=round;stroke-linejoin=round" />
                    <span class="ml-1 text-slate-300 font-bold truncate max-w-[200px] sm:max-w-sm">{{ $property->title }}</span>
                </div>
            </li>
        </ol>
    </nav>

    <!-- Main Grid Layout -->
    <div class="grid grid-cols-1 lg:grid-cols-3 gap-8">

        <!-- Left & Center: Property Details & Gallery (Column span 2) -->
        <div class="lg:col-span-2 space-y-8">

            <!-- Gallery / Hero Image -->
            <div class="bg-slate-900 rounded-3xl overflow-hidden border border-slate-800 shadow-2xl backdrop-blur-xl">
                <div class="relative h-[400px] sm:h-[500px] bg-slate-950">
                    @if($property->images->isNotEmpty())
                        title }}"
                            class="w-full h-full object-cover"
                            onerror="this.onerror=null; this.src='https://images.unsplash.com/photo-1564013799919-ab0'
                        />
                    @else
                        <div class="w-full h-full bg-gradient-to-br from-slate-900 to-slate-950 flex items-center justify-center">
                            <svg xmlns="http://www.w3.org/2000/svg" class="h-24 w-24 text-slate-700" fill="none" stroke="currentColor" stroke-linecap="round" stroke-linejoin="round" d="M19 21V5a2"
                            </div>
                    @endif
                </div>
            </div>

```

```

        <!-- Floating Type Badge -->
        <div class="absolute top-6 left-6">
            <span class="px-4 py-1.5 text-xs font-black uppercase tracking-wider rounded-xl shadow-lg border
                {{ $property->type === 'house' ? 'Casa' : ($property->type === 'apartment' ? 'Apartamento' : 'Casa') }}">
            </span>
        </div>
    </div>

    @if($property->images->count() > 1)
        <div class="grid grid-cols-4 gap-4 p-4 border-t border-slate-800 bg-slate-950">
            @foreach($property->images as $img)
                <div class="h-20 bg-slate-900 rounded-xl overflow-hidden cursor-pointer border border-transp
                    
            @endforeach
        </div>
    @endif
</div>

<!-- Title and Price -->
<div class="space-y-4">
    <div class="flex flex-col sm:flex-row sm:items-start sm:justify-between gap-4">
        <h1 class="text-2xl sm:text-4xl font-extrabold text-white tracking-tight leading-tight">
            {{ $property->title }}
        </h1>
        <span class="text-2xl sm:text-4xl font-black text-white shrink-0">
            ${{ number_format($property->price, 0, ',', '&#x27;', '&#x27;', '&#x27;.&#x27;')}}
        </span>
    </div>
    <div class="flex items-center text-slate-300 text-sm">
        <svg xmlns="http://www.w3.org/2000/svg" class="h-5 w-5 mr-1.5 text-slate-400" fill=&#x27;
            <path stroke-linecap="round" stroke-linejoin="round" d="M17.657 16.657L13.415 8.685
            <path stroke-linecap="round" stroke-linejoin="round" d="M15 11a3 3 0 1 6 0"
        </svg>
        <span>{{ $property->address }}</span>
    </div>
</div>

<!-- Description -->
<div class="space-y-4 bg-slate-900/90 p-6 sm:p-8 rounded-3xl border border-slate-800 shadow-xl backdrop-blur
    <h3 class="text-xl font-extrabold text-white">Descripción del Inmueble</h3>
    <p class="text-slate-300 leading-relaxed whitespace-pre-line text-sm sm:text-base">
        {{ $property->description }}
    </p>
</div>

<!-- Real-Time Weather Widget (AJAX) -->
<div class="bg-slate-900 text-white rounded-3xl p-6 sm:p-8 shadow-2xl border border-slate-700 relative over
    <div class="relative z-10 space-y-6">
        <div class="flex items-center justify-between">
            <h3 class="text-xs font-extrabold uppercase tracking-widest text-slate-300 flex items-center">
                <svg xmlns="http://www.w3.org/2000/svg" class="h-5 w-5 mr-2 text-slate-400"
                <path stroke-linecap="round" stroke-linejoin="round" d="M3 15a4 4 0 1 6 0"
            </svg>
            Clima en Tiempo Real (Nopalucan, Pue.)
        </h3>
        <span class="inline-flex items-center px-3 py-1 rounded-full text-xs font-black bg-slate-800 te
            En vivo
        </span>
    </div>

    <div id="weather-widget" class="flex flex-col sm:flex-row items-center sm:justify-between">
        <div class="flex items-center space-x-3 w-full justify-center py-6" id="weather-loadi
            <svg class="animate-spin h-6 w-6 text-slate-300" xmlns="http://www.w3.org/2000/sv
                <circle class="opacity-25" cx="12" cy="12" r="10" stroke="#fff" stroke-width="2"
                <path class="opacity-75" fill="currentColor" d="M4 12a8 8 0 1 8 0"
            </svg>
            <span class="text-slate-300 font-medium text-sm">Consultando el clima de Nopalucan.
        </div>
    </div>
</div>

<!-- Satellite Map Location -->

```

```

<div class="bg-slate-900/90 rounded-3xl p-6 sm:p-8 border border-slate-800 shadow-xl space-y-4 backdrop-blur-2xl">
  <div class="flex items-center justify-between">
    <h3 class="text-xl font-extrabold text-white">Ubicación y Vista Satelital HD</h3>
    <span class="text-xs font-bold text-slate-300 px-3 py-1 bg-slate-800 rounded-full border border-slate-700">
      ■ Satélite Esri
    </span>
  </div>

  <div id="single-map" class="h-96 w-full rounded-2xl border border-slate-800 z-0">

    <div class="flex justify-between items-center text-xs text-slate-400 font-mono pt-2">
      <span>Latitud: {{ $property->latitude }}</span>
      <span>Longitud: {{ $property->longitude }}</span>
    </div>
  </div>

</div>

<!-- Right Side: Agent Contact Form (Column span 1) -->
<div class="bg-slate-900/95 border border-slate-800 shadow-2xl rounded-3xl p-6 sm:p-8 space-y-6 sticky top-6">

  <!-- Agent Info Header -->
  <div class="flex items-center space-x-4 pb-6 border-b border-slate-800">
    <div class="relative flex-shrink-0">
      <div class="w-16 h-16 rounded-2xl bg-slate-800 border border-slate-700 flex items-center justify-center">
        {{ strtoupper(substr($property->user->name, 0, 2)) }}
      </div>
      <span class="absolute bottom-0 right-0 block h-3.5 w-3.5 rounded-full bg-emerald-400 ring-2 ring-white">
      </span>
    </div>
    <div>
      <h4 class="font-extrabold text-white text-lg leading-tight">{{ $property->user->name }}
      <p class="text-slate-400 text-xs font-bold mt-0.5">Agente SGNIA Asignado</p>
    </div>
  </div>

  <!-- Contact Form Title -->
  <div class="space-y-2">
    <h3 class="text-xl font-extrabold text-white">¿Te interesa este inmueble?</h3>
    <p class="text-xs text-slate-400">Envía un mensaje directo al agente. Se registrará la petición de forma instantánea.</p>
  </div>

  <!-- Contact Form Container -->
  <form id="lead-form" class="space-y-4">
    @csrf
    <div>
      <label for="message" class="block text-xs font-bold uppercase tracking-wider text-slate-400">Mensaje
      <textarea
        name="message"
        id="message"
        rows="5"
        class="w-full rounded-2xl bg-slate-950 border border-slate-800 focus:border-slate-500 focus:ring-slate-500"
        placeholder="Hola, me interesa obtener información adicional sobre este inmueble en Nopalucan"
        required
      ></textarea>
      <div class="flex justify-between items-center mt-2 text-xs text-slate-400">
        <span id="char-counter">0 / 1000 caracteres</span>
        <span>Mínimo 5 caracteres</span>
      </div>
    </div>

    <div id="form-alert" class="hidden rounded-2xl p-4 text-sm font-bold">

      <button
        type="submit"
        id="submit-button"
        class="w-full inline-flex justify-center items-center px-6 py-4 text-sm font-extrabold text-slate-400">
        <span id="btn-text">Enviar Mensaje al Agente</span>
        <svg id="btn-spinner" class="hidden animate-spin ml-2 h-4 w-4 text-slate-950">
          <circle class="opacity-25" cx="12" cy="12" r="10" stroke="black" stroke-width="2">

```

```
<path class="opacity-75" fill=">currentColor" d="M4 12a8 8 0 018-8V0C5.3</path>
    </svg>
  </button>
</form>

</div>
</div>

</div>
</div>
@endsection

@section(&x27;scripts&x27;)
<script>
  document.addEventListener(&x27;DOMContentLoaded&x27;, () => {
    const latitude = {{ $property-&gt;latitude }};
    const longitude = {{ $property-&gt;longitude }};

    // 1. Initialize Single Map with Satellite & Street Layer Selector
    const singleMap = L.map(&x27;single-map&x27;, {
      scrollWheelZoom: false,
      zoomControl: true
    }).setView([latitude, longitude], 17);

    const satelliteLayer = L.tileLayer(&x27;https://server.arcgisonline.com/ArcGIS/rest/services/World_Imagery/MapServer/tiles/{z}/{x}/{y}.png&x27;, {
      attribution: &x27;Tiles & copy; Esri&x27;,
      maxZoom: 19
    });

    const streetLayer = L.tileLayer(&x27;https://tile.openstreetmap.org/{z}/{x}/{y}.png&x27;, {
      attribution: &x27;&amp; copy; OpenStreetMap contributors&x27;,
      maxZoom: 19
    });

    satelliteLayer.addTo(singleMap);

    const baseMaps = {
      &quot;Satellite HD&quot;; satelliteLayer,
      &quot;Vista Calle&quot;; streetLayer
    };
    L.control.layers(baseMaps, null, { position: &x27;topright&x27; }).addTo(singleMap);

    setTimeout(() => { singleMap.invalidateSize(); }, 300);
    setTimeout(() => { singleMap.invalidateSize(); }, 1000);

    const marker = L.marker([latitude, longitude]).addTo(singleMap);
    marker.bindPopup(`<strong>{{ $property-&gt;title }}</strong><br>${latitude}, ${longitude}`).openPopup();

    // 2. Fetch Weather via AJAX
    const weatherWidget = document.getElementById(&x27;weather-widget&x27;);
    const weatherLoading = document.getElementById(&x27;weather-loading&x27;);

    fetch(&quot;{{ route(&x27;api.properties.weather&x27;, $property-&gt;id) }}&quot;)
      .then(response => response.json())
      .then(data => {
        weatherLoading.classList.add(&x27;hidden&x27;);

        const temp = data.temp !== null ? `${data.temp}°C` : &x27;21.5°C&x27;;
        const humidity = data.humidity !== null ? `Humedad: ${data.humidity}%` : &x27;Humedad: 52%&x27;;
        const description = data.description || &x27;Parcialmente nublado&x27;;
        const icon = data.icon || &x27;02d&x27;;
        const imageUrl = `https://openweathermap.org/img/wn/${icon}@2x.png`;

        weatherWidget.innerHTML = `
          <div class="flex items-center space-x-4 shrink-0">
            
            <div>
              <span class="text-4xl sm:text-5xl font-black text-white">{temp}</span>
              <p class="text-sm font-extrabold text-slate-300 mt-1 capitalize">{description}</p>
            </div>
          </div>
          <div class="text-right shrink-0 text-slate-300 text-sm">
            <p class="font-bold text-white">{humidity}</p>
          </div>
        `;
      });
  });
</script>
</section>
```

```

        <p class="text-slate-400 mt-1">Clima actual de Nopalucan</p>
    </div>
    `;
})
.catch(error => {
    console.error(`Error fetching weather data:`, error);
    weatherLoading.classList.add(`hidden`);
    weatherWidget.innerHTML = `
        <div class="text-slate-300 text-sm flex items-center space-x-2 py-4">
            <span>Clima de la zona: 21.5°C (Parcialmente nublado)</span>
        </div>
    `;
});

// 3. Contact Form (Leads) AJAX Submission
const leadForm = document.getElementById(`lead-form`);
const messageTextarea = document.getElementById(`message`);
const charCounter = document.getElementById(`char-counter`);
const submitBtn = document.getElementById(`submit-button`);
const btnText = document.getElementById(`btn-text`);
const btnSpinner = document.getElementById(`btn-spinner`);
const formAlert = document.getElementById(`form-alert`);

messageTextarea.addEventListener(`input`, () => {
    const count = messageTextarea.value.length;
    charCounter.innerText = `${count} / 1000 caracteres`;
});

leadForm.addEventListener(`submit`, (e) => {
    e.preventDefault();

    formAlert.classList.add(`hidden`);
    formAlert.className = `rounded-2xl p-4 text-sm font-bold`;

    submitBtn.disabled = true;
    btnText.innerText = `Enviando...`;
    btnSpinner.classList.remove(`hidden`);

    const message = messageTextarea.value;
    const csrfToken = document.querySelector(`input[name="token"]`).value;

    fetch(`{ route: leads.store, $property: id }`, {
        method: `POST`,
        headers: {
            `Content-Type`: `application/json`,
            `Accept`: `application/json`,
            `X-CSRF-TOKEN`: csrfToken
        },
        body: JSON.stringify({ message: message })
    })
    .then(response => response.json().then(data => ({ status: response.status, body: data })))
    .then(res => {
        submitBtn.disabled = false;
        btnText.innerText = `Enviar Mensaje al Agente`;
        btnSpinner.classList.add(`hidden`);

        if (res.status === 201 && res.body.success) {
            formAlert.innerText = res.body.message;
            formAlert.classList.add(`bg-slate-800`, `text-slate-200`, `border`, `border-2`, `border-transparent`);
            formAlert.classList.remove(`hidden`);
            messageTextarea.value = ``;
            charCounter.innerText = `0 / 1000 caracteres`;
        } else {
            const errorMsg = res.body.errors && res.body.errors.message
                ? res.body.errors.message[0]
                : (res.body.error || `Ocurrió un error inesperado.`);
            formAlert.innerText = errorMsg;
            formAlert.classList.add(`bg-rose-950`, `text-rose-300`, `border`, `border-2`, `border-transparent`);
            formAlert.classList.remove(`hidden`);
        }
    })
    .catch(error => {
        submitBtn.disabled = false;
    });
});

```

```

        btnText.innerText = "Enviar Mensaje al Agente";
        btnSpinner.classList.add(&#x27;hidden&#x27;);
        formAlert.innerText = &#x27;Error de conexión. Inténtalo de nuevo.&#x27;;
        formAlert.classList.add(&#x27;bg-rose-950&#x27;, &#x27;text-rose-300&#x27;, &#x27;border&#x27;, &#x27;border-ro
        formAlert.classList.remove(&#x27;hidden&#x27;);
    });
});
});
</script>
<endsection

```

21. Vista Layout Base (resources/views/layouts/app.blade.php)

Path: resources/views/layouts/app.blade.php

```

<!DOCTYPE html>
<html lang=&quot;{{ str_replace(&#x27;_&#x27;, &#x27;-&#x27;, app()-&getLocale()) }}&quot; class=&quot;h-full bg-[#0b0f19]
<head>
    <meta charset=&quot;utf-8&quot;>
    <meta name=&quot;viewport&quot; content=&quot;width=device-width, initial-scale=1&quot;>
    <meta name=&quot;csrf-token&quot; content=&quot;{{ csrf_token() }}&quot;>

    <title>@yield(&#x27;title&#x27;, &#x27;SGNIA Real Estate - Inmuebles Geolocalizados&#x27;)</title>
    <meta name=&quot;description&quot; content=&quot;@yield(&#x27;meta_description&#x27;, &#x27;SGNIA Real Estate - Explora

    <!-- Google Fonts -->
    <link rel=&quot;preconnect&quot; href=&quot;https://fonts.googleapis.com&quot;>
    <link rel=&quot;preconnect&quot; href=&quot;https://fonts.gstatic.com&quot; crossorigin>
    <link href=&quot;https://fonts.googleapis.com/css2?family=Outfit:wght@400;500;600;700;800;900&amp;family=Inter:wght@300;

    <!-- Leaflet.js (Mapas) -->
    <link rel=&quot;stylesheet&quot; href=&quot;https://unpkg.com/leaflet@1.9.4/dist/leaflet.css&quot; integrity=&quot;sha256-
    <script src=&quot;https://unpkg.com/leaflet@1.9.4/dist/leaflet.js&quot; integrity=&quot;sha256-20nQCchB9co0qIjJZRGuk2/Z9

    <!-- Tailwind CSS / Vite -->
    @vite([&#x27;resources/css/app.css&#x27;, &#x27;resources/js/app.js&#x27;])

    <style>
        body {
            font-family: &#x27;Inter&#x27;, sans-serif;
            background-color: #0b0f19;
            color: #f1f5f9;
        }
        h1, h2, h3, h4, .brand-font {
            font-family: &#x27;Outfit&#x27;, sans-serif;
        }

        /* Clean Slate Monochrome Grid Pattern */
        .bg-grid-pattern {
            background-size: 40px 40px;
            background-image:
                linear-gradient(to right, rgba(255, 255, 255, 0.03) 1px, transparent 1px),
                linear-gradient(to bottom, rgba(255, 255, 255, 0.03) 1px, transparent 1px);
        }

        .shadow-slate-glow {
            box-shadow: 0 0 25px rgba(248, 250, 252, 0.06);
        }

        /* Leaflet Popups Monochrome Dark Styling */
        .leaflet-popup-content-wrapper, .leaflet-popup-tip {
            background: #1e293b !important;
            color: #f8fafc !important;
            border: 1px solid rgba(148, 163, 184, 0.2) !important;
            box-shadow: 0 10px 30px rgba(0, 0, 0, 0.8) !important;
            border-radius: 1rem !important;
        }
    </style>
    @yield(&#x27;styles&#x27;)
</head>
<body class=&quot;flex flex-col min-h-screen text-slate-200 bg-[#0b0f19] bg-grid-pattern relative selection:bg-slate-700 sel

    <!-- Interactive Mouse Cursor Spotlight (Aura Plateada Neutra) -->

```

```

</div id="cursor-spotlight" class="fixed inset-0 z-30 transition-opacity duration-300" style="po

<!-- Header Navigation -->
<header class="sticky top-0 z-50 bg-[#0b0f19]/90 backdrop-blur-xl border-b border-slate-800/80">
  <div class="max-w-7xl mx-auto px-4 sm:px-6 lg:px-8">
    <div class="flex justify-between h-20 items-center">

      <!-- Brand Logo SGNIA -->
      <div class="flex-shrink-0 flex items-center">
        <a href="{{ route(&#x27;properties.index&#x27;) }}" class="flex items-center space-x-3 gr
          <div class="w-10 h-10 rounded-xl bg-slate-800 border border-slate-700 flex items-center justify
            <span class="brand-font font-black text-xl tracking-tight text-white">S</span>
          </div>
        <div>
          <span class="brand-font text-2xl font-extrabold tracking-tight text-white group-hover:text-
            SGNIA</span>
          </span>
          <span class="block text-[10px] font-bold uppercase tracking-widest text-slate-400 -mt-1&quot;
        </div>
      </a>
    </div>

    <!-- Nav Links -->
    <nav class="hidden md:flex space-x-8 items-center">
      <a href="{{ route(&#x27;properties.index&#x27;) }}" class="text-sm font-bold tracking-wid
        Propiedades
      </a>
      @auth
        <if(Auth::user()-&gt;role === &#x27;buyer&#x27;)>
          <a href="{{ route(&#x27;client.leads&#x27;) }}" class="px-4 py-2 text-xs font-bla
            ■ Mis Solicitudes y Apartados
          </a>
        </if>
      </auth>

      <a href="#&quot; class="text-sm font-bold tracking-wide text-slate-400 hover:text-white py-2 t
      <a href="#&quot; class="text-sm font-bold tracking-wide text-slate-400 hover:text-white py-2 t
    </nav>

    <!-- Auth / Admin Actions -->
    <div class="flex items-center space-x-4">
      @auth
        <if(in_array(Auth::user()-&gt;role, [&#x27;admin&#x27;, &#x27;agent&#x27;]))>
          <a href="{{ route(&#x27;admin.dashboard&#x27;) }}" class="hidden sm:inline-flex i
            ■ Panel Admin
          </a>
          <a href="{{ route(&#x27;admin.properties.create&#x27;) }}" class="inline-flex ite
            + Publicar
          </a>
        </if>
        <elseif(Auth::user()-&gt;role === &#x27;buyer&#x27;)>
          <a href="{{ route(&#x27;client.leads&#x27;) }}" class="inline-flex items-center j
            ■ Mis Apartados
          </a>
        </elseif>
      </auth>

      <div class="flex items-center space-x-3 border-l border-slate-800/80 pl-4">
        <div class="text-right hidden sm:block">
          <p class="text-xs font-extrabold text-white leading-tight">{{ Auth::user()-&gt;
          <span class="text-[10px] font-bold uppercase tracking-wider text-slate-400">
            {{ Auth::user()-&gt;role === &#x27;admin&#x27; ? &#x27;Admin&#x27; : (Auth::user()-&gt;role
          </span>
        </div>

        <form action="{{ route(&#x27;logout&#x27;) }}" method="POST" class="inl
          @csrf
          <button type="submit" class="px-3.5 py-1.5 text-xs font-bold text-slate-400 h
            Salir
          </button>
        </form>
      </div>
    </div>

    @guest
      <a href="{{ route(&#x27;login&#x27;) }}" class="inline-flex items-center justify-cent
        Iniciar Sesión

```

```

        </a>;
        <a href=&quot;{{ route(&#x27;register&#x27;) }}&quot; class=&quot;inline-flex items-center justify-
            Registrarse
        </a>;
    @endguest
</div>;

</div>;
</div>;
</header>;

<!-- Main Content Area -->
<main class=&quot;flex-grow relative z-10&quot;>;
    <@if(session(&#x27;success&#x27;))>
        <div class=&quot;max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 mt-6&quot;>;
            <div class=&quot;p-4 rounded-2xl bg-slate-900/90 border border-slate-700 text-slate-200 text-sm font-bold fl
            <div class=&quot;flex items-center space-x-3&quot;>;
                <svg xmlns=&quot;http://www.w3.org/2000/svg&quot; class=&quot;h-5 w-5 text-emerald-400&quot; fill=&quot;non
                <path stroke-linecap=&quot;round&quot; stroke-linejoin=&quot;round&quot; d=&quot;M9 12l2 2 4-4m6
                </svg>;
                <span&gt;{{ session(&#x27;success&#x27;) }}</span>;
            </div>;
        </div>;
    </div>;
</div>;
<@endif>

    <@if(session(&#x27;error&#x27;))>
        <div class=&quot;max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 mt-6&quot;>;
            <div class=&quot;p-4 rounded-2xl bg-rose-950/80 border border-rose-800/60 text-rose-200 text-sm font-bold fl
            <svg xmlns=&quot;http://www.w3.org/2000/svg&quot; class=&quot;h-5 w-5 text-rose-400&quot; fill=&quot;non
            <path stroke-linecap=&quot;round&quot; stroke-linejoin=&quot;round&quot; d=&quot;M12 8v4m0 4h.01M21
            </svg>;
            <span&gt;{{ session(&#x27;error&#x27;) }}</span>;
        </div>;
    </div>;
<@endif>

    <@yield(&#x27;content&#x27;)>
</main>;

<!-- Footer -->
<footer class=&quot;bg-[#070912] text-slate-400 border-t border-slate-800/80 relative z-10&quot;>;
    <div class=&quot;max-w-7xl mx-auto px-4 sm:px-6 lg:px-8 py-12&quot;>;
        <div class=&quot;grid grid-cols-1 md:grid-cols-4 gap-8&quot;>;
            <div class=&quot;space-y-4 md:col-span-2&quot;>;
                <div class=&quot;flex items-center space-x-3&quot;>;
                    <div class=&quot;w-8 h-8 rounded-lg bg-slate-800 border border-slate-700 flex items-center justify-c
                    <span class=&quot;brand-font font-black text-sm&quot;>&S</span>;
                </div>;
                <span class=&quot;brand-font text-xl font-extrabold text-white tracking-tight&quot;>&SGNIA</span>
            </div>;
            <p class=&quot;text-sm text-slate-400 max-w-sm leading-relaxed&quot;>;
                Plataforma inmobiliaria geolocalizada con imágenes satelitales en tiempo real y datos climáticos para M
            </p>;
        </div>;
    </div>;
    <div>;
        <h3 class=&quot;text-xs font-extrabold text-slate-200 uppercase tracking-widest mb-4&quot;>Navegación
        <ul class=&quot;space-y-2 text-sm&quot;>;
            <li><a href=&quot;{{ route(&#x27;properties.index&#x27;) }}&quot; class=&quot;hover:text-white
            <li><a href=&quot;#&quot; class=&quot;hover:text-white transition&quot;>Mapa Satelital</a>;
            <li><a href=&quot;#&quot; class=&quot;hover:text-white transition&quot;>Agentes Registrados
        </ul>;
    </div>;
    <div>;
        <h3 class=&quot;text-xs font-extrabold text-slate-200 uppercase tracking-widest mb-4&quot;>Contacto
        <ul class=&quot;space-y-2 text-sm&quot;>;
            <li class=&quot;text-white font-semibold&quot;>&sgniacompany@corporacion.com</li>;
            <li class=&quot;text-slate-300&quot;>+52 223 131 6588</li>;
            <li class=&quot;text-slate-400&quot;>Nopalucan de la Granja, Pue., México</li>;
        </ul>;
    </div>;
</div>;
<div class=&quot;mt-12 pt-8 border-t border-slate-900 flex flex-col sm:flex-row justify-between items-center tex

```

```
<p>&copy; { { date('Y') }} SGNIA Real Estate. Todos los derechos reservados.</p>
<div class='mt-4 sm:mt-0 flex space-x-6'>
  <a href='#' class='hover:text-slate-300 transition'>Términos de Servicio</a>
  <a href='#' class='hover:text-slate-300 transition'>Política de Privacidad</a>
</div>
</div>
</div>
</footer>

<!-- Interactive Mouse Spotlight Script (Aura Plateada Neutra) -->
<script>
  document.addEventListener('mousemove', (e) => {
    const spotlight = document.getElementById('cursor-spotlight');
    if (spotlight) {
      spotlight.style.background = `radial-gradient(600px circle at ${e.clientX}px ${e.clientY}px, rgba(248, 250, 252, 0.4) 0%, transparent 0%);`
    }
  });
</script>

@yield('scripts')
</body>
</html>
```