ASSIGNMENT 10
INPUT

```
# Design of tension member
# Input values
Tu = float(input("Enter the value of ultimate tensile strength:"))
fy = float(input("Enter the value of yield strength of steel:"))
fu = float(input("Enter the value of ultimate strength of steel:"))
fub = float(input("Enter the value of ultimate strength of bolt:"))
Gamma_mo = float(input("Enter the value of partial factor of safety Gamma_mo:"))
Gamma_m1 = float(input("Enter the value of partial factor of safety Gamma_m1:"))
Gamma_mb = float(input("Enter the value of partial factor of safety Gamma_mb:"))

# Gross Area Required
Agreq = 1.1*Tu*1000/fy
print("The value of gross area required is:", 1.2*Agreq)

# Selection of section
# Assuming Ag value
Ag = float(input("Enter the value of gross area of steel:"))
Lcl = float(input("Enter the length of connected leg:"))
Lol = float(input("Enter the length of outstand leg:"))
t = float(input("Enter the value of least thickness:"))
Ag = 1257  # Example value, you can replace with your calculated value

# Design of connections
d = float(input("Enter the value of diameter of bolt:"))
do = d + 2
print("The diameter of bolt hole is:", do)

# Minimum pitch distance
pmin = 2.5 * d
print("The minimum pitch is:", pmin)

# Edge distance
e = 1.5 * do
print("Enter the value of edge distance:", e)

nn = float(input("Number of shear planes with threaded intercepting the shear plane:"))
ns = float(input("Number of shear planes without threads:"))

Anb =  0.7854 * d * d
print("Threaded area of bolt is:", Anb)

Asb = 0.7854 * d * d
print("Plane shank area of bolt is:", Asb)

Vdsb = (fub / (1.732 * Gamma_mb)) * (nn * Anb + ns * Asb) * 10**-3
print("The value of Vdsb:", Vdsb)
```

```
kbl = e / (3 * do)
print("Kbl:", kbl)

kb2 = (pmin / (3 * do)) - 0.25
print("Kb2:", kb2)

kb3 = fub / fu
print("Kb3:", kb3)

kb4 = 1
print("Kb4:", kb4)

kb = min(kbl, kb2, kb3, kb4)
print("Kb:", kb)

Vdpb = (2.5 * kb * d * t * fu * 10**-3) / Gamma_mb
print("Vdpb:", Vdpb)

Vd = min(Vdsb, Vdpb)
print("Vd:", Vd)

N = Tu / Vd
print("Number of bolts required:", N)

N = float(input("Enter the value of number of bolts:"))

# Check for strength
# Criteria 1: Yielding of Gross Section
Tdg = (Ag * fy * 10**-3) / (Gamma_mo)
print("The value of tensile strength due to yielding of gross section is:", Tdg)

# Criteria 2: Rupture
Anc = (Lcl - (t / 2) - do) * t
print("Net Area of Connecting leg is: (Anc):", Anc)

Ago = (Lol - (t / 2)) * t
print("Gross Area of outstand leg is: (Ago):", Ago)

Lc = (N - 1) * pmin
print("Le:", Lc)

bs = 0.6 * (Lcl + Lol) * t
print("bs:", bs)

Beta = 1.4*(0.076*(fy / fu) * (bs / Lc)) * (Lol / t)
print("Beta:", Beta)
```

```
print("Check 1")
if Beta >1.4:
   print("Not Safe")
else:
   print("Safe")

print("Check 2")
if Beta <0.7:
   print("Not Safe")
else:
   print("Safe")

Tdn = ((0.9 * fu * Anc) / Gamma_m1) + (Beta * Ago * fy / Gamma_mo)
print("Tdn:", Tdn)

# Criteria 3: Block Shear
Avg = (pmin * (N - 1) + e) * t
print("Avg:", Avg)

Avn = ((pmin * (N - 1) + e) - (N - 1) * do + (8.5 * do)) * t
print("Avn:", Avn)

Atg = 0.6 * Lcl * t
print("Atg:", Atg)

Atn = Atg - 0.5 * do
print("Atn:", Atn)

Tb1 = (((Avg * fy) / (1.732 * Gamma_mo)) + (0.9 * fu * Atn) / Gamma_m1) * 10**-3
print("Tb1:", Tb1)

Tb2 = (((0.9 * Avn * fu) / (1.732 * Gamma_m1)) + ((Atg * fy) / Gamma_mo)) * 10**-3
print("Tb2:", Tb2)

Tb = min(Tb1, Tb2)
print("Tb", Tb)

Td = min(Tdg, Tdn, Tb)
print("Td", Td)

if Td > Tu:
   print("SAFE")
else:
   print("Revise the Section")
```

OUTPUT

```
Enter the value of ultimate tensile strength:225
Enter the value of yield strength of steel:250
```

Enter the value of ultimate strength of steel:410
Enter the value of ultimate strength of bolt:400
Enter the value of partial factor of safety Gamma_mo:1.1
Enter the value of partial factor of safety Gamma_m1:1.25
Enter the value of partial factor of safety Gamma_mb:1.25
The value of gross area required is: 1188.0
Enter the value of gross area of steel:1257
Enter the length of connected leg:100
Enter the length of outstand leg:65
Enter the value of least thickness:8
Enter the value of diameter of bolt:20
The diameter of bolt hole is: 22.0
The minimum pitch is: 50.0
Enter the value of edge distance: 33.0
Number of shear planes with threaded intercepting the shear plane:1
Number of shear planes without threads:0
Threaded area of bolt is: 314.16
Plane shank area of bolt is: 314.16
The value of Vdsb: 58.04341801385682
Kbl: 0.5
Kb2: 0.5075757575757576
Kb3: 0.975609756097561
Kb4: 1
Kb: 0.5
Vdpb: 65.6
Vd: 58.04341801385682
Number of bolts required: 3.876408517952635
Enter the value of number of bolts:5
The value of tensile strength due to yielding of gross section is: 285.6818181818182
Net Area of Connecting leg is: (Anc): 592.0
Gross Area of outstand leg is: (Ago): 488.0
Le: 200.0
bs: 792.0
Beta: 1.179733231707317
Check 1
Not Safe
Check 2
Safe
Tdn: 305601.5402439024
Avg: 1864.0
Avn: 1072.8
Atg: 480.0
Atn: 469.0
Tb1: 383.042543439009
Tb2: 291.80130170060886
Tb 291.80130170060886
Td 285.6818181818182
SAFE