

## Hexaware Technologies Data Engineer Interview Guide – Experienced 3+

### Technical round 1 and 2 combined

#### 1. Cumulative Sum in SQL – Explain how to implement.

A cumulative sum (running total) adds each row's value to the sum of the preceding rows. This can be implemented using the SUM() window function.

```
SELECT
    employee_id,
    salary,
    SUM(salary) OVER (ORDER BY hire_date) AS cumulative_salary
FROM
    employees;
```

Explanation:

- OVER (ORDER BY hire\_date) defines the order in which rows are processed.
- No PARTITION BY is used for a global running total; use it to reset per group.

#### 2. Delta Logs File Format – Discuss the format and its significance.

Delta logs are stored in JSON and Parquet format in the `_delta_log/` directory. These files track transaction history and data versions, enabling ACID transactions and time travel.

- **JSON** files store metadata for operations (add/remove files).
- **Parquet** files contain checkpoints for faster access.

#### 3. How to Access Delta Logs – Explain the process.

To access Delta logs in Databricks:

1. Navigate to the `_delta_log/` directory in the Delta Lake path.
2. Use `%fs ls` to list files:

```
%fs ls dbfs:/mnt/delta_table/_delta_log/
```

3. Read JSON logs for operation history or Parquet for checkpoints.

#### 4. How to See Files Before Update (History Records/Versioning).

Delta Lake provides a DESCRIBE HISTORY command to view version history.

```
DESCRIBE HISTORY delta.`/mnt/delta_table`;
```

- Use VERSION AS OF or TIMESTAMP AS OF to query old data versions:

```
SELECT * FROM delta.`/mnt/delta_table` VERSION AS OF 3;
```

## 5. How to Connect to Salesforce – Steps for Integration.

1. Use a connector like **Databricks Partner Connect** or **JDBC/ODBC drivers**.
2. Generate Salesforce credentials (username, password, security token).
3. Example code using Spark:

```
sf_url = "https://login.salesforce.com"
sf_properties = {
    "user": "your_email@example.com",
    "password": "your_password_security_token",
    "driver": "com.salesforce.jdbc.Driver"
}
df = spark.read.jdbc(sf_url, "SalesforceObject", properties=sf_properties)
```

## 6. How to Connect to Blob Storage in Databricks.

storage\_account\_name = "your\_account\_name"

storage\_account\_key = "your\_account\_key"

container\_name = "your\_container"

```
spark.conf.set(f"fs.azure.account.key.{storage_account_name}.blob.core.windows.net",
storage_account_key)
```

df =

```
spark.read.csv(f"wasbs://{container_name}@{storage_account_name}.blob.core.windows.net/data.csv")
```

## 7. SCD1 and SCD2 in Databricks PySpark – Explain with examples.

- **SCD1 (Type 1)** updates data without keeping history:

- **SCD1 (Type 1)** updates data without keeping history:

```
python
```

```
df_new = df_existing.join(df_updates, "id", "left").withColumn("col", df_updates.col)
```

Copy code

- **SCD2 (Type 2)** retains historical records with `start_date` and `end_date`:

```
python
```

```
df_updates = df_updates.withColumn("end_date", lit(None))
```

Copy code

## 8. How to Run One Notebook in Another Notebook – Use %run.

```
%run /Users/username/notebook_path  
# or  
dbutils.notebook.run("/Users/username/notebook_path", 60)
```

## 9. Aggregation Functions in PySpark – Examples and Use Cases.

```
from pyspark.sql.functions import avg, sum, max, min  
  
df.groupBy("category").agg(sum("sales"), avg("sales"))
```

## 10. SparkContext and SparkSession – Explain Their Purpose.

- **SparkContext:** Core entry point for low-level Spark functionality.
- **SparkSession:** Unified API to create DataFrames, supports modern applications.

```
spark = SparkSession.builder.appName("example").getOrCreate()
```

## 11. Broadcast Join in PySpark – When and How to Use.

Use for small lookup tables to avoid shuffle operations:

```
from pyspark.sql.functions import broadcast  
  
df_result = df_large.join(broadcast(df_small), "key")
```

## 12. How to Increase Job Performance – Techniques and Optimizations.

- Use broadcast joins for small tables.
- Optimize partitions using repartition() or coalesce().
- Enable caching for iterative processes.
- Avoid wide transformations when possible.

## 13. Cluster Types for Work – Explain Job vs. Interactive Clusters.

- **Job Clusters:** Temporary, used for scheduled tasks.
- **Interactive Clusters:** Long-running, used for development and testing.

## 14. How to Copy All Files from One Source Path to Target in ADF.

- Use a **Copy Data activity** with source and sink configuration.
- Enable recursive file copying for nested directories.

### **Glassdoor Hexaware Technologies Review –**

[https://www.glassdoor.co.in/Reviews/Hexaware-Technologies-India-Reviews-EI\\_IE29098.0,21\\_IL.22,27\\_IN115.htm](https://www.glassdoor.co.in/Reviews/Hexaware-Technologies-India-Reviews-EI_IE29098.0,21_IL.22,27_IN115.htm)

### **Hexaware Technologies Careers –**

<https://hexaware.com/about-us/join-hexaware/>

### **Subscribe to my YouTube Channel for Free Data Engineering Content –**

<https://www.youtube.com/@shubhamwadekar27>

### **Connect with me here –**

<https://bento.me/shubhamwadekar>

### **Checkout more Interview Preparation Material on –**

[https://topmate.io/shubham\\_wadekar](https://topmate.io/shubham_wadekar)

© Shubham Wadekar