



Name: Ganath Avinash G.R

CSE – B

CH.SC.U4CSE24118

Week –3

1. Merge Sort :

```
C mergesort.c > main()
1  #include <stdio.h>
2
3  void merge(int *arr,int *arr1,int *arr2,int l1,int l2);
4
5  void mergeSort(int *arr,int s,int e){
6      if(e-s<2){
7          return;
8      }
9      int mid=(s+e)/2;
10     mergeSort(arr,s,mid);
11     mergeSort(arr,mid,e);
12     int l1=mid-s;
13     int l2=e-mid;
14     int arr1[l1];
15     int arr2[l2];
16     for (int i = 0; i < l1; i++)
17     {
18         arr1[i]=arr[s+i];
19     }
20
21     for (int i = 0; i < l2; i++)
22     {
23         arr2[i]=arr[mid+i];
24     }
25     merge(arr+s,arr1,arr2,l1,l2);
26 }
27
28 void merge(int *arr,int *arr1,int *arr2,int l1,int l2){
29     int i=0,j=0,k=0;
30     while(i<l1 && j<l2){
31         if(arr1[i]<arr2[j]){
32             arr[k++]=arr1[i++];
33         }
34         else{
35             arr[k++]=arr2[j++];
36         }
37     }
38
39     while(i<l1){
40         arr[k++]=arr1[i++];
41     }
42     while(j<l2){
43         arr[k++]=arr2[j++];
44     }
45 }
```

```

void main(){
    int arr[10]={38, 27, 43, 3, 9, 82, 10, 17, 1, 3};
    int l=10;
    printf("Array: \n");
    for (int i = 0; i < l; i++)
    {
        printf(" %d ",arr[i]);
    }
    printf("\n");
    mergeSort(arr,0,l);
    printf("Sorted Array: \n");
    for (int i = 0; i < l; i++)
    {
        printf(" %d ",arr[i]);
    }
    printf("\n");
}

```

OUTPUT:

```

Array:
 38  27  43  3  9  82  10  17  1  3
Sorted Array:
 1  3  3  9  10  17  27  38  43  82
PS C:\Users\Ganath Avinash\OneDrive\ドキュメント\Back-end\DAA>

```

Time Complexity: $O(n \log n)$

2. Quick Sort :

```
C quicksort.c > quickSort(int [], int, int)
1  #include <stdio.h>
2  void swap(int *a, int *b) {
3      int t = *a;
4      *a = *b;
5      *b = t;
6  }
7  int partition(int arr[], int low, int high) {
8      int pivot = arr[high];
9      int i = low - 1;
10     for (int j = low; j < high; j++) {
11         if (arr[j] < pivot) {
12             i++;
13             swap(&arr[i], &arr[j]);
14         }
15     }
16     swap(&arr[i + 1], &arr[high]);
17     return i + 1;
18 }
19 void quickSort(int arr[], int low, int high)
20 {
21     if (low < high) {
22         int pi = partition(arr, low, high);
23         quickSort(arr, low, pi - 1);
24         quickSort(arr, pi + 1, high);
25     }
26 }
27 int main() {
28     int arr[] = {38, 27, 43, 3, 9, 82, 10};
29     int n = 7;
30     printf("Array: \n");
31     for (int i = 0; i < n; i++)
32     {
33         printf(" %d ", arr[i]);
34     }printf("\n");
35     quickSort(arr, 0, n - 1);
36     printf("Sorted Array: \n");
37     for (int i = 0; i < n; i++)
38     {
39         printf(" %d ", arr[i]);
40     }printf("\n");
41     return 0;
42 }
```

OUTPUT:

```
Array:
 38 27 43 3 9 82 10
Sorted Array:
 3 9 10 27 38 43 82
PS C:\Users\Ganath Avinash\OneDrive\ドキュメント\Back-end\DAA> 
```

Time Complexity: $O(n^2)$