

**Руководство по производству полетов****Часть С Глава 3 Приложение**

Эксплуатационные минимумы каждого из аэродромов,
которые предполагается использовать в качестве
аэродромов намеченной посадки или запасных аэродромов

Per. №
2.O.34.002

DALLAS / Dallas Love Field
Даллас / Поле Любви

KDAL (B)

USA, Texas
США, Техас


LANDING MINIMUMS

RWY	A/c type	ILS CAT 1	ILS ALS out	LOC (GS out)	LOC (GS out) ALS out
13L	Falcon B737 BBJ	DA(H) 685' (200'/60m) RVR 18 (550m) or Vis 1/2 (800m)	DA(H) 685' (200'/60m) RVR 40 (1200m) or Vis 3/4 (1200m)	MDA(H) 920' (435'/135m) RVR 43 (1300m) or Vis 7/8 (1400m)	MDA(H) 920' (435'/135m) RVR 66 (2000m) or Vis 1 1/4 (2000m)
13R	Falcon B737 BBJ	DA(H) 678' (200'/60m) RVR 40 (1200m) or Vis 3/4 (1200m)		MDA(H) 960' (482'/145m) Vis 1 1/2 (2400m)	
31L	Falcon B737 BBJ	DA(H) 676' (200'/60m) RVR 18 (550m) or Vis 1/2 (800m)	DA(H) 676' (200'/60m) RVR 40 (1200m) or Vis 3/4 (1200m)	MDA(H) 1160' (684'/210m) Vis 1 1/2 (2400m)	MDA(H) 1160' (684'/210m) Vis 2 (3200m)
31R	Falcon B737 BBJ	DA(H) 687' (200'/60m) RVR 24 (750m) or Vis 1/2 (800m)	DA(H) 687' (200'/60m) RVR 40 (1200m) or Vis 3/4 (1200m)	MDA(H) 1140' (653'/200m) Vis 1 3/8 (2200m)	MDA(H) 1140' (653'/200m) Vis 1 7/8 (3000m)

RWY	A/c type	RNAV			
		LPV	LNAV/VNAV	LNAV	RNP 0.30
13L	Falcon B737 BBJ	-	DA(H) 761' (276'/85m) RVR 24 (750m) or Vis 1/2 (800m)	MDA(H) 920' (435'/135m) RVR 43 (1300m) or Vis 7/8 (1400m)	DA(H) 846' (361'/110m) RVR 40 (1200m) or Vis 3/4 (1200m)
13R	Falcon B737 BBJ	-	DA(H) 833' (355'/110m) RVR 60 (1800m) or Vis 1 1/8 (1800m)	MDA(H) 920' (442'/135m) Vis 1 3/8 (2200m)	DA(H) 929' (451'/140m) Vis 1 1/2 (2400m)

Дата утверждения

Дата введения в действие
07.02.2017

	<p align="center">Руководство по производству полетов</p> <p align="center">Часть С Глава 3 Приложение</p> <p>Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Per. № 2.O.34.002</p>
--	--	---

RWY	A/c type	RNAV			
		LPV	LNAV/VNAV	LNAV	RNP 0.30
31L	Falcon B737 BBJ	-	-	MDA(H) 1360' (884'/270m) Vis 2 (3200m)	DA(H) 1117' (641'/195m) Vis 1 7/8 (3000m)
31R	Falcon B737 BBJ	-	DA(H) 915' (428'/130m) RVR 50 (1500m) or Vis 1 (1600m)	MDA(H) 1020' (533'/165m) RVR 55 (1700m) or Vis 1 (1600m)	DA(H) 895' (408'/125m) RVR 45 (1400m) or Vis 7/8 (1400m)

RWY	A/c type	CIRCLE-TO-LAND		
		MDA (H)	CEIL	VIS
All RWYs	Falcon	1240' (755'/230m)	1570' (1080'/ 330m)	2 (3200m)
	B737 BBJ	1540' (1050'/320m)	1860' (1380'/420m)	3 (4800m)

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
All RWYs	Falcon B737 BBJ	Both RVRs are required and controlling			RVR 16 (500m)	-
		TDZ RVR 5 (150m) Rollout RVR 5	TDZ RVR 10 (300m) Rollout RVR 10		or Vis 1/4 (400m)	

Дата утверждения	Дата введения в действие 07.02.2017	
------------------	--	--