

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Рег. № 2.О.34.002</p>
---	---	--

DUNHUANG
Дуньхуан

ZLDH (B)

China
Китай

LANDING MINIMUMS

RWY	A/c type	ILS			LOC (GS out)		VOR DME	
		FULL	Limited	ALS out		ALS out		ALS out
08	Falcon RRJ95 B737	60xR550 VIS 800 3890'	60xR750 VIS 800 3890'	60x1200 3890'	155x2100 4200'	155x2400 4200'	155x2100 4200'	155x2400 4200'
26	Falcon RRJ95 B737	60xR550 VIS 800 3871'	60xR750 VIS 800 3871'	60x1600 3871'	135x1600 4110'	135x2000 4110'	135x1600 4110'	135x2000 4110'

RWY	A/c type	CIRCLE-TO-LAND		
		MDA (H)	CEIL	VIS
08/26	Falcon	4450' (230m)	(1080') (330m)	3500
	RRJ95	4450' (230m)	(1080') (330m)	3500
	B737	4910' (370m)	(1540') (470m)	5000

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (RCLL) and Runway Lights (RL)	Without Runway Centerline Lights (RCLL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without RCLL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
08/26	Falcon RRJ95 B737		RVR 400m VIS 800m		RVR 500m VIS 800m	NA

ГОРНЫЙ / MOUNTAINOUS TERRAIN

RWY Heading 084/264

RWY Dimensions 3400x45 m

ARP Coordinates N 40 09.8 E 094 48.6

AD Elevation 3690'/1125m

	Дата введения в действие 14.06.2019	
--	--	--