

## Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

LAÂYOUNE / Hassan I Эль-Аюн / Хасан Первый

GMML (B)

## **LANDING MINIMUMS**

RWY	A/c	ILS	LOC (GS out)	RNAV (GNSS)	VOR (+DME)	CIRCLE-TO-LAND		
	type			LNAV		MDA (H)	CEIL	VIS
02	Falcon	65x1200	95x1600	95x1600	-	880'	(990')	2800
		430'	530'	530'		(200m)	(300m)	
	RRJ95	65x1200	95x1600	100x1600	-	880'	(990')	3000
		430'	530'	550'		(200m)	(300m)	
	B737	65x1200	95x1600	95x1600	-	940'	(1050')	3600
		430'	530'	530'		(220m)	(320m)	
04	Falcon	-		-	130x2000	880'	(990')	2800
			-		640'	(200m)	(300m)	
	RRJ95	-	-	-	130x2000	880'	(990')	3000
					640'	(200m)	(300m)	
	B737	-	-	-	130x2000	940'	(1050')	3600
					640'	(220m)	(320m)	
20 22	Falcon	-	-	-	-	880'	(990')	2800
						(200m)	(300m)	
	RRJ95	-	-	-	-	880'	(990')	3000
						(200m)	(300m)	
	B737	-	-	-	-	940'	(1050')	3600
						(220m)	(320m)	

## **TAKE-OFF MINIMUMS**

RWY	A/c type	With Runway Centerline Lights (RCLL) and		Runway Centerline Lights with Runway Lights (RL)	Runway Centerline Marking (RCLM) without RCLL & RL	
		Runway Lights (RL)	DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
All RWYs	Falcon RRJ95 B737	-	300*	300*	400	-

<sup>\* -</sup> LVP must be in force

RWY Heading 021/201 037/217

RWY Dimensions 2700x45m 2500x45m

ARP Coordinates N 27 09.1 W 013 13.2

AD Elevation 223'/68m

Дата введения в действие	
22.09.2019	