

**Руководство по производству полетов****Часть С Глава 3 Приложение**

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. №
2.О.34.002

TURKMENABAT
Туркменабат

UTAV (A)

Turkmenistan
Туркменистан

LANDING MINIMUMS

RWY	A/c type	ILS			VOR (+DME)		NDB	
		FULL	TDZ or CL out	ALS out		ALS out		ALS out
13	Falcon RRJ95 B737	60xR550 VIS 800 849'	60xR750 VIS 800 849'	60x1200 849'	100x1500 980'	100x1600 980'	305x1200 1650'	
31	Falcon RRJ95 B737	60xR550 VIS 800 840'	60xR750 VIS 800 840'	60x1200 840'	105x1500 980'	105x1600 980'	310x5000 1650'	

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
13/31	Falcon RRJ95 B737	200*	300*	400	400	-

* - LVP must be in force

RWY Heading

125/305

RWY Dimensions

3800x60m

ARP Coordinates

N 38 55.9

E 063 33.8

AD Elevation

649'/198m

Дата введения в действие
08.10.2018