

	<p align="center">Руководство по производству полетов</p> <p align="center">Часть С Глава 3 Приложение</p> <p>Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Пер. № 2.O.34.002</p>
---	---	---

MACAO
Макао

VMMC (B)

PR of China
KHP

LANDING MINIMUMS

RWY	A/c type	LOC (+DME) (GS out)		RNAV (GNSS) LNAV (Missed apch climb grad mim 3.0% up to 5500')		VPT Visual manoeuvring with prescribed flight tracks		
			ALS out		ALS out	MDA (H)	CEIL	VIS
16	Falcon RRJ95	215x3600 720'		290x5000 970'		870' (260m)	(1500') (460m)	6000
	B737	215x3600 720'		290x5000 970'		NOT APPLICABLE		

RWY	A/c type	ILS CAT 2	ILS CAT1		LOC (+DME) (GS out)		RNAV (GNSS)				VOR DME	
							LNAV/VNAV		LNAV			
				ALS out		ALS out		ALS out		ALS out		ALS out
34	Falcon RRJ95 B737	Missed apch climb grad mim 5.4% up to 5500'										
		30xR350 120' RA 100'	60x1200 220 '	90x1200 310'	90xR1500 VIS 1600 310'	160x2700 540 '	170x290 570'	165x2400 550'				

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
16/34	Falcon RRJ95 B737	175	300	300	400m	-

	Дата введения в действие 07.09.2018	
--	--	--