## **Л** Эксплуата

## Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

STAVANGER / Sola Ставангер / Сола ENZV (B)

Norway Норвегия

## **LANDING MINIMUMS**

					RNAV (	GNSS)		CIRC	LE-TO-LA	AND
RWY	A/c	ILS	ILS	LOC	Ì	,	VOR			
≩	type	CAT 2	CAT 1	(GS out)	LNAV/VNAV	LNAV		MDA	CEIL	VIS
	0.2			, ,				(H)		
	F900	-	65xR1200	140xC2200	85xR1300*	140xC2200	140xC2200	1170'	(1470')	2400
			220'	<i>470'</i>	285'	<i>470'</i>	470'	(350m)	(450m)	
11	RRJ95	-	65xR1200	140xC2200	100xR1500	140xC2200	140xC2200	1170'	(1470')	3000
			220'	<i>470'</i>	335'	<i>470'</i>	470'	(350m)	(450m)	
	B737	-	65xR1200	140xC2200	85xR1300*	140xC2200	140xC2200	1670'	(1970')	3600
			220'	<i>470'</i>	285'	470'	470'	(500m)	(600m)	
	F900	30xR300	60xR750	175xC2200	110xR1200	140xR1700	155xR1900	1170'	(1470')	2400
		110'	210'	<i>580'</i>	370'	470'	<i>515'</i>	(350m)	(450m)	
		RA102'								
	RRJ95	30xR300	60xR800	175xC2200	110xR1500	140xR1700	155xR1900	1170'	(1470')	3000
18		110'	210'	<i>580'</i>	370'	470'	<i>515'</i>	(350m)	(450m)	
		RA102'								
	B737	30xR300	60xR750	175xC2200	110xR1200	140xR1700	155xR1900	1670'	(1970')	3600
		110'	210'	<i>580'</i>	370'	470'	515'	(500m)	(600m)	
		RA102'								
	F900	-	-	-	145xR1800	170xC2100	155xC2300	1170'	(1470')	2400
					500'	585'	600'	(350m)	(450m)	
29	RRJ95	-	-	-	145xR1800	170xC2100	155xC2300	1170'	(1470')	3000
					500'	585'	600'	(350m)	(450m)	
	B737	-	-	-	145xR1800	170xC2100	155xC2300	1670'	(1970')	3600
					500'	585′	600'	(500m)	(600m)	
	F900	-	60xR750	115xR1300	105xR1200	155xR1900	145xR1800	1170'	(1470')	2400
2.5			229'	400'	370'	535'	500'	(350m)	(450m)	***
36	RRJ95	-	60xR750	115xR1300	105xR1500	155xR1900	145xR1800	1170'	(1470')	3000
			229'	400'	370'	535'	500'	(350m)	(450m)	2600
	B737	-	60xR750	115xR1300	105xR1200	155xR1900	145xR1800	1670'	(1970')	3600
			229'	400'	370'	535'	500'	(500m)	(600m)	

<sup>\* -</sup> Missed apch climb grad mim 2.8%

## **TAKE-OFF MINIMUMS**

RWY	A/c type	With Runway Centerline		Runway Centerline Lights with Runway Lights (RL)	RCLM (witho Centerline without Runy	Lights,
		Lights (CL)	DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
All RWYs	F900 RRJ95 B737	150	300	300	400	-

Į	<b>Ц</b> ата утверждения	Дата введения в действие	
		06.05.2016	