

	<p align="center">Руководство по производству полетов</p> <p align="center">Часть С Глава 3 Приложение</p> <p>Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Per. № 2.O.34.002</p>
--	---	---

VIGO
Виго

LEVX (B)

Spain
Испания

LANDING MINIMUMS

RWY	A/c type	ILS CAT 2	ILS CAT 1		ILS ALS out		LOC (GS out)	VOR	VOR ALS out
19			Missd apch climb grad mim						
			4.0%	2.5%	4.0%	2.5%			
	Falcon RRJ95 B737/BBJ	53xR450 1003' RA470'	90xR1200 1125'	130xR1800 1260'	90xR1400 1125'	130xR2000 1260'	220xC2400 1530'	300xC2400 1800'	

RWY	A/c type	CIRCLE-TO-LAND & NDB RWY 01 Circling not authorized East of airport		
		MDA (H)	CEIL	VIS
01 19	Falcon	2260' (430m)	(1740') (530m)	2400
	RRJ95	2260' (430m)	(1740') (530m)	3000
	B737/BBJ	2260' (430m)	(1740') (530m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
01/19	Falcon RRJ95 B737/BBJ	150	300	300	400	-

Дата утверждения	Дата введения в действие 27.02.2017	
------------------	--	--