



# Руководство по производству полетов

## Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Per. №  
2.O.34.002

**GALLIVARE**  
Елливаре

**ESNG (B)**

**Sweden**  
Швеция

### LANDING MINIMUMS

RWY	A/c type	ILS		NDB		CIRCLE-TO-LAND		
			ALS out		ALS out	MDA (H)	CEIL	VIS
12	Falcon	-		195x2400		2470' (440m)	(1770') (540m)	2400
	RRJ95	-		195x2400		2470' (440m)	(1770') (540m)	3000
	B737	-		195x2400		NOT APPLICABLE		
30	Falcon	75xR750 VIS 800 1206'	75x1200 1206'	240x2400	1760'	2470' (440m)	(1770') (540m)	2400
	RRJ95	75x800 1206'	75x1200 1206'	240x2400	1760'	2470' (440m)	(1770') (540m)	3000
	B737	75xR750 VIS 800 1206'	75x1200 1206'	240x2400	1760'	NOT APPLICABLE		

### TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
12/30	Falcon RRJ95 B737	-	300*	300*	400	-

\* - LVP must be in force

### ГОРНЫЙ / MOUNTAINOUS TERRAIN

RWY Heading 110/290

RWY Dimensions 1714x45m

ARP Coordinates N 67 08.7 E 020 48.7

AD Elevation 1027' / 313m

Дата введения в действие  
29.06.2018