



OSTEND-BRUGGE / Ostend
Остенде-Брюгге / Остенде

EBOS (A)

Belgium
Бельгия

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	Lctr	2 NDB	SRA	CIRCLE-TO-LAND		
							MDA (H)	CEIL	VIS
08	F900	60xR550 215'	60xR1200 215'	145xR1500 490'	-	150xR1900 507'	835' (250m)	(1148') (350m)	2400m
	RRJ95	60xR800 215'	60xR1200 215'	150x1800 507'	-	150xR1900 507'	835' (250m)	(1148') (350m)	3000m
	B737	60xR550 215'	60xR1200 215'	145xR1500 490'	-	150xR1900 507'	835' (250m)	(1148') (350m)	3600m
26	F900	60xR550 213'	60xR1200 213'	-	160xR1700 538'	175xC2300 587'	835' (250m)	(1148') (350m)	2400m
	RRJ95	60xR800 213'	60xR1200 213'	-	160xR1700 538'	150xR1900 507'	835' (250m)	(1148') (350m)	3000m
	B737	60xR550 213'	60xR1200 213'	-	160xR1700 538'	150xR1900 507'	835' (250m)	(1148') (350m)	3600m

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
08/26	F900 RRJ95 B737	150	300	300	400	-

Дата утверждения

Дата введения в действие
11.03.2016