

	<p align="center">Руководство по производству полетов Часть С Глава 3 Приложение Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Пер. № 2.О.34.002</p>
--	---	--

SEINAJOKI
Сейняйоки

EFSI (A)

Finland
Финляндия

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	LOC (GS out)	RNAV (GNSS)		NDB	CIRCLE-TO-LAND		
					LNAV/VNAV	LNAV		MDA (H)	CEIL	VIS
14	F900	-	-	-	100xR1100 624'	105xR1200 640'	145xR1800 770'	990' (210m)	(1020') (310m)	2400
	RRJ95	-	-	-	100xR1500 624'	105xR1500 640'	150xR1800 786'	990' (210m)	(1020') (310m)	3000
	B737	-	-	-	100xR1100 624'	105xR1200 640'	145xR1800 770'	NOT APPLICABLE		
32	F900	75xR750 530'	75xR1300 530'	115xR1000 530'	115xR1000 660'	115xR1000 660'	120xR1100 680'	990' (210m)	(1020') (310m)	2400
	RRJ95	75xR800 530'	75xR1300 530'	115xR1000 530'	115xR1500 660'	115xR1500 660'	120xR1500 680'	990' (210m)	(1020') (310m)	3000
	B737	75xR750 530'	75xR1300 530'	115xR1000 530'	115xR1000 660'	115xR1000 660'	120xR1100 680'	NOT APPLICABLE		

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
14/32	F900 RRJ95 B737	-	250*	250*	400	-

* - LVP must be in force, otherwise take-off minimum is 400m

RWY Heading	128/308
RWY Dimensions	2000x45m
ARP Coordinates	N 62 41.6 E 022 49.9
AD Elevation	303'/ 92m

Дата утверждения	Дата введения в действие 13.05.2016	
------------------	--	--