Руководство по производству полетов



Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

PHNOM PENH Пномпень VDPP (B)

Cambodia Камбоджа

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	LOC GS out	RNAV (GNSS) LNAV	VOR DME	CIRCLE-TO-LAND Not authorized South of airport between R-180 and R-260 clockwise		ed etween
							MDA (H)	CEIL	VIS
	F900	-	-	-	125x1700 450'	125x1700 450'	1120' (330m)	(1410') (430m)	4800
05	RRJ95	-	-	-	125x1700 450'	125x1700 450'	1120' (330m)	(1410') (430m)	4800
	B737	-	-	-	125x1700 450'	125x1700 450'	1120' (330m)	(1410') (430m)	4800
	F900	70x1000 267'	70x1200 267'	120x1600 430'	180x2500 628'	200x2900 693'	1120' (330m)	(1410') (430m)	4800
23	RRJ95	70x1000 267'	70x1200 267'	120x1600 430'	180x2500 628'	200x2900 693'	1120' (330m)	(1410') (430m)	4800
	B737	70x1000 267'	70x1200 267'	120x1600 430'	180x2500 628'	200x2900 693'	1120' (330m)	(1410') (430m)	4800

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline		t Runway Centerline Lights with Runway Lights (RL)	RCLM (without Runway Centerline Lights, without Runway Lights)	
		Lights (CL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
05/23	F900 RRJ95 B737	-	250*	250*	400	-

^{* -} LVP must be in force, otherwise take-off minimum is 400m

RWY Heading 046/226

RWY Dimensions 3000x45m

ARP Coordinates N 11 32.8 E 104 50.7

AD Elevation + 40'/ 12.2m

Дата утверждения	Дата введения в действие	
	29.02.2016	