

**Руководство по производству полетов****Часть С Глава 3 Приложение**

Эксплуатационные минимумы каждого из аэродромов,  
которые предполагается использовать в качестве  
аэродромов намеченной посадки или запасных аэродромов

Per. №  
2.O.34.002

**PROVIDENCIALES I.**  
**Провиденсиалес**

**MBPV (B)**

**Turks and Caicos**  
**Теркс и Кайкос**

**LANDING MINIMUMS**

RWY	A/c type	RNAV (GNSS)		VOR (+DME)	VOR	NDB	CIRCLE-TO-LAND		
		LNAV/VNAV	LNAV				MDA (H)	CEIL	VIS
10	Falcon	110x2400 380'	105x2400 370'	105x2400 370'	120x2800 420'	155x2400 530'	680' (200)	(980') (300)	3700
	B737	110x2400 380'	105x2400 370'	105x2400 370'	120x2800 420'	155x2400 530'	750' (220)	(1050') (320)	4600
28	Falcon	155x2800 520'	155x2800 520'	-	170x2400 570'	165x2400 540'	680' (200)	(980') (300)	3700
	B737	155x2800 520'	155x2800 520'	-	170x2400 570'	165x2400 540'	750' (220)	(1050') (320)	4600

**TAKE-OFF MINIMUMS**

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
10/28	Falcon B737	-	250*	250*	400	-

\* - LVP must be in force, otherwise take-off minimum is 400m

**RWY Heading**

**103/283**

**RWY Dimensions**

**2807x45m**

**ARP Coordinates**

**N 21 46.4    W 072 16.1**

**AD Elevation**

**28'/ 9m**

Дата утверждения

Дата введения в действие  
18.10.2016