

**Руководство по производству полетов****Часть С Глава 3 Приложение**

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. №  
2.О.34.002

**ALMERIA**  
**Альмерия**

**LEAM (B)**

**Spain**  
**Испания**

**LANDING MINIMUMS**

RWY	A/c type	ILS			LOC (GS out)	
		FULL	Limited	ALS out		ALS out
25	Falcon RRJ95 B737	75xR550 VIS 800 305'	75xR750 VIS 800 305'	75x1200 305'	260x2400 920'	260x2400 920'

RWY	A/c type	RNAV (GNSS)				NDB	
		LNAV/VNAV		LNAV			
			ALS out		ALS out		ALS out
07	Falcon B737	110x1200 376'	110x1600 376'	160x1900 540'	160x2400 540'	255x3400 860'	255x3800 860'
	RRJ95	110x1500 376'	110x1600 376'	160x1900 540'	160x2400 540'	255x3400 860'	255x3800 860'
25	Falcon RRJ95 B737	185x2000 670'	185x2400 670'	190x2100 680'	190x2400 680'	-	-

RWY	A/c type	CIRCLE-TO-LAND		
		MDA (H)	CEIL	VIS
07/25	Falcon	1770' (520m)	(2040') (620m)	2400
	RRJ95	1770' (520m)	(2040') (620m)	3000
	B737	2730' (810m)	(2990') (910m)	3600

**TAKE-OFF MINIMUMS**

RWY	A/c type	With Runway Centerline Lights (RCLL) and Runway Lights (RL)	Without Runway Centerline Lights (RCLL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without RCLL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
07/25	Falcon RRJ95 B737	150	300	300	400	-

Дата введения в действие  
24.05.2019