## CASTIPOM A B H A

## Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

OSTRAVA / Mošnov Острава / Мошнов LKMT (B)

Czechia Чехия

## **LANDING MINIMUMS**

RWY	A/c type	ILS CAT 2	ILS CAT 1			LOC (GS out)		VOR (+DME)	
			FULL	TDZ or CL	ALS out		ALS out		ALS out
				out					
04	Falcon RRJ95 B737/BBJ	-	ı	1	ı	-	ı	115x1500 1220'	115x1700 1220'
22	Falcon RRJ95 B737/BBJ	30xR300 908' RA102'	60xR550 VIS 800 1008'	60xR750 VIS 800 1008'	60x1200 1008'	110x1200 1160'	110x1600 <i>1160'</i>	110x1000* 1170'	110x1700 1170'

<sup>\* -</sup> VIS 1500 for RRJ95

RWY	A/c type	RNAV (GNSS) LNAV/VNAV		RNAV (GNSS) LNAV		NDB (+DME)		CIRCLE-TO-LAND		
			ALS out		ALS out		ALS out	MDA (H)	CEIL	VIS
04	Falcon	80x1100 1108'	80x1300 1108'	110x1400 1200'	110x1600 1200'	115x1500 1220'	115x1700 1220'	1500' (200m)	(990') (300m)	2400
	RRJ95	100x1500 1172'	100x1500 1172'	110x1500 1200'	110x1600 1200'	150x1800 1340'	150x1800 1340'	1500' (200m)	(990') (300m)	3000
	B737 BBJ	80x1100 1108'	80x1300 1108'	110x1400 1200'	110x1600 1200'	115x1500 1220'	115x1700 1220'	2120' (390m)	(1600') (490m)	3600
22	Falcon	90x800 1093'	90x1400 1093'	115x1000 1180'	115x1700 1180'	110x1200 1170'	110x1700 1170'	1500' (200m)	(990') (300m)	2400
	RRJ95	100x1500 1136'	100x1500 1136'	115x1000 1180'	115x1700 1180'	150x1800 1300'	150x1800 1300'	1500' (200m)	(990') (300m)	3000
	B737 BBJ	90x800 1093'	90x1400 1093'	115x1000 1180'	115x1700 1180'	110x1200 1170'	110x1700 1170'	2120' (390m)	(1600') (490m)	3600

## **TAKE-OFF MINIMUMS**

	A/c	With Runway Centerline Lights	Without Runway Centerline Lights (CL) with High Intensity Runway Lights (HIRL)		Runway Centerline Marking (RCLM) without CL & RL		
RWY	type	(CL) and Runway Lights (RL)	DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT	
04/22	Falcon RRJ95 B737/BBJ	150	300	300	500	-	

	Дата введения в действие	
	14.02.2018	