

**Руководство по производству полетов****Часть С Глава 3 Приложение**

Эксплуатационные минимумы каждого из аэродромов,
которые предполагается использовать в качестве
аэродромов намеченной посадки или запасных аэродромов

Рег. №
2.О.34.002

BERGAMO /Orio Al Serio
Бергамо / Орио Аль Серิโอ

LIME (B)

Italy
Италия

LANDING MINIMUMS

| RWY | A/c type | ILS CAT 3A |
|-----|----------|------------------------|
| 28 | Falcon | - |
| | RRJ95 | DH 50'/15m RVR 200m |
| | B737 | DH 50'/15m RVR 200m |

| RWY | A/c type | ILS CAT 2 | ILS CAT 1 | ILS ALS out | LOC (GS out) | VOR | CIRCLE-TO-LAND Not authorized North of rwy | | |
|-----|----------|---------------------------|------------------|-------------------|--------------------|--------------------|--|-------------------|-------|
| | | | | | | | MDA (H) | CEIL | VIS |
| 10 | F900 | - | - | - | - | 150xR1800 1290' | 1766' (300m) | (1312') (400m) | 2400m |
| | RRJ95 | - | - | - | - | 150xR1800 1290' | 1766' (300m) | (1312') (400m) | 3000m |
| | B737 | - | - | - | - | 150xR1800 1290' | 1766' (300m) | (1312') (400m) | 3600m |
| 28 | F900 | 30xR300 854' RA102' | 75xR550 1000' | 75xR1300 1000' | 155xR1600 1260' | 200xC2300 1410' | 1766' (300m) | (1312') (400m) | 2400m |
| | RRJ95 | 30xR300 854' RA102' | 75xR550 1000' | 75xR1300 1000' | 155xR1600 1260' | 200xC2300 1410' | 1766' (300m) | (1312') (400m) | 3000m |
| | B737 | 30xR300 854' RA102' | 75xR550 1000' | 75xR1300 1000' | 155xR1600 1260' | 200xC2300 1410' | 1766' (300m) | (1312') (400m) | 3600m |

TAKE-OFF MINIMUMS

| RWY | A/c type | With Runway Centerline Lights (CL) | Without Runway Centerline Lights (CL) with Runway Lights (RL) | | RCLM (without Runway Centerline Lights, without Runway Lights) | |
|-------|-----------------------|------------------------------------|---|--|--|-------|
| | | | DAY | NIGHT (Runway End Identifier Lights are Needed) | DAY | NIGHT |
| 10/28 | F900 RRJ95 B737 | 150 | 300 | 300 | 400 | - |

Дата утверждения

Дата введения в действие
25.02.2016