



Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. №
2.О.34.002

SINGAPORE / Seletar
Сингапур / Селетар

WSSL (B)

Singapore
Сингапур

LANDING MINIMUMS

Descending from KK NDB (from 3000') and from JB NDB (from 6000') to RWY 03/21 is allowed under VFR if weather conditions as follow:

- Ground and water surfaces are visible
- Vertical distance between aircraft and clouds is not below than 150 meters
- Horizontal distance to clouds is not below 1000 meters
- Visibility is not below 2000 meters at daytime and 4000 meters at nighttime

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
03/21	Falcon RRJ95 B737/BBJ	-	1500	1500	1500	-

* - LVP must be in force

** - Multiple RVR indications (TDZ, Mid, Rollout)

RWY heading

033/213

RWY dimensions

1836x46m

ARP coordinates

N 01 25.0 E 103 52.1

AD elevation

+ 46'/ 14m

Дата введения в действие
08.05.2018