

	<p align="center"><b>Руководство по производству полетов</b></p> <p align="center"><b>Часть С Глава 3 Приложение</b></p> <p align="center">Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</p>	<p align="center">Per. № 2.0.34.002</p>
--	--	---

**FARNBOROUGH**  
**Фарнборо**

**EGLF (B)**

**United Kingdom**  
**Великобритания**

## LANDING MINIMUMS

RWY	A/c type	ILS		ILS ALS out		LOC (GS out)	SRA	CIRCLE-TO-LAND		
								MDA (H)	CEIL	VIS
06		Missed apch climb grad min								
		5.0 %	2.5 %	5.0 %	2.5 %	5.0 %				
	F900	60xR550 425'	185xR2100 830'	60xR1200 425'	185xC2800 830'	155xR1600 730'	240xC2900 1010'	1190' (290m)	(1280') (390m)	2400
	RRJ95	60xR550 425'	185xR2100 830'	60xR1200 425'	185xC2800 830'	155xR1600 730'	240xC2900 1010'	1190' (290m)	(1280') (390m)	3000
	B737	60xR550 425'	185xR2100 830'	60xR1200 425'	185xC2800 830'	155xR1600 730'	240xC2900 1010'	1190' (290m)	(1280') (390m)	3600
24	F900	60xR550 419'		60xR1200 419'		115xR1000 596'	230xC2700 974'	1190' (290m)	(1280') (390m)	2400
	RRJ95	60xR550 419'		60xR1200 419'		115xR1000 596'	230xC2700 974'	1190' (290m)	(1280') (390m)	3000
	B737	60xR550 419'		60xR1200 419'		115xR1000 596'	230xC2700 974'	1190' (290m)	(1280') (390m)	3600

## TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
06/24	F900 RRJ95 B737	-	250*	250*	400	-

\* - LVP must be in force, otherwise take-off minimum is 400m, take-off below 400m available at pilot's discretion

**RWY Heading**

**063/243**

**RWY Dimensions**

**2440x46 m**

**ARP Coordinates**

**N 51 16.5 W 000 46.7**

**AD Elevation**

**+ 238'/ 72.5 m**

Дата утверждения	Дата введения в действие 18.03.2016	
------------------	--	--