Руководство по производству полетов

Часть С Глава 3 Приложение

Рег. № **2.O.34.002**



Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

ROTTERDAM Роттердам

EHRD (B)

Netherlands Нидерланды

LANDING MINIMUMS

						CIR	CLE-TO-LA	AND
RWY	A/c	ILS	ILS	LOC	VOR		Prohibited	
	type		ALS out	(GS out)		Sout	heast of rur	nway
						MDA	CEIL	VIS
						(H)		
	F900	60xR750	60xR1200	155xR1900	255xC3400	840'	(1181')	2400
		186'	186'	495'	<i>820'</i>	(260m)	(360m)	
06	RRJ95	60xR800	60xR1200	155xR1900	255xC3400	840'	(1181')	3000
		186'	186'	495'	<i>820'</i>	(260m)	(360m)	
	B737	60xR750	60xR1200	155xR1900	255xC3400	840'	(1181')	3600
		186'	186′	495'	<i>820'</i>	(260m)	(360m)	
	F900	60xR750	60xR1200	135xR1400	135xR1400	840'	(1181')	2400
		185'	185'	430'	430'	(260m)	(360m)	
24	RRJ95	60xR800	60xR1200	135xR1400	135xR1400	840'	(1181')	3000
		185'	185'	430'	430'	(260m)	(360m)	
	B737	60xR750	60xR1200	135xR1400	135xR1400	840'	(1181')	3600
		185'	185'	430'	430'	(260m)	(360m)	

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline		nt Runway Centerline Lights with Runway Lights (RL)	RCLM (without Runway Centerline Lights, without Runway Lights)	
		Lights (CL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
06/24	F900 RRJ95 B737	150	300	300	400	-

Дата утверждения	Дата введения в действие	
	17.03.2016	