## (ASIIPOM

## Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

SHARJAН Шарджа OMSJ (B)

UAE OAЭ

## **LANDING MINIMUMS**

| RWY   | A/c                     | ILS            |                |                 | LOC             |                  |  |
|-------|-------------------------|----------------|----------------|-----------------|-----------------|------------------|--|
| K W I | type                    | CAT 1          |                |                 | (GS out)        |                  |  |
|       |                         | FULL           | Limited        | ALS out         |                 | ALS out          |  |
| 12    | Falcon<br>RRJ95<br>B737 | 60x550<br>289' | 60x750<br>289' | 60x1200<br>289' | 95x750<br>400'  | 95x1400<br>400'  |  |
| 30    | Falcon<br>RRJ95<br>B737 | 60x550<br>312' | 60x750<br>312' | 60x1200<br>312' | 110x900<br>460' | 110x1600<br>460' |  |

| RWY | A/c    | RNAV (GNSS)<br>LNAV/VNAV |                  | RNAV (GNSS)<br>LNAV |                  | RNAV (RNP)<br>RNP 0.30 |                  |
|-----|--------|--------------------------|------------------|---------------------|------------------|------------------------|------------------|
|     | type   |                          | ALS out          |                     | ALS out          |                        | ALS out          |
|     | Falcon | 80x750<br>339'           | 80x1300<br>339'  | 115x1000<br>460'    | 115x1700<br>460' | 110x900<br>441'        | 110x1600<br>441' |
| 12  | RRJ95  | 100x1500<br>418'         | 100x1500<br>418' | 115x1500<br>460'    | 115x1700<br>460' | 110x1500<br>441'       | 110x1600<br>441' |
|     | B737   | 80x750<br>339'           | 80x1300<br>339'  | 115x1000<br>460'    | 115x1700<br>460' | 110x900<br>441'        | 110x1600<br>441' |
|     | Falcon | 85x750<br>387'           | 85x1300<br>387'  | 115x1000<br>490'    | 115x1700<br>490' | 95x750<br>413'         | 95x1400<br>413'  |
| 30  | RRJ95  | 100x1500<br>440'         | 100x1500<br>440' | 115x1500<br>490'    | 115x1700<br>490' | 100x1500<br>440'       | 100x1500<br>440' |
|     | B737   | 85x750<br>387'           | 85x1300<br>387'  | 115x1000<br>490'    | 115x1700<br>490' | 95x750<br>413'         | 95x1400<br>413'  |

## **TAKE-OFF MINIMUMS**

| RWY   | A/c<br>type             | With Runway<br>Centerline Lights<br>(RCLL) and Runway<br>Lights (RL) | Without Runway Centerline Lights<br>(RCLL)<br>with Runway Lights (RL) |  | Runway Centerline Marking<br>(RCLM)<br>without RCLL & RL |       |
|-------|-------------------------|--|---|--|--|-------|
|       |                         |  | DAY   | NIGHT ( Runway End<br>Identifier Lights are<br>Needed) | DAY  | NIGHT |
| 12/30 | Falcon<br>RRJ95<br>B737 | 350*   | 350*  | 350*   | 400  | -     |

<sup>\* -</sup> LVP must be in force