

## Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

DHAKA / Hazrat Shahjalal Дакка / им. Шаха Джалала VGHS (B)

Bangladesh Бангладеш

RWY	A/c	ILS CAT1		LOC (GS out)		Lctr "DA"		NDB "DCN"	
	type		ALS out		ALS out		ALS out		ALS out
14	Falcon RRJ95 B737	70x600 250'	70x1400 250'	100x2800 350'	100x2800 350'	100x2800* 160x2800 350' 550'			
32	Falcon RRJ95 B737	90x1200 320'	90x1400 320'	100x2400 350'		-		-	

<sup>150</sup>x2800 MDA 520' for RRJ95

RWY	A/c type	RI LNAV	NP /VNAV	RNP LNAV		VOR DME	VOR	
			ALS out		ALS out	ALS out	ALS out	
	Falcon	95x800	95x1600	125x1300	125x2000	125x2800	135x2800	
		<i>330'</i>	330'	430'	430'	430'	<i>470'</i>	
14	RRJ95	100x1500	100x1600	125x1500	125x2000	125x2800	135x2800	
14		<i>356'</i>	356'	430'	430'	430'	470'	
	B737	95x800	95x1600	125x1300	125x2000	125x2800	135x2800	
		330'	330'	430'	430'	430'	<i>470'</i>	
32	Falcon	95x1400	95x1800	135x2200	135x2600	140x2800	200x2800	
		334'	334'	470'	470'	480'	<i>680'</i>	
	RRJ95	100x1500	100x1800	135x2200	135x2600	140x2800	200x2800	
		<i>356'</i>	356'	470'	470'	480'	<i>680'</i>	
	B737	95x1400	95x1800	135x2200	135x2600	140x2800	200x2800	
		334'	334'	470'	470'	480'	<i>680'</i>	

## **TAKE-OFF MINIMUMS**

A/c RWY type		With Runway Centerline Lights (RCLL) and		nt Runway Centerline Lights L) with Runway Lights (RL)	Runway Centerline Marking (RCLM) without RCLL & RL	
		Runway Lights (RL)	DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
14/32	Falcon RRJ95 B737	200*	300*	300*	400	-

<sup>\* -</sup> LVP must be in force

Дата введения в действие	
24.01.2020	