

	<p align="center"><b>Руководство по производству полетов</b>  <b>Часть С Глава 3 Приложение</b>  <b>Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов</b></p>	<p align="center"><b>Рег. №</b>  <b>2.O.34.002</b></p>
---	---	--

**OHRID / St Paul the Apostle**  
**Охрид / Св. Апостол Павел**

**LWOH (B)**

**Macedonia**  
**Македония**

### LANDING MINIMUMS

RWY	A/c type	ILS		VOR		CIRCLE-TO-LAND Not authorized East of runway		
			ALS out		ALS out	MDA (H)	CEIL	VIS
01	Falcon RRJ95 B737/BBJ	330x2400 3357'	330x2400 3357'	260x3600 3130'	260x3800 3130'	-	-	-
19	Falcon RRJ95 B737/BBJ	-		-		3380' (330m)	(1410') (430m)	3800

### TAKE-OFF MINIMUMS

RWY	A/c type	Minimum climb gradient required	With Runway Centerline Lights (CL) and Runway Lights (RL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		Runway Centerline Marking (RCLM) without CL & RL	
				DAY	NIGHT ( Runway End Identifier Lights are Needed)	DAY	NIGHT
01	Falcon RRJ95 B737/BBJ	4.93%	150	300	300	400	-
19	Falcon RRJ95 B737/BBJ	4.5%	-	300	300	400	-

	Дата введения в действие 12.04.2018	
--	--	--