(ASIIPOM

Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

MALTA / Luqa Мальта / Лука LMML (B)

Malta Мальта

LANDING MINIMUMS

RWY	A/c type	ILS	ILS ALS out	LOC+DME (GS out)	LOC+DME (GS out) ALS out	LOC (GS out)	LOC (GS out) ALS out	RNAV VISUAL	
	Falcon	60xR750 456'	60xR1200 456'	130xR1200 680'	130xR1900 680'	200xC2300 910'	200xC2400 910'		
13	RRJ95	60xR800 456'	60xR1200 456'	130xR1200 680'	130xR1900 680'	200xC2300 910'	200xC2400 910'	-	
	B737	60xR750 456'	60xR1200 456'	130xR1200 680'	130xR1900 680'	200xC2300 910'	200xC2400 910'		
	Falcon	60xR750 430'	60xR1200 430'	-	-	140xR1400 690'	140xC2100 690'	No MDA(H) established	
31	RRJ95	60xR800 430'	60xR1200 430'	-	-	140xR1400 690'	140xC2100 690'	CEIL - 2000' VIS – 5km	
	B737	60xR750 430'	60xR1200 430'	-	-	140xR1400 690'	140xC2100 690'		
05/23	Falcon RRJ95	ONLY VFR FLIGHTS							
	B737								

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline		t Runway Centerline Lights with Runway Lights (RL)	RCLM (without Runway Centerline Lights, without Runway Lights)	
		Lights (CL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
05/23	Falcon RRJ95 B737	-	350	350	400	-

Дата утверждения	Дата введения в действие	
	20.07.2016	