

**Руководство по производству полетов****Часть С Глава 3 Приложение**

Эксплуатационные минимумы каждого из аэродромов,
которые предполагается использовать в качестве
аэродромов намеченной посадки или запасных аэродромов

Per. №
2.O.34.002

LEEDS BRADFORD**EGNM (B)****United Kingdom****Лидс-Брэдфорд****Великобритания****LANDING MINIMUMS**

RWY	A/c type	ILS CAT 3A	ILS CAT 2	ILS CAT 1	ILS ALS out	LOC (GS out) CDFA	LOC (GS out) ALS out CDFA
14	Falcon RRJ95 B737	-	-	60x750 874'	60x1200 874'	160x1600 1190'	160x2400 1190'
32	Falcon	-	30x300 762' RA104'	60x550 862'	95x1200 862'	95x750 970'	125x1400 970'
	RRJ95	DH 50'/15m RVR 200m	30x300 762' RA104'	60x550 862'	95x1200 862'	95x750 970'	125x1400 970'
	B737	DH 50'/15m RVR 200m	30x300 762' RA104'	60x550 862'	95x1200 862'	95x750 970'	125x1400 970'

RWY	A/c type	NDB DME CDFA	NDB DME ALS out CDFA	CIRCLE-TO-LAND		
				MDA (H)	CEIL	VIS
14	Falcon	160xR1600 1190'	160xC2400 1190'	1440' (230m)	(1080') (330m)	2400
	RRJ95	160xR1800 1190'	160xC2400 1190'	1440' (230m)	(1080') (330m)	3000
	B737	160xR1600 1190'	160xC2400 1190'	1630' (290m)	(1280') (390m)	3600
32	Falcon	120xR1100 1050'	120xR1800 1050'	1440' (230m)	(1080') (330m)	2400
	RRJ95	150xR1800 1155'	150xR1800 1155'	1440' (230m)	(1080') (330m)	3000
	B737	120xR1100 1050'	120xR1800 1050'	1630' (290m)	(1280') (390m)	3600

TAKE-OFF MINIMUMS

RWY	A/c type	With Runway Centerline Lights (CL)	Without Runway Centerline Lights (CL) with Runway Lights (RL)		RCLM (without Runway Centerline Lights, without Runway Lights)	
			DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT
14/32	Falcon RRJ95 B737	150	300	300	400	-

Дата утверждения

Дата введения в действие
15.11.2016