(ASIIPOM A B A A

Руководство по производству полетов

Часть С Глава 3 Приложение

Эксплуатационные минимумы каждого из аэродромов, которые предполагается использовать в качестве аэродромов намеченной посадки или запасных аэродромов

Рег. № 2.О.34.002

VAGAR Barap EKVG (C)

Faroe Islands Фарерские острова

LANDING MINIMUMS

RWY	A/c	LOC	CLOUD BREAK PROCEDURE "MY" NDB CIRCLE-TO-LAND						
	type	(GS out)	DAY			NIGHT			
		CDFA	MDA (H)	CEIL	VIS	MDA (H)	CEIL	VIS	
12	Falcon RRJ95 B737	DA(H) 820' (170m) CEIL - 400' VIS - 2500m	1000' (220m)	(1050') (320m)	8000m	_	NOT IORIZE	D	

RWY	A/c		ILS		LOC (GS out)	CLOUD BREAK PROCEDURE "MY" NDB CIRCLE-TO-LAND			
	type	Misse	d apch climb	grad min	,	CIRCLE-1U-LAND			
		5.0%		2.5%	CDFA	DAY			
		FULL	ALS out	ALS out		MDA (H)	CEIL	VIS	NIGHT
30	Falcon RRJ95 B737	135x1700 680'	135x2100 680'	310x2400 1240'	DA(H) 1330' (335m) CEIL - 700' VIS - 4000m	1000' (220m)	(1050') (320m)	8000	NA

TAKE-OFF MINIMUMS

	IMC RWY 12 Aircraft must be able to operate above 3.8% take-off obstacle free surface					VMC ALL RWYS		
A/c	With Runway	Wi Ce	thout Runway nterline Lights	RCLM (without Runway Centerline				
type	Centerline Lights (CL) and	,	L) with Runway Lights (RL)	Lights, without Runway Lights)				
	Runway Lights (RL)	DAY	NIGHT (Runway End Identifier Lights are Needed)	DAY	NIGHT	DAY	NIGHT	
Falcon RRJ95 B737	150	300	300	400m	-	CEIL - 700' / 213m VIS - 8.0km	CEIL - 2000' / 610m	

Дата введения в действие	
09.06.2018	